



Views

Tilt

Specifications

Copyright © 2014 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2014 - 03 Rev. A00

Regulatory model: W09B | Type: W09B001 Computer model: Inspiron 20 Model 3048




Front



Right



Front



Microphone (touchscreen computer only)

Provides high-quality digital sound input for audio recording, voice calls, and so on.

2 Microphone (non-touchscreen computer only)

Provides high-quality digital sound input for audio recording, voice calls, and so on.

S Camera-cover latch

Covers your computer camera lens. Slide the latch to the right-side of your computer to cover the camera lens.

4 Camera

Allows you to video chat, capture photos, and record videos.

5 Camera-status light

Turns on when the camera is in use.












Left



Media-card reader

Reads from and writes to media cards.

2 USB 3.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provide data transfer speeds up to 5 Gbps.

Headset port

Connect a headphone, a microphone, or a headphone and microphone combo (headset).












Right



L Optical drive

Reads from and writes to CDs and DVDs.

- 2 Display-brightness increase button
 - Press to increase the display brightness.
- 3 Display-brightness decrease button
 Press to decrease the display brightness.
- 4 Display off/on button

Press and hold to turn-off the display; press again to turn-on the display.

5 Hard-drive activity light

Turns on when the computer reads from or writes to the hard drive.

6 Power button

Turns on your computer or changes the power state of your computer.



Front







Back



Power-adapter port

Connect a power adapter to provide power to your computer.

Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.

The two lights next to the connector indicate the connectivity status and network activity.

HDMI port

Connect a TV or other HDMI-in enabled devices. Provides video and audio output.

Audio-out port

Connect audio-output devices such as speakers, amplifiers, and so on.

USB 2.0 ports (4)

Connect peripherals such as storage devices, printers, and so on. Provide data transfer speeds up to 480 Mbps.



Tilt







Dimensions and Weight

Height	385.58 mm (15.18 in)		
Width	489.92 mm (19.29 in)		
Depth	204.97 mm (8.07 in)		
Weight (maximum):	Touchscreen	Non-touchscreen	
Without stand	5.22 kg (11.51 lb)	4.53 kg (9.99 lb)	
With stand	6.72 kg (14.82 lb)	6.03 kg (13.29 lb)	
		NOTE : The weight of your computer varies depending on the configuration ordered and the manufacturing variability.	



Media-Card

Reader





Ports and Connectors









Memory Connectors













System Information

Computer model	Inspiron 20 Model 3048	
Processor	• 4 th Generation Intel Core i3	
	 4th Generation Intel Pentium Dual Core 4th Generation Intel Celeron Dual Core 	
System chipset	Intel H81 Chipset	

















Connectors

















Memory

Slots Two SODIMM slots

Type Dual-channel DDR3

Speed Up to 1600 MHz

Configurations supported 2 GB, 4 GB, 8 GB, and 16 GB

















mm,















Ports and Connectors

External:	
Network	One RJ45 port
USB	Four USB 2.0 portsTwo USB 3.0 ports
Audio/Video	One headset portOne audio-out portOne HDMI-out port

Internal:

M.2 card One M.2 card slot for WLAN and Bluetooth



















unications Video















Wireless

Specifications

Communications

10/100/1000 Mbps Ethernet controller integrated on system board Ethernet

- Wi-Fi 802.11 n
- Wi-Fi 802.11 ac
- Bluetooth 4.0































Video

Controller:

• Intel HD Graphics 4400 for Intel Core i3

• Intel HD Graphics for Intel Pentium Dual Core/Intel Celeron Dual Core

Discrete AMD Radeon R5 A240

Memory:

Integrated Shared system memory

Discrete 1 GB DDR3









Connectors









nications Video A



Reader













Audio

Controller Realtek Al C3661 with Waves MaxxAudio

Speakers Two

Speaker output:

Average 2 W Peak 2.5 W

Microphone Digital microphone in camera assembly

Volume controls Program menus

















Connectors

















Storage

Interface • SATA 3 Gbps for optical drive

• SATA 6 Gbps for hard drive

Hard drive One 2.5-in drive

Optical drive One 9.5-mm DVD+/-RW drive











Memory



Ports and Connectors



Communications



Video



Audio



Storage

















Media-Card Reader

Type One 4-in-1 slot

Cards supported

• SD card

• MultiMediaCard (MMC)

• SD Extended Capacity (SDXC) card

• SD High Capacity (SDHC) card









Connectors









Media-Card Reader













Display

Type • 19.5-in HD+ touchscreen

• 19.5-in HD+ non-touchscreen

Resolution (maximum) 1600 x 900

Dimensions:

 Height
 236.34 mm (9.30 in)

 Width
 433.92 mm (17.08 in)

 Diagonal
 495.30 mm (19.50 in)

Diagonal 495.30 Refresh rate 60 Hz

Pixel pitch 0.2712 mm x 0.2626 mm

Controls Brightness can be controlled through the display-brightness

increase/decrease button

















Commu

















Camera

Resolution:

Still image 0.92 megapixels

1280 x 720 at 30 fps (maximum) Video

Diagonal viewing angle 74 degrees







Connectors













Media-Card Reader













Stand

 Height
 183.18 mm (7.21 in)

 Width
 204.97 mm (8.07 in)

 Depth
 204.97 mm (8.07 in)



Reader





























Power Adapter

• 130 W Type

• 150 W (only for AMD Radeon R5 A240)

Input voltage 100 VAC-240 VAC

Input frequency 50 Hz-60 Hz

2.50 A Input current (maximum)

Output current:

130 W 6.70 A

150 W 7.70 A

Rated output voltage 19.50 VDC

Temperature range:

Operating:

130 W 0°C to 40°C (32°F to 104°F)

150 W 0°C to 35°C (32°F to 95°F)

-40°C to 70°C (-40°F to 158°F) Storage



Weight





Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-Card Reader



Camera









Computer Environment

Airborne contaminant level	G1 as defined by ISA-S71.04-1985	
	Operating	Storage
Temperature range	0°C to 40°C (32°F to 104°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum)	110 G [†]	160 G [‡]
Altitude (maximum)	-15.2 m to 3048 m (-50 ft to 10,000 ft)	-15.2 m to 10,668 m (-50 ft to 35,000 ft)

^{*} Measured using a random vibration spectrum that simulates user environment.

















rstem Memory













[†] Measured using a 2 ms half-sine pulse when the hard drive is in use.

[‡] Measured using a 2 ms half-sine pulse when the hard-drive head is in parked position.