

# **Specifications**

#### © 2013 Dell Inc.

Trademarks used in this text:  $Dell^m$ , the DELL logo, and Inspiron<sup>m</sup> are trademarks of Dell Inc. Intel<sup>®</sup> is a registered trademark and  $Core^m$  is a trademark of Intel Corporation in the U.S. and other countries. Bluetooth<sup>®</sup> is a registered trademark owned by Bluetooth SIG, Inc. and is used by Dell under license.

2013 - 10 Rev. A00

Regulatory model: W06B | Type: W06B001 Computer model: Inspiron One 2020

#### **Dimensions**

Difficusions	
Height	376.9 mm (14.8 inches)
Width	506.8 mm (20.0 inches)
Depth	
Edge (touch)	35.0 mm (1.4 inches)
Chassis (touch)	65.5 mm (2.6 inches)
Edge (non-touch)	34.5 mm (1.4 inches)
Chassis (non-touch)	63.2 mm (2.5 inches)
Stand	
Width x Depth	220.0 mm (8.7 inches) x 220.0 mm (8.7 inches)
Weight (approximate)	
Without stand (touch)	7.1 kg (15.6 lb)
With stand (touch)	8.6 kg (18.9 lb)
Without stand (non-touch)	5.9 kg (13.0 lb)
With stand (non-touch)	7.4 kg (16.3 lb)
	<b>NOTE:</b> The weight of your computer varies depending on the configuration ordered and the manufacturing variability.

# **System Information**

Computer model	Inspiron One 2020
Processor	<ul> <li>Intel Core i5 (3rd generation)</li> <li>Intel Core i3 (3rd generation)</li> <li>Intel Pentium dual core</li> <li>Intel Celeron dual core</li> </ul>
L2 cache	256 KB
L3 cache	up to 8 MB
System chipset	Intel H61 Express Chipset
SDRAM bus width	up to 1600 MT/s
BIOS EPROM	4 MB + 2 MB
Graphics bus	PCle x16 Gen2

### **Memory**

Connectors	two internally-accessible DDR3
	SODIMM sockets
Capacities	2 GB and 4 GB
Type	non-ECC, dual-channel DDR3
Speed	up to 1600 MHz
Configurations supported	2 GB, 4 GB, 6 GB, and 8 GB

#### Stand

Tilt	-5 degrees to 30 degrees	

#### Camera

Resolution	720p HD; 1280 x 720 pixels
Video resolution (maximum)	1280 x 720 pixels
Diagonal viewing angle	66 degrees

#### **Media-Card Reader**

Туре	one 8-in-1 slot
Cards supported	<ul> <li>Secure Digital Extended Capacity (SDXC)</li> <li>Multi Media Card (MMC)</li> <li>Secure Digital (SD)</li> <li>Hi Speed-SD</li> <li>Hi Capacity-SD</li> </ul>
	<ul> <li>Memory Stick (MS)</li> <li>Memory Stick PRO</li> <li>xD-Picture Card</li> </ul>

#### **Ports and Connectors**

Rear Panel Ports	
USB	three USB 2.0 ports
Network	one RJ45 port
Side Panel Ports	
USB	two USB 2.0 port
Audio	<ul> <li>one headphone port</li> </ul>
	<ul> <li>one microphone port</li> </ul>

#### **Communications**

Network adapter	10/100/1000 Mbps Ethernet LAN on system board
Wireless	<ul> <li>mini-card supporting single-band Wi-Fi b/g/n and Wi-Fi display</li> <li>mini-card supporting Bluetooth 4.0, single-band Wi-Fi b/g/n, and Wi-Fi display</li> </ul>

# **Expansion Slots**

Mini-card slots	one half-height slot
-----------------	----------------------

#### **Video**

Video controller		
Integrated	<ul> <li>Intel HD graphics</li> </ul>	
	<ul><li>Intel HD2500</li></ul>	
Discrete	GeForce 610M	
Video memory		
Integrated	system shared memory	
Discrete	1 GB GDDR3	

### **Audio**

Controller	Intel High Definition Audio with Waves MaxxAudio 3
Speakers	2 x 3 W
Internal microphone	single microphone in camera assembly
Volume controls	program menus

### Storage

Interface	SATA 2.0
Internally accessible	
Hard drives	one
Drives supported	one 3.5-inch hard drive
Externally accessible	
Optical drives	one tray-load drive
Drives supported	DVD+/- RW

# Display

Туре	20.2-inches FHD WLED touchscreen	
Maximum resolution	1600 x 900	
Dimensions		
Height	249.08 mm (9.81 inches)	
Width	442.80 mm (17.43 inches)	
Diagonal	513.10 mm (20.20 inches)	
Refresh rate	60 Hz	
Horizontal viewing angle	150 degrees to 170 degrees	
Vertical viewing angle	140 degrees to 160 degrees	
Pixel pitch	0.27 mm x 0.27 mm	
Controls	brightness can be controlled through display-brightness increase/decrease button	

# **AC Adapter**

Type	130 W	
Input voltage	100 VAC-240 VAC	
Input current (maximum)	2.50 A	
Input frequency	50 Hz-60 Hz	
Output current (continuous)	6.70 A	
Rated output voltage	19.50 +/- 1 VDC	
Temperature range		
Operating	0 °C to 40 °C (32 °F to 104 °F)	
Storage	-40 °C to 70 °C (-40 °F to 158 °F)	

#### **Computer Environment**

_		
Iam	perature	ranga.
16111	perature	range.

Operating 0 °C to 35 °C (32 °F to 95 °F)

Storage -40 °C to 65 °C (-40 °F to 149 °F)

#### Relative humidity (maximum):

Operating 10% to 90% (non-condensing)
Storage 10% to 95% (non-condensing)

Maximum vibration (using a random vibration spectrum that simulates user environment):

Operating 0.66 GRMS Storage 1.30 GRMS

Maximum shock (measured with hard drive in operating status and a 2-ms half-sine pulse for operating. Also measured with hard drive in head-parked position and a 2-ms half-sine pulse for storage):

Operating 110 G Storage 160 G

Altitude (maximum)

Operating -15.2 m to 3048 m (-50 ft to 10,000 ft)

Storage -15.2 m to 10,668 m (-50 ft to 35,000 ft)

Airborne contaminant level G1 as defined by ISA-S71.04-1985