

Dell™ U2413/U2713H

© 2012 Dell Inc. All rights reserved.

Dell Inc.

가 : Dell DELL Dell Inc ; Microsoft, Windows /
 Corporation Microsoft Corporation . Intel 가 Intel
 . ATI Advanced Micro Devices, Inc. ; ENERGY STAR
 . Dell Inc. ENERGY STAR ENERGY
 STAR

가 : Dell DELL Dell Inc ; Microsoft, Windows /
 Corporation Microsoft Corporation . Intel 가 Intel
 . ATI Advanced Micro Devices, Inc. .


가 . Dell Inc. 가 .

U2413f/U2713Hb

2012 11 Rev. A00

Dell™ U2413/U2713H

가



/



:



:

가



:

가

© 2012 Dell Inc. All rights reserved.

Dell Inc.

: Dell DELL
Microsoft Corporation
Advanced Micro Devices, Inc.

Dell Inc
Intel

; Microsoft, Windows
가

/
Intel Corporation

가

. ATI

. Dell Inc.

가

가

U2413f/U2713Hb

2012 11 Rev. A00

가

Dell™ U2413/U2713H

- _____
- _____
- _____
- _____
- _____
- _____ (USB) _____
- _____
- LCD _____
- _____

Dell _____





:

가



:








()

DisplayPort (Mini DP DP)

U2413: DVI-D ()
U2713H: DVI-D ()

	USB 3.0 (USB)
	
	

Dell U2413/U2713H

(TFT)

(LCD)

LED

가

U2413: 가 60.96 cm (24) (). 1920 x 1200

U2713H: 가 68.47 cm (27) (). 2560 x 1440

VESA 100 mm

가

OSD

CD

(INF),

(ICM), Dell Display Manager

가

가

가

TCO

Dell Display Manager (CD).

(2,000,000:1).

BFR/PVC

가

EPEAT

ENERGY STAR

Adobe sRGB

Dell U2413/U2713H sRGB Adobe RGB (RGB) (RGB) (6).


(12) HDMI 12

14 LUT 12


USB 3.0 (SD/Mini SD, MS/HSMD/MSPRO, MMC).

DVI-D, DisplayPort, Mini DisplayPort, HDMI, DP1.1a, DP 1.2 MST(DP) HBR2(DP1.1a) . MST , "[DP MST](#)"

PBP(Picture by Picture) PIP(Picture in Picture)




1	()
2	(LED)




가

1	VESA (100 mm x 100 mm -)	VESA (100 mm x 100 mm)
2		
3		
4		
5		
6		
7		
8		



1		_____ ()
2	USB	USB
3	USB	USB USB 1.5A 가 BC 1.2



1	AC	
2	DC	()
3		(2)
4	DisplayPort	DP
5	Mini DisplayPort	Mini DP DP
6	DVI	DVI (U2713H) DVI
7	HDMI	HDMI
8	DisplayPort (MST)	MST()가 가 . MST DisplayPort . DP1.1 MST "DP MST"
9	USB	USB USB
10	USB	USB USB USB
11		M3 x 6mm ()



:

	U2413	U2713H
	- TFT LCD	- TFT LCD
	AH	AH
	609.6 cm (24)	684.7 cm (27)
가	518.4 mm (20.4) 324.0 mm (12.8)	596.7 mm (23.49) 335.7 mm (13.21)
	0.27 mm	0.231 mm
	178° () , 178° (가)	178° () , 178° (가)
	350 cc/m ² () , 50 cd/m ² ()	350 cc/m ² () , 50 cd/m ² ()
	1000 1() 2M 1 ()	1000 1() 2M 1 ()
	3H	3H
	LED	LED
	6 ms ()	6 ms ()
	10 7	10 7
	103%* (CIE 1931), 120% (CIE 1976)	103%* (CIE 1931), 120% (CIE 1976)
()	3 ()	3 ()

*[U2413/U2713H] sRGB 100% (CIE 1931 CIE 1976) , AdobeRGB 99% (CIE 1931 CIE 1976) .

	U2413	U2713H
	30 kHz ~ 81 kHz()	29 kHz ~ 113 kHz()
	56 Hz ~ 76 Hz()	49 Hz ~ 86 Hz()
	1920 x 1200(60 Hz)	2560 x 1440(60 Hz)

	U2413/U2713H
HDMI) (DVI & DP &	480p, 480i, 576p, 576i, 720p, 1080p, 1080i

U2413

	(kHz)	(Hz)	(MHz)	(/)
VESA, 640 x 480	31.5	60.0	25.2	-/-
VESA, 640 x 480	37.5	75.0	31.5	-/-
VESA, 720 x 400	31.5	70.0	28.3	-/+
VESA, 800 x 600	37.9	60.3	40.0	+/+
VESA, 800 x 600	46.9	75.0	49.5	+/+
VESA, 1024 x 768	48.4	60.0	65.0	-/-
VESA, 1024 x 768	60.0	75.0	78.8	+/+
VESA, 1152 x 864	67.5	75.0	108.0	+/+
VESA, 1280 x 1024	80.0	75.0	135.0	+/+
VESA, 1280 x 1024	64.0	60.0	108.0	+/+
VESA, 1600 x 1200	75.0	60.0	162.0	+/+
VESA, 1920 x 1200	74.0	60.0	154.0	+/-

U2713H

	(kHz)	(Hz)	(MHz)	(/)
VESA, 640 x 480	31.5	60.0	25.2	-/-
VESA, 640 x 480	37.5	75.0	31.5	-/-
VESA, 720 x 400	31.5	70.0	28.3	-/+
VESA, 800 x 600	46.9	75.0	49.5	+/+
VESA, 1024 x 768	48.4	60.0	65.0	-/-
VESA, 1024 x 768	60.0	75.0	78.8	+/+
VESA, 1152 x 864	67.5	75.0	108.0	+/+

VESA, 1280 x 800	49.7	60.0	83.5	-/+
VESA, 1280 x 1024	64.0	60.0	108.0	+/+
VESA, 1280 x 1024	80.0	75.0	135.0	+/+
VESA, 1600 x 1200	75.0	60.0	162.0	+/+
VESA, 1680 x 1050	65.3	60.0	146.3	-/+
VESA, 1920 x 1080	67.5	60.0	148.5	+/+
VESA, 1920 x 1200	74.6	60.0	193.3	-/+
VESA, 2560 x 1440	88.8	60.0	241.5	+/-

	U2413 /U2713H
	DVI-D TMDS, 600 mV, 50 DisplayPort *, 600 mV, 100 ohm HDMI, 600 mV, 100 ohm
AC / /	100 VAC ~ 240 VAC / 50 Hz 60 Hz \pm 3 Hz / 1.5 A ()
	120 V : 42 A () 0 °C 240 V : 80 A () 0 °C

*DP1.2(CORE) , HBR2, MST DP .

	U2413	U2713H
	DVI-D, DP, Mini DP HDMI USB 3.0	(DP DP)
	DVI-D Mini DP DP HDMI USB 3.0	

()		
()	530.9 mm (20.90)	538.4 mm (21.20)
()	415.9 mm (16.37)	423.4 mm (16.67)
	556.0 mm (21.89)	639.3 mm (25.17)
	200.5 mm (7.89)	200.5 mm (7.89)
()		
	361.6 mm (14.24)	378.2 mm (14.89)
	556.0 mm (21.89)	639.3 mm (25.17)
	67.1 mm (2.64)	74.1 mm (2.92)
()	418.4 mm (16.47)	418.4 mm (16.47)
()	372.3 mm (14.66)	372.3 mm (14.66)
	314.8 mm (12.39)	314.8 mm (12.39)
	200.5 mm (7.89)	200.5 mm (7.89)
()	9.35 kg (20.57 lb)	10.95 kg (24.09 lb)
	7.32 kg (16.10 lb)	8.75 kg (19.25 lb)
(VESA)	5.01 kg (11.02 lb)	6.30 kg (13.86 lb)
	1.78 kg (3.92 lb)	1.92 kg (4.22 lb)
	- 5.0 ()	

	U2413	U2713H
	0°C ~ 40 °C (0 °F ~ 104 °F)	

	: -20 °C ~ 60 °C(-4 °F ~ 140 °F) : -20 °C ~ 60 °C(-4 °F ~ 140 °F)	
	10% ~ 80% ()	
	: 5% ~ 90% () : 5% ~ 90% ()	
	5,000 m (16,500 ft)	
	12,192 m (40,000 ft)	
	409.56 BTU/ () 204.78 BTU/ ()	443.58 BTU/ () 204.73 BTU/ ()

PC VESA DPM™

가

가

*

가

VESA

U2413

U2713H

120 W () **

130 W () **

60 W ()

60 W ()

0.5 W

0.5 W

0.5 W

0.5 W

OSD

가 가 :

Dell U2413/U2713H

There is no signal coming from your computer. Press any key on the keyboard or move the mouse to wake it up. If there is no display, press the monitor button now to select the correct Input source on the On-Screen-Display menu.



OSD



:

ENERGY STAR®




* OFF()

** , Soundbar, USB

가

U2413 DVI

U2713H DVI ()




	24
1	TMDS RX2-
2	TMDS RX2+
3	TMDS
4	
5	
6	DDC
7	DDC
8	
9	TMDS RX1-
10	TMDS RX1+
11	TMDS
12	
13	
14	+5V/+3.3V
15	가
16	
17	TMDS RX0-
18	TMDS RX0+
19	TMDS
20	

	24
1	TMDS RX2-
2	TMDS RX2+
3	TMDS
4	TMDS RX4-
5	TMDS RX4+
6	DDC
7	DDC
8	
9	TMDS RX1-
10	TMDS RX1+
11	TMDS
12	TMDS RX3-
13	TMDS RX3+
14	+5V/+3.3V
15	가
16	
17	TMDS RX0-
18	TMDS RX0+
19	TMDS
20	TMDS RX5-

21	
22	TMDS
23	TMDS +
24	TMDS -

21	TMDS RX5+
22	TMDS
23	TMDS +
24	TMDS -


DisplayPort (DP DP)



	20
1	ML0(p)
2	GND
3	ML0(n)
4	ML1(p)
5	GND
6	ML1(n)
7	ML2(p)
8	GND
9	ML2(n)
10	ML3(p)
11	GND
12	ML3(n)
13	GND
14	GND
15	AUX(p)
16	GND

17	AUX(n)
18	HPD
19	DP_PWR_ 가
20	+3.3 V DP_PWR


Mini DisplayPort



20	
1	GND
2	
3	ML3(n)
4	GND
5	ML3(n)
6	GND
7	GND
8	GND
9	ML2(n)
10	MLO(p)
11	ML2(p)
12	MLO(p)
13	GND
14	GND

15	ML1(n)
16	AUX(p)
17	ML1(p)
18	AUX(n)
19	GND
20	+3.3 V DP_PWR

HDMI



	19
1	TMDS 2+
2	TMDS 2
3	TMDS 2-
4	TMDS 1+
5	TMDS 1
6	TMDS 1-
7	TMDS 0+
8	TMDS 0
9	TMDS 0-
10	TMDS
11	TMDS
12	TMDS -
13	CEC
14	(N.C.)

15	DDC (SCL)
16	DDC (SDA)
17	DDC/CEC
18	+5 V
19	

(DDC)

(EDID)

(USB)

USB



: このモニタはSuper-Speed USB 3.0互換です。

	5G bps	4.5W(,)
	480M bps	4.5W(,)
	12M bps	4.5W(,)



*: BC1.2


USB



)

1.5A

USB



	9
1	VCC
2	D-
3	D+
4	GND
5	SSTX-
6	SSTX+
7	GND
8	SSRX-
9	SSRX+

USB



	9
1	VCC
2	D-
3	D+
4	GND
5	SSTX-
6	SSTX+

7	GND
8	SSRX-
9	SSRX+

USB

4 1 - - 2 , 2

USB



), 가 BC1.2


: USB 3.0 USB 3.0 가

: USB 가 가 가

() USB
 Microsoft® Windows Vista® Windows® 7.
 (, ,) () /

가 :

Microsoft® Windows Vista® Windows® 7.
 (Microsoft® Windows Vista® Windows® 7.)



가 :

--	--

1	xD- High Speed Memory Stick (HSMS) Memory Stick Pro Card (MS PRO), Memory Stick Duo() MS Duo Secure Digital(Mini-SD), Secure Digital Card, Mini Secure Digital() TransFlash(SD, SDHC) MultiMedia Card (MMC)
---	---

U2413/U2713H

			U2413/U2713H
MS Pro HG	Pro-HG가 USB3.0	32 GB	
MSDuo	Duo	32 GB	
SD	SD	32 GB	
MMC		32 GB	

OS USB 2.0/3.0 (USB)
 Microsoft® Windows Vista® Windows® 7

LCD

LCD

가
 : www.dell.com/support/monitors .



:



:

.가

가


가

가

가

Dell™ U2413/U2713H

- _____
- _____
- _____
- AX510/AY511 () _____
- _____
- () _____




- 1.
- 2.
3. 가




- 1.
2. (DVI-D) (DisplayPort/Mini DP/HDMI)


DVI




DisplayPort (Mini DP DP)




DisplayPort (DP DP)



HDMI




DP (MST)











U2413 /U2713H DP MST PC 가 MST DP1.2

U2413/U2713H DP 1.1a DP (DP1.2) DP DP1.2

1. OSD

Dell U2413 Energy Use 

 Brightness / Contrast	Aspect Ratio ▶ Wide 16:10
 Input Source	Sharpness ▶ 50
 Color Settings	Noise Reduction
 Display Settings	Dynamic Contrast
 PIP Settings	Uniformity Compensation ▶ Off
 Other Settings	Smart Video Enhance ▶ Movie
 Personalize	DisplayPort 1.2 ▶ Disable
	Display Info
	Reset Display Settings

 **Resolution: 1920 x 1200 @ 60Hz**



2. DisplayPort 1.2

3.

4. DP1.2 DP1.1a

Dell U2413/U2713H

Please ensure your Graphics Card can support DP MST(Daisy Chain)/HBR2(High Bit Rate) before changing the monitor setting to DP1.2.

Incorrect setting may result in blank screen on monitor .

Confirm

Exit

Dell U2413/U2713H


DP MST/HBR2 will be disabled for DP1.1a.



Confirm


Exit

B) 가 ()


1. OSD OSD .



2.   "DisplayPort" "Mini DisplayPort"



3.  8
4. DisplayPort 가



Dell U2413/U2713H

DisplayPort 1.2 ?

Enable

Disable



5.

DP 1.2



DP 1.1a



:

USB 3.0

DVI/Mini DP/DP/HDMI

USB 3.0

1. USB 3.0 ()

2. USB 3.0 USB 3.0

3.


4.

가 가 가

5.

USB 3.0 ()








(_____)

AX510/AY511 ()



:



:

+12V DC

1.

2. 가

3. DC (—).

4.




:

LCD




:



- 1.
- 2.
- 3.

()



(: M4 x 10 mm).

VESA

- 1.
- 2.
3. Philips
- 4.
- 5.



: /

6.30 kg UL


가

Dell™ U2413/U2713H










- _____
- _____
- OSD _____
- _____
- _____
- _____
- _____
- _____







OSD가







가		
1	 가 /	
2	 가 / /	/ /
3		DVI-D DisplayPort Mini DisplayPort HDMI   
4		(OSD) OSD
5		가 OSD
6	 ()	LED 가 LED U2413/U2713H가 DPMS



가		
1		OSD (가).
2		OSD ().
3		
4		

OSD

 : OSD 가 . OSD 가 .
 1.OSD  .

Dell U2413 Energy Use

Brightness/Contrast

- Input Source
- Color Settings
- Display Settings
- PIP Settings
- Other Settings
- Personalize

Brightness 50


Contrast 50

Resolution: 1920 x 1200 @ 60Hz




- 1. U2413 1920 x 1200 @ 60Hz U2713H 2560 x 1440 @ 60Hz
- 2.
- 3.
- 4.
- 5.
- 6. 가 OSD


	/	/
--	---	---





 (0 ~ 100).
 : Energy Smart Dynamic Contrast () 가


 (0 ~ 100).



 가 DVI-D , DisplayPort , Mini DisplayPort HDMI



Dell U2413 Energy Use

Brightness / Contrast	Input Color Format ▶ RGB
Input Source	Gamma ▶ PC
Color Settings	Preset Modes ▶ Standard
Display Settings	Reset Color Settings
PIP Settings	
Other Settings	
Personalize	

Resolution: 1920 x 1200 @ 60Hz



Dell U2413 Energy Use

RGB: 가 DVI DVD DVD RGB가
YPbPr: 가 YPbPr-DVI DVD DVD RGB가

Brightness / Contrast	Input Color Format ✓ RGB
Input Source	Gamma YPbPr
Color Settings	Preset Modes
Display Settings	Reset Color Settings
PIP Settings	
Other Settings	
Personalize	

Resolution: 1920 x 1200 @ 60Hz



PC MAC

Dell U2413 Energy Use

Brightness / Contrast	Input Color Format
Input Source	Gamma
Color Settings	Preset Modes
Display Settings	Reset Color Settings
PIP Settings	
Other Settings	
Personalize	

Resolution: 1920 x 1200 @ 60Hz



Modes () Standard (), Multimedia (), Movie (), Game (), , , , Custom Color ()

Dell U2413 Energy Use

Brightness / Contrast	Input Color Format
Input Source	Gamma
Color Settings	Preset Modes
Display Settings	Reset Color Settings
PIP Settings	
Other Settings	
Personalize	

Resolution: 1920 x 1200 @ 60Hz



5000K, 5700K, 6500K, 7500K, 9300K 10000K
 Adobe RGB, sRGB, CAL1, CAL2

Color Space

- Adobe RGB
- sRGB
- CAL1
- CAL2



Adobe RGB: Adobe RGB (99%)

sRGB : 72% NTSC

CAL1 / CAL2: Dell Ultrasharp Dell

Dell Ultrasharp X-rite i1Display Pro i1Display Pro Dell Electronics,

: sRGB, AdobeRGB, CAL1 CAL2 RGB RGB

sRGB AdobeRGB Uniformity Compensation() Off()

Custom Color () :



(R, G, B)

Custom Color

- Gain
- Offset
- Hue
- Saturation



: RGB (100).

: RGB (50)

: RGBCMY

: RGBCMY



'0' '100'



touch



touch

: Movie () Game () 가



'0' '100'



touch

가



touch

가

: Movie () Game () 가



Dell U2413 Energy Use

- Brightness / Contrast
- Input Source
- Color Settings
- Display Settings
- PIP Settings
- Other Settings
- Personalize

- Aspect Ratio ▶ Wide 16:10
- Sharpness ▶ 50
- Noise Reduction
- Dynamic Contrast
- Uniformity Compensation ▶ Off
- Smart Video Enhance ▶ Movie
- DisplayPort 1.2 ▶ Disable
- Display Info
- Reset Display Settings

Resolution: 1920 x 1200 @ 60Hz



Aspect Ratio ()

Smart Video Enhance

DisplayPort 1.2

16:10, 16:9, 4:3, 1:1

16:10 U2713H

가

2M:1

가

: Game () Movie () 가

Dell

Smart Video Enhance "Movie"

Smart Video Enhance () 2

가

: (SVE) (가)

DisplayPort 1.2

DP MST() HBR2 DP1.2

: DP1.2 가



PIP

U2413					U2713H				
Main Window	Sub-Window				Main Window	Sub-Window			
	DVI-D	DP	Mini DP	HDMI		DVI-D	DP	Mini DP	HDMI
DVI-D	X	✓	✓	✓	DVI-D	X	✓	✓	X
DP	✓	X	X	✓	DP	✓	X	X	✓
Mini DP	✓	X	X	✓	Mini DP	✓	X	X	✓
HDMI	✓	✓	✓	X	HDMI	X	✓	✓	X

: PBP

PIP/PBP 가 PIP/PBP


Dell U2413 Energy Use ■■■■■■■■■■ ■■■■■■■■■■

- Brightness / Contrast** PIP Mode ▶ Off
- Input Source**
- Color Settings**
- Display Settings**
- PIP Settings**
- Other Settings**
- Personalize**

Resolution: 1920 x 1200 @ 60Hz



PIP/PBP 가 PIP/PBP



PIP

가 가 : PIP (Picture in Picture) PBP (Picture by Picture)



"Off" (), "PIP" "PBP"

PIP



PIP



PIP/PBP



가








가 가

OSD 가

OSD






	OSD 8 () 가
	  (: 0 - : 100).
	OSD : 가 OSD가   5 60 1
	: OSD가 OSD OSD " " 가 가
	가
	가 Dell Display Manager(DDM) PC 가 가 () OSD가
	: Auto Rotate() PIP/PBP가
	OSD

DDC/CI

DDC/CI (/) (,)


Dell U2413 Energy Use 

Brightness / Contrast	Language
Input Source	Menu Transparency
Color Settings	Menu Timer
Display Settings	Menu Lock
PIP Settings	Menu Button Sound
Other Settings	Auto Rotate
Personalize	Energy Smart
	Menu Location
	Power Save Audio
DDC/CI	<input checked="" type="checkbox"/> Enable
LCD Conditioning	<input type="checkbox"/> Disable
Factory Reset	

Resolution: 1920 x 1200 @ 60Hz



LCD

Dell U2413 Energy Use 


Brightness / Contrast	Language
Input Source	Menu Transparency
Color Settings	Menu Timer
Display Settings	Menu Lock
PIP Settings	Menu Button Sound
Other Settings	Auto Rotate
Personalize	Energy Smart
	Menu Location
	Power Save Audio
DDC/CI	<input checked="" type="checkbox"/> Enable
LCD Conditioning	<input checked="" type="checkbox"/> Enable
Factory Reset	<input type="checkbox"/> Disable








Resolution: 1920 x 1200 @ 60Hz




OSD

"Preset Modes ()", "Brightness/Contrast (/)", "Input Source ()", 가

Dell U2413 Energy Use 

 Brightness / Contrast	Shortcut Key 1	▶ Preset Modes
 Input Source	Shortcut Key 2	▶ Brightness/Contrast
 Color Settings	Shortcut Key 3	▶ Input Source
 Display Settings	Reset Personalize	
 PIP Settings		
 Other Settings		
 Personalize		

 Resolution: 1920 x 1200 @ 60Hz

▲
▼
→
✖

OSD

Game () Movie ()

Energy Smart

Dell U2413/U2713H

To allow manual adjustment of brightness, the Energy Smart / Dynamic

Contrast will be switched off.

Do you want to continue?

No

Yes

가 가 :

Dell U2413

The current input timing is not supported by the monitor display. Please
change your input timing to **1920 x 1200 @ 60Hz** or any other monitor
listed timing as per the monitor specifications.



Dell U2713H

The current input timing is not supported by the monitor display. Please
change your input timing to **2560 x 1440 @ 60Hz** or any other monitor
listed timing as per the monitor specifications.



가 가 : 가

1920 x 1200 (U2413)/2560 x 1440 (U2713H)

Dell U2413/U2713H

The function of adjusting display setting using PC application will be disabled.

Do you wish to disable DDC/CI function?

No

Yes

가 가 가 :

Dell U2413/U2713H

Entering Power Save Mode.



OSD

가 가 :

DVI-D/DP/Mini DP/HDMI

Dell U2413/U2713H

There is no signal coming from your computer. Press any key on the keyboard or move the mouse to wake it up. If there is no display, press the monitor button now to select the correct Input source on the On-Screen-Display menu.



Uniformity Compensation() " " /

Dell U2413/U2713H

To allow manual adjustment of brightness / Contrast , the Uniformity Compensation will be switched off.





Do you want to continue?

No

Yes

DVI, DP, Mini DP HDMI

가



Windows Vista® Windows® 7 Windows® 8

1. Windows® 8
- 2.
- 3.
- 4.

Desktop ()

Screen resolution ()

1920 x 1200 (U2413) 2560 x 1440 (U2713H)

가


Dell

<http://support.dell.com>

IDell ()가

2


LED, 2



- 1.
- 2.
- 3.
- 4.



가



:




:

115 mm



() () 가 가



☒ : (가)

☒ : (3D) 가



: Dell

- 1.
- 2.
3. ATI
nVidia
Intel®

nVidia

NVRotate



: <http://support.dell.com>

가

가

Dell™ U2413/U2713H

- 가
-
-
-
- USB
- Dell™
-



가

가

가

가

가

- 1.
- 2.
- 3.

가


가 ()

가

LED가


가

Dell U2413/U2713H




No DVI-D Cable

The display will go into Power Save Mode in 5 minutes.




Dell U2413/U2713H




No DisplayPort Cable

The display will go into Power Save Mode in 5 minutes.




Dell U2413/U2713H




No Mini DisplayPort Cable

The display will go into Power Save Mode in 5 minutes.




Dell U2413/U2713H



No HDMI Cable

The display will go into Power Save Mode in 5 minutes.




- 4.
- 5.

가



:

가 가



1. (가).
2. 가 가
3. 1 4 2
- 4.
5. 4
- 6.
7. 5 6 가 4

가

/ LED		가
		가

/ LED		OSD 가 가
/		U2713H : DVI () 가
	LCD	가 LCD : www.dell.com/support/monitors .
	LCD	가 LCD : www.dell.com/support/monitors .
		OSD
	가	
가 /		가 가 U2713H : DVI () 가
		가 가 U2713H : DVI () 가
	가 가	
		가 가 가
		가
		OSD OSD OSD PC RGB YPbPr 가 OSD R/G/B
		()

가	가	OSD
	OSD가	OSD 가 가 10 . Menu lock()
가	, LED	가
가		DVD () 가
DP PC 가		DP (DP 1.1a DP 1.2) DP 1.1a DP 1.2 DP "DP MST" 가

(USB)

USB 가	USB 가	가 USB (가) HDD USB
USB 3.0 가	USB 3.0 가	가 USB 3.0 USB 3.0 USB 2.0 USB 1.1 가 USB 가 USB ()



가		가 (/ LED)가 가
가		Windows (CD MP3) (CD)
가	가	Windows 가 (CD , MP3)
가	가	가 /

	가	Windows 가 (/) (CD)
		Windows / (CD , MP3)

△ : 가 가

(Windows® XP only)		가 A. (Manage) (Disk Management) B. (Removable Device) (Change Drive Letter and Paths) C. D. (OK) , (OK)
가	"Error copying file or folder ()" () () " , 가 " () () 가	/
가 , LED 가	가 , LED 가	
가		가

가

Dell™ U2413/U2713H

가



FCC ()

Dell



:



:

,

,

/

가

FCC ()

For FCC

www.dell.com/regulatory_compliance

Dell

800-WWW-DELL(800-999-3355)



:

Dell

Dell

가

가

가

1. www.dell.com/support/monitors

Dell

:

1. support.dell.com

2. 가/

3.

4.

5. Dell

가

가

Dell™ U2413/U2713H

가

Microsoft® Windows®

1920 x 1200 (U2413) / 2560 x 1440 (U2713H)

Windows Vista® Windows® 7 Windows® 8 :

1. Windows® 8 Desktop ()

2. Screen resolution ()

3. **1920 x 1200 (U2413) 2560 x 1440 (U2713H)**

4. (OK)

가

가

1: **Dell™ desktop or a Dell™ Dell.**

2: **Dell™**

가

가

Dell™ U2413/U2713H


가

Dell™

Dell™

1. <http://support.dell.com>

2. (U2713H) 1920 x 1200 (U2413)/2560 x 1440

 : 1920 x 1200/2560 x 1440
Dell.

가

가

Dell™ U2413/U2713H

가

Dell™

Windows Vista®

Windows® 7

Windows® 8

:

1. Windows® 8

Desktop()

2.

3.

4.

5.

(: NVIDIA, ATI, Intel).

6.

(: <http://www.ATI.com> [http://](http://www.NVIDIA.com)

www.NVIDIA.com).

7.

1920 x 1200 (U2413)/**2560 x 1440**

(U2713H)



:

가