

Dell™ PowerEdge™ Systems
Dell Oracle Database 10g R2
Standard Edition on
Microsoft® Windows Server®
2003 R2 with SP2,
Standard x64 Edition

Deployment Guide Version 4.0



Notes and Cautions



NOTE: A NOTE indicates important information that helps you make better use of your computer.



CAUTION: A CAUTION indicates potential damage to hardware or loss of data if instructions are not followed.

Information in this document is subject to change without notice.

© 2008 Dell Inc. All rights reserved.

Reproduction of these materials in any manner whatsoever without the written permission of Dell Inc. is strictly forbidden.

Trademarks used in this text: *Dell*, the *DELL* logo, *OpenManage*, *PowerEdge*, and *PowerVault* are trademarks of Dell Inc.; *Intel* and *Xeon* are registered trademarks of Intel Corporation; *EMC*, *Navisphere*, and *PowerPath* are registered trademarks of EMC Corporation; *Microsoft*, *Windows*, and *Windows Server* are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries; *AMD* and *Opteron* are trademarks of AMD Corporation.

Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell Inc. disclaims any proprietary interest in trademarks and trade names other than its own.

October 2008

Rev. A08

Contents

Terminology Used in this Document	7
Software and Hardware Requirements	8
Minimum Software Requirements	8
Minimum Hardware Requirements for Direct-Attached SAS or Fibre Channel Cluster Configurations	8
Installing and Configuring the Operating System	10
Installing the Operating System Using the Deployment CD/DVDs	10
Verifying the Temporary Directory Paths	14
Verifying Cluster Hardware and Software Configurations	14
Setting Up Your Fibre Channel Cluster	15
Before You Begin	17
Cabling Your Dell EMC Fibre Channel Storage	17
Setting Up Your SAS Cluster with a PowerVault MD3000	19
Before You Begin	20
Cabling Your SAS Storage System	20
Configuring Networking and Storage for Oracle RAC 10g R2	21
Configuring the Public and Private Networks	22
Installing the Host-Based Software Needed for Storage	27
Verifying the Storage Assignment to the Nodes	28
Preparing the Disks for Oracle Clusterware	29
Removing the Assigned Drive Letters	33

Installing Oracle RAC 10gR2 Using ASM	33
Installing Oracle Clusterware Version 10.2.0.1	33
Installing Oracle10g Database With Real Application Clusters 10.2.0.1.	35
Installing Patchset 10.2.0.4	37
Configuring the Listener	38
Creating the Seed Database	39
Configuring and Deploying Oracle Database 10g (Single Node).	43
Installing Oracle Clusterware Version 10.2.0.1	43
Installing Oracle10g Database With Real Application Clusters 10.2.0.1.	45
Installing Patchset 10.2.0.4	46
Configuring the Listener	48
Creating the Seed Database	48
Adding a New Node to an Existing Oracle 10g RAC Cluster.	52
Preparing the Node to be Added to a Cluster	52
Adding Nodes at the Oracle Clusterware Layer	53
Adding Nodes at the Oracle RAC Database Layer	54
Adding Database Instances to New Nodes	54
Troubleshooting	55
Working Around Clusterware Installation Failure	55
Uninstalling Oracle Clusterware	56
Additional Troubleshooting	60
Getting Help	66
Dell Support.	66
Oracle Support	66
Obtaining and Using Open Source Files.	66

Index 69

This document provides information about installing, configuring, reinstalling, and using your Oracle Database 10g R2 software following Dell's Supported Configurations for Oracle.

Use this document in conjunction with the *Dell Deployment* CD to install your software. If you install your operating system using only the operating system CDs, the steps in this document may not be applicable.

This document covers the following topics:

- Software and hardware requirements
- Installing and configuring Microsoft® Windows Server® 2003 R2 with SP2, Standard x64 Edition
- Verifying cluster hardware and software configurations
- Configuring networking and storage for Oracle Database Real Application Clusters (RAC) 10g R2
- Installing Oracle Database RAC 10g R2 10.2.0.4 *patchset* and software updates
- Supported software stack
- Troubleshooting
- Getting help

For more information on Dell's Supported Configurations for Oracle, see the Dell and Oracle website at dell.com/10g.

If you purchased the Oracle Database RAC 10g Deployment Service, your Dell Professional Services representative will assist you with the following:

- Verifying cluster hardware and software configurations
- Configuring networking and storage
- Installing Oracle Database RAC 10g R2 10.2.0.4 *patchset* and software updates

Terminology Used in this Document

This document uses the terms *logical unit number* (LUN) and *virtual disk*. These terms are synonymous and can be used interchangeably. The term *LUN* is commonly used in a Dell|EMC Fibre-Channel storage system

environment and *virtual disk* is commonly used in a Direct-attached SAS (Dell MD3000/MD3000i and Dell MD3000/MD3000i with MD1000 expansion) storage environment.

Software and Hardware Requirements

The following sections describe the minimum software and hardware requirements for Dell's Supported Configurations for Oracle.

Minimum Software Requirements

Table 1-1 lists the minimum software requirements.



 **NOTE:** Your Dell configuration includes a 30-day trial license of Oracle software. If you do not have a license for this product, contact your Dell sales representative.

Table 1-1. Software Requirements

Software Component	Configuration
Microsoft Windows Server 2003 R2	Standard x64 Editions
Oracle10g R2	Version 10.2.0.1 Standard Edition, including the RAC option for clusters Oracle Patchset 10.2.0.4
EMC® PowerPath® (Fibre Channel clusters only)	Version 5.2

Minimum Hardware Requirements for Direct-Attached SAS or Fibre Channel Cluster Configurations

Table 1-2 lists the minimum hardware requirements for direct-attached SAS or fibre channel cluster configurations. For more information on specific hardware components, see the documentation included with your system.

 **NOTE:** Depending on the number of users, the application you use, your batch processes, and other factors, you may need a system that exceeds the minimum hardware requirements to achieve your desired performance.


 **NOTE:** The hardware configuration of all the cluster nodes should be identical.


Table 1-2. Minimum Hardware Requirements - Direct-Attached SAS or Fibre Channel Cluster Configurations

Hardware Component	Configuration
Dell PowerEdge 1950, 2900, 2950, 1950 III, 2900 III, 2950 III system (up to 2 nodes)	<p>Intel® Xeon® processor family.</p> <p>1 GB of RAM.</p> <p>Two 73-GB hard drives connected to an internal RAID controller.</p> <p>NOTE: Dell recommends two 73-GB hard drives (RAID 1) connected to an internal RAID controller based on your system. See your PowerEdge system documentation for more details.</p> <p>Three Gigabit Network Interface Cards (NICs).</p> <p>Two Host Bus Adapters (HBAs) (1 QLE2462 or QLE2562[dual port] HBA for use with PowerEdge 1950 or 1950 III).</p>
Dell PowerEdge 2970, R805 system (up to 2 nodes)	<p>AMD™ Opteron™ processor family.</p> <p>1 GB of RAM.</p> <p>Two 73-GB hard drives connected to an internal RAID controller.</p> <p>NOTE: Dell recommends two 73-GB hard drives (RAID 1) connected to an internal RAID controller based on your system. See your PowerEdge system documentation for more details.</p> <p>Three Gigabit Network Interface Cards (NICs).</p> <p>Two host bus adapters (HBAs) for PowerEdge 2970.</p>
Gigabit Ethernet switch (two required)	See dell.com/10g for information on supported configurations.

Table 1-2. Minimum Hardware Requirements - Direct-Attached SAS or Fibre Channel Cluster Configurations (continued)

Hardware Component	Configuration
For Fibre Channel: Dell EMC CX3-10C, CX3-20 (C/F), CX4-120, CX4-240, CX4-480, CX4-960, AX4-5F Fibre Channel storage system	See the Dell EMC system documentation for more details.
For Direct-attached SAS: Dell™ PowerVault™ MD3000 with MD1000 expansion storage system.	See your Dell™ PowerVault™ MD3000 and MD1000 storage system documentation for more details.


Installing and Configuring the Operating System

 **CAUTION:** To ensure that the operating system is installed correctly, disconnect all external storage from the system **before** you install the operating system.


This section provides information about installing and configuring the Windows Server 2003 SP2 Standard x64 Edition operating system for Oracle deployment.

Installing the Operating System Using the Deployment CD/DVDs


Repeat the steps in this section for all nodes in the cluster.

 **NOTE:** See the Dell Support website at support.dell.com for the latest BIOS, firmware, and driver updates.

- 1 Shut down your system.
- 2 Disconnect all external storage devices from your system.
- 3 Locate the *Microsoft Windows Server 2003 R2 Standard/Enterprise x64 Edition SP2 CD* and the *Dell Systems Management Tools and Documentation version 5.5 DVD* for your Dell Server.

 **NOTE:** The *Dell Systems Management version 5.5 DVD* is packaged with your Dell server.

- 4 Start up your system.
- 5 Insert the *Dell Systems Management version 5.5 DVD* in your system drive.

 **NOTE:** If your server does not have a CD/DVD drive, you can use an externally-attached USB CD/DVD drive.

The boot menu screen appears.

6 In the **Select Language Screen**, select **English**.

7 On the **Software License Agreement** page, click **Accept**.

The **Systems Build and Update Utility** home page appears.

8 From the **Dell Systems Build and Update Utility** home page, click **Server OS Installation**. The **Server OS Installation** screen appears.

The Server Operating System Installation (SOI) module in the Dell™ Systems Build and Update Utility enables you to install Dell-supported operating systems on your Dell systems.



NOTE: For more information on the specific SOI screens, see the Dell Systems Build and Update Utility online help.

The following steps will guide you through the SOI.

Set Date and Time:

a Set the current date and time and the time zone, then click **Continue**.

Select Operation System:

b Select **Microsoft Windows Server 2003 Service Pack 2 x64 Edition**.

c Select **Yes for Create Utility Partition**.

d Click **Continue**.

Configure RAID



NOTE: This menu may not appear depending on the system

e Choose default selections and click **Continue**.

Configure Physical disk:

f Choose default selections and click **Continue**.

Network Configuration:

g Choose default selections and click **Continue**.



NOTE: To configure the public network properly, the computer name and public host name must be identical.

Enter OS Information:

- h** Enter the appropriate **User Name**, **Organization**, and **Product ID**.
- i** Enter all other necessary information.
- j** Install **SNMP** (default).



NOTE: If you have the *Dell OpenManage* CD and want to install it during your OS install, select **Install Server Administrator**. The **Server Administrator** can be installed anytime after the OS is installed.

Installation Summary:

- k** Eject **CD/DVD Automatically** (default).



NOTE: Once you click **Continue**, the installation begins and you cannot change the configuration details of your system.

- l** Click **Continue**.

The Microsoft Windows Server 2003 Service Pack 2 x64 Edition Installation Wizard appears and the installation begins.



NOTE: This procedure may take several minutes to complete.

- m** When prompted, insert the *Windows Server 2003 Service Pack 2 x64 Standard Edition CD* in the CD drive.



NOTE: This procedure may take several minutes to complete.



NOTE: If you selected **Install Server Administrator** in the OS installation steps, the prompt will ask you to insert the *Dell OpenManage™* CD prior to installing the *Windows Server 2003 Service Pack 2 x64 Edition CD*.


- n** When the installation is completed, remove the CD from CD/DVD drive and click **Finish**.


The system reboots, copying the OS information to the Deployment partition, and the installation continues.




NOTE: This procedure may take several minutes to complete.

- 9** In the **Personalize Your Software** window in the **Name** and **Organization** fields, enter the appropriate information and click **Next**.
- 10** When prompted, enter your **Product Key** for Windows Server 2003 SP2 Standard x64 Edition and click **Next**.
- 11** In the **Computer Name** and **Administrator** password fields, enter the appropriate information and click **Next**.

 **CAUTION:** Do not leave the administrator password blank.

 **NOTE:** To configure the public network properly, the computer name and public host name must be identical.


 **NOTE:** Record the password that you created in this step. You will need this information in step 14.

When the installation procedure completes, the **Welcome to Windows** window appears.

12 Shut down the system, reconnect all external storage devices, and restart the system.

13 In the **Welcome to Windows** window, press <Ctrl><Alt><Delete> to continue. The **Log On** window appears.

14 In the **Password** field, enter the administrator password that you created in step 11 in this procedure and click **OK**. You will be prompted to insert the *Windows Server* CD2. You can insert the *Windows Server* CD2 or select **Cancel**.

 **NOTE:** If you insert the *Windows Server* CD2, follow the prompts through the normal installation process. The following process assumes you are not inserting the *Windows Server* CD2.


15 Select **Cancel**. You will be prompted that media on *Windows Server* CD2 will not be installed.

16 Select **OK**. You will be prompted to configure Windows Server Post-Setup (optional).

17 Select **Finish**. You will be prompted to close the page.

18 Select **Yes**. The **Manage Your Server** windows management window displays.

19 Close the window.


 **NOTE:** To use the Broadcom Advanced Control Suite 3 (BACS), install Microsoft .NET Framework 2.0. The Microsoft .NET Framework 2.0 can be downloaded from www.microsoft.com

Installing the Resource CD:

20 Insert the CD labeled *Dell RCD x64 4.0*.


21 Go to **My Computer** and double-click your CD-ROM drive.

22 Run `install_drivers.bat`

 **NOTE:** This procedure may take several minutes to complete.

23 Press any key to continue.

24 Check the logs to verify that all drivers were installed correctly.

 **NOTE:** Log information can be found at: `C:\Dell_Resource_CD\logs`

25 When installation is complete, remove the CD from the CD drive.

26 Reboot your system.

Verifying the Temporary Directory Paths

Verify that the paths to the **Temp** and **Tmp** directories have been set correctly. Repeat the following steps for all nodes in the cluster.

- 1 Click **Start** and select **Run**.
- 2 In the **Open** field, enter `cmd` and click **OK**.
- 3 At the command prompt, enter `echo %Temp%`. The following path appears:

```
%SystemDrive%\Temp
```

where `%SystemDrive%` is the user's local drive.

- 4 At the command prompt, enter `echo %Tmp%`. The following path appears:

```
%SystemDrive%\Temp
```

where `%SystemDrive%` is the user's local drive.

- 5 Repeat all steps in this section for all nodes in the cluster.

Verifying Cluster Hardware and Software Configurations

Before you begin the cluster setup, ensure that you have the minimum hardware installed as shown in Table 1-2. This section provides setup information for hardware and software cluster configurations.

Each node must have the following software installed:

- Windows Server 2003 SP2 Standard x64 Edition (see Table 1-1)

- HBA drivers.
- *PowerVault MD3000 Resource* CD (when using the PowerVault MD3000 as backend storage)

The storage must be configured with a minimum of four virtual disks/LUNs (two for the redundant Voting Disk and Oracle Cluster Registry and two for the database and Flash Recovery area) assigned to cluster nodes.


Table 1-3. Virtual Disk (LUN) Configuration and Sizes

Virtual Disk/LUN	Minimum Size	Number of Partitions	Used for
1	2 GB	5 (3 x 50 MB and 2 x 120 MB)	Voting disk (3 x 50 MB) Oracle Registry (2 x 120 MB)
2	Larger than the database	1	Database
3	At least twice the size of the database	1	Flash Recovery Area

Setting Up Your Fibre Channel Cluster

After a Dell Managed Services representative completes the setup of your Fibre Channel cluster, verify the hardware connections and the hardware and software configurations as described in this section. Figure 1-1, Figure 1-2, and Table 1-4 illustrate the required cluster connections for a storage area network (SAN)-attached Fibre Channel cluster with two nodes.

Figure 1-1. Hardware Connections for a SAN-attached Fibre Channel Cluster



Dell | EMC CX3-10c, CX3-20, CX3-20F, CX3-40, CX3-40F, CX3-80, CX4-120, CX4-240, CX4-480, CX4-960, and AX4-5F Fibre Channel storage systems

Table 1-4. Fibre Channel Hardware Interconnections

Cluster Component	Connections
PowerEdge system node	<p>One CAT 5e/6 cable from public NIC to the local area network (LAN)</p> <p>One CAT 5e/6 cable from private Gigabit NIC to Gigabit Ethernet switch (private network)</p> <p>One CAT 5e/6 cable from redundant private Gigabit NIC to redundant Gigabit Ethernet switch (private network)</p> <p>One optical cable from optical HBA 0 to Fibre Channel switch 0 and one optical cable from HBA 1 to switch 1</p>

Table 1-4. Fibre Channel Hardware Interconnections (continued)

Cluster Component	Connections
Dell EMC Fibre Channel storage system	Two CAT 5e/6 cables connected to LAN (one from each storage processor) One to four optical connections to each Fibre Channel switch in a SAN-attached configuration See "Cabling Your Dell EMC Fibre Channel Storage" on page 17 for more information.
Dell EMC Fibre Channel switch	One optical connection to each PowerEdge system's HBA and one optical connection to a port on each storage processor
Gigabit Ethernet switch	One Cat 5e/6 connection to the private Gigabit NIC on each PowerEdge system One Cat 5e/6 connection to the other Gigabit Ethernet switch

Before You Begin

Verify that the following tasks have been completed for your cluster:

- All hardware is installed in the rack.
- All hardware interconnections are configured.
- All virtual disks/LUNs, RAID groups, and storage groups are created on the storage system.
- Storage groups are assigned to the cluster nodes.




CAUTION: Before you perform the procedures in the following sections, ensure that the system hardware and cable connections are installed correctly.

Cabling Your Dell|EMC Fibre Channel Storage

You can configure your Oracle cluster storage system in a four-port SAN-attached configuration, depending on your needs. See the following procedures for both configurations.

Figure 1-2 illustrates the hardware connections used in setting up a SAN-attached Fibre Channel cluster.

Figure 1-2. Cabling in a Dell|EMC SAN-Attached Fibre Channel Cluster



Use the following procedure to configure your Oracle cluster storage system in a four-port, SAN-attached configuration.

- 1 Connect one optical cable from SP-A port 0 to Fibre Channel switch 0.
- 2 Connect one optical cable from SP-A port 1 to Fibre Channel switch 1.
- 3 Connect one optical cable from SP-B port 0 to Fibre Channel switch 1.
- 4 Connect one optical cable from SP-B port 1 to Fibre Channel switch 0.
- 5 Connect one optical cable from HBA 0 on node 1 to Fibre Channel switch 0.
- 6 Connect one optical cable from HBA 1 on node 1 to Fibre Channel switch 1.
- 7 Connect one optical cable from HBA 0 of each additional node to Fibre Channel switch 0.

- 8 Connect one optical cable from HBA 1 of each additional node to Fibre Channel switch 1.

Setting Up Your SAS Cluster with a PowerVault MD3000

To configure your PowerEdge Systems and PowerVault MD3000 hardware and software to function in an Oracle Real Application Cluster environment, verify the following hardware connections and the hardware and software configurations as described in this section using Figure 1-3, Table 1-5, Figure 1-4 and Table 1-3.

Figure 1-3. Cabling the SAS Cluster and PowerVault MD3000




Table 1-5. SAS Cluster Hardware Interconnections

Cluster Component	Connections
PowerEdge system node	<p>One CAT 5e/6 cable from public NIC to the local area network (LAN)</p> <p>One CAT 5e/6 cable from private Gigabit NIC to Gigabit Ethernet switch (private network)</p> <p>One CAT 5e/6 cable from redundant private Gigabit NIC to redundant Gigabit Ethernet switch (private network)</p> <p>Two SAS connections to a PowerVault MD3000 storage system node using a SAS 5/E. See "Cabling Your SAS Storage System" on page 20</p>
Dell PowerVault MD3000	<p>Two CAT 5e/6 cables connected to a LAN (one from each storage processor module)</p> <p>Two SAS connections to each PowerEdge system node using a SAS 5/E controller. See "Cabling Your SAS Storage System" on page 20</p>
Gigabit Ethernet switch	<p>One Cat 5e/6 connection to the private Gigabit NIC on each PowerEdge system</p> <p>One Cat 5e/6 connection to the other Gigabit Ethernet switch</p>

Before You Begin

Verify that the following tasks have been completed for your cluster:

- All hardware is installed in the rack.
- All hardware interconnections are configured.
- All virtual disks/LUNs, RAID groups, and storage groups are created on the storage system.
- Storage groups are assigned to the cluster nodes.



CAUTION: Before you perform the procedures in the following sections, ensure that the system hardware and cable connections are installed correctly.


Cabling Your SAS Storage System

Because SAS clusters can only be installed in a direct-attached cluster, they are limited to two nodes only.

To configure your nodes in a direct-attached configuration (see Figure 1-4), complete the following steps:

- 1** Connect one SAS cable from a port of the SAS controller of node 1 to the In-0 port of RAID controller 0 in the MD3000 RAID enclosure.
- 2** Connect one SAS cable from a port of the other SAS controller of node 1 to the In-0 port of RAID controller 1 in the MD3000 RAID enclosure.
- 3** Connect one SAS cable from a port of the SAS controller of node 2 to the In-1 port of RAID controller 0 in the MD3000 RAID enclosure.
- 4** Connect one SAS cable from a port of the other SAS controller of node 2 to the In-1 port of RAID controller 1 in the MD3000 RAID enclosure.


Figure 1-4. Cabling in a Direct-attached SAS Cluster




Configuring Networking and Storage for Oracle RAC 10g R2

This section provides the following information about network and storage configuration:

- Configuring the public and private networks.
- Verifying the storage configuration.
- Configuring the shared storage for Oracle Clusterware and the Oracle Database.

 **NOTE:** Oracle RAC 10g R2 is a complex database configuration that requires an ordered list of procedures. To configure networking and storage in a minimal amount of time, perform the following procedures in order.

Configuring the Public and Private Networks

 **NOTE:** Each node requires a unique public and private internet protocol (IP) address and an additional public IP address to serve as the virtual IP address for the client connections and connection failover. The virtual IP address must belong to the same subnet as the public IP address. All public IP addresses, including the virtual IP address, should be registered with the domain naming system (DNS). If a DNS server is not available, the IP addresses have to be registered in the hosts file on all cluster nodes.

Depending on the number of NIC ports available, configure the public and private interfaces as shown in Table 1-6.


Table 1-6. NIC Port Assignments

NIC Port	Three Ports Available	Four Ports Available
1	Public IP and virtual IP	Public IP
2	Private IP (NIC team)	Private IP (NIC team)
3	Private IP (NIC team)	Private IP (NIC team)
4	NA	Optional Public team or 3 member Private Team

Configuring and Teaming the Private Network

Before you deploy the cluster, assign a private IP address and host name to each cluster node. This procedure ensures that the nodes can communicate with each other through the private interface.

Table 1-7 provides an example of a network configuration for a two-node cluster.

 **NOTE:** This example assumes all the IP addresses are registered in the hosts file of all cluster nodes.


 **NOTE:** The two bonded NIC ports for a private network should be on separate PCI buses. For example, a bonded pair can consist of one on-board NIC and one add-on NIC card.

Table 1-7. Network Configuration Example for a Two-Node Cluster

Host Name	Type	IP Address	Registered In
rac1	Public	155.16.170.1	%SystemRoot%\system32\drivers\etc\hosts
rac2	Public	155.16.170.2	%SystemRoot%\system32\drivers\etc\hosts
rac1-vip	Virtual	155.16.170.201	%SystemRoot%\system32\drivers\etc\hosts
rac2-vip	Virtual	155.16.170.202	%SystemRoot%\system32\drivers\etc\hosts
rac1-priv	Private	10.10.10.1	%SystemRoot%\system32\drivers\etc\hosts
rac2-priv	Private	10.10.10.2	%SystemRoot%\system32\drivers\etc\hosts

Configuring NIC Teaming For Your Private Network Adapters



NOTE: TCP Offload Engine (TOE) functionality of a TOE-capable NIC is not supported in this solution.

- 1 On node 1, identify two network adapters that will be used for NIC teaming.
- 2 Connect an Ethernet cable from each selected network adapter to the private network switch.
- 3 If node 1 is configured with Broadcom NICs, go to step 4. If node 1 is configured with Intel NICs, configure NIC teaming by performing the following steps:
 - a Right-click **My Computer** and select **Manage**.
 - b In the **Computer Management** window, select **Device Manager**.
 - c Expand the **Network Adapters** tab.
 - d Right-click the **Intel NIC**, which is identified for NIC teaming and select **Properties**.
 - e Click the **Teaming** tab.
 - f Select **Team with other Adapters** and then select **New Team**.
 - g Specify a name for NIC team and click **Next**.
 - h In the **Select the adapters to include in this team** box, select the remaining network adapters that you identified for NIC teaming and click **Next**.
 - i In the **Select a team mode** list box, select **Adaptive Load Balancing**.
 - j Click **Finish** to complete the teaming.

- k In the **Team Properties** window, click **OK**.
 - l In the **Intel NIC's Properties** window, click **OK**.
 - m Close the **Computer Management** window.
- 4 If node 1 is configured with Broadcom NICs, configure NIC teaming by performing the following steps. If not go to step 5.



NOTE: Before you run the Broadcom Advanced Control Suite (BACS) to team the adapters, make sure your system has the Microsoft .NET Framework version 2.0 installed.

- a Click **Start → Programs → Broadcom → Broadcom Advanced Control Suite 3**

The **Broadcom Advanced Control Suite 3** window appears.

- b Highlight **Team Management**, and click **Teams** and select **Create a Team**.

The **Broadcom Teaming Wizard** window appears.

- c Click **Next**.

- d In the **Enter the name for the team** field, enter **Private** and click **Next**.

- e In the **Team Type** field, select **Smart Load Balancing (TM)** and **Failover (SLB)** and click **Next**.

- f In the **Assigning Team Members** window, in the **Available Adapters** box, select the network adapters you identified for NIC teaming and add them to the **Team Members** box.

- g Click **Next**.

- h In the **Designating Standby Member** window, select **Do not configure a Standby Member** and click **Next**.

- i In the **Configuring Live Link** window, select **No** and click **Next**.


- j In the **Creating/Modifying a VLAN** window, select **Skip Manage VLAN** and click **Next**.

- k In the last window, click **Preview** to verify the NIC team and the adapters. Once verified, select **Commit changes to system** and exit the wizard. Click **Finish**.


- l In the information message window click **Yes** to proceed.

- m In the **Broadcom Advanced Control Suite 3** window, click **File** then **Exit**.
- 5 Repeat step 1 through step 4 on the remaining nodes.


Configuring the IP Addresses for Your Public and Private Network Adapters

 **NOTE:** The TOE functionality of TOE-capable NIC is not supported in this solution.

- 1 Update the adapter's network interface name, if required. Otherwise, go to step 3.
 - a On node 1, click **Start**—**Settings**—**Control Panel**→**Network Connections**.
 - b In the **Network Connections** window, right-click the public network adapter you want to rename, and select **Rename**.

 **NOTE:** When you configure your network adapters on the cluster nodes, use identical names for the public adapters and the private adapters on all cluster nodes. Otherwise, the Oracle database installer generates an error and prevents you from completing the installation procedure.

- c Rename the public adapter name to **Public** and press <Enter>.
 - d Right-click the Private NIC team you want to rename and select **Rename**.
 - e Rename the Private NIC team to **Private** and press <Enter>.
- 2 Configure the IP addresses.


 **NOTE:** You must set a default gateway for your public interface, otherwise, the Clusterware installation may fail.

- a Click **Start**→**Settings**—**Control Panel**—**Network Connections**→**Public**—**Properties**.
- b Double-click **Internet Protocol (TCP/IP)**.
- c Click **Use the following IP address**, enter the required IP address, default gateway address, and the DNS server IP address, and click **OK**.
- d In the **Public Properties** window, select **Show icon in notification area when connected**.


The network adapter status will appear in the system tray after you perform the procedures in this section.

- e Click **OK**.


- f In the **Properties** window, click **Close**.
- g Repeat step a through step f for the Private NIC team.

 **NOTE:** Private NIC team does not require a default gateway address and DNS server entry.

- 3 Ensure that the public and private network adapters appear in the appropriate order for access by network services.
 - a On the Windows desktop, click **Start—Settings—Control Panel—> Network Connections**.
 - b In the **Network Connections** window, click **Advanced** and select **Advanced Settings**.
 - c Select the **Adapter and Bindings** tab.
 - d Ensure that the network adapters are listed in the following order:
 - Public
 - Private
 - <Any other network adapter>

 **NOTE:** Click the up- and down- arrows to change the adapter order.

- e Click **OK**.
 - f Close the **Network Connections** window.
- 4 On all nodes, add the public, private, and virtual IP addresses and host name to the %SystemRoot%\system32\drivers\etc\hosts file.


 **NOTE:** Add the public and virtual IP addresses to the hosts file only if they are not registered with the DNS server.

For example, the following entries use the adapter IP and host name as shown in Table 1-7:

```
IP AddressNode Name
155.16.170.1rac1
155.16.170.2rac2
10.10.10.1rac1-priv
10.10.10.2rac2-priv
```

155.16.170.201rac1-vip

155.16.170.202rac2-vip

 **NOTE:** Registering the private IP addresses with the DNS server is not required as the private network IP addresses are not accessible from the public network.

- 5 Repeat step 1 through step 4 on the remaining nodes.
- 6 Ensure that the cluster nodes can communicate with the public and private networks.
 - a On node 1, open a command prompt window.


b At the command prompt, enter:

```
ping <public_host_name>
```

```
ping <private_host_name>
```

where *<public_host_name>* and *<private_host_name>* are the host names for the public and private network adapters in the remaining node.

If the node's network adapters do not respond to ping commands, check your network configuration and then repeat this step.

 **NOTE:** Virtual internet protocol (VIP) is configured later and cannot be pinged at this point.

c Repeat step a through step b on the remaining nodes.

Installing the Host-Based Software Needed for Storage

To install the EMC Naviagent software using the EMC software that came with your Dell|EMC system, follow the procedures in your Dell|EMC documentation.


To install the necessary host-based storage software for the PowerVault MD3000 storage system, use the *Dell PowerVault Resource* CD software that came with your MD3000 storage system. Follow the procedures in your Dell documentation that is included with the PowerVault MD3000 storage system to install the "Modular Disk Storage Manager Software" on the Master node and the Multi-Path (MPIO) software on the remaining nodes.

Verifying the Storage Assignment to the Nodes

- 1 On the Windows desktop, right-click **My Computer** and select **Manage**.
- 2 In the **Computer Management** window, click **Device Manager**.
- 3 Expand **Disk drives**.
- 4 Under **Disk drives**, ensure that four small computer system interface (SCSI) disk devices appear for each LUN/virtual disk assigned in the storage.
- 5 Expand **Storage** and click **Disk Management**.

If the **Welcome to the Initialize and Convert Disk Wizard** appears, perform step a through step d. Otherwise, go to step 6.


- a In the **Welcome to the Initialize and Convert Disk Wizard** window, click **Next**.
- b In the **Select Disks to Initialize** window, in the **Disks** window, select the disks that are associated with your storage LUNs/virtual disks and click **Next**.
- c In the **Select Disks to Convert** window, deselect the disk(s) that you selected in step b and click **Next**.

 **NOTE:** This procedure ensures that your disks are configured as **Basic** disks.

- d Click **Finish**.
- 6 In the **Disk Management** window, verify that four disks appear. The disks should be similar in size to each other and to the LUNs/virtual disks that are assigned to the nodes in the storage system.
 - 7 Repeat step 1 through step 6 on the remaining nodes.

Installing Multi-Path Software for Storage

Follow the documentation accompanying the storage device to install the appropriate multi-path software.

 **NOTE:** In the case of a SAS (MD3000 storage system) cluster, the Multi-Path software should already be installed on your hosts as instructed in the section "Installing the Host-Based Software Needed for Storage" on page 27.

Installing PowerPath for Dell/EMC Systems

- 1 On node 1, install EMC[®] PowerPath[®].



NOTE: For more information, see the EMC PowerPath documentation that came with your Dell|EMC storage system.

- 2 When the installation procedure is complete, restart your system.
- 3 Repeat step 1 and step 2 on the remaining nodes.

Installing Multi-Path driver software for MD3000

- 1 On node 1, install the Multi-Path driver software from the *PowerVault MD3000 Resource CD*.



NOTE: For more information, see the documentation that came with your Dell MD3000 storage system.

- 2 When the installation procedure is complete, restart your system.
- 3 Repeat step 1 and step 2 on the other node.

Verifying Multi-Path Driver Functionality

- 1 Right-click **My Computer** and select **Manage**.
- 2 Expand **Storage** and click **Disk Management**. One disk appears for each LUN assigned in the storage.
- 3 Ensure that each LUN is configured as a **Basic** disk.
- 4 Repeat step 1 through step 3 on the remaining nodes.

Preparing the Disks for Oracle Clusterware

This section provides information for creating the logical drives for the following disks:

- Oracle Cluster Registry (OCR) disk — Contains the cluster configuration information
- Voting disk — Provides arbitration between the cluster nodes when the private network or attached storage is unavailable to one or more nodes
- Data and backup disks — Provide storage areas for creating the database (data disk) and saving the backup and log data (backup disk)

During the cluster configuration described in this document, you will create partitions on your shared storage. When you create the partitions, ensure that the cluster nodes can detect the LUNs or logical disks that are created in the attached storage system.

To prepare the disks for Oracle Clusterware, identify the OCR, voting, data and flash recovery area disks. After you identify the appropriate disks, perform the following steps on node 1.

Enabling the Automount Option for the Shared Disks

- 1** On node 1, click **Start** and select **Run**.
- 2** In the **Run** field, enter `cmd` and click **OK**.
- 3** At the command prompt, enter `diskpart`.
- 4** At the **DISKPART** command prompt, enter `automount enable`. The following message appears:

```
Automatic mounting of new volumes enabled.
```
- 5** At the **DISKPART** command prompt, enter `exit`.
- 6** Close the command prompt.
- 7** Repeat step 1 through step 6 on each of the remaining nodes.

Preparing the OCR and Voting Disks for Clusterware

- 1** On the Windows desktop, right-click **My Computer** and select **Manage**.
- 2** Expand **Storage** and click **Disk Management**. The storage disk that you initialized in the "Verifying Multi-Path Driver Functionality" on page 29 appears as **Unallocated**.
- 3** Right-click the partition area of the first shared disks assigned to the cluster nodes and select **New Partition**. The **Welcome to the New Partition Wizard** appears.
- 4** Click **Next**.
- 5** In the **Select Partition Type** window, select **Extended partition** and click **Next**.
- 6** In the **Specify Partition Size** window, accept the default partition size and click **Next**.
- 7** Click **Finish**.
The disk partition area you selected in step 3 is configured as an extended partition.
- 8** Repeat step 3 through step 7 on all shared disks that are assigned to the cluster nodes.

- 9** Create a logical drive for the OCR disk.
 - a** On the partition area of the disk identified for OCR and voting disk (1 GB LUN/virtual disk), right-click the free space and select **New Logical Drive**.

The **Welcome to the New Partition Wizard** appears.
 - b** Click **Next**.
 - c** In the **Select Partition Type** window, select **Logical drive** and click **Next**.
 - d** In the **Specify Partition Size** window, enter 120 in the **Partition size in MB** field and click **Next**.
 - e** In the **Assign Drive Letter or Path** window, select **Do not assign a drive letter or drive path** and click **Next**.
 - f** In the **Format Partition** window, select **Do not format this partition** and click **Next**.
 - g** Click **Finish**.
 - h** Repeat steps a through g to create an additional OCR disk.
- 10** Create a logical drive for the Voting Disk.
 - a** On the partition area of the disk identified for the OCR and voting disk (1 GB LUN/virtual disk), right-click the free space and select **New Logical Drive**. The **Welcome to the New Partition Wizard** appears.
 - b** Click **Next**.
 - c** In the **Select Partition Type** window, select **Logical drive** and click **Next**.
 - d** In the **Specify Partition Size** window, in the **Partition size in MB** field, enter 50 and click **Next**.
 - e** In the **Assign Drive Letter or Path** window, select **Do not assign a drive letter or drive path** and click **Next**.
 - f** In the **Format Partition** window, select **Do not format this partition** and click **Next**.
 - g** Click **Finish**.
 - h** Repeat steps a through g two times to create two additional voting disk partitions.



NOTE: If you are using Redundant Voting Disk and OCR, repeat the steps outlined in step 9 and step 10 for the redundant Voting Disk and OCR.

Preparing the Database Disk and Flash Recovery Area for Database Storage

This section provides information about creating logical drives that will be used to create ASM disk storage. ASM disk storage consists of one or more disk groups that can span multiple disks.

- 1** Create one logical drive for the Database.
 - a** Locate the disk that is assigned for the Oracle database.
 - b** On the disk partition area, right-click the free space and select **New Logical Drive**. The **Welcome to the New Partition Wizard** appears.
 - c** Click **Next**.
 - d** In the **Select Partition Type** window, select **Logical drive** and click **Next**.
 - e** In the **Specify Partition Size** window, enter the appropriate size in the **Partition size in MB** field and click **Next**.
 - f** In the **Assign Drive Letter or Path** window, select **Do not assign a drive letter or drive path** and click **Next**.
 - g** In the **Format Partition** window, select **Do not format this partition** and click **Next**.
 - h** Click **Finish**.
- 2** Create one logical drive for the Flash Recovery Area.
 - a** Locate the disk that is assigned for the Flash Recovery Area.
 - b** Perform step b through step h in step 1.
- 3** Restart all other nodes and log in as the administrator.

Removing the Assigned Drive Letters

- 1** On the Windows desktop for each node, right-click **My Computer** and select **Manage**.
- 2** In the **Computer Management** window, expand **Storage** and click **Disk Management**.

- 3** If you find any drive letters assigned to the drives that you created in "Preparing the OCR and Voting Disks for Clusterware" on page 30 perform the following steps:
 - a** Right-click the logical drive and select **Change Drive Letter and Paths**.
 - b** In the **Change Drive Letter and Paths** window, select the drive letter and click **Remove**.
 - c** In the **Confirm** window, click **Yes**.
 - d** Repeat step a through step c for the remaining logical drives on the storage partition.

Installing Oracle RAC 10g R2 Using ASM

This section provides the following information about installing the Oracle RAC 10g R2 software:

- Installing Oracle Clusterware Version 10.2.0.1
- Installing Oracle 10g Database with Real Application Clusters 10.2.0.1
- Installing Patchset 10.2.0.4
- Configuring the Listener
- Creating the Seed Database

Installing Oracle Clusterware Version 10.2.0.1

- 1** On node 1, insert the *Oracle Clusterware* CD into the CD drive.
The Oracle User Interface (OUI) starts and the **Welcome** screen appears.
If the **Welcome** screen does not appear:
 - a** Click **Start** and select **Run**.
 - b** In the **Run** field, enter the following, and click **OK**:
`%CD drive%\autorun\autorun.exe`
where `%CD drive%` is the drive letter of your CD drive.
- 2** In the **Oracle Clusterware** window, click **Install/Deinstall Products**.
- 3** In the **Welcome** screen, click **Next**.

- 4 In the **Specify Home Details** window, accept the default settings and click **Next**.



NOTE: Record the OraCR10g_home (CRS Home) path for later use.

- 5 In the **Product-Specific Prerequisite Checks** window, click **Next**.
- 6 In the **Specify Cluster Configuration** window, perform the following steps:
 - a Verify the public, private, and virtual Host names for the primary node.
 - b If you want to change these values, click **Edit** and enter the desired values, and click **OK**.
 - c Click **Add**.
 - d Enter the public, private, and virtual Host names for the second node, and click **OK**.
- 7 Click **Next**.

The **Specify Network Interface Usage** window appears, displaying a list of cluster-wide network interfaces.

- 8 In the **Interface Type** drop-down menus, configure the public **Interface Type** as **Public** and the private **Interface Type** as **Private** (if required) by selecting the **Interface Name** and clicking **Edit**. Select the correct **Interface Type** and click **OK**.
- 9 Click **Next**.
- 10 In the **Cluster Configuration Storage** screen, perform the following steps for the OCR disk:
 - a Locate the two 120 MB partitions that you created in the subsection "Preparing the OCR and Voting Disks for Clusterware" on page 30.
 - b Select the first partition and click **Edit**.
 - c In the **Specify Disk Configuration** window, select **Place OCR (Primary)** on this partition and click **OK**.
 - d Select the second partition and click **Edit**.
 - e In the **Specify Disk Configuration** window, select **Place OCR (Mirror)** on this partition and click **OK**.

- 11 In the **Cluster Configure Storage** screen, perform the following steps for the Voting disk:
 - a Locate the three 50 MB partitions that you created in the subsection "Preparing the OCR and Voting Disks for Clusterware" on page 30.
 - b Select the first partition and click **Edit**.
 - c In the **Specify Disk Configuration** window, select **Place Voting Disk on this partition** and click **OK**.
 - d Repeat steps b and c on the remaining Voting Disk partitions.
- 12 Click **Next**.
- 13 Ignore the warning messages and click **OK**.
- 14 In the **Summary** window, click **Install** to start the installation procedure.



NOTE: If a failure occurs in the **Configuration Assistant** window, perform the following steps and see "Troubleshooting" on page 55 and "Working Around Clusterware Installation Failure" on page 55.

The **Install** window appears, displaying an installation progression bar.

The **Configuration Assistant** window appears and the OUI runs a series of configuration tools.

The **End of Installation** window appears.

- 15 Click **Exit** to finish the OUI session.
- 16 In the **Exit** window, click **Yes**.

Installing Oracle10g Database With Real Application Clusters 10.2.0.1

- 1 Insert the *Oracle Database 10g Release 2* CD into the CD drive.




The OUI starts and the **Welcome** screen appears.

If the **Welcome** screen does not appear:


- a Click **Start** and select **Run**.
- b In the **Run** field, enter:
`%CD drive%\autorun\autorun.exe`
where `%CD drive%` is the drive letter of your CD drive.

- 2 Click **OK** to continue.

The OUI starts and the **Welcome** window appears.

- 3 Click **Next**.
- 4 In the **Select Installation Type** window, click **Standard Edition** and click **Next**.
- 5 In the **Specify Home Details** window under **Destination**, verify the following:
 - In the **Name** field, the Oracle database home name is `OraDb10g_home1`
 - In the **Path** field, the complete Oracle home path is `%SystemDrive%\oracle\product\10.2.0\db_1`
where `%SystemDrive%` is the user's local drive.
-  **NOTE:** Record the path because you will need this information later.
-  **NOTE:** The Oracle home path must be different from the Oracle home path that you selected in the Oracle Clusterware installation procedure. You cannot install the Oracle Database 10g R2 Standard x64 Edition with RAC and Clusterware in the same home directory.
- 6 Click **Next**.
- 7 In the **Specify Hardware Cluster Installation Mode** window, click **Select All** and click **Next**.
- 8 In the **Product-Specific Prerequisite Checks** window, click **Next**.
- 9 In the **Select Configuration Option** window, select **Install database Software only**, and click **Next**.
- 10 In the **Summary** window, click **Install**.
- 11 In the **End of Installation** window, perform the steps as listed.
 -  **NOTE:** You should perform the steps as listed in the window before proceeding with the next step.
- 12 Click **Exit**.

Installing Patchset 10.2.0.4

-  **NOTE:** The following patchset installation steps install only Oracle softwares such as 10.2.0.1 Clusterware and 10.2.0.1. Database binaries with seed database that are not yet created on your system.

- 1 Download the patchset 10.2.0.4 from the Oracle Metalink website located at metalink.oracle.com.
- 2 Unzip the patchset to the following location `%SystemDrive%`, where `%SystemDrive%` is the user's local drive.

Installing Patchset 10.2.0.4 for Oracle 10g Clusterware

Before You Begin

- 1 Stop `nodeapps` on all nodes. Enter the following:

```
%SystemDrive%:\%CRS_HOME%\bin> srvctl stop nodeapps -n <node_name>
```

where `%SystemDrive%` is the user's local drive.
- 2 Click **Start**→**Programs**→**Administrator Tools**→**Services** to locate all Oracle services and stop them on both nodes.

Installing the Patchset



NOTE: You must install the patchset software from the node where the Oracle RAC 10g R2 software was installed. If this is not the node where you are running the OUI, exit and install the patchset from that node.

- 1 Start the OUI located in the patchset folder.
- 2 In the **Welcome** window, click **Next**.
- 3 In the **Specify home details** window, select the name as `OraCr10g_home` and install the patchset to the Clusterware home and click **Next**.
- 4 In the **Specify Hardware Cluster Installation Mode** Window, click **Next**.
- 5 In the **Summary** window, click **Install**.
- 6 At the **End of installation** window, perform all the steps listed in the **Summary** window except step 1.
- 7 At the **End of installation** screen, click **Exit** and then click **Yes** to exit from the OUI.

Installing Patchset 10.2.0.4 for Oracle 10g Database



NOTE: Complete the following steps before creating a listener and a seed database. Ensure that all the Oracle services are running.



NOTE: You must install the patchset software from the node where the Oracle RAC 10g R2 software was installed. If this is not the node where you are running the OUI, exit and install the patchset from that node.

Patchset Installation Steps

- 1 Start the OUI located in the patchset folder.
- 2 In the **Welcome** window, click **Next**.
- 3 In the **Specify home details** window, select the name as **OraDb10g_home1** from the drop down list to install the patchset to Oracle home and click **Next**.
- 4 In the **Specify Hardware Cluster Installation Mode** window, click **Next**.
- 5 In the **Summary** window, click **Install**.

During the installation, the following error message may appear: **Error in writing to file oci.dll**. To work around this issue, perform the following steps:

- a Cancel the patchset installation.
 - b Rename the %Oracle_home%\BIN directory to \bin_save.
 - c Reboot the system.
 - d After the reboot, rename the \bin_save file to \bin.
 - e Run the **setup.exe** file from the patchset folder. Allow all the Oracle default services to run.
- 6 From the **End of Installation** screen, perform the necessary steps listed in the **Summary** windows.
 - 7 At the **End of Installation** screen, click **Exit** and then click **Yes** to exit the OUI.

Configuring the Listener

This section contains procedures to configure the listener, which is required to establish a remote client connection to a database.

Perform the following steps on node 1:


- 1 Click **Start-Run** and enter `netca`.
- 2 Click **OK**.



- 3 In the **Real Application Clusters Configuration** window, select **Cluster configuration** and click **Next**.
- 4 In the **Real Application Clusters Active Nodes** window, select **Select All nodes** and click **Next**.
- 5 In the **Welcome** window, select **Listener configuration** and click **Next**.
- 6 In the **Listener Configuration Listener** window, select **Add** and click **Next**.
- 7 In the **Listener Configuration Listener Name** window, select the **default setting** in the **Listener name** field and click **Next**.
- 8 In the **Listener Configuration Select Protocols** window, select **TCP** in the **Selected protocols** field and click **Next**.
- 9 In the **Listener Configuration TCP/IP Protocol** window, select **Use the standard port number of 1521** and click **Next**.
- 10 In the **Listener Configuration More Listeners** window, select **No** and click **Next**.
- 11 In the **Listener Configuration Done** window, click **Next**.
- 12 In the **Welcome** window, click **Finish**.

Creating the Seed Database

Perform the following steps to create the seed database using Oracle ASM:

- 1 Verify the Oracle Clusterware is running.
 - a Open a command prompt window. Click **Start–Run** and enter `cmd`.
 - b Enter `crsctl check crs`.
You should see the following output:


```
CSS appears healthy
CRS appears healthy
EVM appears healthy
```
-  **NOTE:** If you don't see the output indicated above, enter `crsctl start crs`.
- c Enter `exit` to close the window.
- 2 On node 1, click **Start–Run**.

- 3 In the **Run** field, enter `dbca` and click **OK**. The Database Configuration Assistant starts.
- 4 In the **Welcome** window, select **Oracle Real Application Clusters database** and click **Next**.
- 5 In the **Operations** window, click **Create a Database** and click **Next**.
- 6 In the **Node Selection** window, click **Select All** and click **Next**.
- 7 In the **Database Templates** window, click **Custom Database** and click **Next**.
- 8 In the **Database Identification** window, in the **Global Database Name** field, enter a name such as `racdb` and click **Next**.
- 9 In the **Management Options** window, click **Next**.
- 10 In the **Database Credentials** window, click **Use the Same Password for All Accounts**, enter a new password in the appropriate fields, and click **Next**.
 **NOTE:** Record your new password because you will need this information later for database administration.
- 11 In the **Storage Options** window, select **Automatic Storage Management (ASM)** and click **Next**.
- 12 In the **Create ASM Instance** window, perform the following steps:
 - a In the **SYS password** field, enter a new password in the appropriate fields.
 - b Select **Create initialization parameter file (IFILE)**.
 - c Click **Next**.
- 13 In the **Database Configuration Assistant** window, click **OK**. The **ASM Creation** window appears, and the ASM Instance is created.
 **NOTE:** If the warning message `Failed to retrieve network listener resources` appears, click **Yes** to allow DBCA to create the appropriate listener resources.
- 14 In the **ASM Disk Groups** window, click **Create New**.
- 15 In the **Create Disk Group** window, enter the following information for the database files.
 - a In the **Disk Group Name** field, enter a name for the new disk group. For example, `DATABASE`.

- b** In the **Redundancy** box, select **External**.
 - c** Click **Stamp Disks**.
 - d** Select **Add or change label** and click **Next**.
 - e** In the **Select disks** screen, select the disks which you plan to use for the database files. Note that the **Status** is marked as **Candidate device**.
 - f** In the **Generate stamps with this prefix** field, keep the default settings and click **Next**.
 - g** In the **Stamp disks** window, click **Next**.
 - h** Click **Finish** to save your settings.
 - i** Select the check boxes next to the available disks and click **OK**.
- 16** In the **ASM Disk Groups** window, click **Create New**.
- 17** In the **Create Disk Group** window, enter the following information for the Flash Recovery Area.
- a** In the **Disk Group Name** field, enter a name for the new disk group.
For example, `FLASH`.
 - b** In the **Redundancy** box, select **External**.
 - c** Click **Stamp disks**.
 - d** In the **Select disks** screen, select the disk which you plan to use for the Flash Recovery Area. Note that the **Status** is marked as **Candidate device**.
 - e** In the **Generate stamps with this prefix** field, enter `FLASH`, and click **Next**.
 - f** In the **Stamp disks** window, click **Next**.
 - g** Click **Finish** to save your settings.
 - h** Select the check boxes next to the available disks and click **OK**.
- The **ASM Disk Group Window** appears, indicating that the software is creating the disk group. When complete, the `FLASH` disk group appears in the **Disk Group Name** column.
- 18** Select only the Disk Group Name that you assigned to the database in step 15 (for example, `+DATABASE/`) and click **Next**.

- 19** In the **Database File Locations** window, select **Use Oracle-Managed Files** and **Multiplex Redo Logs and Control Files** and click **Next**.
- 20** In the **Recovery Configuration** window, perform the following steps:
 - a** Select **Specify Flash Recovery Area**.
 - b** Click **Browse**.
 - c** Select the **FLASH** disk group that you created in step 17 and click **OK**.
 - d** In the **Flash Recovery Area Size** text box enter the total size of the flash disk group created in step 17.
 - e** Select **Enable Archiving**.
 - f** Click **Edit Archive Mode Parameters**.
 - g** In the **Edit Archive Mode Parameters** window, ensure that the path listed under the **Archive Log Destinations** is as follows: **+FLASH/**, where **FLASH** is the Flash Recovery Area disk group name that you specified in step a of step 17.
 - h** Click **Next**.
- 21** In the **Database Content** window, click **Next**.
- 22** In the **Database Services** window, click **Next**.
- 23** In the **Initialization Parameters** window, click **Next**.
- 24** In the **Database Storage** window, click **Next**.
- 25** In the **Creation Options** window, click **Finish**.
- 26** In the **Summary** window, click **OK**.

The **Database Configuration Assistant** window appears, and the Oracle software creates the database.

 **NOTE:** This procedure may take several minutes to complete.

When completed, the **Database Configuration Assistant** window provides database configuration information.

- 27** Record the information in the **Database Configuration Assistant** window for future database administration.
- 28** Click **Exit**.


The **Start Cluster Database** window appears and the cluster database starts.

Configuring and Deploying Oracle Database 10g (Single Node)

This section provides information about installing the Oracle 10g R2 software on a single node. This section covers the following topics:

- Installing Oracle Clusterware Version 10.2.0.1
- Installing Oracle 10g Database with Real Application Clusters 10.2.0.1
- Installing the Oracle Database 10g 10.2.0.4 Patchset
- Configuring the Listener
- Creating the Seed Database

Installing Oracle Clusterware Version 10.2.0.1

- 1 On node 1, insert the *Oracle Clusterware* CD into the CD drive.
The Oracle User Interface (OUI) starts and the **Welcome** screen appears.
If the **Welcome** screen does not appear:
 - a Click **Start–Run**.
 - b In the **Run** field, enter the following, and click **OK**:
`%CD drive%\autorun\autorun.exe`
where `%CD drive%` is the drive letter of your CD drive.
- 2 In the **Oracle Clusterware** window, click **Install/Deinstall Products**.
- 3 In the **Welcome** screen, click **Next**.
- 4 In the **Specify Home Details** window, accept the default settings and click **Next**.
 **NOTE:** Record the OraCR10g_home (CRS Home) path for later use.
- 5 In the **Product-Specific Prerequisite Checks** window, click **Next**.
- 6 In the **Specify Cluster Configuration** window, perform the following steps:
 - a Verify the public, private, and virtual host names for the primary node.
 - b If you want to change these values, click **Edit** and enter the desired values, and click **OK**.

7 Click Next.

The **Specify Network Interface Usage** window appears, displaying a list of cluster-wide network interfaces.

8 In the **Interface Type** drop-down menus, configure the public **Interface Type** as **Public** and the private **Interface Type** as **Private** (if required) by selecting the **Interface Name** and clicking **Edit**. Select the correct **Interface Type** and click **OK**.

9 Click Next.

10 In the **Cluster Configuration Storage** screen, perform the following steps for the OCR disk:

- a Locate the 20 MB partition that you created in the subsection "Preparing the OCR and Voting Disks for Clusterware" on page 30.
- b Select the partition and click **Edit**.
- c In the **Specify Disk Configuration** window, select **Place OCR (Primary) on this partition** and click **OK**.


11 In the **Cluster Configure Storage** screen, perform the following steps for the Voting disk:

- a Locate a 50 MB partition that you created in the subsection "Preparing the OCR and Voting Disks for Clusterware" on page 30.
- b Select the partition and click **Edit**.
- c In the **Specify Disk Configuration** window, select **Place Voting Disk on this partition** and click **OK**.

12 Click Next.

13 Ignore the warning messages and click **OK**.

14 In the **Summary** window, click **Install** to start the installation procedure.

 **NOTE:** If a failure occurs in the **Configuration Assistant** window, perform the following steps and see "Troubleshooting" on page 55 and "Working Around Clusterware Installation Failure" on page 55.

The **Install** window appears, displaying an installation progression bar.

The **Configuration Assistant** window appears and the OUI runs a series of configuration tools.

The **End of Installation** window appears.

- 15 Click **Exit** to finish the OUI session.
- 16 In the **Exit** window, click **Yes**.

Installing Oracle10g Database With Real Application Clusters 10.2.0.1


- 1 Insert the *Oracle Database 10g Release 2* CD into the CD drive.
The OUI starts and the **Welcome** screen appears.
If the **Welcome** screen does not appear:
 - a Click **Start–Run**.
 - b In the **Run** field, enter:


```
%CD drive%\autorun\autorun.exe
```


where `%CD drive%` is the drive letter of your CD drive.
- 2 Click **OK** to continue.
The OUI starts and the **Welcome** window appears.
- 3 Click **Next**.
- 4 In the **Select Installation Type** window, click **Standard Edition** and click **Next**.
- 5 In the **Specify Home Details** window under **Destination**, verify the following:
 - In the **Name** field, the Oracle database home name is `OraDb10g_home1`.
 - In the **Path** field, the complete Oracle home path is

```
%SystemDrive%\oracle\product\10.2.0\db_1
```


where `%SystemDrive%` is the user's local drive.

 **NOTE:** Record the path because you will need this information later.

 **NOTE:** The Oracle home path must be different from the Oracle home path that you selected in the Oracle Clusterware installation procedure. You cannot install the Oracle Database 10g R2 Standard x64 Edition with RAC and Clusterware in the same home directory.
- 6 Click **Next**.
- 7 In the **Specify Hardware Cluster Installation Mode** window, click **Local Installation** and click **Next**.

- 8 In the **Product-Specific Prerequisite Checks** window, click **Next**.
- 9 In the **Select Configuration Option** window, select **Install Database Software only**, and click **Next**.
- 10 In the **Summary** window, click **Install**.
- 11 In the **End of Installation** window, perform the steps as listed.
 -  **NOTE:** You should perform the steps as listed in the window before proceeding with the next step.
- 12 Click **Exit**.

Installing Patchset 10.2.0.4

 **NOTE:** The following patchset installation steps install only Oracle software versions such as 10.2.0.1 Clusterware and 10.2.0.1. database binaries with a seed database that is not yet created on your system.


- 1 Download the patchset 10.2.0.4 from the Oracle Metalink website located at metalink.oracle.com.
- 2 Unzip the patchset to the following location:
`%SystemDrive%`
where `%SystemDrive%` is the user's local drive.

Installing Patchset 10.2.0.4 for Oracle 10g Clusterware

Before You Begin


- 1 Enter the following to stop the nodeapps on all nodes:
`%SystemDrive%:\%CRS_HOME%\bin> srvctl stop nodeapps -n <node_name>`
where `%SystemDrive%` is the user's local drive.
- 2 Stop all the Oracle services on all the nodes.
- 3 Click **Start**→**Programs**→**Administrator Tools**→**Services**.
- 4 Locate all Oracle services and stop them on both nodes.


Installing the Patchset

 **NOTE:** You must install the patchset software from the node where the Oracle RAC 10g R2 software was installed. If this is not the node where you are running the OUI, exit and install the patchset from that node.

- 1 Start the OUI located in the patchset folder.
- 2 In the **Welcome** window, click **Next**.
- 3 In the **Specify home details** window, select the name as **OraCr10g_home** and install the patchset to the Clusterware home and click **Next**.
- 4 In the **Specify Hardware Cluster Installation Mode** Window, click **Next**.
- 5 In the **Summary** window, click **Install**.
- 6 At the **End of installation** window, perform all the steps listed in the **Summary** window except step 1.
- 7 At the **End of installation** screen, click **Exit** and then click **Yes** to exit from the OUI.

Installing Patchset 10.2.0.4 for Oracle 10g Database

 **NOTE:** Complete the following steps before creating a listener and a seed database. Ensure that all the Oracle services are running.

 **NOTE:** You must install the patchset software from the node where the Oracle RAC 10g R2 software was installed. If this is not the node where you are running the OUI, exit and install the patchset from that node.

Patchset Installation Steps

- 1 Start the OUI located in the patchset folder.
- 2 In the **Welcome** window, click **Next**.
- 3 In the **Specify home details** window, select the name as **OraDb10g_home1** from the drop down list to install the patchset to Oracle home and click **Next**.
- 4 In the **Specify Hardware Cluster Installation Mode** window, select **Local Installation** and click **Next**.

- 5 In the **Summary** window, click **Install**.

During the installation, the following error message may appear:
Error in writing to file oci.dll.

To work around this issue, perform the following steps:

- a Cancel the patchset installation.
 - b Rename the %Oracle_home%\BIN directory to \bin_save.
 - c Reboot the system.
 - d After the reboot, rename the \bin_save file to \bin.
 - e Run the **setup.exe** file from the patchset folder. Allow all the Oracle default services to run.
- 6 From the **End of Installation** screen, perform the necessary steps listed in the **Summary** windows.
 - 7 At the **End of Installation** screen, click **Exit** and then click **Yes** to exit the OUI.

Configuring the Listener

This section contains procedures to configure the listener, which is required to establish a remote client connection to a database.

Perform the following steps on node 1:

- 1 Click **Start-Run** and enter `netca`.
- 2 Click **OK**.
- 3 In the **Real Application Clusters Configuration** window, select **Single Node configuration** and click **Next**.
- 4 In the **Welcome** window, select **Listener configuration** and click **Next**.
- 5 In the **Listener Configuration Listener** window, select **Add** and click **Next**.
- 6 In the **Listener Configuration Listener Name** window, select the **default setting** in the **Listener name** field and click **Next**.
- 7 In the **Listener Configuration Select Protocols** window, select **TCP** in the **Selected protocols** field and click **Next**.
- 8 In the **Listener Configuration TCP/IP Protocol** window, select **Use the standard port number of 1521** and click **Next**.

- 9 In the **Listener Configuration More Listeners** window, select **No** and click **Next**.
- 10 In the **Listener Configuration Done** window, click **Next**.
- 11 In the **Welcome** window, click **Finish**.

Creating the Seed Database

Perform the following steps to create the seed database using Oracle ASM:

- 1 Verify the Oracle Clusterware is running.
 - a Open a command prompt window. Click **Start–Run** and enter `cmd`.
 - b Enter `crsctl check crs`.

You should see the following output:

```
CSS appears healthy
```

```
CRS appears healthy
```

```
EVM appears healthy
```



NOTE: If you don't see the output indicated above, enter `crsctl start crs`.

- c Enter `exit` to close the window.
- 2 On node 1, click **Start–Run**.
- 3 In the **Run** field, enter `dcb` and click **OK**:
The Database Configuration Assistant starts.
- 4 In the **Welcome** window, click **Next**.
- 5 In the **Operations** window, click **Create a Database** and click **Next**.
- 6 In the **Database Templates** window, click **Custom Database** and click **Next**.
- 7 In the **Database Identification** window, in the **Global Database Name** field, enter a name such as `singlepdb` and click **Next**.
- 8 In the **Management Options** window, click **Next**.
- 9 In the **Database Credentials** window, click **Use the Same Password for All Accounts**, enter a new password in the appropriate fields, and click **Next**.



NOTE: Record your new password for in database administration.

10 In the **Storage Options** window, select **Automatic Storage Management (ASM)** and click **Next**.

11 In the **Create ASM Instance** window, perform the following steps:

a In the **SYS password** field, enter a new password in the appropriate fields.

b Click **Next**.

12 In the **Database Configuration Assistant** window, click **OK**.

The **ASM Creation** window appears, and the ASM Instance is created.



NOTE: If the warning message `Failed to retrieve network listener resources` appears, click **Yes** to allow DBCA to create the appropriate listener resources.

13 In the **ASM Disk Groups** window, click **Create New**.

14 In the **Create Disk Group** window, enter the following information for the database files.

a In the **Disk Group Name** field, enter a name for the new disk group.
For example, `DATABASE`.

b In the **Redundancy** box, select **External**.

c Click **Stamp Disks**.

d Select **Add or change label** and click **Next**.

e In the **Select disks** screen, select the disks which you plan to use for the database files. Note that the **Status** is marked as **Candidate device**.

f In the **Generate stamps with this prefix** field, keep the default settings and click **Next**.

g In the **Stamp disks** window, click **Next**.

h Click **Finish** to save your settings.

i Select the check boxes next to the available disks and click **OK**.

15 In the **ASM Disk Groups** window, click **Create New**.

16 In the **Create Disk Group** window, enter the following information for the Flash Recovery Area.

a In the **Disk Group Name** field, enter a name for the new disk group.

For example, `FLASH`.

- b** In the **Redundancy** box, select **External**.
- c** Click **Stamp disks**.
- d** In the **Select disks** screen, select the disk which you plan to use for the Flash Recovery Area. Note that the **Status** is marked as **Candidate device**.
- e** In the **Generate stamps with this prefix** field, enter `FLASH`, and click **Next**.
- f** In the **Stamp disks** window, click **Next**.
- g** Click **Finish** to save your settings.
- h** Select the check boxes next to the available disks and click **OK**.

The **ASM Disk Group Window** appears, indicating that the software is creating the disk group.

When completed, the `FLASH` disk group appears in the **Disk Group Name** column.

- 17** Select only the Disk Group Name that you assigned to the database in step 15 (for example, `+DATABASE/`) and click **Next**.
- 18** In the **Database File Locations** window, select **Use Oracle-Managed Files** and **Multiplex Redo Logs and Control Files** and click **Next**.
- 19** In the **Recovery Configuration** window, perform the following steps:
 - a** Select **Specify Flash Recovery Area**.
 - b** Click **Browse**.
 - c** Select the `FLASH` disk group that you created in step 17 and click **OK**.
 - d** In the **Flash Recovery Area Size** text box enter the total size of the flash disk group created in step 17.
 - e** Select **Enable Archiving**.
 - f** Click **Edit Archive Mode Parameters**.
 - g** In the **Edit Archive Mode Parameters** window, ensure that the path listed under the **Archive Log Destinations** is as follows: `+FLASH/`, where `FLASH` is the Flash Recovery Area disk group name that you specified in step a of step 17.

h Click **Next**.

20 In the **Database Content** window, click **Next**.

21 In the **Database Services** window, click **Next**.


22 In the **Initialization Parameters** window, click **Next**.

23 In the **Database Storage** window, click **Next**.

24 In the **Creation Options** window, click **Finish**.

25 In the **Summary** window, click **OK**.

The **Database Configuration Assistant** window appears, and the Oracle software creates the database.

 **NOTE:** This procedure may take several minutes to complete.

When completed, the **Database Configuration Assistant** window provides database configuration information.

26 Record the information in the **Database Configuration Assistant** window for future database administration.

27 Click **Exit**.

The **Start Cluster Database** window appears and the cluster database starts.

Adding a New Node to an Existing Oracle 10g RAC Cluster

The following describes how to add nodes and instances to Oracle RAC databases on Windows.

Preparing the Node to be Added to a Cluster

Perform the following steps on the node(s) that you want to add to an existing cluster:

- 1** Install and configure the operating system using the *Deployment* CDs.
- 2** Configure the networking and fiber channel storage subsystem.

Make sure that you can execute the following command from *each* of the existing nodes of your cluster where the *host_name* is the public network name of the new node:

```
NET USE \\host_name\C$
```

You have the required administrative privileges on each node if the operating system responds with:

Command completed successfully.



NOTE: If you are using ASM, then make sure that the new nodes can access the ASM disks with the same permissions as the existing nodes.



NOTE: If you are using Oracle Cluster File Systems, then make sure that the new nodes can access the cluster file systems in the same way that the other nodes access them.

Now the node(s) is ready to be added to an existing cluster.

The steps to add a node to an existing cluster can be summarized as below:

- 1 Adding Nodes at the Oracle Clusterware Layer
- 2 Adding Nodes at the Oracle RAC Database Layer
- 3 Adding Database Instances to New Nodes

Adding Nodes at the Oracle Clusterware Layer

Perform the following steps:

- 1 On one of the *existing* nodes, go to the **CRS home\oui\bin** directory. Run the **addNode.bat** script to start the OUI.
- 2 The OUI runs in the add node mode and the **OUI Welcome** page appears. Click **Next** and the **Specify Cluster Nodes for Node Addition** page appears.
- 3 The upper table on the **Specify Cluster Nodes for Node Addition** page shows the existing nodes associated with the CRS home from which you launched the OUI. Use the lower table to enter the public and private node names of the new nodes.
- 4 If all the checks succeed, then the OUI displays the **Node Addition Summary** page.
- 5 Click **Next** and the OUI displays the **Cluster Node Addition Progress** page.
- 6 On completion, click **Exit** to end the OUI session. After the OUI displays the **End of Node Addition** page, click **Exit** to end the OUI session.

- 7 Execute the following command to identify the node names and node numbers that are currently in use:

```
CRS home\bin\olsnodes -n
```

- 8 Execute the **crssetup.exe** command using the next available node names and node numbers to add CRS information for the new nodes. For example:

```
crssetup.exe add -nn publicnode3,3 -pn pvtnode3,3  
-vn vipnode3,3
```

- 9 Execute the **racgons** utility from the **bin** subdirectory of the CRS home to configure the Oracle Notification Services (ONS) port number as follows:

```
racgons add_config new_node_name:4948
```

After you have completed the procedures in this section for adding nodes at the Oracle Clusterware layer, you have successfully extended the CRS home from your existing CRS home to the new nodes.

Adding Nodes at the Oracle RAC Database Layer

- 1 From the `%ORACLE_HOME%\oui\bin` directory, run the **addNode.bat** script. The OUI starts in the **Add Node** mode, and displays the **OUI Welcome** page. Click **Next** on the **Welcome** page, and the OUI displays the **Specify Cluster Nodes for Node Addition** page.
- 2 The **Specify Cluster Nodes for Node Addition** page has a table showing the existing nodes associated with the Oracle home from which you launched the OUI. A node selection table appears on the bottom of this page showing the nodes that are available for addition. Select the nodes that you want to add and click **Next**.

If all of the checks succeed, then the **Node Addition Summary** page appears on the OUI display.

- 3 Click **Finish** and the **Cluster Node Addition Progress** page appears on the OUI display.
- 4 After the OUI displays the **End of Node Addition** page, click **Exit** to end the OUI session.
- 5 Execute the **VIPCA** utility from the **bin** subdirectory of the Oracle home using the **-nodelist** option with the following syntax that identifies the complete set of nodes that are now part of your RAC database beginning with **Node1** and ending with **NodeN**:

```
vipca -nodelist Node1,Node2,Node3,...NodeN
```

- 6 Add a listener to the new node only by running the **Net Configuration Assistant (NetCA)**.

After completing the procedures in the previous section, the new nodes are defined at the cluster database layer. New database instances can now be added to the new nodes.

Adding Database Instances to New Nodes

Execute the following procedures for each new node to add instances:

- 1 Click **Start—Programs—Oracle - HOME_NAME—Configuration and Migration Tools—Database Configuration Assistant**.
- 2 The DBCA displays the **Welcome** page for RAC. Click **Help** on any DBCA page for additional information.
- 3 Select **Real Application Clusters database** and click **Next**. The DBCA displays the **Operations** page.
- 4 Select **Instance Management** and click **Next**. The DBCA displays the **Instance Management** page.
- 5 Select **Add Instance** and click **Next**. The DBCA displays the **List of Cluster Databases** page that shows the databases and their current status, such as **ACTIVE**, or **INACTIVE**.
- 6 From the **List of Cluster Databases** page, select the active RAC database to which you want to add an instance.
- 7 Click **Next** to add a new instance. The DBCA displays the **Adding an Instance** page.
- 8 On the **Adding an Instance** page, enter the instance name in the field at the top of this page. Then select the new node name from the list, click **Next**, and the DBCA displays the **Services Page**.
- 9 Enter the services information for the new node's instance, click **Next**, and the DBCA displays the **Instance Storage** page.
- 10 Click **Finish**, and the DBCA displays a **Summary** dialog.

- 11 Review the information on the **Summary** dialog and click **OK**. The DBCA displays a progress dialog showing the DBCA performing the instance addition operation. When the DBCA completes the instance addition operation, the DBCA displays a dialog asking whether you want to perform another operation.
- 12 Click **No** and exit the DBCA, or click **Yes** to perform another operation.

Troubleshooting

Working Around Clusterware Installation Failure

Oracle Clusterware Configuration Assistant Fails

In the **Configuration Assistants** window, if the installation fails using the **Oracle Clusterware Configuration Assistant**, then perform the following steps:

- 1 Open the file:
`%ORA_CLUSTERWARE_HOME%\cfgtoollogs\configToolFailedCommands` where `%ORA_CLUSTERWARE_HOME%` is the CRS home directory that you created in "Installing Oracle Clusterware Version 10.2.0.1" on page 33.
- 2 Copy and run the first three commands (with the parameters) listed in the file from the DOS command prompt.
- 3 Follow the section "Virtual Private IP Configuration Assistant Fails" on page 56, below, to run the failed virtual private IP configuration assistants (VIPCA).

Virtual Private IP Configuration Assistant Fails

If the VIPCA fails during the installation of Oracle Clusterware, the following message may display:

```
Virtual Private IP Configuration Assistant failed
```

If this occurs, perform the following steps to work around the error. These steps are detailed in Metalink Note ID 338924.1. This generally occurs if the Public interface is configured with an IP address in the networks 10.0.0.0/8, 172.16.0.0/16 or 192.168.1.0/24.

- 1 Click **Start**–**Run**.
- 2 In the **Run** field, enter the following and click **OK**:

`%SystemDrive%\Oracle\product\10.2.0\crs\bin\vipca`

where `%SystemDrive%` is the user's local drive.

- 3 Follow the steps in VIPCA by selecting the interface appropriate for the public interface, and specifying the correct VIP address to be used.
- 4 Click **Finish**.

Uninstalling Oracle Clusterware



NOTE: Copy the `GUIOraObjman` folder to a different location before uninstalling Clusterware. Utilities in this folder can be used to clean the share disks later.

You may be required to uninstall Oracle Clusterware to troubleshoot the following issues:

- The Oracle Clusterware installation procedure failed.
- The Configuration Assistant failed to install successfully.

To uninstall Oracle Clusterware, run OUI on the cluster node, delete any remaining Oracle services, and clean the storage devices.

Running OUI

- 1 On node 1, open an Explorer window and navigate to the following directory:
`%SystemDrive%\oracle\product\10.2.0\crs\oui\bin`
where `%SystemDrive%` is the user's local drive.
- 2 Double-click `setup.exe` to launch the OUI.
- 3 In the **Welcome** window, click **Deinstall Products**.
- 4 In the **Inventory** window, select `OraCr10g_home` and then click **Remove**.
- 5 In the **Confirmation** window, click **Yes**.
If an error message appears, click **Cancel**.
- 6 In the **Welcome** window, click **Cancel**.
- 7 When prompted, click **Cancel** and then click **Yes**.

Deleting Oracle Services

- 1 On node 1, launch the **Services** console.

- a Click **Start–Run**.
- b In the **Run** field, enter the following and click **OK**:
`services.msc`

The **Services** window appears.

2 Identify and delete any remaining Oracle services.

To delete a service:

- a Click **Start–Run**.
- b In the **Run** field, enter `cmd` and click **OK**.
- c Open a command prompt and enter the following:
`sc delete <oracle_service_name>`
- d Repeat step c for each additional service that you need to remove.

3 Restart node 1 and log in as administrator.

4 Restart each of the other nodes and log in as administrator.

Cleaning the Storage Devices

1 Clean the partitions that will be configured for the OCR registry (OCRCFG, OCRMIRRORCFG) and the voting disks, **Votedsk1**, **Votedsk2**, and **Votedsk3**.

- a Click **Start–Run**.
- b In the **Run** field, enter `cmd` and click **OK**.
- c At the command prompt, enter the following:
`%SystemDrive%\oracle\product\10.2.0\crs\bin\ExportSYMLinks`

where `%SystemDrive%` is the user's local drive.

The Oracle Symbolic Link Exporter (ExportSYMLinks) imports the symbolic links to the **SYMMAP.TBL** file to your current directory.

- d At the command prompt, enter the following:
`notepad SYMMAP.TBL`

2 Ensure that **OCRCFG**, **OCRMIRRORCFG**, **Votedsk1**, **Votedsk2**, and **Votedsk3** appear in the file.

If **OCRCFG**, **OCRMIRRORCFG**, **Votedsk1**, **Votedsk2**, and **Votedsk3** do not appear in the file, assign **OCRCFG**, **OCRMIRRORCFG**, **Votedsk1**, **Votedsk2**, and **Votedsk3** to the appropriate disk and save the file.

Use the Oracle Symbolic Link Importer (ImportSYMLinks) to import the symbolic links into the assigned storage disks (**OCRCFG**, **OCRMIRRORCFG**, **Votedsk1**, **Votedsk2**, and **Votedsk3**).

At the command prompt, enter the following:

```
%SystemDrive%\oracle\product\10.2.0\crs\bin\ImportSYMLinks
```

where *%SystemDrive%* is the user's local drive.

- 3 Using the Oracle Logical Partition Formatter (LogPartFormat), format the **OCRCFG**, **OCRMIRRORCFG**, **Votedsk1**, **Votedsk2**, and **Votedsk3** partitions on both nodes.

At the command prompt, enter:

```
%SystemDrive%\oracle\product\10.2.0\crs\bin\LogPartFormat \\.\OCRCFG
```

Then, enter:

```
%SystemDrive%\oracle\product\10.2.0\crs\bin\LogPartFormat \\.\Votedsk1
```

where *%SystemDrive%* is the user's local drive.

- 4 The following message appears:

```
Are you sure you want to continue... (Y/N)?
```

Enter *y* to continue.

- 5 Launch the Oracle GUI Object Manager.

At the command prompt, enter the following:

```
%SystemDrive%\ora_bin_utils\GUIOracleOBJManager.exe
```

where *%SystemDrive%* is the user's local drive.

The **Oracle Object Manager** window appears.

- 6** Delete the symlinks for the OCR (**OCRCFG** and **OCRMIRRORCFG**) and the voting disks (**Votedsk1**, **Votedsk2**, and **Votedsk3**).
 - a** Select **OCRCFG**, **OCRMIRRORCFG**, **Votedsk1**, **Votedsk2**, and **Votedsk3**.
 - b** Click **Options** and select **Commit**.
If successful, the **OCRCFG**, **OCRMIRRORCFG**, **Votedsk1**, **Votedsk2**, and **Votedsk3** entries disappear.
 - c** Click **Options** and select **Exit** to close the Oracle Object Manager.
- 7** Launch the Computer Management Console.
 - a** On the Windows desktop, click **Start—Run**.
 - b** In the **Run** field, enter the following:

```
compmgmt.msc
```


The **Computer Management Console** window appears.
- 8** Delete the ASM partitions.
 - a** In the **Computer Management Console** window, click **Storage** and select **Disk Management**.
 - b** Right-click the first partition and select **Delete Logical Drive**.
 - c** When prompted, click **Yes**.
 - d** Repeat step b and step c for each remaining partition until all partitions, including the original extended partition, have been deleted.
- 9** Restart node 1 and log in as administrator.
- 10** After you are logged in as administrator on node 1, restart each of the remaining nodes and log in as administrator.
- 11** Repeat the procedures "Preparing the Disks for Oracle Clusterware" on page 29 and "Removing the Assigned Drive Letters" on page 33 to recreate your logical partitions and the procedure, "Installing Oracle RAC 10g R2 Using ASM" on page 33 to re-install Oracle RAC for ASM.

Additional Troubleshooting

This section provides recommended actions for additional problems that you may encounter.

PowerPath Installation

- **PROBLEM:** PowerPath installation fails.
 - **CAUSE:** Unknown installation error.
 - **RESOLUTION:** Reboot the system on which the PowerPath installation fails.

NIC Teaming

- **PROBLEM:** Broadcom NIC teaming fails.
 - **CAUSE:** The following steps may result in a NIC teaming failure:
 - One of the Broadcom NICs that was used in the NIC teaming fails or is disabled. Due to the availability of the second NIC, the private network is still active on this node through the second NIC.
 - When the first NIC is still down or disabled, the second NIC in the teaming also fails or is disabled. This failure causes the private network to go down completely on this node. The private IP address on this node cannot be pinged.
 - When the second NIC that failed or was disabled becomes enabled, the private network of this node remains inactive.



NOTE: A private network becomes inactive only if the failed second NIC becomes enabled. If the first failed NIC becomes enabled, the private network becomes active.

- **RESOLUTION:** The most likely cause of this issue is a Spanning Tree Protocol on your switch. If this issue is caused by a Spanning Tree Protocol, perform one of the following procedures:
 - Turn off **Spanning Tree** on the switch.
 - Enable **Port Fast Learning** (or equivalent, which may be called something different depending on the brand of switch) on the ports of the switch to which your teamed NICs are attached.
 - Use Broadcom's LiveLink feature by right-clicking the team, choosing **Enable LiveLink**, and following the instructions in the window.



NOTE: Though the suggested solutions may fix the above mentioned issue, be aware of the implications or issues that may arise from enabling Port Fast Learning or turning off Spanning Tree on your switches.

Installing Oracle Clusterware

- **PROBLEM:** During Clusterware installation you get the error message: The specified nodes are not clusterable.
 - **CAUSE:** The administrative or the account used to install Oracle has a blank password associated with it.
 - **RESOLUTION:** Perform the following steps:
 - a** Right-click **My Computer** and select **Manage**.
 - b** In the **Computer Management** window, in the left pane, expand **System Tools** and **Local Users** and then expand **Groups**.
 - c** Click **Users** in the left pane.
 - d** In the right pane, right-click the administrative account being used to install Oracle and select **Set Password**.
 - e** A warning window displays. Ignore the message and click **Proceed**.
 - f** In the **Set Password** window, enter the passwords and click **OK**.
 - g** Log off the machine and log back in with the administrative account you just changed/assigned the password for.
 - h** Restart the Clusterware installation.
- **PROBLEM:** The Oracle Clusterware installation fails.
 - **CAUSE:** The symlinks for OCRCFG and/or Votedsk1 are unavailable.
 - **RESOLUTION:** Perform the following procedures:
 - a** Uninstall Oracle Clusterware using OUI.
 - b** Uninstall any remaining Oracle services.
 - c** Clean the storage devices.
See "Uninstalling Oracle Clusterware" on page 56 for more information.
- **PROBLEM:** The Configuration Assistant fails to install successfully.
 - **CAUSE:** One or more storage devices need to be reformatted.
 - **RESOLUTION:** Perform the following procedures:

- a Uninstall Oracle Clusterware using OUI.
 - b Uninstall any remaining Oracle services.
 - c Clean the storage devices.
- See "Uninstalling Oracle Clusterware" on page 56 for more information.

Oracle Clusterware

- **PROBLEM:** The cluster node restarts with a blue screen.
 - **CAUSE:** The cluster node cannot communicate with the storage disks.
 - **RESOLUTION:** Perform the following steps:
 - a Restart the cluster node.
 - b During POST, press <F8>.
 - c In the **Windows Advanced Options Menu** screen, select **Safe Mode**.
 - d Select the appropriate operating system.
 - e Log on to the system.
 - f In the **Desktop** screen, click **OK**.
 - g On the Windows desktop, right-click **My Computer** and select **Manage**.
 - h In the **Computer Management** window, expand **Services and Applications**.
 - i Click **Services**.
 - j Right-click the first Oracle service and select **Properties**.
 - k Click the **Startup** drop-down menu and record the default startup type for this service.
 - l In the Startup drop-down menu, select **Disabled**.
 - m Repeat step 10 through step 12 for all remaining Oracle services.
 - n Verify the following:
 - The storage system is functioning properly.
 - All fiber-optic cables are connected and secure.
 - The cluster node can access the shared storage disks.

See "Installing the Host-Based Software Needed for Storage" on page 27 and "Verifying Multi-Path Driver Functionality" on page 29.

- o Repeat step a through step n and reset each Oracle service back to its original setting.

System Blue Screen

- **PROBLEM:** The cluster nodes generate a blue screen.
 - **CAUSE:** The cluster nodes cannot access the voting disk.
 - **RESOLUTION:** Perform the following steps:
 - a Ensure that the HBA connection mode firmware settings are configured properly for your storage configuration.
 - If your cluster nodes and storage system are configured in a direct-attached configuration, configure **Connection** mode as: **0 - loop only**.
 - If your cluster nodes and storage system are connected to each other through a Fibre Channel switch, configure the **Connection** mode as **2 - loop preferred, otherwise point-to-point**.
 - b If the problem persists, increase the CSS misscount to a value greater than 120.
 - c Perform the following:
 - 1 Shut down all nodes except node 1.
 - 2 On node 1, open a command prompt.
 - 3 Enter the following:

```
%ORA_CLUSTERWARE_HOME%\bin
```

where %ORA_CLUSTERWARE_HOME% is the CRS home directory that you created in "Installing Oracle Clusterware Version 10.2.0.1" on page 33.
 - 4 At the command prompt, enter the following:

```
crsctl set css misscount n
```

where *n* is a value greater than 120.
 - d Restart node 1 and log on as administrator.
 - e Restart each of the other nodes and log on as administrator.

Storage

- **PROBLEM:** Disks appear as unreachable.
 - **CAUSE:** On the Windows desktop, when you right-click **My Computer**, select **Computer Management**, and then click **Disk Management**, the disks appear unreachable. Potential causes are that the LUNs are not assigned to the cluster nodes, cabling is incorrectly installed, or the HBA drivers are not installed on the cluster node(s).
 - **RESOLUTION:** Ensure that the storage LUNs are assigned to both cluster nodes and that the fiber-optic cables connected to the cluster nodes and storage system are installed correctly.
See "Cabling Your Dell | EMC Fibre Channel Storage" on page 17 for more information.
- **PROBLEM:** SCSI disk devices do not appear.
 - **CAUSE:** On the Windows desktop, when you right-click **My Computer**, select **Computer Management**, and then click **Disk drivers**, the SCSI disk devices do not appear. Possible causes are that the LUNs are not assigned to the cluster nodes, cabling is incorrectly installed, or the HBA drivers are not installed on the cluster node(s).
 - **RESOLUTION:** First, ensure that the storage LUNs are assigned to both cluster node by performing the following steps.
 - a** On the Windows desktop, right-click **My Computer** and select **Manage**.
 - b** In the **Manage** window, expand **Device Manager**.
 - c** In the right-window pane, right-click the host computer name and select **Scan for hardware changes**.
 - d** Repeat step c until the disk devices appear.
 - e** Restart the system (if required).Next, ensure that the fiber optic cables connected to the cluster nodes and storage system are installed correctly. See "Cabling Your Dell | EMC Fibre Channel Storage" on page 17 for more information.

VIPCA

- **PROBLEM:** The VIPCA configuration fails.

- **CAUSE:** The public network adapter interface (or the network interface assigned for VIP in case 4 network interfaces) name is not identical on both cluster nodes.
- **RESOLUTION:** Ensure that the public network adapter interface name is identical on both cluster nodes. To verify the public network adapter interface name:
 - a On node 1, click **Start** and select **Settings**→**Control Panel**→**Network Connections**.
 - b In the **Network Connections** window, right-click the public network adapter that you want to rename and select **Rename**.
 - c Repeat step a and step b on each of the remaining nodes.

Uninstall Oracle Clusterware

- **PROBLEM:** Configuration assistant fails to install.
 - **CAUSE:** Previous installation is not completely removed.
 - **RESOLUTION:** Even though Oracle is uninstalled using the GUI, the empty directories in Oracle home and the Oracle folder under **Program Files** remain; you must manually delete these folders.

Getting Help

Dell Support

For detailed information about using your system, see the documentation that came with your system components. For white papers, Dell Supported Configurations, and general information, visit dell.com/10g. For Dell technical support for your hardware and operating system software and to download the latest updates for your system, visit the Dell Support website at support.dell.com. Information about contacting Dell is provided in your system *Installation and Troubleshooting Guide*.

Dell Enterprise Training and Certification is now available; see dell.com/training for more information. This training service may not be offered in all locations.

Oracle Support

For information about Oracle software and application clusterware training and contacting Oracle, see the Oracle website at www.oracle.com or your Oracle documentation.

Technical support, downloads, and other technical information are available at the Oracle MetaLink website at www.metalink.oracle.com.

Obtaining and Using Open Source Files

The software contained on the *Deployment* CD is an aggregate of third-party programs as well as Dell programs. Use of the software is subject to designated license terms. All software that is designated as under the terms of the GNU GPL may be copied, distributed, and/or modified in accordance with the terms and conditions of the GNU General Public License, Version 2, June 1991. All software that is designated as under the terms of the GNU LGPL (or Lesser GPL) may be copied, distributed, and/or modified in accordance with the terms and conditions of the GNU Lesser General Public License, Version 2.1, February 1999. Under these GNU licenses, you are also entitled to obtain the corresponding source files by contacting Dell at 1-800-WWW-DELL. You can also obtain the corresponding source files from the following website: www.dell.com/oracle.

Index

C

- cabling
 - SAS storage, 20
- cluster
 - fibre channel, 9, 15
- Clusterware
 - installing, 33, 43
 - preparing disks, 29
 - uninstalling, 56

D

- disks
 - flash recovery, 30
 - voting, 29

E

- EMC
 - Naviagent, 27
 - PowerPath, 8

F

- fibre channel
 - cluster configuration, 9
 - Dell|EMC, 17
 - SAN-attached, 16
 - setting up, 15

- flash recovery
 - disks, 30

H

- hardware
 - connections, 16
 - requirements, 9
- help, 66
 - Dell support, 66
 - Oracle support, 66

I

- IP addresses
 - configuring, 25
- iSCSI
 - hardware requirements, 10

L

- listener
 - configuring, 38, 48

M

- Multi-Path, 28
 - driver, 29

N

Naviagent, 27

network

 configuring, 21

NIC

 port assignments, 22

O

OCR

 disk, 29

Oracle

 preparing disks for

 Clusterware, 29

Oracle Database 10g

 configuring, 43

 deploying, 43

OUI

 running, 57

P

partitions

 creating, 30

patchset

 installing, 37, 46

PowerPath

 installing, 29

S

SAS

 cluster configuration, 9

storage

 configuring, 21

T

TOE, 23

V

voting disk, 30

 creating logical drive, 31

W

Windows

 configuring, 10

 installing, 10