



Views

Specifications

Copyright © 2014 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2014 - 11 Rev. A01

Regulatory model: P49G | Type: P49G001 Computer model: Inspiron 5447/Inspiron 5448



Front

Front



Left



Right



Base



Display



Power and battery-status light

Indicates the power state and battery state of the computer.

White — Power adapter is connected and the battery is being charged.

Amber — Battery charge is low or critical.

Hard-drive activity light

Turns on when the computer reads from or writes to the hard drive.

Views





Left

Front



Left



Right



Base



Display



Security-cable slot

Connect a security cable to prevent unauthorized movement of your computer.

Power-adapter port

Connect a power adapter to provide power to your computer and charge the battery.

USB 2.0 port

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.


Media-card reader

Reads from and writes to media cards.



Display

Right



Headset port

Connect a headphone, a microphone, or a headphone and microphone combo (headset).

USB 3.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provide data transfer speeds up to 5 Gbps.

HDMI port

Connect a TV or another HDMI-in enabled device. Provides video and audio output.

Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.

Views



Base

Front



Left



Right



Base



Display



Power button

Press to turn on the computer if it is turned off or in sleep state.

Press to put the computer in sleep state if it is turned on. Press and hold for 10 seconds to force shut-down the computer.

NOTE: You can customize the power-button behaviour in Power Options. For more information, see Me and My Dell at dell.com/support/manuals.

2 Right-click area

Press to right click.

Touchpad

Move your finger on the touchpad to move the mouse pointer. Tap to left-click.

Left-click area

Press to left click.

Views



Front



Left



Right



Base



Display

Display



Left microphone 1

Provides high-quality digital sound input for audio recording, voice calls, and so on.

2 Camera-status light

Turns on when the camera is in use.

Camera

Allows you to video chat, capture photos, and record videos.

Right microphone

Provides high-quality digital sound input for audio recording, voice calls, and so on.



Dimensions and Weight

Height:

Touch 22 mm (0.87 in)

Non-touch 21.60 mm (0.85 in)

Width 342 mm (13.46 in)

246 mm (9.69 in) Depth

Weight:

Touch 2.05 kg (4.52 lb)

Non-touch 1.93 kg (4.25 lb)

NOTE: The weight of your laptop varies depending on the configuration ordered

and the manufacturing variability.











Ports and Connectors















Media-card reader



Keyboard















System Information

Computer model	Inspiron 5447	Inspiron 5448		
Processor	 4th generation Intel Core i3 ULV 4th generation Intel Core i5 ULV 4th generation Intel Core i7 ULV 	 5th generation Intel Core i3 ULV 5th generation Intel Core i5 ULV 5th generation Intel Core i7 ULV 		
L3 cache	generation inter-cond-in-	4 MB		
Chipset	Integrate	Integrated in processor		





































Memory

Slots Two SODIMM slots

Type Dual-channel DDR3L

Speed 1600 MHz

Configurations supported 4 GB, 6 GB, 8 GB, 12 GB, and 16 GB



















o | Au



reader

Display















Ports and Connectors

Network One RJ45 port

USB • One USB 2.0 port

• Two USB 3.0 ports

Audio/Video • One HDMI port

• One headphone and microphone combo (headset) port

Internal:

M.2 Card One M.2-2230 slot for Wi-Fi and Bluetooth combo card

















Memory









Media-card reader











Communications

10/100 Mbps Ethernet controller integrated on system board **Ethernet** Wireless

- Wi-Fi 802.11 b/g/n/ac
- WiDi (Wireless Display)
- Bluetooth 4.0









Communications Connectors





























Video

\sim				
Cor	۱Ť۱	\sim	Δוו	r.
\sim 01	ıu	\cup	ис	Ι.

Integrated

• Inspiron 5447 — Intel HD Graphics 4400

• Inspiron 5448 — Intel HD Graphics 5500

Discrete

AMD Radeon R7 M265

• AMD Radeon R7 M270 (Inspiron 5448 only)

Memory:

Integrated Discrete

Shared system memory

• AMD Radeon R7 M265 - 2 GB DDR3

• AMD Radeon R7 M270 - 4 GB DDR3







































Audio

Controller Realtek ALC3234CG with Waves MaxxAudio

Speakers Two

Output:

2 watt Average Peak 2.5 watt

Microphone Digital array-microphones

Volume controls Media-control shortcut keys







Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-card reader



Display



Camera













Storage

Interface SATA 6 Gbps

Hard drive One 2.5-inch drive (supports Intel Smart Response Technology)



















nformation Connectors Connectors



reader

















Media-card reader

One 5-in-1 slot Type Cards supported • SD card • SD High-Capacity (SDHC) card • SD Extended Capacity (SDXC) card with Ultra High Speed (UHS) • Memory Stick (MS) • Memory Stick PRO (MS PRO)

















Memory

Ports and Connectors

Video

Audio

Storage

Media-card

reader

















Display

Type • 14-inch HD

• 14-inch HD touchscreen

Resolution (maximum) 1366 x 768

Pixel pitch 0.2265 mm

Dimensions:

Refresh rate

Height 173.95 mm (6.85 in)

Width 309.40 mm (12.18 in)

Diagonal 355.60 mm (14 in)

Operating angle 0 degrees (closed) to 135 degrees

Controls Brightness can be controlled using shortcut keys.

60 Hz



Dimensions and Weight



System Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-card reader



Display

Keyboard















Keyboard

Type

• Standard keyboard

• Backlit keyboard — optional

Shortcut keys

Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key.

NOTE: You can define the primary behavior of the shortcut keys by pressing Fn+Esc or by changing **Function Key Behavior** in System Setup.









Connectors











Media-card reader

















Camera

Resolution:

Still image 0.92 megapixel

1280 x 720 (HD) at 30 fps Video

Diagonal viewing angle 74 degrees





















reader

















Touchpad

Resolution:

Horizontal 1260 dpi Vertical 1207 dpi

Dimensions:

 Width
 105 mm (4.13 in)

 Height
 80 mm (3.15 in)







Ports and Connectors









ications Video





















Battery

• 3 cell "smart" lithium ion (43.50 WHr) Type

• 4 cell "smart" lithium ion (58 WHr)

3 cell 4 cell

Dimensions:

Width 208.25 mm (8.20 in)

Depth 124.70 mm (4.91 in)

7.80 mm (0.31 in) Height

Weight (maximum) 0.28 kg (0.62 lb) 0.35 kg (0.77 lb)

11.10 VDC 7.40 VDC Voltage

Operating time Varies depending on operating conditions and can significantly reduce under

certain power-intensive conditions.

Life span (approximate) 300 discharge/charge cycles

Temperature range:

Operating 0°C to 35°C (32°F to 95°F)

Storage -40°C to 65°C (-40°F to 149°F)

Coin-cell battery CR-2032



Dimensions and Weight



Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-card reader



Display

















Power Adapter

65 W Type

Input voltage 100 VAC-240 VAC

50 Hz-60 Hz Input frequency

Input current (maximum) 1.50 A

Output current (continuous) 3.34 A

19.50 VDC Rated output voltage

Temperature range:

Operating 0°C to 40°C (32°F to 104°F)

Storage -40°C to 70°C (-40°F to 158°F)



Dimensions and Weight



Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-card reader



Display



Keyboard







Touchpad





Power Adapter





Computer Environment

Airborne contaminant level	G1 as defined by ISA-S71.04-1985	
	Operating	Storage
Temperature range	0°C to 35°C (32°F to 95°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum)	110 G [†]	160 G [‡]
Altitude (maximum)	-15.20 m to 3048 m (-50 ft to 10,000 ft)	-15.20 m to 10,668 m (-50 ft to 35,000 ft)

^{*} Measured using a random vibration spectrum that simulates user environment







Memory



















Media-card reader









Battery Power Adapter

Environment

[†] Measured using a 2 ms half-sine pulse when the hard drive is in use.

[‡] Measured using a 2 ms half-sine pulse when the hard-drive head is in parked position.