



Dell™ Inspiron™ 1464

Comprehensive Specifications

This document provides information that you may need when setting up, updating drivers for, and upgrading your computer.



NOTE: Offerings may vary by region. For more information regarding the configuration of your computer, click **Start**  → **Help and Support** and select the option to view information about your computer.

Processor

Type	Intel® Core™ i5 Intel Core i3
L1 cache	32-KB instruction and 32-KB data first-level cache for each core
L2 cache	256-KB shared instruction/data second-level cache for each core
L3 cache	Up to 4-MB shared instruction/data third-level cache shared among all cores

Computer Information

System chipset	Intel HM55
Data bus width	64 bits
DRAM bus width	64 bits
Flash EPROM	4 MB

Memory Card Reader

Card reader controller	Realtek RTS5159
Card reader connector	7-in-1 combo card reader
Flash cards supported	<ul style="list-style-type: none">• Secure Digital (SD) memory card• Secure Digital High Capacity (SDHC) memory card• Multi Media Card (MMC)• MMC+• Memory Stick• Memory Stick Pro• xD-Picture Card (type - M and type - H)

Memory

Memory connectors	two internally-accessible SODIMM connectors
Memory capacities	1 GB, 2 GB, and 4 GB
Memory type	DDR3 1066 MHz
Memory configurations	2 GB, 3 GB, 4 GB, 6 GB, and 8 GB

NOTE: For instructions on upgrading memory, see the *Service Manual* at support.dell.com/manuals.

Connectors

Audio	one microphone-in connector one stereo headphone/speaker connector
Mini-Card	one half-size Mini-Card connector
HDMI	one 19-pin connector
Network adapter	one RJ45 connector
USB	three 4-pin USB 2.0-compliant connectors
Video	one 15-hole connector

Communications

Network adapter	10/100 Ethernet LAN on system board
Wireless	internal WLAN Mini-Card with WiFi 802.11a/b/g/n, and Bluetooth® wireless technology

Video

Discrete video type	integrated on system board
Discrete video controller and memory	ATI M92-LP 512 MB DDR3 ATI Park 1 GB DDR3
UMA video type	integrated on system board
UMA video controller	Intel Graphics Media Accelerator HD
UMA video memory	up to 1752 MB of shared memory
LCD interface	Low-voltage differential signaling (LVDS)

Audio

Audio type	2-channel High Definition
Audio controller	Realtek ALC269Q-GR
Stereo conversion	24-bit (analog-to-digital and digital-to-analog)
Internal interface	Intel High Definition audio
Speakers	2 x 2 watt speakers
Volume controls	keyboard function keys

Camera

Camera resolution	1.3 megapixel
Video resolution	640 x 480 at 30 fps (maximum)
Diagonal viewing angle	66°

Display

Type	14.0-inch HD WLED with TrueLife
Height	173.95 mm (6.85 inches)
Width	309.4 mm (12.2 inches)
Diagonal	355.6 mm (14.0 inches)
Luminance	220/200 nits
Maximum resolution	1366 x 768
Refresh rate	60 Hz
Operating angle	0° (closed) to 140°
Horizontal viewing angle	40/40
Vertical viewing angle	15/30 (H/L)
Pixel pitch	0.252 x 0.252 mm
Controls	brightness can be controlled through keyboard shortcuts (see the <i>Dell Technology Guide</i> for more information)

Keyboard

Number of keys	86 (U.S. and Canada); 87 (Europe); 90 (Japan)
Layout	QWERTY/AZERTY/Kanji

Touch Pad

X/Y position resolution (graphics table mode)	240 cpi
Width	79.7 mm (3.13 inches) sensor-active area
Height	47.7 mm (1.87 inches) rectangle

Battery

6-cell “smart” lithium ion

Depth	53.12 mm (2.09 inches)
Height	22.3 mm (0.88 inches)
Width	274.5 mm (10.8 inches)
Weight	0.35 kg (0.77 lb)

9-cell “smart” lithium ion

Depth	53.12 mm (2.09 inches)
Height	42.9 mm (1.69 inches)
Width	274.5 mm (10.8 inches)
Weight	0.56 kg (1.23 lb)

Voltage 11.1 VDC

Charge time (approximate) 4 hours when the computer is turned off

Life span (approximate) 300 discharge/charge cycles

Temperature range

Operating 0° to 35° C (32° to 95°F)

Storage -40° to 65° C (-40° to 149°F)

Coin-cell battery CR-2032

AC Adapter

Input voltage 100–240 VAC

Input current 1.5 A

Input frequency 50–60 Hz

Output power 65 W or 90 W

Output current 3.34 A (65 W) (continuous)

4.62 A (90 W) (continuous)

Rated output voltage 19.5 ± 1 VDC

AC Adapter (continued)

Temperature range

Operating	0° to 35°C (32° to 95°F)
Storage	-40° to 65°C (-40° to 149°F)

Physical

Height	20.8 mm to 32.8 mm (0.82 inches to 1.3 inches)
Width	340.0 mm (13.4 inches)
Depth	242.5 mm (9.5 inches)
Weight (with 6-cell battery)	configurable to less than 2.24 kg (4.9 lb)

Computer Environment

Temperature range

Operating	0° to 35°C (32° to 95°F)
Storage	-40° to 65°C (-40° to 149°F)

Relative humidity (maximum)

Operating	10% to 90% (non-condensing)
Storage	5% to 95% (non-condensing)

Maximum vibration (using a random vibration spectrum that simulates user environment)

Operating	0.66 GRMS
Non-Operating	1.30 GRMS

Maximum shock (for operating — measured with Dell Diagnostics running on the hard drive and a 2-ms half-sine pulse; for non-operating — measured with the hard drive in head-parked position and a 2-ms half-sine pulse)

Operating	110 G
Non-Operating	160 G

Computer Environment (continued)

Altitude (maximum)	
Operating	-15.2 to 3048 m (-50 to 10,000 ft)
Storage	-15.2 to 10,668 m (-50 to 35,000 ft)
Airborne contaminant level	G2 or lower as defined by ISA-S71.04-1985

Information in this document is subject to change without notice.

© 2009 Dell Inc. All rights reserved.

Reproduction of these materials in any manner whatsoever without the written permission of Dell Inc. is strictly forbidden.

Trademarks used in this text: *Dell*, the *DELL* logo, and *Inspiron* are trademarks of Dell Inc.; *Intel* is a registered trademark and *Core* is a trademark of Intel Corporation in the U.S. and other countries; *Microsoft*, *Windows*, and the *Windows Vista* start button logo are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries; *Bluetooth* is a registered trademark owned by Bluetooth SIG, Inc. and is used by Dell under license.

Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell Inc. disclaims any proprietary interest in trademarks and trade names other than its own.

Regulatory Model: P09G series

Regulatory Type: P09G001

December 2009

Rev: A00

