



Views

Specifications

Copyright @ 2014 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2014 - 06 Rev. A00

Regulatory model: P39F | Type: P39F002 Computer model: Inspiron 5545



Front

Front



Left



Right



Base



Display



Power and battery-status light

Indicates the power state and battery state of the computer.

White light — Power adapter is connected and the battery is being charged.

Amber light — Battery charge is low or critical.

Hard-drive activity light

Turns on when the computer reads from or writes to the hard drive.

Views





Left

Front



Left



Right



Base



Display



Security-cable slot

Connect a security cable to prevent unauthorized movement of your computer.

Power-adapter port

Connect a power adapter to provide power to your computer and charge the battery.

USB 2.0 port

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.

Media-card reader

Reads from and writes to media cards.





Right

Front



Left




Right



Base



Display



Headset port

Connect a headphone, a microphone, or a headphone and microphone combo (headset).

USB 3.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 5 Gbps.

HDMI port

Connect a TV or another HDMI-in enabled device. Provides video and audio output.

Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.

Views





Base

Front



Left



Right



Base



Display



Power button

Press to turn on the computer if it is turned off or in Sleep state.

Press to put the computer in Sleep state if it is turned on. Press and hold for 4 seconds to force shut-down the computer.

NOTE: You can customize the power-button behaviour in Power Options. For more information, see Me and My Dell at dell.com/support.

2 Right-click area

Press to right click.

Touchpad

Move your finger on the touchpad to move the mouse pointer. Tap to left-click.

Left-click area

Press to left click.

Views



Display

Front



Left



Right



Base





DELL

Left microphone 1

Provides high-quality digital sound input for audio recording, voice calls, and so on.

2 Camera-status light

Turns on when the camera is in use.

Camera

Allows you to video chat, capture photos, and record videos.

Right microphone

Provides high-quality digital sound input for audio recording, voice calls, and so on.



Dimensions and Weight

Height:

Touch screen 22 mm (0.87 in)

Non touch-screen 21.80 mm (0.86 in)

Width 380.40 mm (14.98 in)

Depth 259 mm (10.20 in)

Weight:

Touch 2.38 kg (5.25 lb)

Non touch 2.18 kg (4.81 lb)

NOTE: The weight of your laptop varies depending on the configuration ordered

and the manufacturing variability.



Dimensions and Weight



System Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-Card Reader



Display

Keyboard













System Information

Computer model	Inspiron 5545
ocessor • AMD A8-7100 APU with Radeon R5 Grpahics	
	AMD A10-7300 APU with Radeon R6 Graphics
Chipset	AMD A76M FCH

















Ports and Communication





















Memory

Connector One SODIMM slot

DDR3L Type

Speed 1600 MHz

Configurations supported 4 GB and 8 GB



















Communications



















Ports and Connectors

External:	
Network	One RJ45 port
USB	One USB 2.0 port
	Two USB 3.0 ports
HDMI	One HDMI port
Audio	One headset port
Internal:	
M.2	One M.2-2230 slot for Wi-Fi and Bluetooth combo card









Communications Connectors



Video









Reader

















Wireless

Specifications

Communications

10/100 Mbps Ethernet controller integrated on system board Ethernet

• Wi-Fi 802.11 b/g/n

• Bluetooth 4.0





































Video

Controller:

Integrated • AMD A8-7100 APU with AMD Radeon R5 Graphics

• AMD A10-7300 APU with AMD Radeon R6 Graphics

Discrete AMD Radeon R7 M265 Graphics

Memory:

Shared system memory Integrated

Discrete 2 GB DDR3













Video





Audio



Reader

















Audio

Controller Realtek ALC3234CG with Waves MaxxAudio

Speakers Two

Speaker output:

2 watt Average Peak 2.5 watt

Microphone Digital array-microphones

Volume controls Media-control shortcut keys



Dimensions and Weight



Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-Card Reader



Display

Keyboard















Storage

Interface SATA 6 Gbps

One 2.5-inch drive Hard drive





















Media-Card Reader



Keyboard













Media-Card Reader

One 5-in-1 slot Type Cards supported • SD card • SD 3.0 card • SD High-Capacity (SDHC) card

• Memory Stick Pro

Memory Stick





















Reader















Power Adapter



Display

• 15.6-inch HD Type • 15.6-inch HD touchscreen

Refresh rate 60 Hz

Operating angle 0 degrees (closed) to 135 degrees

Brightness can be controlled using shortcut keys. Controls

1366 x 768 Resolution (maximum) 0.252 mm Pixel pitch

Non touch-screen Touch screen Dimensions: 224.30 mm (8.83 in) 225.06 mm (8.86 in) Height 344.20 mm (13.55 in) 344.23 mm (13.55 in) Width





Dimensions and Weight







Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-Card Reader



Keyboard







Touchpad





Power Adapter



Computer Environment



Keyboard

Type

Standard keyboard

Shortcut keys

Backlit keyboard

Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key.

NOTE: You can define the primary behavior of the shortcut keys by changing **Function Key Behavior** in System Setup.









Connectors









Aud



Reader

















Camera

Resolution:

Still image 0.92 megapixels

Video 1280 x 720 (HD) at 30 fps

Diagonal viewing angle 74 degrees

















o | Aud



Media-Card Reader

















Touchpad

Resolution:

Horizontal 1260 dpi 1207 dpi Vertical

Dimensions:

Width 105 mm (4.13 in) Height 80 mm (3.15 in)







Ports and Connectors











Audio









Keyboard















Battery

• 3-cell "smart" lithium ion (43.50 WHr) Type

• 4-cell "smart" lithium ion (58 WHr)

Dimensions:

Width 208.25 mm (8.20 in)

Depth 124.70 mm (4.91 in) Height 7.80 mm (0.31 in)

Life span (approximate) 300 discharge/charge cycles

Varies depending on operating conditions and can significantly reduce under Operating time

certain power-intensive conditions.

Temperature range:

Operating 0°C to 35°C (32°F to 95°F)

-40°C to 65°C (-40°F to 149°F) Storage

3 cell 4 cell

Weight (maximum) 0.28 kg (0.62 lb) 0.35 kg (0.77 lb) 11.10 VDC 7.40 VDC Voltage

CR-2032 Coin-cell battery



Dimensions and Weight



Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-Card Reader



Keyboard



Camera











Power Adapter

65 W Type

Input voltage 100 VAC-240 VAC

50 Hz-60 Hz Input frequency

1.5 A Input current

Output current 3.34 A

19.50 VDC Rated output voltage

Temperature range:

Operating 0°C to 40°C (32°F to 104°F)

Storage -40°C to 70°C (-40°F to 158°F)



Dimensions and Weight



Information



Memory



Ports and Connectors



Communications



Video



Audio



Storage



Media-Card Reader



Display



Keyboard



Camera Touchpad



Battery







Computer Environment

Airborne contaminant level	G1 as defined by ISA-S71.04-1985	
	Operating	Storage
Temperature range	0°C to 35°C (32°F to 95°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum)	110 G [†]	160 G [‡]
Altitude (maximum)	-15.2 m to 3048 m (-50 ft to 10,000 ft)	-15.2 m to 10,668 m (-50 ft to 35,000 ft)

^{*} Measured using a random vibration spectrum that simulates user environment.









Connectors

























Battery Power Adapter

[†] Measured using a 2 ms half-sine pulse when the hard drive is in use.

[‡] Measured using a 2 ms half-sine pulse when the hard-drive head is in parked position.