




ews

**Specifications** 

**Copyright © 2015 Dell Inc. All rights reserved.** This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2015 - 01 Rev. A00 Regulatory model: P28F | Type: P28F002 Computer model: Inspiron M531R - 5535











Display

### 1 Power-status light

Indicates the power state of the computer.

White light – Power adapter is connected and the battery is fully charged.

### 2 Hard-drive activity light

Turns on when the computer reads from or writes to the hard drive.

### 3 Battery-status light

Indicates the battery state of the computer. Solid yellow light — Battery charge is low or critical. Blinking yellow light — Battery charge is critical.

### 4 Wireless-status light

Turns on when wireless is turned on.

#### 5 Media-card reader

Reads from and writes to media cards.





Right



Base



Display

### 1 Power-adapter port

Connect a power adapter to provide power to your computer and charge the battery.

### 2 HDMI port

Connect a TV or another HDMI-in enabled device. Provides video and audio output.

#### 3 Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.

The two lights next to the connector indicate the connectivity status and network activity.

### 4 USB 3.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provide data transfer speeds up to 5 Gbps.


### 5 USB 2.0 port

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.

### 6 Headset port

Connect a headphone, a microphone, or a headphone and microphone combo (headset).





Right



Base



Display

### 1 USB 2.0 port (supports Windows debugging)

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.

This USB port can be used for Windows debugging.

#### 2 Optical drive

Reads from and writes to CDs , DVDs and Blu-ray discs.

### 3 Security-cable slot

Connect a security cable to prevent unauthorized movement of your computer.



Base











Display



### 1 Power button

Press to turn on the computer if it is turned off or in Sleep state.

1

Press to put the computer in Sleep state if it is turned on. Press and hold for 10 seconds to force shut-down the computer.

NOTE: You can customize the power-button behaviour in Power Options. For more information, see *Me and My Dell* at dell.com/support.

### 2 Touchpad

Move your finger on the touchpad to move the mouse pointer. Tap to left-click.







Left

Right





Display





### 1 Digital microphone

Provides high-quality digital sound input for audio recording, voice calls, and so on.

### 2 Camera-status light

Turns on when the camera is in use.

### 3 Camera

Allows you to video chat, capture photos, and record videos.



# **Dimensions and Weight**

Height	1 in (25.40 mm)
Width	14.80 in (376 mm)
Depth	10.20 in (259 mm)
Weight with 6-cell battery (maximum)	5.73 lbs (2.60 kg)
	<b>NOTE</b> : The weight of your laptop varies depending on the configuration ordered and the manufacturing variability.



# **System Information**

Computer model	Inspiron M531R
Processor	• AMD A4-5145M APU
	• AMD A6-5345M APU
	AMD Quad Core A8-5545M APU
L1 cache	Up to 192 KB
L2 cache	Up to 4 MB
Chipset	AMD A76M FCH





## Memory

Connectors	Two DDR3/DDR3L SODIMM connectors
Capacity	2 GB and 4 GB
Туре	1600 MHz dual-channel DDR3 configuration (operating at 1333 MHz)
Configurations supported	2 GB, 4 GB, 6 GB, and 8 GB



# **Ports and Connectors**

External:	
Network	One RJ45 port
USB	Two USB 3.0 ports
	One USB 2.0 port
	<ul> <li>One USB 2.0 port with Windows debugging</li> </ul>
HDMI	One HDMI port
Audio	One headphone and microphone combo (headset) port
Internal:	
Mini-card	One mini-card slot



## Communications

Ethernet

Wireless

10/100 Mbps Ethernet controller integrated on system board

- Wi-Fi 802.11 b/g/n
- Bluetooth 4.0





## Video

Controller:	
Integrated	AMD Radeon HD 8310G
	AMD Radeon HD 8410G
	AMD Radeon HD 8510G
Discrete	AMD Radeon HD 8670M (1 GB DDR3)
	<ul> <li>AMD Radeon HD 8410G+8670M (1 GB DDR3 or 2 GB DDR3)</li> </ul>
	<ul> <li>AMD Radeon HD 8510G+8670M (2 GB DDR3)</li> </ul>





## Audio

Controller	ALC3223
Speakers	Two
Speaker output:	
Average	2 watt
Peak	2 watt
Microphone	Digital microphone in the camera assembly
Volume controls	Program menus and keyboard media-control keys





## Storage

Interface	<ul><li>SATA 1.5 Gbps</li><li>SATA 3 Gbps</li></ul>
	SATA 6 Gbps
Hard drives	One 7 mm/9.5 mm SATA drive
Optical drives	One 9.5 mm SATA drive
Drives supported	DVD+/-RW



## Media-card reader

Туре

Cards supported

One 8-in-1 slot

- Secure Digital (SD) memory card
- SD High-Capacity (SDHC) card
- Secure-Digital Extended Capacity (SDXC) card with Ultra High Speed (UHS)
- Memory Stick
- Memory Stick PRO
- Memory Stick XC (MSXC)
- MultiMedia Card (MMC)
- MultiMedia Card plus (MMC+)





# Display

Туре	15.6-inch HD True-Life
Resolution (maximum)	HD — 1366 x 768
Dimensions:	
Height	8.83 in (224.30 mm)
Width	14.17 in (360 mm)
Diagonal	15.60 in (396.24 mm)
Refresh rate	60 Hz
Operating angle	0 degree (closed) to 135 degrees
Pixel pitch	0.252 mm x 0.252 mm
Controls	Brightness can be controlled using shortcut keys.





# Keyboard


Туре	Chiclet keyboard
Shortcut keys	Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key.
	<b>NOTE</b> : You can define the primary behavior of the shortcut keys by changing <b>Function Key Behavior</b> in BIOS setup program.





## Camera


Resolution:	
Still image	0.92 megapixel
Video	1280 x 720 (HD) at 30 fps (maximum)
Diagonal viewing angle	66 degrees





# Touchpad

Resolution:		
Horizontal	1261 dpi	
Vertical	1810 dpi	
Dimensions:		
Width	2.13 in (54 mm)	
Height	3.86 in (98 mm)	





# Battery

Туре	<ul> <li>4-cell "smart" lithium ion (40 WHr)</li> <li>6-cell "smart" lithium ion (65 WHr)</li> </ul>	
Dimensions:	4-cell	6-cell
Height	0.79 in (20 mm)	1.08 in (27.4 mm)
Width	10.72 in (272.40 mm)	10.72 in (272.40 mm)
Depth	1.94 in (49.30 mm)	1.94 in (49.3 mm)
Weight (maximum)	0.57 lb (0.26 kg)	0.79 lb (0.36 kg)
Voltage	14.80 VDC	11.10 VDC
Operating time	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.	
Life span (approximate)	300 discharge/charge cycles	
Temperature range:		
Operating	0 °C to 35 °C (32 °F to 95 °F)	
Storage	−40 °C to 65 °C (−40 °F to 149 °F)	
Coin-cell battery	CR-2032	





# **Power Adapter**

Туре	<ul> <li>65 W</li> <li>90 W</li> </ul>
Input voltage	100 VAC-240 VAC
Input frequency	50 Hz-60 Hz
Input current	1.50A/1.60A/1.70A/2.50A
Output current	3.34 A/4.62 A
Rated output voltage	19.50 VDC
Temperature range:	
Operating	0 °C to 40 °C (32 °F to 104 °F)
Storage	–40 °C to 70 °C (–40 °F to 158 °F)



# **Computer Environment**

Airborne contaminant level	G1 as defined by ISA-S71.04-1985	
	Operating	Storage
Temperature range	0 °C to 40 °C (32 °F to 104 °F)	–40 °C to 70 °C (–40 °F to 158 °F)
Relative humidity (maximum)	10 % to 90 % (non-condensing)	10 % to 95 % (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS
Shock (maximum) <sup>†</sup>	110 G	160 G
Altitude (maximum)	-15.2 m to 3048 m (-50 ft to 10,000 ft)	-15.2 m to 10,668 m (-50 ft to 35,000 ft)

\* Measured using a random vibration spectrum that simulates user environment

† Measured with hard drive in operating status and a 2-ms half-sine pulse for operating. Also measured with hard drive in head-parked position and a 2-ms half-sine pulse for storage

