

Statement of Volatility – Dell 5130cdn

CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

The Dell 5130cdn Color Laser Printer contains both volatile and non-volatile (NV) components. Volatile components lose their data immediately after power is removed from the component. Non-volatile (NV) components continue to retain their data even after power is removed from the component. The following NV components are present on the system board.

Table 1. List of Volatile and Non-Volatile Components on System Board

Color Laser Product	Memory Application	Memory Size	Memory Type	Volatile/ Non- Volatile	User Data
	Firmware, Usage Statistics, Configuration, Fax	SIZE NOT AVAILABLE	EEPROM	Non- Volatile	No
	Running Code	SIZE NOT AVAILABLE	FLASH	Non- Volatile	No
5130cdn	Base Memory	256 MB	DDR2- SDRAM	Volatile	Yes
	Optional Memory	1024 MB	DDR2- SDRAM	Volatile	Yes
	Drum	NA	NA	Volatile	Yes
	Fuser	NA	NA	Volatile	Yes
	Hard Disk	80 GB or greater	HDD	Non- Volatile	Yes

CAUTION: All other components on the motherboard will lose data if power is removed from the system. Primary power loss (unplugging the power cord) will cause user data on the memory to be lost.

Notes:

- EEROM may be used and could contain user data.
- User Data utilized by memory type.
- User data is not stored in EEPROM.
- User data is not stored in FLASH.
- Last Print job latent image from user, overwritten with next print job
- Print Job, User data remains as photogene on the surface of Fuser roll.
- Print job stay on hard disk

This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

Copyright © 2014 Dell Inc. All rights reserved.