CPU Profile

Document Number: DCIM1041 Document Type: Specification Document Status: Published

Document Language: E Date: 2012-03-08



THIS PROFILE IS FOR INFORMATIONAL PURPOSES ONLY, AND MAY CONTAIN TYPOGRAPHICAL ERRORS AND TECHNICAL INACCURACIES. THE CONTENT IS PROVIDED AS IS, WITHOUT EXPRESS OR IMPLIED WARRANTIES OF ANY KIND. ABSENT A SEPARATE AGREEMENT BETWEEN YOU AND DELL™ WITH REGARD TO FEEDBACK TO DELL ON THIS PROFILE SPECIFICATION, YOU AGREE ANY FEEDBACK YOU PROVIDE TO DELL REGARDING THIS PROFILE SPECIFICATION WILL BE OWNED AND CAN BE FREELY USED BY DELL.

© 2010-2012 Dell Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of Dell, Inc. is strictly forbidden. For more information, contact Dell.

Dell and the DELL logo are trademarks of Dell Inc. Microsoft and WinRM are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others.

CONTENTS

1	Scope	5
2	Normative References	5
3	Terms and Definitions	5
4	Symbols and Abbreviated Terms	6
5	Synopsis	
6	Description	
7	Implementation Description	
	7.1 CPU View	
	7.2 CPU Profile Profile Registration	
8	Methods	
9	Use Cases	15
10	CIM Elements	15
11	Privilege and License Requirement	15

Figures

Figure 1 – Class Diagram	8
Figure 2 – CPU Profile Implementation	
· ·	
Tables	
Table 1 – Related Profiles	7
Table 2 –Class Requirements: CPU Profile	10
Table 3 – DCIM_CPUView - Operations	10
Table 4 – DCIM_CPUView - Properties	11
Table 5 – DCIM_LCRegisteredProfile - Operations	14
Table 6 – DCIM_LCRegisteredProfile	14
Table 7 – Privilege and License Requirements	15

CPU Profile

1 Scope

The DCIM CPU Profile describes the properties and interfaces for executing system management tasks related to the management of processors within a system. The profile standardizes and aggregates the description for the CPU properties into a CPU view representation as well as provides static methodology for the clients to query the CPU views without substantial traversal of the model.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

DMTF DSP1033, Profile Registration Profile 1.0.0

Dell Lifecycle Controller Best Practices Guide 1.0, http://en.community.dell.com/techcenter/extras/m/white_papers/20066173.aspx

Dell WSMAN Licenses and Privileges 1.0

DMTF DSP0226, Web Services for Management (WS-Management) Specification 1.1.0

DMTF DSP0227, WS-Management CIM Binding Specification 1.0.0

Dell Tech Center MOF Library http://www.delltechcenter.com/page/DCIM.Library.MOF

- DCIM CPUView.mof
- DCIM_LCEnumeration.mof
- DCIM LCRegisteredProfile.mof

3 Terms and Definitions

For the purposes of this document, the following terms and definitions apply.

3.1

conditional

indicates requirements to be followed strictly in order to conform to the document when the specified conditions are met

3.2

mandatory

indicates requirements to be followed strictly in order to conform to the document and from which no deviation is permitted

3.3

may

indicates a course of action permissible within the limits of the document

3.4

optional

indicates a course of action permissible within the limits of the document

3.5

referencing profile

indicates a profile that owns the definition of this class and can include a reference to this profile in its "Related Profiles" table

3.6

shall

indicates requirements to be followed strictly in order to conform to the document and from which no deviation is permitted

3.7

FQDD

Fully Qualified Device Descriptor is used to identify a particular component in a system.

3.8

Interop Namespace

Interop Namespace is where instrumentation instantiates classes to advertise its capabilities for client discovery.

3.9

Implementation Namespace

Implementation Namespace is where instrumentation instantiates classes relevant to executing core management tasks.

3.10

ENUMERATE

Refers to WS-MAN ENUMERATE operation as described in Section 8.2 of DSP0226_V1.1 and Section 9.1 of DSP0227_V1.0

3.11

GET

Refers to WS-MAN GET operation as defined in Section 7.3 of DSP00226_V1.1 and Section 7.1 of DSP0227_V1.0

4 Symbols and Abbreviated Terms

4.1

CIM

Common Information Model

4.2

iDRAC

Integrated Dell Remote Access Controller - management controller for blades and monolithic servers

4.3

CMC

Chassis Manager Controller – management controller for the modular chassis

4.4

WBEM

Web-Based Enterprise Management

5 Synopsis

Profile Name: CPU

Version: 1.0.0

Organization: Dell

CIM Schema Version: 2.26 Experimental

Dell Schema Version: 1.0.0

Interop Namespace: root/interop

Implementation Namespace: root/dcim

Central Class: DCIM CPUView

Scoping Class: DCIM_ComputerSystem

The Dell CPU Profile is a component profile that contains the Dell specific implementation requirements

for CPU view.

DCIM_CPUView shall be the Central Class.

Table 1 identifies profiles that are related to this profile.

Table 1 - Related Profiles

Profile Name	Organization	Version	Relationship
Profile Registration	DCIM	1.0	Reference

6 Description

The Dell CPU Profile describes platform's CPUs. Each CPU's information is represented by an instance of DCIM_CPUView class.

Figure 1 details the class diagram of the Dell CPU Profile.




Figure 1 - Class Diagram

Figure 2 details typical Dell CPU Profile implementation for a platform containing two CPUs. In order for client to discover the instrumentation's support of this profile, CPUProfile is instantiated in the Interop Namespace. CPUProfile instance describes the information about the implemented profile: most importantly, the name and version of the profile and the organization name that produced the profile.

CPU1 and CPU2 are the CPU views representing the two CPUs in the Implementation Namespace. They are associated to the Interop namespace's CPUProfile instance.




Figure 2 – CPU Profile Implementation

7 Implementation Description

This section describes the requirements and guidelines for implementing Dell CPU Profile.

Table 2 - Class Requirements: CPU Profile

Element Name	Requirement	Description			
Classes					
DCIM_CPUView	Mandatory	The class shall be implemented in the Implementation Namespace. See section 7.1.			
DCIM_LCElementConformsToProfile	Mandatory	The class shall be implemented in the Implementation Namespace.			
DCIM_LCElementConformsToProfile	Mandatory	The class shall be implemented in the Interop Namespace.			
DCIM_LCRegisteredProfile	Mandatory	The class shall be implemented in the Interop Namespace. See section 7.2.			
Indications					
None defined in this profile					

7.1 CPU View

This section describes the implementation for the DCIM_CPUView class.

This class shall be instantiated in the Implementation Namespace.

The DCIM_LCEIementConformsToProfile association(s) shall reference the DCIM_CPUView instance(s).

7.1.1 Resource URIs for WinRM®

The class Resource URI shall be "http://schemas.dell.com/wbem/wscim/1/cim-schema/2/DCIM_CPUView?__cimnamespace=root/dcim"

The key property shall be the InstanceID.

The instance Resource URI for DCIM_CPUView instance shall be:

"http://schemas.dell.com/wbem/wscim/1/cim-

schema/2/DCIM_CPUView?__cimnamespace=root/dcim+InstanceID=<FQDD>"

7.1.2 Operations

The following table details the implemented operations on DCIM_CPUView.

Table 3 - DCIM_CPUView - Operations

Operation Name	Requirements	Required Input
Get	Mandatory	Instance URI
Enumerate	Mandatory	Class URI

7.1.3 Properties

The following table details the implemented properties for DCIM_CPUView instance representing a processor in a system. The "Requirements" column shall denote the implementation requirement for the corresponding property. If the column "Property Name" matches the property name, the property either shall have the value denoted in the corresponding column "Additional Requirement", or shall be implemented according to the requirements in the corresponding column "Additional Requirement".

Table 4 - DCIM_CPUView - Properties

InstanceID Mandatory String A string containing the Fully Qualified Device Description, a user-friendly name for the object. PQDD Mandatory Mandatory Mandatory String CPUFamily Mandatory Mandatory Mandatory Mandatory Mandatory String CPUFamily Mandatory Man	Property Name	Requirements	Туре	Requirement and Description
FQDD Mandatory string object. PUFamily Mandatory string object. CPUFamily Mandatory string object. The property shall represent processor family type in hexadecimals. The property value shall be in MHz. The current Speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of the external bus interface (known as the front side bus). PrimaryStatus Mandatory uint32 FrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NUTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores available for processor. Voltage Mandatory uint32 Mandatory uint32 Processor in Volts. CPUStatus Mandatory uint32 Mandatory uint34 Mandatory uint35 Mandatory uint36 Mandatory uint36 Mandatory uint36 Mandatory uint36 Mandatory uint36 Mandatory uint36 Mandatory uint46 Mandatory ui		•		
PODD Mandatory string Description, a user-friendly name for the object. The property shall represent processor family type in hexadecimals. The property value shall be in MHz. The current Speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of the external bus interface (in MHz) of the external bus interface (in MHz) of the strend bus interface (in MHz) of the external bus interface (in MHz) of the strend bus	InstanceID	Mandatory	string	
FQDD Mandatory string Object. CPUFamily Mandatory String Object. The property shall represent processor family type in hexadecimals. The property value shall be in MHz. The current Speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of the external bus interface (known as the front side bus). PrimaryStatus Mandatory uint32 PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this processor. NumberofEnabledCores Mandatory uint32 processor. Number of processor cores enabled for processor. Number of processor cores available for processor. Voltage Mandatory uint32 processor. The property shall represent the voltage(s) of the processor in the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory size of the cache in KBytes.				
CPUFamily Mandatory String CPUFamily Mandatory CurrentClockSpeed Mandatory MaxClockSpeed Mandatory Mandatory MaxClockSpeed Mandatory Mandatory Mandatory Mandato				
CPUFamily Mandatory string type in nexadecimals. The property value shall be in MHz. The current Speed (in MHz) of this Processor. MaxClockSpeed Mandatory uint32 turnent speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of the external bus interface (known as the front side bus). Mandatory uint32 (known as the front side bus). PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores available for processor. Number of processor cores available for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Mandatory uint32 (shadon) Mandatory uint32 (shadon) Mandatory uint32 (shadon) Mandatory uint32 (shadon) The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The name of the organization responsible for producing the processor. Mandatory uint16 The cache level for Cache1 labeled cache. The name of the organization responsible for producing the processor. The cache level for Cache2 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	FQDD	Mandatory	string	
CurrentClockSpeed Mandatory uint32 The property value shall be in MHz. The current speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of the external bus interface (known as the front side bus). PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. NumberofEnabledCores Mandatory uint32 processor. Number of processor cores enabled for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	05.15 "			
CurrentClockSpeed Mandatory uint32 current speed (in MHz) of this Processor. MaxClockSpeed Mandatory uint32 maximum speed (in MHz) of this Processor. The property value shall be in MHz. The maximum speed (in MHz) of this Processor. The property value shall be in MHz. The speed (in MHz) of the external bus interface (known as the front side bus). PrimaryStatus PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores available for processor. Number of processor cores available for processor. Voltage Mandatory uint32 mandatory uint32 mandatory vintage string the processor in Volts. CPUStatus Mandatory uint6 disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory string The mane of the organization responsible for producing the processor. Mandatory vint16 The cache level for Cache1 labeled cache. Cache1Level Mandatory uint16 The cache level for Cache2 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	CPUFamily	Mandatory	string	
MaxClockSpeed Mandatory uint32 The property value shall be in MHz. The maximum speed (in MHz) of this Processor. ExternalBusClockSpeed Mandatory uint32 The property value shall be in MHz. The speed (in MHz) of the external bus interface (known as the front side bus). PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores enabled for processor. Number of processor cores available for processor. Voltage Mandatory uint32 tring the processor in Volts. CPUStatus Mandatory uint16 disabled due to a POST error (value=3). The characteristics include certain features of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache1Size Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	Commont Clouds Connord	Mondotom		
MaxClockSpeed Mandatory uint32 maximum speed (in MHz) of this Processor. ExternalBusClockSpeed Mandatory uint32 The property value shall be in MHz. The speed (in MHz) of the external bus interface (known as the front side bus). PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. PrimaryStatus Mandatory Uint32 Green type representation of status. NoTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. NumberofEnabledCores Mandatory uint32 Number of processor cores enabled for processor. Number of Processor Cores Mandatory vint32 Number of processor cores available for processor. Voltage Mandatory string Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). CPUStatus Mandatory uint32 The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Characteristics Mandatory The name of the organization responsible for produc	CurrentClockSpeed	Mandatory	umtsz	
ExternalBusClockSpeed Mandatory uint32 (In MHz) of the external bus interface (known as the front side bus). PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. NumberofEnabledCores Mandatory uint32 processor. Number of processor cores enabled for processor. Number of processor cores enabled for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value-3). The characteristics include certain features of the processor such as 64 bit support of data width of the processor. Model Mandatory uint32 tring The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. The property shall represent the total memory size of the cache in KBytes.	MayClockSpeed	Mandatory	uint32	
ExternalBusClockSpeed Mandatory uint32 speed (in MHz) of the external bus interface (known as the front side bus; value, intended to align with Red-Yellow-uint32 Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. NumberofEnabledCores Mandatory uint32 processor. Number of processor cores enabled for processor. Number of processor cores available for processor. Number of processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes.	WaxClockOpeed	Manuatory	unitoz	
ExternalBusClockSpeed Mandatory uint32 (known as the front side bus). PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores enabled for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory uint32 width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory				
PrimaryStatus provides a high level status value, intended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. NumberofEnabledCores Mandatory uint32 processor. Number of processor cores enabled for processor. Number of processor cores available for processor. Number of processor cores available for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor inght be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache1Size Mandatory uint64 The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	ExternalBusClockSpeed	Mandatory	uint32	
PrimaryStatus Mandatory Mandatory Walue, İntended to align with Red-Yellow-Green type representation of status. Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores enabled for processor. Number of processor cores available for processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory String The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory Mandato				
Total number of hardware enabled threads for processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores enabled for processor. Number of processor cores available for processor. Number of processor cores available for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory uint32 width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory size of the cache in KBytes.				
processor. NOTE: The disabling of the multithreading by the BIOS does not affect the number of hardware enabled threads reported by this property. Number of processor cores enabled for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory size of the cache in KBytes.	PrimaryStatus	Mandatory	uint32	
NumberofEnabledThreads Mandatory uint32 property. NumberofEnabledCores Mandatory uint32 processor. NumberOfProcessorCores Mandatory uint32 processor. Number of processor cores enabled for processor. Number of processor cores available for processor. Number of processor volts as definition processor. Number of processor. Number of processor. Number of processor. Number of				Total number of hardware enabled threads for
NumberofEnabledThreads Mandatory Vint32 Number of processor cores enabled for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory Mandatory String The make and or model of the product The name of the organization responsible for producing the processor. Mandatory String The cache level for Cache1 labeled cache. Cache2Level Mandatory Uint16 The cache level for Cache2 labeled cache. The property shall represent the total memory Size of the cache in KBytes. The property shall represent the total memory				
NumberofEnabledThreads Nandatory Number of processor cores enabled for processor. NumberOfProcessorCores Mandatory Voltage Mandatory Man				
NumberofEnabledCores Mandatory uint32 property. Number of processor cores enabled for processor. NumberOfProcessorCores Mandatory uint32 processor. Number of processor cores available for processor. Number of processor cores available for processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache1Size Mandatory uint6 The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory				
Number of processor cores enabled for processor. NumberOfProcessorCores Mandatory Voltage Mandatory Manda	Ni. was be a rest Core blood There and a	Mondotom		· · ·
NumberofEnabledCores Mandatory	NumberorEnabled infeads	Manualory	umisz	
NumberOfProcessorCores Mandatory uint32 processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	NumberofEnabledCores	Mandatory	uint32	•
NumberOfProcessorCores Mandatory uint32 processor. The property shall represent the voltage(s) of the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	14d11beroiE1tabledeores	Mandatory	diritoz	•
Voltage Mandatory string the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Mandatory string The cache level for Cache1 labeled cache. Cache1Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	NumberOfProcessorCores	Mandatory	uint32	·
Voltage Mandatory string the processor in Volts. Indicates the current status of the Processor. For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Mandatory string producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory				
For example, the Processor might be disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Mandatory string Producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	Voltage	Mandatory	string	
CPUStatus Mandatory uint16 disabled due to a POST error (value=3). The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Manufacturer Mandatory string producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory				Indicates the current status of the Processor.
The characteristics include certain features of the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Manufacturer Mandatory string producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory				
the processor such as 64 bit support for data width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Manufacturer Mandatory string producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory	CPUStatus	Mandatory	uint16	
Characteristics Mandatory uint32 width of the processor. Model Mandatory string The make and or model of the product The name of the organization responsible for producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory				
ModelMandatorystringThe make and or model of the productManufacturerMandatoryThe name of the organization responsible for producing the processor.Cache1LevelMandatoryuint16The cache level for Cache1 labeled cache.Cache2LevelMandatoryuint16The cache level for Cache2 labeled cache.Cache3LevelMandatoryuint16The cache level for Cache3 labeled cache.Cache1SizeMandatoryuint64size of the cache in KBytes.The property shall represent the total memoryThe property shall represent the total memory	Ob a va ata viati a a	Manadatam	:	
Manufacturer Mandatory string producing the processor. Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory		1	1	·
ManufacturerMandatorystringproducing the processor.Cache1LevelMandatoryuint16The cache level for Cache1 labeled cache.Cache2LevelMandatoryuint16The cache level for Cache2 labeled cache.Cache3LevelMandatoryuint16The cache level for Cache3 labeled cache.The property shall represent the total memoryCache1SizeMandatoryuint64size of the cache in KBytes.The property shall represent the total memory	Model	Mandatory	string	
Cache1Level Mandatory uint16 The cache level for Cache1 labeled cache. Cache2Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory cache1Size Mandatory uint64 size of the cache in KBytes. The property shall represent the total memory	Manufacturer	Mandatory	etring	
Cache3Level Mandatory uint16 The cache level for Cache2 labeled cache. Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory		•	•	
Cache3Level Mandatory uint16 The cache level for Cache3 labeled cache. The property shall represent the total memory Cache1Size Mandatory uint64 size of the cache in KBytes. The property shall represent the total memory		•		
Cache1Size Mandatory uint64 The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory size of the cache in KBytes. The property shall represent the total memory		· · · · · · · · · · · · · · · · · · ·		
Cache1Size Mandatory uint64 size of the cache in KBytes. The property shall represent the total memory	CaciledLevel	iviariuatury	unitio	
The property shall represent the total memory	Cache1Size	Mandatory	uint64	
	0.0.10.10.120	a.raa.ory		
Table I managery winter Size of the basic in Novice.	Cache2Size	Mandatory	uint64	size of the cache in KBytes.

Dua na anta a Mana a	Daminamanta	T	Demoinement and December
Property Name	Requirements	Туре	Requirement and Description
0 1 00:		04	The property shall represent the total memory
Cache3Size	Mandatory	uint64	size of the cache in KBytes.
			Cache1PrimaryStatus provides a high level
Ocal ad Discour Otal	Mandatas		status value, intended to align with Red-
Cache1PrimaryStatus	Mandatory	uint32	Yellow-Green type representation of status.
			Cache2PrimaryStatus provides a high level
Cash a ODsissa a su Otatura	Manadatam	:	status value, intended to align with Red-
Cache2PrimaryStatus	Mandatory	uint32	Yellow-Green type representation of status.
			Cache3PrimaryStatus provides a high level
Cook of Drive on Chatter	Mandatani		status value, intended to align with Red-
Cache3PrimaryStatus	Mandatory	uint32	Yellow-Green type representation of status.
			Cache ErrorMethodology - Contains the
Cook of Free Whath a dalage.	Ontional		enumerated value that describes the cache's
Cache1ErrorMethodology	Optional	uint16	error detection/correction mechanism
			Cache ErrorMethodology - Contains the enumerated value that describes the cache's
CoobooErrorMothodology	Ontional	uint16	
Cache2ErrorMethodology	Optional	ullito	error detection/correction mechanism
			Cache ErrorMethodology - Contains the enumerated value that describes the cache's
Coobo2ErrorMotbodology	Ontional	uint16	error detection/correction mechanism
Cache3ErrorMethodology	Optional	ullito	
			Defines whether this is write-back (value=1)
			or write-through (value=0) Cache, or whether this information \"Varies with Address\" (2) or
Cache1WritePolicy	Mandatory	uint16	\"Unknown\" (3) can be specified.
Cacherwhiterolicy	ivialiuatory	ullitto	Defines whether this is write-back (value=1)
			or write-through (value=0) Cache, or whether
			this information \"Varies with Address\" (2) or
Cache2WritePolicy	Mandatory	uint16	\"Unknown\" (3) can be specified.
Cachez viner oney	Wandatory	diricio	Defines whether this is write-back (value=1)
			or write-through (value=0) Cache, or whether
			this information \"Varies with Address\" (2) or
Cache3WritePolicy	Mandatory	uint16	\"Unknown\" (3) can be specified.
	,		Defines whether this is for instruction caching
			(value=3), data caching (value=4) or both
			(value=5, \"Unified\"). Also, \"Other\" (1) and
Cache1Type	Mandatory	uint16	\"Unknown\" (2) can be defined.
7,			Defines whether this is for instruction caching
			(value=3), data caching (value=4) or both
			(value=5, \"Unified\"). Also, \"Other\" (1) and
Cache2Type	Mandatory	uint16	\"Unknown\" (2) can be defined.
,			Defines whether this is for instruction caching
			(value=3), data caching (value=4) or both
			(value=5, \"Unified\"). Also, \"Other\" (1) and
Cache3Type	Mandatory	uint16	\"Unknown\" (2) can be defined.
			An integer enumeration defining the system
			cache associativity:
			"1" - "Unknown",
			"2" - "Other",
			"3" - "Direct Mapped"
			"4" - "2-way Set-Associative",
			"5" - "4-way Set-Associative",
			"6" - "Fully Associative",
			"7" - "8-way Set-Associative",
			"8" - "16-way Set-Associative",
Cache1Associativity	Mandatory	uint16	"9" - "12-way Set-Associative",

Property Name	Requirements	Туре	Requirement and Description
			"10" - "24-way Set-Associative",
			"11" - "32-way Set-Associative",
			"12" - "48-way Set-Associative",
			"13" - "64-way Set-Associative"
			"14" - "20-way Set-Associative"
			An integer enumeration defining the system
			cache associativity:
			"1" - "Unknown",
			"2" - "Other",
			"3" - "Direct Mapped"
			"4" - "2-way Set-Associative",
			"5" - "4-way Set-Associative",
			"6" - "Fully Associative",
			"7" - "8-way Set-Associative",
			"8" - "16-way Set-Associative",
			"9" - "12-way Set-Associative",
			"10" - "24-way Set-Associative",
			"11" - "32-way Set-Associative",
			"12" - "48-way Set-Associative",
			"13" - "64-way Set-Associative"
Cache2Associativity	Mandatory	uint16	"14" - "20-way Set-Associative"
			An integer enumeration defining the system
			cache associativity:
			"1" - "Unknown",
			"2" - "Other",
			"3" - "Direct Mapped"
			"4" - "2-way Set-Associative",
			"5" - "4-way Set-Associative",
			"6" - "Fully Associative",
			"7" - "8-way Set-Associative",
			"8" - "16-way Set-Associative",
			"9" - "12-way Set-Associative",
			"10" - "24-way Set-Associative",
			"11" - "32-way Set-Associative",
			"12" - "48-way Set-Associative",
Cache3Associativity	Mandatory	uint16	"13" - "64-way Set-Associative" "14" - "20-way Set-Associative"
	Mandatory	uint16	
Cache1SRAMType	•	+	Cache SRAM Type.
Cache2SRAMType	Mandatory	uint16	Cache SRAM Type.
Cache3SRAMType	Mandatory	uint16	Cache SRAM Type.
			This property provides the last time \"System \"Inventory Collection On Reboot(CSIOR)\"
			` '
LastSystemInventoryTime	Mandatory	string	was performed. The value is represented as yyyymmddHHMMSS.
			This property provides the last time the data
			was updated. The value is represented as
LastUpdateTime	Mandatory	string	yyyymmddHHMMSS

7.2 CPU Profile Profile Registration

This section describes the implementation for the DCIM_LCRegisteredProfile class.

This class shall be instantiated in the Interop Namespace.

The DCIM_LCElementConformsToProfile association(s) shall reference the DCIM_LCRegisteredProfile instance.

7.2.1 Resource URIs for WinRM®

The class Resource URI shall be "http://schemas.dmtf.org/wbem/wscim/1/cim-schema/2/CIM_RegisteredProfile?__cimnamespace=root/interop"

The key property shall be the InstanceID property.

The instance Resource URI shall be: "http://schemas.dell.com/wbem/wscim/1/cim-schema/2/DCIM_LCRegisteredProfile?__cimnamespace=root/interop+InstanceID=DCIM:CPU:1.0.0"

7.2.2 Operations

The following table details the implemented operations on DCIM LCRegisteredProfile.

Table 5 - DCIM_LCRegisteredProfile - Operations

Operation Name	Requirements	Required Input
Get	Mandatory	Instance URI
Enumerate	Mandatory	Class URI

7.2.3 Properties

The following table details the implemented properties for DCIM_LCRegisteredProfile instance representing CPU Profile implementation. The "Requirements" column shall denote the implementation requirement for the corresponding property. If the column "Name" matches the property name, the property either shall have the value denoted in the corresponding column "Additional Requirements", or shall be implemented according to the requirements in the corresponding column "Additional Requirements".

Table 6 - DCIM_LCRegisteredProfile

Property Name	Requirement	Туре	Additional Requirements
InstanceID	Mandatory	String	DCIM:CPU:1.0.0
RegisteredName	Mandatory	String	This property shall have a value of "CPU".
RegisteredVersion	Mandatory	String	This property shall have a value of "1.0.0".
RegisteredOrganization	Mandatory	Uint16	This property shall have a value of 1 (Other).
OtherRegisteredOrganization	Mandatory	String	The property value shall match "DCIM".
AdvertisedTypes[]	Mandatory	Uint16	This property array shall contain [1(Other), 1 (Other)].
AdvertiseTypeDescriptions[]	Mandatory	String	This property array shall contain ["WS-ldentify", "Interop Namespace"].
			This property array shall describe the required licenses for this profile.
ProfileRequireLicense[]	Mandatory	String	If no license is required for the profile, the property shall have value NULL.
			This property array shall contain the status for the corresponding license in the same element index of the ProfileRequireLicense array property. Each array element shall
ProfileRequireLicenseStatus[]	Mandatory	String	contain:

"LICENSED"
"NOT_LICENSED"
If no license is required for the profile, the property shall have value NULL.

8 Methods

This section details the requirements for supporting extrinsic methods for the CIM elements defined by this profile.

No additional details specified.

9 Use Cases

See Lifecycle Controller (LC) Integration Best Practices Guide.

10 CIM Elements

No additional details specified.

11 Privilege and License Requirement

The following table describes the privilege and license requirements for the listed operations . For the detailed explanation of the privileges and licenses, refer to the Dell WSMAN Licenses and Privileges specification.

Table 7 - Privilege and License Requirements

Class and Method	Operation	User Privilege Required	License Required
	ENUMERATE,		LM_REMOTE_ASSET_IN
DCIM_CPUView	GET	Login	VENTORY
DCIM_LCElementConformsToProfile	ENUMERATE, GET	Login	None.
DCIM_LCRegisteredProfile	ENUMERATE, GET	Login	None.