

# Dell Command | PowerShell Provider

## Version 2.6 Reference Guide



## Notes, cautions, and warnings

 **NOTE:** A NOTE indicates important information that helps you make better use of your product.

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.

<b>Chapter 1: Introduction to Dell Command   PowerShell Provider 2.6.....</b>	<b>4</b>
<b>Chapter 2: Attributes supported in Dell Command   PowerShell Provider 2.6.....</b>	<b>5</b>
AdvancedBootOptions.....	6
AdvancedConfigurations.....	7
BatteryInformation.....	7
BIOSSetupAdvancedMode.....	8
Boot Configuration.....	8
BootSequence.....	8
Connection.....	8
Integrated Devices.....	9
IntelSoftwareGuardExtensions.....	10
Keyboard.....	11
Manageability.....	11
Maintenance.....	12
MemoryInformation.....	13
MiscellaneousDevices.....	14
Passwords.....	15
Performance.....	16
POSTBehavior.....	20
PowerManagement.....	22
PreEnabled.....	28
ProcessorInformation.....	30
SecureBoot.....	31
Security.....	31
StealthModeControl.....	35
SupportAssistSystemResolution.....	36
SystemConfiguration.....	37
SystemInformation.....	50
SystemLogs.....	50
System Management.....	51
ThermalConfiguration.....	51
TPMSecurity.....	51
USBConfiguration.....	53
Video.....	57
VirtualizationSupport.....	58
Wireless.....	60
<b>Chapter 3: Error reporting in Dell Command   PowerShell Provider 2.6.....</b>	<b>62</b>
<b>Chapter 4: Accessing documents from the Dell support site.....</b>	<b>67</b>

# Introduction to Dell Command | PowerShell Provider 2.6


The Dell Command | PowerShell Provider module enables BIOS configuration for Dell enterprise client systems through the Windows PowerShell interface. It works for local systems, remote systems, and Windows Preinstallation Environment (WinPE).

This document describes the supported attributes, and error reporting in Dell Command | PowerShell Provider.


# Attributes supported in Dell Command | PowerShell Provider 2.6

The following are categories in Dell Command PowerShell Provider and contains BIOS attributes.

**Table 1. Attributes supported in Dell Command | PowerShell Provider**

Category Name	Description
AdvancedBootOptions	Displays the attributes to configure advanced boot settings.
AdvancedConfigurations	Displays the attributes to configure various advanced settings.
BatteryInformation	Displays information about each battery with the percent charged information.
BIOSSetupAdvancedMode	Displays the attributes to configure various BIOS setups advanced mode settings.
BootSequence	Displays the attributes to configure the system boot settings.
BootConfiguration	Displays the attributes to configure the system boot settings.
IntegratedDevices	Displays the attributes to configure the Integrated Device settings.
IntelSoftwareGuardExtensions	Displays the attributes to configure Intel Software Guard Extensions settings.
Manageability	Displays the attributes to configure various manageability settings.
Maintenance	Displays the attributes to configure maintenance-related settings.
MemoryInformation	Displays noneditable information about memory.
MiscellaneousDevices	Displays the attributes to configure various miscellaneous onboard devices.
Passwords	Displays the attributes to configure performance-related settings.
Performance	Displays the attributes to configure performance-related settings.
POSTBehavior	Displays the attributes to configure system's behavior after POST.
PowerManagement	Displays the attributes to configure power management settings.
PreEnabled	Displays the attributes to configure various preenabled settings.  <b>NOTE:</b> This category describes the miscellaneous BIOS settings.
ProcessorInformation	Displays noneditable information about processors.
SecureBoot	Displays the attributes to configure Secure Boot settings.
Security	Displays the attributes to configure the security feature of the system.
StealthModeControl	Displays the attributes to configure stealth mode settings.
SupportAssistSystemResolution	Displays the attributes to configure various SupportAssist settings.
SystemConfiguration	Displays the attributes to configure devices that are integrated on the system board.
SystemManagement	Displays information that uniquely identifies the system.
SystemInformation	Displays information that uniquely identifies the system.
SystemLogs	Displays the attributes to configure system logs settings.
TPMSecurity	Displays the attributes to configure TPM device settings.
Thermal Configuration	Displays the attributes to configure thermal configuration settings.

**Table 1. Attributes supported in Dell Command | PowerShell Provider (continued)**

Category Name	Description
USBConfiguration	Displays the attributes to configure USB settings.  <b>NOTE:</b> USB keyboard and mouse always work as defined in the BIOS setup, irrespective of these settings.
Video	Displays the attributes to configure video settings.
VirtualizationSupport	Displays the attributes to configure virtualization settings.
Wireless	Displays the attributes to configure wireless devices.

**Topics:**

- [AdvancedBootOptions](#)
- [AdvancedConfigurations](#)
- [BatteryInformation](#)
- [BIOSSetupAdvancedMode](#)
- [Boot Configuration](#)
- [BootSequence](#)
- [Connection](#)
- [Integrated Devices](#)
- [IntelSoftwareGuardExtensions](#)
- [Keyboard](#)
- [Manageability](#)
- [Maintenance](#)
- [MemoryInformation](#)
- [MiscellaneousDevices](#)
- [Passwords](#)
- [Performance](#)
- [POSTBehavior](#)
- [PowerManagement](#)
- [PreEnabled](#)
- [ProcessorInformation](#)
- [SecureBoot](#)
- [Security](#)
- [StealthModeControl](#)
- [SupportAssistSystemResolution](#)
- [SystemConfiguration](#)
- [SystemInformation](#)
- [SystemLogs](#)
- [System Management](#)
- [ThermalConfiguration](#)
- [TPMSecurity](#)
- [USBConfiguration](#)
- [Video](#)
- [VirtualizationSupport](#)
- [Wireless](#)

## AdvancedBootOptions

**Table 2. AdvancedBootOptions**

Attribute Name	Description
<b>AttemptLegacyBoot</b>	Determines if BIOS should attempt to boot from the legacy boot list when the UEFI boot list fails. The following are the possible values:

**Table 2. AdvancedBootOptions (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>Enabled—If the UEFI boot list fails, then BIOS attempts to boot from the Legacy boot list.</li> <li>Disabled—BIOS discontinues the booting process if the UEFI boot list fails.</li> </ul>
<b>LegacyOrom</b>	<p>If enabled, allows legacy option ROMs to load. Without this option, only UEFI option ROMs load. This option is required for Legacy boot mode. This mode cannot be enabled with Secure Boot. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>UefiBootPathSecurity</b>	<p>Determines whether the system should prompt the user to enter the Admin password, if set, while booting from a UEFI boot path from the F12 Boot Menu. The following are the possible values:</p> <ul style="list-style-type: none"> <li>AlwaysExceptInternalHdd—All UEFI boot paths require the user to enter the Admin password, except for the boot paths that are hosted on an internal hard disk drive.</li> <li>Always—Bootting from any UEFI boot path requires the user to enter the Admin password.</li> <li>Never—The Admin password is not required for booting from UEFI boot paths.</li> <li>AlwaysExceptInternalHddPxe—All UEFI boot paths require the Admin password, except for boot paths hosted on internal hard disk drives or PXE Boot.</li> </ul>

## AdvancedConfigurations

**Table 3. AdvancedConfigurations**

Attribute Name	Description
<b>Aspm</b>	<p>Set the ASPM (Active State Power Management) level. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Auto—There is handshaking between the device and PCI Express hub to determine the best ASPM mode supported by the device.</li> <li>Disabled—ASPM power management is turned off always.</li> <li>L1—ASPM power management is set to use L1.</li> </ul>
<b>OneTBSystemMemoryLimitEnable</b>	<p>Confines the system memory to less than 1 TB when more than 1TB memory is installed in the computer. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>PcieLinkSpeed</b>	<p>This feature in BIOS setup allows you to select the maximum PCIe link speed within the system. Adjusting the setting improves the compatibility with older PCIe add-in adapters. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Auto—Setting the system to Auto option, allows the devices (if capable) to obtain the maximum speed for hardware configuration.</li> <li>Gen1—Setting the system to Gen1 changes the device capabilities.</li> <li>Gen2—Setting the system to Gen2 changes the device capabilities.</li> <li>Gen3—Setting the system to Gen3 changes the device capabilities.</li> <li>Gen4—Setting the system to Gen4 changes the device capabilities.</li> </ul>

## BatteryInformation

**Table 4. BatteryInformation**

Attribute Name	Description
<b>PercentCharged</b>	<p>Displays the charged percentage of the battery. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Read-only</li> </ul>

# BIOSSetupAdvancedMode

Table 5. BIOSSetupAdvancedMode

Attribute Name	Description
AdvancedMode	Enabling BIOS Setup Advanced Mode makes all BIOS settings visible. The following are the possible values: <ul style="list-style-type: none"><li>• Enabled</li><li>• Disabled</li></ul>

## Boot Configuration

Table 6. Boot Configuration

Attribute Name	Description
MicrosoftUefiCa	Enabled or disabled the Microsoft UEFI CA in SecureBoot. The following are the possible values: <ul style="list-style-type: none"><li>• Enabled—Enables Microsoft UEFI CA in a secure boot.</li><li>• Disabled—Disables Microsoft UEFI CA in a secure boot.</li></ul>

## BootSequence

Table 7. BootSequence

Attribute Name	Description
BootList	Determines the system's boot mode. The following are the possible values: <ul style="list-style-type: none"><li>• Uefi — Enables booting to Unified Extensible Firmware Interface (UEFI) capable operating systems.</li><li>• Legacy — (the default) Ensures compatibility with operating systems that do not support UEFI.</li></ul> <p><b>NOTE:</b> Legacy boot mode is not allowed when secure boot is enabled or legacy option ROM is disabled.</p>
BootSequence	Specifies the order in which a system searches for devices when trying to find an operating system to boot. The BootSequence option allows users to customize the boot order and boot ability of boot devices. The UEFI BIOS allows the selection of UEFI boot paths or Legacy boot devices.

## Connection

Table 8. Connection

Attribute	Description
GpsAntSwitch	This setting configures to decide which antenna to be used, when the system is docked. When the system is undocked, the system antennas are used and there is no impact. The following are the possible values: <ul style="list-style-type: none"><li>• DockAntenna—If set to the <b>DockAntenna</b>, then the radio switches to use the external docking station antenna.</li><li>• SystemAntenna—If set to the <b>SystemAntenna</b>, the radio continues to use the internal system antenna.</li></ul> <p><b>NOTE:</b> This setting applies to the Rugged docking stations and does not apply to the USB Type-C docking stations.</p>



**Table 8. Connection (continued)**

Attribute	Description
<b>HTTPsBoot</b>	Enables or disables boot capabilities on the platform. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Enabled</b>—Enables HTTP(s) boot capabilities on the platform.</li> <li>• <b>Disabled</b>—Disables HTTP(s) boot capabilities on the platform.</li> </ul>
<b>HTTPsBootMode</b>	HTTP(s) boot allows the boot URL to read and extract from the Dynamic Host Configuration Protocol (DHCP). The following are the possible values: <ul style="list-style-type: none"> <li>• <b>ManualMode</b>—HTTP(s) boot reads the boot URL that has been provided.</li> <li>• <b>AutoMode</b>—HTTP(s) boot automatically extracts boot URL from the Dynamic Host Configuration Protocol (DHCP).</li> </ul>
<b>WlanAntSwitch</b>	This setting configures on a radio-by-radio basis to decide which antenna to use when the system is docked. The available options are docking station or system antenna. When the system is undocked, the system antennas are used and there is no impact. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>DockAntenna</b>—If set to the <b>DockAntenna</b>, then the radio switches to use the external docking station antenna.</li> <li>• <b>SystemAntenna</b>—If set to the <b>SystemAntenna</b>, the radio continues to use the internal system antenna.</li> </ul> <p><b>NOTE:</b> This setting applies to the Rugged docking stations and does not apply to the USB Type-C docking stations.</p>
<b>WwanAntSwitch</b>	This setting configures on a radio-by-radio basis to decide which antenna to be used, when the system is docked. When the system is undocked, the system antennas are used and there is no impact. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>DockAntenna</b>—If set to the <b>DockAntenna</b>, then the radio switches uses the external docking station antenna.</li> <li>• <b>SystemAntenna</b>—If set to the <b>SystemAntenna</b>, the radio continues to use the internal system antenna.</li> </ul> <p><b>NOTE:</b> This setting applies to the Rugged docking stations and does not apply to the USB Type-C docking stations.</p>

## Integrated Devices

**Table 9. Integrated Devices**

Attribute	Description
<b>DisUsb4Pcie</b>	The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Enabled</b>—Enable the USB4 PCIE tunneling.</li> <li>• <b>Disabled</b>—Disable the USB4 PCIE tunneling.</li> </ul>
<b>PCleBifurcation</b>	This setting allows the bifurcation feature configuration of the CPU's PCIe port. The auto setting configures the PCIe port to its maximum width (1x16) unless a mass storage controller card is installed. When a mass storage controller card is installed, the PCIe port is automatically bifurcated to 1x8 + 2x4. The remaining and mutually-exclusive options allow explicit bifurcation configuration of the CPU's PCIe port. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Auto</b></li> <li>• <b>1x16</b></li> <li>• <b>2x8</b></li> <li>• <b>1x8+2x4</b></li> </ul>
<b>VideoPowerOnlyPorts</b>	Limits the Type-C port functionality to video or power. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Enabled</b></li> <li>• <b>Disabled</b></li> </ul>

**Table 9. Integrated Devices (continued)**

Attribute	Description
<b>TypeCDockAudio</b>	This field allows you to connect an audio device on the Dell dock external ports. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Enabled</b></li> <li>• <b>Disabled</b></li> </ul>
<b>TypeCDockLan</b>	This field allows you to connect LAN on the Dell dock external ports. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Enabled</b></li> <li>• <b>Disabled</b></li> </ul>
<b>TypeCDockOverride</b>	This field allows the Type-C Dell dock to initiate a data stream when the external USB ports are disabled. When the Type-C dock override is enabled, it activates video, audio, or LAN connection that can be used. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Enabled</b></li> <li>• <b>Disabled</b></li> </ul>
<b>TypeCDockVideo</b>	This field allows you to connect a video device on the Dell dock external ports. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>Enabled</b></li> <li>• <b>Disabled</b></li> </ul>

## IntelSoftwareGuardExtensions

**Table 10. IntelSoftwareGuardExtensions**

Attribute Name	Description
<b>EnclaveSize</b>	Displays the memory allocation size for the Intel Software Guard Extension (SGX) processor reserved memory. The following are the possible values: <ul style="list-style-type: none"> <li>• 32MB</li> <li>• 64MB</li> <li>• 128MB</li> <li>• 256MB</li> </ul> <p><b>i</b> <b>NOTE:</b> You cannot set the Enclave Reserve Memory Size using the Dell Command   PowerShell Provider. One of the methods of setting Enclave Reserve Memory Size is from the BIOS setup screen.</p>
<b>SgxLaunchControl</b>	Sets the Intel Software Guard Extensions Launch Control Policy. The following are the possible values: <ul style="list-style-type: none"> <li>• <b>IntelLocked</b>—Locks SGX to support Intel Enclave Launch Provider.</li> <li>• <b>RuntimeSelectable</b>—Allows operating system or hypervisor control of Enclave Launch Provider.</li> </ul>
<b>SoftGuardEn</b>	Configures Software Guard Extensions (SGX) feature. You can select Enabled or SoftControlled if this option is disabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> <li>• SoftControlled</li> </ul> <p><b>i</b> <b>NOTE:</b> Using the Dell Command   PowerShell Provider, you cannot do the following: <ul style="list-style-type: none"> <li>• Disable this feature if the current state is Enabled or SoftControlled</li> <li>• Enable this feature if the current state is SoftControlled</li> <li>• Change this feature to SoftControlled if the current state is Enabled</li> </ul> </p> <p><b>i</b> <b>NOTE:</b> One of the methods of configuring Software Guard Extensions (SGX) feature is from the BIOS setup screen.</p>

# Keyboard

Table 11. Keyboard

Attribute	Description
<b>DeviceHotkeyAccess</b>	<p>DeviceHotkeyAccess manages whether you can access device configuration screen through hotkeys during system reboot. This setting prevents the access to Intel® RAID (<b>CTRL+I</b>), LSI RAID (<b>CTRL+C</b>), or Intel Management Engine BIOS Extension (<b>CTRL+P/F12</b>).The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enabling device configuration hotkey allows you to access the device configuration screen by pressing the hotkeys during the system reboot.</li> <li>• One time enable—You can access the device configuration screen by using hotkeys after a successful reboot. On the next system reboot, the setting reverts back to a disabled state.</li> <li>• Disabled—You cannot access the device configuration screen using hotkeys.</li> </ul>
<b>RgbPerKeyKbdLang</b>	<p>Select the language that matches the keyboard configuration of the system. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• English US</li> <li>• English International</li> <li>• Canada Bilingual MUI</li> <li>• Korean</li> <li>• Arabic</li> <li>• Russian</li> <li>• UK-English</li> <li>• German</li> <li>• French</li> <li>• European</li> <li>• Spanish (LATAM)</li> <li>• Nordic MUI</li> <li>• Japanese</li> </ul>
<b>RgbPerKeyKbdColor</b>	<p>Select the keyboard color that matches the keyboard configuration of the system. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Dark</li> <li>• Light</li> </ul>

# Manageability

Table 12. Manageability






Attribute	Description
<b>AmtCap</b>	<p>Set the intel active management technology (AMT) capability. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—If Intel Active Management Technology is enabled, MEBx is available through the F12 menu and you can provision AMT. MEBx may not be not accessible if OROM Keyboard Access is disabled.</li> <li>• Disabled—If Intel Active Management Technology is disabled, MEBx is not available in pre-boot. Once disabled, Intel Active Management Technology can only be enabled through the BIOS interface. If the Intel AMT is already provisioned, AMT cannot be disabled. Un-provisioning AMT is required to disable AMT.</li> <li>• Restrict MEBx Access—If Intel Active Management Technology is enabled, MEBx is not available in pre-boot, but you can provision AMT from the operating systems.</li> </ul>

**Table 12. Manageability (continued)**

Attribute	Description
<b>PostMebxKey</b>	MEBx stands for Intel Management Engine BIOS Extension. Enables or disables the MEBx hotkey function when the system boots. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbProvision</b>	Enables or disables provisioning of Intel AMT from a USB storage device. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Intel AMT can be provisioned using the local provisioning file via a USB storage device.</li> <li>• Disabled—Provisioning of Intel AMT from a USB storage device is blocked.</li> </ul>

## Maintenance

**Table 13. Maintenance**


Attribute Name	Description
<b>AllowBIOSDowngrade</b>	Allows or restricts downgrading of the system BIOS. <p> <b>NOTE:</b> You cannot enable the Allow BIOS Downgrade feature using the Dell Command   PowerShell Provider.</p> <p> <b>NOTE:</b> One of the methods of enabling the Allow BIOS Downgrade feature is from the BIOS setup screen.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Allows the system to downgrade the system BIOS.</li> <li>• Disabled—Restricts the system to downgrade the system BIOS.</li> </ul> <p> <b>NOTE:</b> The read-only mechanism is not displayed at option level, while the AllowBIOSDowngrade is enabled.</p>
<b>BiosAutoRcvr</b>	Enables or disables BIOS auto recovery feature. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—If BIOS corruption is detected, the system automatically recovers BIOS without any user interaction.</li> <li>• Disabled—Disables BIOS auto recovery feature.</li> </ul> <p> <b>NOTE:</b> You can enable this option only if BiosRcvrFrmHdd option is enabled.</p>
<b>BiosIntegrityCheck</b>	Enables or disables the BIOS integrity check during the booting process. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—BIOS checks the BIOS image integrity during every booting process.</li> <li>• Disabled—BIOS checks the BIOS image integrity only if the previous booting process did not complete.</li> </ul> <p> <b>NOTE:</b> BIOS checks the BIOS image integrity only if the BiosAutoRcvr option is enabled.</p>
<b>BiosRcvrFrmHdd</b>	Enables or disables the system BIOS Recovery option. This feature saves a recovery image to a primary hard disk drive storage, or to an external USB, and uses this recovery image to recover the BIOS image when system BIOS fails. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—BIOS stores the recovery image on a primary hard disk drive storage. So the BIOS recovery image is available both from the primary hard disk drive permanent storage and via an external USB.</li> <li>• Disabled—BIOS does not store the recovery image on primary hard disk drive storage. So the BIOS recovery image is available only via an external USB.</li> </ul>
<b>MicrocodeUpdateSupport</b>	This feature enables or disables the microcode updates either from the flash update utility or the operating system. The following are the possible values:

**Table 13. Maintenance (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>NodeInterleave</b>	<p>This field controls the distribution of the system memory among the physical processors. This affects the performance because a processor can access its local memory faster than the memory which is allocated to the other processors. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—When enabled, system memory is configured in Non-Uniform Memory Access (NUMA) mode. Memory is configured into blocks to each processor. A NUMA-aware operating system can use this configuration to allocate memory for optimal performance.</li> <li>• Disabled—When disabled, system memory is configured in SMP (Symmetric MultiProcessing) mode. Memory is configured into one contiguous block that is interleaved between multiple processors. This mode provides better performance for operating systems that are non-NUMA-aware and do not allocate memory.</li> </ul>
<b>Serr</b>	<p>Enables or disables the SERR on the DRAM controller and the PEG controller in the north bridge. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled—Disable the SERR DMI messaging mechanism.</li> <li>• Enabled—Allows SERR messages to be generated.</li> </ul>

## MemoryInformation

**Table 14. MemoryInformation**

Attribute Name	Description
<b>DIMMASize</b>	Displays the amount of main memory physically installed in the DIMM slot A. The following are the possible values: Read-only
<b>DIMMBSize</b>	Displays the amount of main memory physically installed in the DIMM slot B. The following are the possible values: Read-only
<b>DIMMCSize</b>	Displays the amount of main memory physically installed in the DIMM slot C. The following are the possible values: Read-only
<b>DIMMDSize</b>	Displays the amount of main memory physically installed in the DIMM slot D. The following are the possible values: Read-only
<b>MemoryAvailable</b>	<p>Displays the amount of main memory available to the operating system.</p> <p> <b>NOTE:</b> Due to an amount of memory allocated for the system use, MemoryAvailable is less than MemoryInstalled. Certain operating systems may not be able to use all the available memory.</p> <p>The following are the possible values: Read-only</p>
<b>MemoryInstalled</b>	Displays the amount of main memory physically installed in the system. The following are the possible values: Read-only
<b>MemorySpeed</b>	Displays the clock frequency of the main memory. The following are the possible values: Read-only
<b>MemoryTechnology</b>	Displays the technology of the main memory installed in the system. The following are the possible values: Read-only

# MiscellaneousDevices

Table 15. MiscellaneousDevices


Attribute Name	Description
<b>BroadComTruManage</b>	Enables or disables Broadcom TruManage technology. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Camera</b>	Enables or disables the camera. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Camera2</b>	Enable or disables the backward-facing camera. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DediGPSRadio</b>	Enables or disables the internal GPS radio. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>EsataPorts</b>	Enables or disables all e-SATA ports. If the system supports a dock, all e-SATA ports into the dock are also enabled or disabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>ExpressCard</b>	Enables or disables the ExpressCard. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>HdFreeFallProtect</b>	Enables or disables hard drive free fall protection. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>MediaCard</b>	Enables or disables the media card. If disabled, the media card is hidden from the OS and not seen in the Device Manager. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>MediaCardand1394</b>	Enables or disables the media card and 1394. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>MiniCardSSDDevice</b>	Enables or disables the mini card Solid State Drive (SSD) module. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>ModuleBayDevice</b>	Enables or disables the module bay. The module bay is a hot-pluggable bay where storage and media devices such as HDDs, CDs or DVDs can be installed. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>OnboardModem</b>	Enables or disables the onboard internal modem. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PcCard</b>	Enables or disables the PC card. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

**Table 15. MiscellaneousDevices (continued)**

Attribute Name	Description
<b>PciSlots</b>	Enables or disables the various on-board PCI slots. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PCMCIA</b>	Enables or disables the PCMCIA device slot. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SdCard</b>	Enables or disables the SD card slot. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SdCardBoot</b>	Enables or disables booting the system from an SD card. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Allows the system to boot from an SD card.</li> <li>• Disabled—Prevents the system from detecting or boot from the SD card.</li> </ul>
<b>SdCardReadOnly</b>	Enables or disables the read-only mode for SD card. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

## Passwords

**Table 16. Passwords**

Attribute Name	Description
 <b>NOTE:</b> If the criteria PwdMinLen >=8, PwdLowerCaseRqd=Enabled, and PwdUpperCaseRqd=Enabled is followed, then StrongPassword is Enabled. If this criteria is not followed, then StrongPassword is Disabled. Vice-versa is also applicable.	
<b>PwdMinLen</b>	This feature controls the minimum number of characters that are mandatory for a password. The following are the possible values: 4 - 32
<b>PwdLowerCaseRqd</b>	This feature reinforces that the password must contain one lower case letter. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PwdUpperCaseRqd</b>	This feature reinforces that the password must contain one upper case letter. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PwdDigitRqd</b>	This feature reinforces that the password must contain one digit number. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PwdSpecialCharRqd</b>	This feature reinforces password must contain one special character. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

# Performance

Table 17. Performance

Attribute Name	Description
<b>AdaptiveCStates</b>	<p>Adaptive C-States allow the system to dynamically detect high usage of a discrete graphics and adjust system parameters for higher performance during that time period. This feature requires an AC adapter due to higher energy consumption, and dynamically it is not possible to activate higher performance without an appropriate AC adapter. Other settings that conserve power may block the utilization of this feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>AdjCachePrefetch</b>	<p>Enables or disables the AdjacentCacheLinePrefetch feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—CPU fetches the adjacent cache line in the other half of the sector.</li> <li>• Disabled—CPU only fetches the cache line that contains the data that are currently required by the CPU.</li> </ul>
<b>CPUCore</b>	<p>This field specifies whether the processor has one or more cores enabled. The performance of some applications improve with additional cores. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• CoresAll—All cores are enabled.</li> <li>• Cores1—Only one core is enabled.</li> <li>• Cores2—Two cores are enabled.</li> <li>• Cores3—Three cores are enabled.</li> <li>• Cores4—Four cores are enabled.</li> <li>• Cores5—Five cores are enabled.</li> <li>• Cores6—Six cores are enabled.</li> <li>• Cores7—Seven cores are enabled.</li> <li>• Cores8—Eight cores are enabled.</li> <li>• Cores9—Nine cores are enabled.</li> <li>• Cores10—Ten cores are enabled.</li> <li>• Cores11—Eleven cores are enabled.</li> <li>• Cores12—Twelve cores are enabled.</li> <li>• Cores13—Thirteen cores are enabled.</li> <li>• Cores14—Fourteen cores are enabled.</li> <li>• Cores15—Fifteen cores are enabled.</li> <li>• Cores16—Sixteen cores are enabled.</li> <li>• Cores17—Seventeen cores are enabled.</li> <li>• Cores18—Eighteen cores are enabled.</li> <li>• Cores19—Nineteen cores are enabled.</li> <li>• Cores20—Twenty cores are enabled.</li> <li>• Cores21—Twenty one cores are enabled.</li> <li>• Cores22—Twenty two cores are enabled.</li> <li>• Cores23—Twenty three cores are enabled.</li> <li>• Cores24—Twenty four cores are enabled.</li> <li>• Cores25—Twenty five cores are enabled.</li> <li>• Cores26—Twenty six cores are enabled.</li> <li>• Cores27—Twenty seven cores are enabled.</li> <li>• Cores28—Twenty eight cores are enabled.</li> </ul> <p><b>NOTE:</b> If the <b>CpuCore</b> is not set to <b>CoresAll</b> option, then you cannot change the <b>MultipleAtomCores</b> option to <b>0</b>.</p> <p><b>NOTE:</b> If the <b>MultipleAtomCores</b> is not set to <b>0</b>, then you cannot change the <b>CpuCore</b> option.</p>
<b>CpuSnoopMode</b>	<p>Configures the CPU snoop mode. The following are the possible values:</p>




**Table 17. Performance (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Early—Enables early snoop mode. Use this mode for latency-sensitive applications that do not require high remote bandwidth.</li> <li>• Home—Enables home snoop mode. Use this mode for applications that require high memory bandwidth.</li> <li>• ClusterOnDie—Enables cluster on die mode. Dell recommends this mode for NUMA-optimized applications to achieve lowest local memory latency, and highest local memory bandwidth.</li> <li>• OppSnoop—Enables opportunistic snoop mode. Directory with Opportunistic Snoop Broadcast (OSB) offers a good balance of latency and bandwidth.</li> <li>• NoSnoop—Enables no snoop mode.</li> </ul>
<b>CStatesCtrl</b>	<p>Enables or disables additional processor sleep states. The operating system may optionally use these states for additional power savings when idle. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DRmt</b>	<p>The Dell Reliable Memory Technology (RMT) feature identifies and filters out defective regions of the memory modules before they are consumed by the BIOS or OS. When enabled, the system automatically identifies errors, record their locations, and exclude bad location on reboot. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DynTunML</b>	<p>Enables operating system capability to enhance dynamic power tuning capabilities based on detected workloads. Protections for exposure: The <code>-Admin</code> password restricts editing the command <code>-Removed</code> in case when you are using command line interface. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>EnableMultiCoreSupport</b>	<p>Enables or disables multiple CPU cores. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—The operating system is allowed to access additional cores present on a single CPU package.</li> <li>• Disabled—The operating system is prevented to access additional cores present on a single CPU package.</li> </ul>
<b>HwPrefetcher</b>	<p>Enables or disables the CPU's hardware prefetcher. If enabled, the processor's Hardware Prefetcher will automatically prefetch data and code for the processor. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IntelRapidStart</b>	<p>Enables or disables the Intel Rapid Start feature. The Intel Rapid Start feature reduces power consumption by putting the system into a low-power state during sleep mode after the specified amount of time (minutes). The resume time may be slightly more than resuming the system from a sleep mode, but less than resuming from a hibernate mode. Intel Rapid Start Technology is automatically be disabled due to configuration changes, such as:</p> <ul style="list-style-type: none"> <li>• Hard disk configuration or partition changes</li> <li>• Memory capacity over 8GB is installed.</li> <li>• System or HDD password is enabled.</li> <li>• A Dell Encryption Accelerator card is installed.</li> <li>• The BlockSleep setting is enabled.</li> </ul>
<b>IntelRapidStartInstantOnDisplay</b>	<p>Enables or disables displaying the system logo from cache during system resume using Intel Rapid Start Technology. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Displays the system logo from cache during system resume using Intel Rapid Start Technology.</li> </ul>

**Table 17. Performance (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>Disabled—Does not display the system logo from cache during system resume using Intel Rapid Start Technology.</li> </ul>
<b>IntelSpdSelTech</b>	<p>Intel Speed Select Technology allows you to choose up to two additional base frequency conditions. Cfg 1: TDP Level 3 Cfg 2: TDP Level 4. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Configuration 1</li> <li>Configuration 2</li> </ul>
<b>IrstTimer</b>	<p>Sets the Intel Rapid Start Timer. The value can be specified in minutes ranging from 0 to 999. Specify the Rapid Start timer value as 0 to put the system into a low-power state immediately after the system transition to a sleep mode. The following are the possible values: Integer ranging from 0 to 999.</p>
<b>LimitCpuidValue</b>	<p>Restricts the maximum CPUID functions supported by the processor. Some operating system does not complete the installation when more than three CPUID functions are supported. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>LogicProc</b>	<p>Enables or disables HyperThreading in the processor. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>MultipleAtomCores</b>	<p>This setting allows you to change the number of atom cores available in the operating system. The default value is set to the maximum number of available atom cores.</p> <p><b>NOTE:</b> If the <b>CpuCore</b> is not set to <b>CoresAll</b> option, then you cannot change the <b>MultipleAtomCores</b> option to <b>0</b>.</p> <p><b>NOTE:</b> If the <b>MultipleAtomCores</b> is not set to <b>0</b>, then you cannot change the <b>CpuCore</b> option.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>CoresAll</li> <li>0</li> <li>1</li> <li>2</li> <li>3</li> <li>4</li> <li>5</li> <li>6</li> <li>7</li> </ul>
<b>MultiCoreSupport</b>	<p>Specifies whether the processor has one or more cores enabled. The performances of some applications improve with additional cores. The following are the possible values:</p> <ul style="list-style-type: none"> <li>CoresAll—All cores are enabled.</li> <li>Cores1—Only one core is enabled.</li> <li>Cores2—Two cores are enabled.</li> <li>Cores4— Four cores are enabled.</li> <li>Cores6— Six cores are enabled.</li> <li>Cores8— Eight cores are enabled.</li> <li>Cores10—Ten cores are enabled.</li> <li>Cores12—Twelve cores are enabled.</li> <li>Cores14—Fourteen cores are enabled.</li> <li>Cores16—Sixteen cores are enabled.</li> </ul>
<b>NodeInterleave</b>	<p>Enables or disables memory interleave mode. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>

**Table 17. Performance (continued)**

Attribute Name	Description
<b>PcieResizableBar</b>	<p>Enables or disables the PCIe resizable bar support. If there are no compatibility issues with the supported graphics card, then the platform considers to set the default option as enabled.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Speedstep</b>	<p>Intel SpeedStep technology that allows the processor to operate at two or more operating speeds called P-states in ACPI terminology. When disabled, the processor operates at its maximum frequency. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• Enabled</li> <li>• MaximumPerformance</li> <li>• MaximumBattery</li> </ul>
<b>IsochronousMode</b>	<p>Enables or disables System Isochronous mode.</p> <p> <b>NOTE:</b> Isochronous mode may be best for audio and video streaming applications.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enable this mode to reduce the latency of memory transactions at the expense of bandwidth.</li> <li>• Disabled—Disable this mode for applications that need high memory bandwidth.</li> </ul>
<b>TCCActOffset</b>	<p>This option adjusts the CPU's TCC offset. The higher TCC offset setting moderates the CPU performance. The following are the possible values:</p> <p>0-15</p>
<b>TurboMode</b>	<p>Enables or disables the Intel TurboBoost mode of the processor. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled—Does not allow the TurboBoost driver to increase the performance state of the processor preceding the standard performance.</li> <li>• Enabled—Allows the Intel Turbo driver to increase the performance of the CPU or graphics processor.</li> </ul>
<b>AmdCpuCore</b>	<p>This field specifies whether the processor has one or more cores enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• CoreAll</li> <li>• Core1p0</li> <li>• Core1p1</li> <li>• Core2p0</li> <li>• Core3p0</li> <li>• Core2p2</li> <li>• Core4p0</li> <li>• Core3p3</li> </ul>
<b>AmdThreadControl</b>	<p>Each processor core contains two threads. Each thread appears as a separate processor to the operating system. However, the threads share part of the processor core with one another. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>AmdTurboCore</b>	<p>Enables or disables the AMD Turbo Core Technology in the processor. When enabled, AMD Turbo Core Technology dynamically adjusts processor frequency to provide a performance boost at the operating system's request. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

**Table 17. Performance (continued)**


Attribute Name	Description
<b>MemRSA</b>	Enables or disables the Reliability Availability Serviceability (RSA) support on memory module. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PcieRSA</b>	Enables or disables the Reliability Availability Serviceability (RSA) support on PCIe devices. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>CpuRSA</b>	Enables or disables the Reliability Availability Serviceability (RSA) support on CPUs. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

## POSTBehavior




**Table 18. POSTBehavior**

Attribute Name	Description
<b>DockWarningsEnMsg</b>	Enables or disables dock warning messages. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>ExternalHotKey</b>	Enables or disables Fn key emulation. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—The Scroll Lock key on external keyboards emulate the Fn key only when running in a non-ACPI operating system.</li> <li>• Disabled—The Scroll Lock key behaves normally.</li> </ul>
<b>ExtPostTime</b>	Creates an extra preboot delay for specified seconds to allow the user to see POST status messages. The following are the possible values: <ul style="list-style-type: none"> <li>• 0s—Does not delay.</li> <li>• 5s—Delays for 5 seconds.</li> <li>• 10s—Delays for 10 seconds.</li> </ul>
<b>Fastboot</b>	Controls specific steps that are performed during boot to decrease boot time or increase boot checks. This option can speed up the boot process by bypassing some compatibility steps. The following are the possible values: <ul style="list-style-type: none"> <li>• Minimal—Reduces boot time by skipping certain hardware and configuration initialization during boot.</li> <li>• Thorough—Performs complete hardware and configuration initialization during boot.</li> <li>• Auto—Allows the BIOS to decide configuration initialization to be performed during boot.</li> </ul>
<b>FnLock</b>	This option controls the behavior of the dual function keys, when Fn key is pressed and when it is not. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Fn+Esc key combination toggles the primary behavior of F1 to F12 keys between their normal and secondary functions.</li> <li>• Disabled—You cannot toggle the primary behavior of these keys.</li> </ul>
<b>FnLockMode</b>	If Enabled, F1 to F12 keys behave as function keys holding Fn key is required to access their secondary functions. Without holding Fn key, the dual function keys behave as normally labeled. <ul style="list-style-type: none"> <li>• EnableSecondary</li> <li>• DisableStandard</li> </ul>
<b>FullScreenLogo</b>	Enables or disables the full screen logo that appears during BIOS POST. The following are the possible values:

**Table 18. POSTBehavior (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Keypad</b>	<p>Activates the internal keyboard's embedded keypad either when Numlock LED is on or when the Fn key is pressed.</p> <p> <b>NOTE:</b> When Setup is running, this option has no effect, Setup works in the EnabledByFnKey mode.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• EnabledByFnKey—The keypad is enabled only when you hold the Fn key.</li> <li>• EnabledByNumLock—The keypad is enabled when, the Numlock LED is On and no external keyboard is attached.</li> </ul>
<b>MacAddrPassThru</b>	<p>This feature replaces the external NIC MAC address (in a supported dock or dongle) with the selected MAC address from the system. The default value is the System Unique MAC Address. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• SystemUnique</li> <li>• IntegratedNic1</li> <li>• Disabled</li> </ul>
<b>NumLock</b>	<p>Enables or disables the NumLock function when the system boots. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>NumLockLed</b>	<p>Enables or disables the NumLockLed function when the system boots. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PntDevice</b>	<p>Defines how the system handles mouse and touchpad input. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• SerialMouse—Uses a serial mouse and disables the internal touchpad.</li> <li>• Ps2Mouse—Disables the integrated touchpad when an external PS2 mouse is present.</li> <li>• Touchpad—Leave the integrated touchpad enabled when an external PS2 mouse is present.</li> <li>• SwitchToExternalPS2—Sets the pointing device to switch to external ps2.</li> </ul>
<b>PostF12Key</b>	<p>Enables or disables &lt;F12&gt; Boot Menu on POST boot screen. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enables F12 Boot Option Menu.</li> <li>• Disabled—Disables F12 Boot Option Menu.</li> </ul>
<b>PostF2Key</b>	<p>Enables or disables &lt;F2&gt; boot menu on POST boot screen. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PostHelpDeskKey</b>	<p>Enables or disables display of the (ctrl+h) help Desktop hotkey message on the POST screen if Management Engine (ME) is alive and Client Initiated Remote Access (CIRA) is supported. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PowerWarn</b>	<p>Enables or disables display of warning messages when you use certain power adapters. The system displays these messages when you attempt to use a power adapter that has too little capacity for your configuration. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

**Table 18. POSTBehavior (continued)**

Attribute Name	Description
<b>RptKeyErr</b>	Enables or disables reporting of keyboard-related errors when the system boots. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SignOfLifeByKbdBacklight</b>	This option allows the system to indicate that the power button has been pressed during POST by turning on the keyboard backlight. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SignOfLifeByDisplay</b>	This option allows the system to indicate that the power button has been pressed during POST by displaying the Dell Logo. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SignOfLifeByAudio</b>	This option allows the system to indicate that the power button has been pressed during POST with an audible tone. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SignOfLifeIndication</b>	During POST, system acknowledges that the power button has been pressed in a manner that the user can either hear or feel. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>WarningsAndErr</b>	During POST the system continues to boot, or pauses when warnings or errors are detected. This feature can be used for the remotely managed systems that does not have a keyboard or a console for the user to respond. The following are the possible values: <ul style="list-style-type: none"> <li>• PromptWrnErr—System pauses for the user to respond when warnings or errors are detected.</li> <li>• ContWrn—System continues to boot when warnings are detected, but pauses for the user to respond when errors are detected.</li> <li>• ContWrnErr—System continues to boot when warnings or errors are detected.</li> </ul> <p> <b>NOTE:</b> Errors deemed critical to the operation of the system hardware always pause the system.</p>
<b>WyseP25Access</b>	Enables or disables the WyseP25Access feature. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Allows remote access to BIOS setup through Dell Wyse P25, Dell Wyse P45, or through any other compatible portal.</li> <li>• Disabled—Restricts remote access to BIOS setup through Dell Wyse P25, Dell Wyse P45, or through any other compatible portal.</li> </ul> <p> <b>CAUTION:</b> If Dell Wyse P25 BIOS Access feature is disabled, it cannot be enabled remotely through the Dell Wyse P25, Dell Wyse P45, or through any other compatible portal. Disabling this feature prevents keyboard access to Diagnostics, Safe Mode, Boot Options, and other Pre-OS functionalities.</p> <p> <b>NOTE:</b> This feature is enabled by default.</p>

## PowerManagement






**Table 19. PowerManagement**

Attribute Name	Description
<b>AcPwrRcvry</b>	Controls the system's behavior when AC power is restored after AC power has been lost. The following are the possible values: <ul style="list-style-type: none"> <li>• Off—System stays off after AC power is restored.</li> </ul>

**Table 19. PowerManagement (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>On—System powers on after AC power is restored.</li> <li>Last—System returns to the previous state after AC power recovery.</li> </ul>
<b>AdvancedBatteryChargeConfiguration</b>	<p>Configures the days settings based on BeginningOfDay and workperiod. Advanced Battery charge mode uses standard charging algorithm and other methods during working hours to maximize battery health. During working hours, express charge is used to charge the batteries faster. You can configure the days and the work period during which the battery has to be charged. To enable advanced battery charging, provide the day. The following are the possible values:</p> <ul style="list-style-type: none"> <li>BeginningOfDay—To configure the AdvanceBatteryCharge start time in 24 hours format. The value of hour must be in the range 0–23 and minute must be 0, 15, 30, or 45.</li> <li>Workperiod—To configure the duration of charging.</li> </ul>
<b>AdvBatteryChargeCfg</b>	<p>Enables or disables the Advanced Battery Charge configuration. During working hours, with the Advanced Battery Charge configuration, the batteries can be charged faster using ExpressCharge. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>AutoOn</b>	<p>Configures the days when the system has to turn on automatically at the time specified in AutoOnHr and AutoOnMn. This function can turn on the system either every day, on weekdays, or on selected days. If AutoOnHr is set to 23, and AutoOnTime is set to 53, then setting AutoOnTime to Weekdays turns on the system automatically on weekdays (Monday to Friday) at 11:53 p.m.. To turn on the system on particular days, set AutoOnTime as Select Days, and then enable or disable individual days by setting AutoOnSun -enabled, AutoOnMon -disabled, etc. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Disabled</li> <li>EveryDay</li> <li>SelectDays</li> <li>Weekdays</li> </ul>
<b>AutoOnHr</b>	<p>Configures the hour when the system has to turn on automatically. Provide the value ranging from 0 to 23. To set the time 11:59 p.m., provide the value as 23. The following are the possible values: Integers ranging from 0 to 23.</p>
<b>AutoOnMn</b>	<p>Configures the minute when the system has to turn on automatically. Provide the value ranging from 0 to 59. To set the time 11:59 p.m., provide the value as 59. The following are the possible values: Integers ranging from 0 to 59.</p>
<b>AutoOnSun</b>	<p>Enables or disables the AutoOn functionality at the specified time on Sundays. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>AutoOnMon</b>	<p>Enables or disables the AutoOn functionality at the specified time on Mondays. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>AutoOnTue</b>	<p>Enables or disables the AutoOn functionality at the specified time on Tuesdays. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>AutoOnWed</b>	<p>Enables or disables the AutoOn functionality at the specified time on Wednesdays. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>AutoOnThur</b>	<p>Enables or disables the AutoOn functionality at the specified time on Thursdays. The following are the possible values:</p>

**Table 19. PowerManagement (continued)**



Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>AutoOnFri</b>	<p>Enables or disables the AutoOn functionality at the specified time on Fridays. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>AutoOnSat</b>	<p>Enables or disables the AutoOn functionality at the specified time on Saturdays. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>AutoWakePeriod</b>	<p>Defines the time in minutes after which the system should automatically wake up from Standby, Hibernate, or Switched off mode. The following are the possible values: integers ranging from 0 to 254.</p> <p> <b>NOTE:</b> The system wakes up from Sleep, Hibernate, or Switched off mode only if the AutoOn option is enabled for everyday of the week.</p>
<b>BlinkPowerSupply1LED</b>	<p>Normally, the status LEDs on the back of the Power Supply Unit (PSU) displays solid green color. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—The first power supply (PSU 1) status LED blinks for few seconds.</li> </ul> <p> <b>NOTE:</b> There is no need for disabling the LEDs manually. When the Embedded Controller (EC) gives the control back to PSU, the LED turns off automatically.</p>
<b>BlinkPowerSupply2LED</b>	<p>Normally, the status LEDs on the back of the Power Supply Unit (PSU) displays solid green color. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—The second power supply (PSU 2) status LED blinks for few seconds.</li> </ul> <p> <b>NOTE:</b> There is no need for disabling the LEDs manually. When the Embedded Controller (EC) gives the control back to PSU, the LED turns off automatically.</p>
<b>BlockSleep</b>	<p>Blocks the system entering sleep (S3 state) mode in an OS environment. If enabled, the system does not go into sleep mode, Intel Rapid Start is disabled automatically, and OS Power option is blank if it was set to Sleep earlier. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>CustomChargeStart</b>	<p>Sets the percentage value ranging from 50 to 95 at which custom battery charging should start. The following are the possible values: Integers ranging from 50 to 95.</p> <p> <b>NOTE:</b> Primary Battery Custom Charge Start percent must be less than the Primary Battery Custom Charge End percent and the minimum difference between the two must be 5 percent.</p>
<b>CustomChargeStop</b>	<p>Sets the percentage value ranging from 55 to 100 at which the custom battery charging should stop. The following are the possible values: Integers ranging from 55 to 100.</p> <p> <b>NOTE:</b> Primary Battery Custom Charge Start percentage must be less than the Primary Battery Custom Charge End percent and the minimum difference between the two must be 5 percent.</p>
<b>DeepSleepCtrl</b>	<p>Controls when Deep Sleep is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• S5Only</li> <li>• S4AndS5</li> </ul>
<b>DockBatteryChargeConfiguration</b>	<p>Configures the dock battery charge mode. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Standard—Charges the battery over a long period of time.</li> <li>• Express—Charges the battery in Express Charge mode using Dell's fast charging technology.</li> </ul>
<b>FanCtrlOvrd</b>	<p>Runs the system fan at full speed. The following are the possible values:</p>




**Table 19. PowerManagement (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>FanSpeed</b>	<p>Sets the speed of the fan to Auto, High, Medium, Low, Medium High, or Medium Low. When set to Auto, the system run time automatically sets the speed. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Auto</li> <li>• High</li> <li>• Med</li> <li>• Low</li> <li>• MedHigh</li> <li>• MedLow</li> </ul>
<b>FanSpeed</b>	<p>Sets the speed of the fan to Auto, High, Medium, Low, Medium High, or Medium Low. When set to Auto, the system run time automatically sets the speed. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Auto</li> <li>• High</li> <li>• Med</li> <li>• Low</li> <li>• MedHigh</li> <li>• MedLow</li> </ul>
<b>FanSpeedLvl</b>	<p>Configures the fan speed control if the fan speed is set to Auto using FanSpeed attribute. 0 sets the fan speed to the optimal speed level, and a higher percentage provides enhanced cooling. The following are the possible values: Integers ranging from 0 to 100.</p>
<b>IntelReadyModeEn</b>	<p>This option enables or disables Intel Ready Mode Technology (iRMT). The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IntlSmartConnect</b>	<p>Intel Smart Connect Technology (ISCT) identifies the nearby wireless connections while system is in a sleeping state. SmartConnect Synchronizes email or social media applications that were open when the system entered the sleep state. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>LidSwitch</b>	<p>Enables or disables the lid switch functions. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—OS setting determines the display behavior when lid is closed.</li> <li>• Disabled—Display will not be affected when lid is closed.</li> </ul>
<b>ModBattChargeCfg</b>	<p>Configures the module bay battery charge mode. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Standard—Charges the battery at a standard rate.</li> <li>• Express—Charges the battery faster using the express charging algorithm, Dell's fast charging technology</li> </ul>
<b>PeakShiftBatteryThreshold</b>	<p>Sets the value of the Peak Shift battery threshold. The acceptable value range is from 15 to 100 percent. When the Peak Shift battery threshold level is reached, the system starts using AC power. The following are the possible values: Integers ranging from 15 to 100.</p>
<b>PeakShiftCfg</b>	<p>Enables or disables Peak Shift configuration. Using Peak Shift, you can minimize the consumption of AC power during the peak power usage period of the day. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PeakShiftDayConfiguration</b>	<p>Configures the days settings based on StartTime, EndTime, and ChargeStartTime. Using Peak Shift configuration, you can minimize the consumption of AC power during the peak power usage period of the day. You can set a start and end times for the Peak Shift period.</p>

**Table 19. PowerManagement (continued)**

Attribute Name	Description
	<p>During this period, the system runs on battery if the battery charge is preceding the set battery threshold value. After the Peak Shift period, the system runs on AC power without charging the battery. The system functions normally using AC power and recharging the battery after the specified ChargeStartTime. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PowerOnLidOpen</b>	<p>Set the PowerOnLidOpen feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—If the feature is set to enabled, the system powers up from the off state whenever the lid is opened. This system powers on when powered either by the AC adapter or the system battery.</li> <li>• Disabled—If the feature is set to disabled, the system does not power up from the off state whenever the lid is opened.</li> </ul>
<b>PowerUsageMode</b>	<p>Sets the system power usage modes. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• PowerSaver—This mode reduces processor sustained power to enhance battery life depending on the use case. This mode may impact system performance.</li> <li>• Balanced—This mode balances performance, noise, temperature, and battery life. The default option is set to Balanced Mode.</li> <li>• Performance—This mode uses the processor's typical power and utilizes discrete graphics.</li> <li>• HighPerformance—This mode increases processor sustained power to produce higher system performance, but produces more noise, increases system surface temperature, and reduces the battery life.</li> </ul>
<b>PrimaryBattChargeCfg</b>	<p>Configures the primary battery charge mode. The selected charging mode applies to all batteries installed in the system. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Adaptive—Battery settings are adoptively optimized based on your typical battery usage pattern.</li> <li>• Standard—Charges the battery at a standard rate.</li> <li>• Express—Charges the battery faster using the express charging algorithm, Dell's fast charging technology.</li> <li>• PrimAcUse—Charges the battery while plugged in, a mode preferred by the users who operate their systems while plugged in to an external power source.</li> <li>• Custom—The battery charging starts and stops based on user settings specified in Primary Battery Custom Charge Start and Primary Battery Custom Charge End.</li> </ul>
<b>SfpwakeOnLan</b>	<p>Enables the system to power on by a special LAN signal, or by a special SFP signal. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• SFP—Allows the system to be powered on by special SFP signals.</li> <li>• LANSFP—Allows the system to be powered on by either by LAN, or by SFP signals.</li> <li>• SFP PXE—Allows the system to be powered on by SFP signals, and immediately boot to PXE.</li> </ul> <p> <b>NOTE:</b> This feature works only if the system is connected to AC power.</p>
<b>SleepMode</b>	<p>Determines which sleep mode to be used by the operating system.</p> <p> <b>NOTE:</b> The BIOS can only support either Modern Standby sleep mode (connected or disconnected), or S3 sleep mode.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• OSAutoSelection—Allows the operating system to select the appropriate sleep mode automatically.</li> <li>• ForceS3—Forces the operating system to use the S3 sleep mode only.</li> </ul>
<b>SliceBattChargeCfg</b>	<p>Configures the battery slice charging feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Standard—The battery is charged over a long period of time.</li> <li>• Express—Charges the battery in Express Charge mode using the express charging algorithm, Dell's fast charging technology.</li> </ul>

**Table 19. PowerManagement (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>PrimAcUse—Recommended setting for a user who primarily operates battery while plugged in.</li> <li>Adaptive—Charges the battery in Express Charge mode using the express charging algorithm, Dell's fast charging technology.</li> <li>Custom—Charges the battery in Express Charge mode using the express charging algorithm, Dell's fast charging technology.</li> </ul>
<b>Speedshift</b>	<p>Enables or disables the Intel Speed Shift Technology support. Setting this option to Enabled allows the operating system to select the appropriate processor performance automatically. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ThermalManagement</b>	<p>ThermalManagement cools the fan and the processor to improve the system performance by reducing noise and temperature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Optimized</li> <li>Cool</li> <li>Quiet</li> <li>UltraPerformance</li> </ul>
<b>TypeCPower</b>	<p>Configures the maximum power for type-C connector. The following are the possible values:</p> <ul style="list-style-type: none"> <li>7.5W</li> <li>15W</li> </ul>
<b>UsbWake</b>	<p>Enables USB devices to wake the system from Standby.</p> <p> <b>NOTE:</b> This feature is functional only when the AC power adapter is connected.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>WakeOnAc</b>	<p>Controls the system's behavior when AC power is restored after AC power was lost. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Disabled—System stays off after AC power is restored.</li> <li>Enabled—System powers on after AC power is restored.</li> </ul>
<b>WakeOnDock</b>	<p>Enables or disables waking the system when a docking connection is made. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>WakeOnLan</b>	<p>Configures the wake-on-LAN feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>LanOnly—The system wake-on-LAN feature is enabled; either an onboard or an add-in NIC can wake the system up.</li> <li>Disabled—Does not allow the system to power on when it receives a wakeup signal from the LAN or wireless LAN.</li> <li>AddInCard—Enables NICs, plugged into the power connector, as the source of any wake-on-LAN signal.</li> <li>WlanOnly—Allows the system to be powered on by special WLAN signal.</li> <li>LanWlan—Allows the system to be powered on by special LAN or wireless LAN signal.</li> <li>AddInCard—Allows the system to be powered on by NICs plugged into the special power connector.</li> <li>Onboard—Allows the system to be powered on by Onboard NIC.</li> <li>LanWithPxeBoot—Enables the network controller and wakes up the system to boot the PXE when a wake packet is sent to the system in the S4 or S5 state.</li> <li>SfpNic—Allows the system to wake-up by certain SFP signals.</li> <li>LanOrSfpNic—Allows the system to wake-up either by LAN, or by SFP signals.</li> </ul>

**Table 19. PowerManagement (continued)**






Attribute Name	Description
	<ul style="list-style-type: none"> <li>• <b>SfpNicWithPxeBoot</b>—Allows the system to wake-up by SFP signals, and immediately boot to PXE.</li> </ul>
<b>WakeOnLan2</b>	<p>Defines the wake-on-LAN2 feature.</p> <ul style="list-style-type: none"> <li>• <b>LanOnly</b>—The system wake-on-LAN feature is enabled; either an onboard or an add-in NIC can wake up the system.</li> <li>• <b>Disabled</b>—The system does not respond to magic packets or other means of wake-on-LAN. The NIC chip section that looks for packets will not be powered.</li> <li>• <b>LanWithPxeBoot</b>—Enables the network controller and causes the system to wake up and immediately boot to PXE when a wake packet is sent to the system in the S4 or S5 state.</li> </ul>
<b>WlanAutoSense</b>	<p>Enables or disables the WLAN radio when the system is connected to a wired network. When disconnected from the wired network, WLAN radio is re-enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>WwanAutoSense</b>	<p>Enables or disables the WWAN radio when the system is connected to a wired network. When disconnected from the wired network, WWAN radio is re-enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

## PreEnabled


**Table 20. PreEnabled**

Attribute	Description
<b>AmdSmartShift</b>	<p>Sets the AmdSmartShift. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• <b>Enabled</b>—On a discrete GPU system, AMD SmartShift allows the system's CPU and discrete GPU to share the power limits. This allows the potential performance that increases within the systems power or thermal limitation,</li> <li>• <b>Disabled</b>—AmdSmartShift feature disabled. .</li> </ul>
<b>BiosConnectActivation</b>	<p>Configures the state of the available BiosConnect boot paths. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• <b>Deactivate</b>—BIOS setup options are not available and all BiosConnect boot paths are disabled.</li> <li>• <b>FullActivation</b>—BIOS Setup options are enabled and all BiosConnect boot paths are enabled.</li> <li>• <b>LaunchpadActivationOnly</b>—BIOS setup options are enabled and only launchpad code path is enabled.</li> </ul>
<b>CamVisionSen</b>	<p>Setting this attribute to enabled sets the <b>SafeShutter BIOS</b> option to <b>Manual</b> mode and hides the setup option. SafeShutter is not applicable when this attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DashSupport</b>	<p>Enables and disables the support for Desktop and Mobile Architecture for System Hardware (DASH) management through Platform Level Data Model (PLDM) exchanges. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisGpuExtDisplay</b>	<p>Enables or disables the platform external displays. The following are the possible values:</p>

**Table 20. PreEnabled (continued)**

Attribute	Description
	<ul style="list-style-type: none"> <li>Enabled—Allows discrete Graphics Processing Unit (dGPU) to enable the platform external displays such as HDMI, NB DP and Type-C, etc. with the purpose of enabling discrete graphic features such as Eyefinity, Mosaic, 10bit DP displays, etc..</li> <li> <b>NOTE:</b> Embedded Display Port (eDP) will be enabled by Integrated Graphics Processing Unit (iGPU).</li> <li>Disabled—The normal hybrid graphics mode is enabled.</li> <li> <b>NOTE:</b> This feature is used in hybrid graphics mode only.</li> </ul>
<b>ExpansionBay 1</b>	<p>Enables or disables Expansion Bay 1. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ExpansionBay 2</b>	<p>Enables or disables Expansion Bay 2. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ExpansionBay 3</b>	<p>Enables or disables Expansion Bay 3. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>FaultTolerantMemLogClear</b>	<p>Enables or disables the Fault Tolerant Memory Log Clear option. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—System clears fault tolerant memory log during the next boot.</li> <li>Disabled—Fault Tolerant Memory Log Clear option will be disabled, and no action will be taken during the next boot.</li> <li> <b>NOTE:</b> Fault Tolerant Memory Log Clear option will be reset to disabled state after log gets cleared.</li> </ul>
<b>GpsWwan</b>	<p>Enables or disables GPS WWAN Radio. The following are the possible values:\</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>GraphicSpecMode</b>	<p>Enables or disables the modes. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Allows discrete Graphics Processing Unit (dGPU) to enable the platform external displays such as HDMI, NB DP and Type-C, etc. with the purpose of enabling modes graphic features.</li> <li> <b>NOTE:</b> Embedded Display Port (eDP) will be enabled by Integrated Graphics Processing Unit (iGPU).</li> <li>Disabled—The normal hybrid graphics mode is enabled.</li> <li> <b>NOTE:</b> This feature is used in hybrid graphics mode only.</li> </ul>
<b>MemPerMonitor</b>	<p>Enables or disables the memory performance monitor feature. The following are the possible values:\</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>PcieBusAllocation</b>	<p>This feature controls the PCIe bus resources allocation among the PCIe SLOTS. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Default</li> <li>OptimizeforThunderbolt</li> <li>Option1</li> <li>Option2</li> <li>Option3</li> </ul>
<b>RecoveryTool</b>	<p>Enables or disables the Dell recovery tool. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Enables the Dell recovery tool.</li> <li>Disabled—Disables the Dell recovery tool.</li> </ul>

**Table 20. PreEnabled (continued)**

Attribute	Description
<b>ReportLogoType</b>	<p>Reports the type of splash screen logo (Dell or custom) that is passed from BIOS to user. The following are the possible values:</p> <ul style="list-style-type: none"> <li>0 and 1</li> </ul> <p> <b>NOTE:</b> You cannot enable or disable this feature using Dell Command   PowerShell Provider.</p>
<b>RuggedDeskDockNicPxe</b>	<p>Enables or disables the support for PXE Boot from Rugged Desk Dock NIC device. The following are the possible values:]</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ServiceOSClear</b>	<p>Deletes the service OS non-volatile region. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Deletes the service OS non-volatile region and changes the token status to Disabled.</li> <li>Disabled—Does not delete the service OS non-volatile region.</li> </ul>
<b>TelemetryAccessLvl</b>	<p>This feature controls the type of telemetry for data support. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Disabled—No telemetry</li> <li>Basic—Flash and Diags only</li> <li>Enhanced—Flash, Diags, and Boot Event</li> <li>Full—All telemetry</li> </ul>
<b>UsbWakeS4En</b>	<p>Enables or disables the USB wake from s4 power state of the system. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Enables the USB wake from s4 power state of the system.</li> <li>Disabled—Disables the USB wake from s4 power state of the system.</li> </ul>





## ProcessorInformation

**Table 21. ProcessorInformation**

Attribute Name	Description
<b>64-BitTechnology</b>	Specifies whether the installed processors support 64-bit extensions. The following are the possible values: Read-only.
<b>CoreCount</b>	Displays the number of cores in each processor. By default, the maximum number of cores per processor are enabled. The following are the possible values: Read-only.
<b>CurrentClockSpeed</b>	Displays the current speed of the processor. The following are the possible values: Read-only.
<b>HTCapable</b>	Specifies whether the system supports Hyper Threading (HT). The following are the possible values: Read-only.
<b>MaximumClockSpeed</b>	Displays the maximum speed supported by the processor. The following are the possible values: Read-only.
<b>ProcessorID</b>	Displays the processor ID that contains the processor-specific information that describes the features of the processor. The following are the possible values: Read-only.
<b>ProcessorL2Cache</b>	Displays the L2 cache size. The following are the possible values: Read-only.
<b>ProcessorL3Cache</b>	Displays the L3 cache size. The following are the possible values: Read-only.
<b>ProcessorType</b>	Displays the brand information of the processor installed on the system. The following are the possible values: Read-only.

# SecureBoot

Table 22. SecureBoot




Attribute Name	Description
<b>MSUefiCA</b>	<p>Enabling and disabling the Microsoft UEFI CA includes the UEFI CA in the BIOS UEFI secure boot DB.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enabling the Microsoft UEFI CA includes the UEFI CA in the BIOS UEFI secure boot DB.</li> <li>• Disabled—Disabling the Microsoft UEFI CA removes the UEFI CA from the BIOS UEFI secure boot DB. The system may not boot if the Microsoft UEFI CA is disabled. System graphics may not function. The system may go into an unrecoverable state.</li> </ul>
<b>SecureBoot</b>	<p>Enables or disables the SecureBoot feature. For SecureBoot to be enabled, the system must be in UEFI boot mode, and the Enable Legacy Option ROMs option must be turned off.</p> <p> <b>CAUTION:</b> You cannot disable the SecureBoot feature using the Dell Command   PowerShell Provider.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul> <p> <b>NOTE:</b> One of the methods to disable SecureBoot feature is from the BIOS setup screen.</p> <p> <b>NOTE:</b> The read-only mechanism is not displayed at option level, while the SecureBoot is disabled.</p>
<b>SecureBootMode</b>	<p>Allows the modification of secure boot operational mode. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Deployed mode is the normal mode of operation for measuring the UEFI executable images. Audit Mode enables the evaluation of changes to the Secure Boot key database.</li> </ul> <p> <b>NOTE:</b> In Secure Boot Mode, <b>Audit Mode</b> can be changed to <b>Deployed Mode</b>, but changing from <b>Deployed Mode</b> to <b>Audit Mode</b> is not supported.</p>

# Security

Table 23. Security




Attribute Name	Description
<b>Absolute</b>	<p>Sets the value to the Absolute interface, and control the Absolute service. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• EnabledAbsolute—The Absolute service is activated or deactivated.</li> <li>• DisabledAbsolute—If disabled, then the Absolute service does not run.</li> <li>• PermanentlyDisabled—If the Absolute interface is permanently disabled, then the Absolute feature can be enabled by using the factory reset feature.</li> </ul>
<b>AdminPassword</b>	<p>Sets, changes, or clears the administrator (admin) password (also called the setup password). If you delete the admin password, the system password, if set, is also deleted. The following are the possible values: String containing minimum 4 and maximum 32 characters including whitespace.</p>
<b>AdminSetupLockout</b>	<p>Enables or disables admin setup lockout. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>AmdTSME</b>	<p>Possible values:</p>

**Table 23. Security (continued)**



Attribute Name	Description
	<ul style="list-style-type: none"> <li>Enabled—AMD Transparent Secure Memory Encryption (TSME) allows encryption of contents on the memory DIMMS.</li> <li> <b>NOTE:</b> For best results while diagnosing potential memory DIMM issues, turn off this feature prior to running diagnostic functions or tools.</li> <li>Disabled—AMD Transparent Secure Memory Encryption (TSME) does not allow encryption on the memory DIMMS.</li> </ul>
<b>CapsuleFirmwareUpdate</b>	<p>Enables or disables BIOS updates via UEFI capsule update packages. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ChasIntrusion</b>	<p>The chassis intrusion switch is a physical switch which triggers an event when the chassis is opened. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—The system detects and reports chassis intrusion events to the system display on boot-up.</li> <li>Disabled—The system does not detect and report the Chassis Intrusion events to the system display on boot-up.</li> <li>SilentEnable—The system detects, but does not report the Chassis Intrusion events to the system display on boot-up.</li> </ul>
<b>ChassisIntrusionStatus</b>	<p>Displays the status of chassis intrusion.</p> <p> <b>NOTE:</b> Except TripReset, all values are read-only.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>DoorOpen—Indicates that chassis door is open.</li> <li>Tripped—Indicates that the chassis door was opened since the last time the sensor-detection logic was reset.</li> <li>DoorClosed—Indicates that chassis door is closed.</li> <li>TripReset—Resets the sensor-detection logic to detect the next closed-to-open transition on the chassis door.</li> </ul>
<b>Computrace</b>	<p>This feature allows the users to enable or disable Absolute Software's Computrace security software BIOS ROM. After this token is written, the state is permanently maintained (this is a write-once field). This token is for Factory use only. Application and management software must ignore this token. Write-once permanent is different from write-once. Write-once is reset on a power cycle and/or chipset reset. Write-once permanent cannot be reset or change once it is set. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Disable</li> <li>Activate</li> </ul> <p> <b>NOTE:</b> You cannot enable or disable this feature using Dell Command   Configure.</p>
<b>CpuXdSupport</b>	<p>Enables or disables the run disable mode of the processor. The operating system can use this feature to hinder software that exploits buffer overflows. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>DisPwdJumper</b>	<p>DisPwdJumper controls the physical password clear jumper on the motherboard. The following are the possible values: Enabled—When this option is not selected, the password jumper on the motherboard is activated to clear the BIOS admin and the user passwords. Disabled—When this option is selected, the password jumper is disabled, and the BIOS passwords are not cleared.</p>
<b>GeneralPurposeEncryption</b>	<p>Enables or disables general-purpose encryption. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>HDDInfo</b>	<p>Displays the details of each HDD. The following information is displayed:</p>



**Table 23. Security (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• <b>HDDName</b>—The name of the HDD.</li> <li>• <b>Present</b>—Whether the HDD is physically present.</li> <li>• <b>PwdProtected</b>—Whether a password exists for the HDD.</li> <li>• <b>PendingRestart</b>—Whether a reboot is pending to set the password.</li> <li>• <b>AdminOnlyChange</b>—Whether the changes to the password can be made only by an administrator.</li> <li>• <b>SecureEraseSupported</b>—Whether HDD Secure Erase is supported.</li> <li>• <b>SecureEraseEnabled</b>—Whether HDD Secure Erase is enabled.</li> </ul> <p>The following are the possible values: Read-only.</p>
<b>HDDPassword</b>	<p>Sets, changes, or clears the HDD password. Enter the HDD password, if set, when the system is powered on.</p> <p> <b>NOTE:</b> After setting the HDD password, restart the system.</p> <p>Possible values: String containing minimum 1 and maximum 32 characters including whitespace.</p>
<b>HddProtection</b>	Lets the user choose loading of HDD Protection OPROM.
<b>IntIPlatformTrust</b>	<p>Enables or disables IntIPlatformTrust feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Displays the Intel Platform Trust Technology (PTT) device from the operating system on the next boot.</li> <li>• Disabled—Hides the Intel Platform Trust Technology (PTT) device from the operating system on the next boot.</li> </ul> <p> <b>NOTE:</b> When disabled, the PTT device is not displayed to the operating system, and no changes can be made to the PTT device or its content.</p>
<b>IntelTME</b>	<p>Controls the total memory encryption (TME) feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IsAdminPasswordSet</b>	Specifies if an admin password has been set. Possible values: True, false (Read-only)
<b>IsSystemPasswordSet</b>	Specifies if a system password has been set. Possible values: True, false (Read-only)
<b>LegacyInterfaceAccess</b>	<p>This setting allows the platform administrator to control the access through the legacy manageability interface when the ABI is enabled and provisioned. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—The legacy manageability interface is used to read and change the BIOS configuration settings.</li> <li>• ReadOnly—BIOS configuration settings can be read, but cannot be changed through the legacy manageability interface.</li> <li>• Disabled—When disabled, the changes (read and write) of the BIOS configuration are allowed through AB.</li> </ul>
<b>MasterPasswordLockout</b>	<p>Enables or disables master password settings.</p> <p> <b>CAUTION: Using the Dell Command   PowerShell Provider, you cannot disable this feature.</b></p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—The master password cannot be used to: <ul style="list-style-type: none"> <li>◦ clear other passwords</li> <li>◦ unlock and access Hard Disk Drive</li> <li>◦ erase data from Hard Disk Drive.</li> </ul> </li> <li>• Disabled—The master password can be used to: <ul style="list-style-type: none"> <li>◦ clear other passwords</li> <li>◦ unlock and access Hard Disk Drive</li> <li>◦ erase data from Hard Disk Drive.</li> </ul> </li> </ul>

**Table 23. Security (continued)**

Attribute Name	Description
	<p> <b>NOTE:</b> One of the methods of configuring this feature is from the BIOS setup screen.</p> <p> <b>NOTE:</b> You cannot enable MasterPasswordLockout while setting up with Hdd or Owner's password.</p>
<b>NonAdminPsidRevert</b>	<p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—When enabled, the PSID revert is allowed to proceed without providing the BIOS admin password.</li> <li>• Disabled—When disabled, and if the BIOS admin password is set, PSID revert is protected and the BIOS admin password can be entered before performing the revert.</li> </ul>
<b>NVMePwdFeature</b>	<p>This feature enables or disables the NVMe password. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>OromKeyboardAccess</b>	<p>Determines whether users are able to enter Option ROM Configuration screens using hotkeys during boot. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Users are able to enter OROM configuration screens using hotkeys during boot.</li> <li>• OneTimeEnable—Users will be able to enter OROM configuration screens using hotkeys during next boot only. After next boot, the settings will revert to disabled.</li> <li>• Disabled—Users are able to enter OROM configuration screens using hotkeys during boot.</li> </ul>
<b>PasswordBypass</b>	<p>Allows users to skip the entry of the system password, HDD password, fingerprint scan, or smartcard on either/both reboot (warm boot) or S3 resume (resume from standby). The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• RebootBypass</li> <li>• ResumeBypass</li> <li>• RebootAndResumeBypass</li> </ul>
<b>PasswordLock</b>	<p>Determines whether the changes to the system and HDD passwords are permitted or restricted if an admin password is set. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled—If disabled, then the system and HDD passwords are locked by admin password and cannot be set, modified, or deleted unless admin password is provided.</li> <li>• Enabled—If enabled, then the system and the HDD passwords can be set, modified, or deleted.</li> </ul>
<b>Ppibypassforblocksid</b>	<p>When there is no drive ownership and the ppibypassforblocksid is enabled, the BIOS requires user input while sending the Block SID authentication command to SED drives. When disabled, BIOS does not require user input while sending the Block SID command. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SafeShutter</b>	<p>The device camera shutter opens automatically when you grant permission to the application and closes when permission is terminated. Disable dynamic behavior by pressing F9. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Dynamic Shutter</li> <li>• Manual Shutter Control</li> </ul>
<b>SedBlockSidAuthentication</b>	<p>When there is no drive ownership and the SedBlockSidAuthentication is enabled, BIOS sends the Block SID authentication command to SED drives. When disabled, BIOS does not send the Block SID command. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> </ul>

**Table 23. Security (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>Disabled</li> </ul> <p><b>NOTE:</b> You can disable SedBlockSidAuthentication in manufacturing mode or while setting up the BIOS Setup Administrator password.</p> <p><b>NOTE:</b> The read-only mechanism can be changed when the system is in manufacturing mode, while the SedBlockSidAuthentication is disabled.</p>
<b>Smmsecuritymitigation</b>	<p>Enables or disables the additional UEFI SMM Security Mitigation protections. The operating system uses this feature to protect the secure environment created by virtualization-based security. Enabling this feature provides the additional UEFI SMM Security Mitigation protections support. However, this feature may cause compatibility or functionality issues with some legacy tools and applications. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul> <p><b>NOTE:</b> You can disable Smmsecuritymitigation in manufacturing mode.</p> <p><b>NOTE:</b> The read-only mechanism can be changed when the system is in manufacturing mode, while the Smmsecuritymitigation is disabled.</p>
<b>StrongPassword</b>	<p>Enables or disables the enforced use of a strong password. If enabled, the admin and system passwords must contain at least one upper case character, at least one lowercase character, and minimum eight characters. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>SystemPassword</b>	<p>Sets, changes, or clears the system password (also known as the user password). Enter the system password, if set, when the system is powered on. Possible values: String containing minimum 4 and maximum 32 characters including whitespace.</p>
<b>WirelessSwitchChanges</b>	<p>Determines if changes to the wireless switch setting are permitted or restricted when an administrator password is set. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Permits the changes to the wireless switch setting when an administrator password is set.</li> <li>Disabled—Restricts the changes to the wireless switch setting when an administrator password is set.</li> </ul> <p><b>NOTE:</b> Provide the administrator password to be able to change the wireless switch setting. If the Administrator password is not set, this setting has no effect.</p>

## StealthModeControl

**Table 24. StealthModeControl**

Attribute	Description
<b>StealthMode</b>	<p>Sets the behavior of system elements. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—The system elements operate in the preprogrammed stealth mode.</li> <li>Disabled—The system elements operate in normal mode.</li> </ul>
<b>StealthModeBluetoothRadio</b>	<p>Enables or disables Stealth Mode behavior for bluetooth radio if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>StealthModeFans</b>	<p>Enables or disables Stealth Mode behavior for fans if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> </ul>

**Table 24. StealthModeControl (continued)**

Attribute	Description
	<ul style="list-style-type: none"> <li>Disabled</li> </ul>
<b>StealthModeGPSReceiver</b>	<p>Enables or disables Stealth Mode behavior for GPS receiver if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>StealthModeLCD</b>	<p>Enables or disables Stealth Mode behavior for the LCD if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>StealthModeLEDs</b>	<p>Enables or disables Stealth Mode behavior for LEDs if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>StealthModeSpeakers</b>	<p>Enables or disables Stealth Mode behavior for speakers if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>StealthModeWiGigRadio</b>	<p>Enables or disables Stealth Mode behavior for WiGig radio if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>StealthModeWLANRadio</b>	<p>Enables or disables Stealth Mode behavior for WLAN radio if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>StealthModeWWANRadio</b>	<p>Enables or disables Stealth Mode behavior for WWAN radio if the StealthMode attribute is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>

## SupportAssistSystemResolution

**Table 25. SupportAssistSystemResolution**

Attribute	Description
<b>AutoOSRecoveryThreshold</b>	<p>Sets the threshold value for auto OS recovery. Possible values: 0 to 3Controls the automatic boot flow for SupportAssist System Resolution console and for Dell OS Recovery Tool. The system boots to the SupportAssist System Resolution console and for Dell OS Recovery Tool if;</p> <ul style="list-style-type: none"> <li>the primary operating system fails to boot consecutively</li> <li>the count of boot failure is greater than or equal to the value of the Auto OS Recovery threshold setup option</li> <li>SupportAssist OS Recovery option is enabled</li> </ul> <p><b>NOTE:</b> If Auto OS Recovery threshold is set to 0, then all automatic boot flow for SupportAssist System Resolution console and for Dell OS Recovery Tool will be disabled.</p>
<b>BiosConnect</b>	<p>Enables or Disables BIOS Connect feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>

**Table 25. SupportAssistSystemResolution (continued)**

Attribute	Description
<b>SupportAssistOSRecovery</b>	Enables or disables the boot flow for SupportAssist OS recovery tool in the event of certain system errors. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>MpmCfg</b>	This feature controls the level of monitoring of Memory Performance Monitor (MPM). MPM monitors the memory for faults and perform fault recovery when possible. The following are the possible values: <ul style="list-style-type: none"> <li>• OFF</li> <li>• Low</li> <li>• Med</li> <li>• High</li> </ul>

## SystemConfiguration

**Table 26. SystemConfiguration**

Attribute Name	Description
<b>AnalogDigitalInterfaceModeChannel1</b>	Sets the defined Analog or Digital Interface mode for channel 1. The following are the possible values: <ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>AnalogDigitalInterfaceModeChannel2</b>	Sets the defined Analog or Digital Interface mode for channel 2. The following are the possible values: <ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>AnalogDigitalInterfaceModeChannel3</b>	Sets the defined Analog or Digital Interface mode for channel 3. The following are the possible values: <ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>AnalogDigitalInterfaceModeChannel4</b>	Sets the defined Analog or Digital Interface mode for channel 4. The following are the possible values: <ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>AnalogDigitalInterfaceModeChannel5</b>	Sets the defined Analog or Digital Interface mode for channel 5. The following are the possible values:

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>AnalogDigitalInterfaceModeChannel6</b>	<p>Sets the defined Analog or Digital Interface mode for channel 6. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>AnalogDigitalInterfaceModeChannel7</b>	<p>Sets the defined Analog or Digital Interface mode for channel 7. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>AnalogDigitalInterfaceModeChannel8</b>	<p>Sets the defined Analog or Digital Interface mode for channel 8. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Unused—Channel is unused.</li> <li>• ADCInput—Sets the channel mode as Analog-to-Digital Converter (ADC) input.</li> <li>• DACOutput—Sets the channel mode as Digital-to-Analog Converter (DAC) output.</li> <li>• DACAndADC—Sets the channel mode as DAC output, but can be monitored through ADC input.</li> <li>• GPIO—Sets the channel mode as General Purpose Input or Output.</li> </ul>
<b>BatteryFuelGauge</b>	<p>This feature controls the battery fuel gauge. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enabling this feature allows the battery fuel gauge to be activated on touch or swipe.</li> <li>• Disabled—Disabling this feature prevents the battery fuel gauge from being activated on touch or swipe.</li> </ul>
<b>CanBus</b>	<p>Enables or disables the Controller Area Network (CAN) Bus. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisBluetoothRadio</b>	<p>Bluetooth radio stops functioning when stealth mode is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisOnboardFans</b>	<p>Onboard fans stop functioning when stealth mode is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisGPSReceiver</b>	<p>GPS receiver stops functioning when stealth mode is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

**Table 26. SystemConfiguration (continued)**


Attribute Name	Description
<b>DisOnboardLCDScreen</b>	Onboard LCD screen stops functioning when stealth mode is enabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisOnboardLEDs</b>	Onboard LEDs stop functioning when stealth mode is enabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisOnboardSpeakers</b>	Onboard speakers stop functioning when stealth mode is enabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisOsdBtn</b>	Enables or disables the On-screen Display (OSD) buttons on All-In-One system. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisWLANRadio</b>	WLAN radio stops functioning when stealth mode is enabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DisWWANRadio</b>	WWAN radio stops functioning when stealth mode is enabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DockSupportOnBattery</b>	Enabling DockSupportOnBattery allows you to use the docking station, when AC power is absent, but only when the battery is preceding a certain charge percentage. The percentage may change per battery and per platform. For example, the dock may only be powered when the battery is at 60 percent charge or higher, and when the battery drops below this level (without AC power) the dock loses power. The following are the possible values: Possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DustFilter</b>	Enables or disables the BIOS messages for maintaining the optional dust filter installed in the computer. BIOS generates a pre-boot reminder to clean or replace the dust filter based on the interval settings. The following are the possible values: Disabled, 15days, 30days, 60days, 90days, 120days, 150days, 180days.
<b>EmbNic1</b>	Controls the state of on-board LAN controller 1. The following are the possible values: <ul style="list-style-type: none"> <li>• Disabled</li> <li>• Enabled</li> <li>• EnabledPxe</li> <li>• OnWithImageServerBoot</li> <li>• EnabledwithRPLBoot</li> <li>• EnabledwithISCSIBoot</li> </ul>
<b>EmbNic2</b>	Controls the state of on-board LAN controller 2. The following are the possible values: <ul style="list-style-type: none"> <li>• Disabled</li> <li>• EnabledPXE</li> <li>• Enabled</li> <li>• EnabledwithImageServerBoot</li> <li>• EnabledwithRPLBoot</li> <li>• EnabledwithISCSIBoot</li> </ul>

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
<b>EmbSataRaid</b>	Configures the operating mode of the integrated SATA hard drive controller. The following are the possible values: <ul style="list-style-type: none"> <li>• Disabled—The SATA controllers are hidden.</li> <li>• Ata—SATA is configured for ATA mode.</li> <li>• Ahci—SATA is configured for AHCI mode.</li> <li>• Raid—SATA is configured to support RAID mode (Intel Rapid Restore Technology).</li> </ul>
<b>EmbUnmngNic</b>	This option controls the on-board USB LAN controller. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—The internal LAN is enabled.</li> <li>• Disabled—The internal LAN is disabled.</li> </ul>
<b>Emmcdevice</b>	Enables or disables the eMMC drive. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>FrontBezelLEDIntensity</b>	Controls the light intensity of system's front bezel LED. The following are the possible values: <ul style="list-style-type: none"> <li>• Disabled</li> <li>• Low</li> <li>• Medium</li> <li>• Full</li> </ul>
<b>FrontFan</b>	The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—When enabled, the front fan utilizes the thermal solution of the system.</li> <li>• Disabled—When disabled, thermal solution of the system utilizes only the fan from the back panel.</li> </ul>
<b>FingerprintReader</b>	Enables or disables the Fingerprint Reader device. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Fingerprint Reader device is enabled.</li> <li>• Disabled—Fingerprint Reader device is disabled.</li> </ul>
<b>FingerprintReaderSingleSignOn</b>	Enables or disables the FingerprintReaderSingleSignOn. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—FingerprintReaderSingleSignOn is enabled.</li> <li>• Disabled—FingerprintReaderSingleSignOn is disabled.</li> </ul>
<b>ForcePXEasFirstBootDevice</b>	Enables or disables Preboot Execution Environment (PXE) as the first boot device for all subsequent boots. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>ForcePxeNextBoot</b>	Enables or disables Force PXE on next boot in BIOS. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—If enabled, when the BIOS boots next time, the first PXE-capable device is inserted as the first device in the boot sequence. Enabling this value causes this operation on the next boot only, and does not cause a change in the defined boot sequence of the system. The BIOS chooses the first PXE-capable device as the onboard network controller of the system, if present and enabled, or the first bootable network device found in the standard PCI search order of the system, whichever comes first.</li> <li>• Disabled—If disabled, the boot override feature is disabled and the system boot sequence is in effect.</li> </ul>
<b>FrontPowerButton</b>	Enables or disables the front power button. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Hdd1FanEnable</b>	Enables or disables the automatic fan controller, an error check of a fan. If a fan is detected, this function is automatically enabled. Disabling the fan requires physical removal of the HDD fan. The following are the possible values:



**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Hdd2FanEnable</b>	<p>Enables or disables the automatic fan controller, an error check of a fan. If a fan is detected, this function is automatically enabled. Disabling the fan requires physical removal of the HDD2 fan. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Hdd3FanEnable</b>	<p>Enables or disables the automatic fan controller, an error check of a fan. If a fan is detected, this function is automatically enabled. Disabling the fan requires physical removal of the HDD3 fan. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IgnitionSwitchEnable</b>	<p>Enables or disables the external ignition pin. Disabled by default. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IgnitionSwitchOnDelay</b>	<p>The delay is displayed in seconds when the power button event is passed to the OS to initiate a boot of the system. Possible values are from (0—21600). By default the value is 5s.</p>
<b>IgnitionSwitchOffDelay</b>	<p>The delay is displayed in seconds until the power button event is passed to the OS for shutting down the system. Possible values are from (0—21600). By default the value is 5s.</p>
<b>IgnitionSwitchDebounceCycle</b>	<p>De-Bounce Ignition Power Switch cycle time is displayed in milli-seconds. Possible values are from (50—5000). By default the value is 50ms.</p>
<b>IntegratedAudio</b>	<p>Enables or disables the integrated audio controller. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> <li>• Auto</li> </ul>
<b>IntegratedSas</b>	<p>Enables or disables the integrated Serial Attached SCSI (SAS) controller.</p> <p> <b>NOTE:</b> This option affects the SAS RAID controller Only. This controller operates the connectors on the motherboard that are marked SASA and SASB.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IntelGna</b>	<p>Enables or disables the Intel GNA device.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>InternalSpeaker</b>	<p>Enables or disables the built-in speaker. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> <li>• Low</li> <li>• Medium</li> <li>• High</li> </ul>
<b>IoModule</b>	<p>Enables or disables I/O module. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IoModule 2</b>	<p>Enables or disables I/O module 2. The following are the possible values:</p>


**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IoModule 3</b>	Enables or disables I/O module 3. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>IoModule 4</b>	Enables or disables I/O module 4. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>KbdBacklightTimeoutAc</b>	Configures the time-out value for the keyboard backlight when an AC adapter is plugged into the system. The following are the possible values: <ul style="list-style-type: none"> <li>• 5s—Keyboard backlight stays on for 5 seconds.</li> <li>• 10s—Keyboard backlight stays on for 10 seconds.</li> <li>• 15s—Keyboard backlight stays on for 15 seconds.</li> <li>• 30s—Keyboard backlight stays on for 30 seconds.</li> <li>• 1m—Keyboard backlight stays on for 1 minute.</li> <li>• 5m—Keyboard backlight stays on for 5 minutes.</li> <li>• 15m—Keyboard backlight stays on for 15 minutes.</li> <li>• Never—Keyboard backlight always stays on.</li> </ul>
<b>KbdBacklightTimeoutBatt</b>	Configures the time-out value for the keyboard backlight when the system is running only on battery power. The following are the possible values: <ul style="list-style-type: none"> <li>• 5s—Keyboard backlight stays on for 5 seconds.</li> <li>• 10s—Keyboard backlight stays on for 10 seconds.</li> <li>• 15s—Keyboard backlight stays on for 15 seconds.</li> <li>• 30s—Keyboard backlight stays on for 30 seconds.</li> <li>• 1m—Keyboard backlight stays on for 1 minute.</li> <li>• 5m—Keyboard backlight stays on for 5 minutes.</li> <li>• 15m—Keyboard backlight stays on for 15 minutes.</li> <li>• Never—Keyboard backlight always stays on.</li> </ul>
<b>KeyboardBacklightActiveColor</b>	Displays or sets an active color for the keyboard backlight in a rugged system. 6 colors are available: four predefined colors (white, red, green, blue), and two user configurable colors (custom1 and custom2). Active color indicates the color used on startup. Any one of the 6 colors can be chosen as an active color. The following are the possible values: <ul style="list-style-type: none"> <li>• White</li> <li>• Red</li> <li>• Green</li> <li>• Blue</li> <li>• Custom1</li> <li>• Custom2</li> </ul>
<b>KeyboardBacklightCustom1Color</b>	Configures the Custom1 color by specifying the RGB values by mentioning it in 'R:G:B' format. Each color component value ranges from 0 to 255. Possible values: [0-255]:[0-255]
<b>KeyboardBacklightCustom2Color</b>	Configures the Custom2 color by specifying the RGB values by mentioning it in 'R:G:B' format. Each color component value ranges from 0 to 255. Possible values: [0-255]:[0-255]
<b>KeyboardBacklightEnabledColors</b>	Displays or enables the supported colors for the keyboard backlight in the rugged systems. 6 colors are available: 4 predefined colors (white, red, green, blue), and 2 user-configurable colors (custom1 and custom2). Multiple colors out of the 6 colors can be enabled at the same time. After enabling colors, you can switch among the enabled colors by pressing <Fn+C> keys. Enabling NoColor means that the keyboard backlight is turned off. Possible values: Either combination of, <ul style="list-style-type: none"> <li>• White</li> </ul>

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Red</li> <li>• Green</li> <li>• Blue</li> <li>• Custom1</li> <li>• Custom2</li> </ul> <p>Or</p> <ul style="list-style-type: none"> <li>• NoColor</li> </ul> <p><b>NOTE:</b> If value NoColor is selected, you cannot use &lt;Fn+C&gt; to switch to another keyboard backlight color. The value NoColor cannot be combined with any other color.</p>
<b>KeyboardBacklightOnAc</b>	<p>Disables the fade if an AC adapter is plugged in. For example, if you have set the back light to 25 percent using KeyboardIllumination, and the system is on AC power, then the keyboard backlight remains at 25 percent regardless of internal keyboard or touch pad activity. This feature is in effect only if the Keyboard backlight is enabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Keyboard backlight fades after 10 seconds of inactivity.</li> <li>• Disabled—Disables the timer that fades the backlight after 10 seconds of inactivity if the system is running on AC power.</li> </ul>
<b>KeyboardIllumination</b>	<p>This field lets you configure the keyboard illumination brightness percentage. The keyboard automatically illuminates when the internal keyboard, touchpad, or pointstick are used. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Auto—Sets the illumination based on ambient light level.</li> <li>• Disabled—Turns off keyboard illumination.</li> <li>• 25—Sets the brightness level to 25 percent.</li> <li>• Dim—Sets the brightness level to 50 percent.</li> <li>• 75—Sets the brightness level to 75 percent.</li> <li>• Bright—Sets the brightness level to 100 percent.</li> </ul>
<b>LiquidCooler1</b>	<p>Enables or disables the liquid cooler 1. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enables the liquid cooler 1.</li> <li>• Disabled—Disables the liquid cooler 1.</li> </ul>
<b>LiquidCooler2</b>	<p>Enables or disables the liquid cooler 2. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enables the liquid cooler 2.</li> <li>• Disabled—Disables the liquid cooler 2.</li> </ul>
<b>LptMode</b>	<p>Determines how the parallel port on the docking station operates. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled—Port is disabled.</li> <li>• At—Port is configured for IBM AT compatibility.</li> <li>• Ps2—Port is configured for IBM PS2 compatibility.</li> <li>• Ecp—Extended Capability Port protocol.</li> </ul>
<b>M2PcieSsd0</b>	<p>Enables or disables M2 PCIE SSD 0. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>M2PcieSsd1</b>	<p>Enables or disables M2 PCIE SSD 1. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>M2PcieSsd2</b>	<p>Enables or disables M2 PCIE SSD 2. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>M2PcieSsd3</b>	<p>Enables or disables M2 PCIE SSD 3. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> </ul>

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Disabled</li> </ul>
<b>Microphone</b>	<p>Enables or disables the internal or external microphone. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>MEMSSensors</b>	<p>Enables or disables the Micro Electro Mechanical Sensors. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>MmioAbove4Gb</b>	<p>Enables or disables decoding of 64-bit capable devices in more than 4 GB address space only if the system supports 64-bit PCI decoding. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Minisas0</b>	<p>Enables or disables the Minisas drive 0. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Minisas1</b>	<p>Enables or disables the Minisas drive 1. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Minisas2</b>	<p>Enables or disables the Minisas drive 2. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Minisas3</b>	<p>Enables or disables the Minisas drive 3. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Nfc</b>	<p>Enables or disables the Near Field Computing (Nfc) device. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>OnboardUSBNIC</b>	<p>Configures the state of the onboard secondary, unmanaged Network Interface Card (NIC). The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> <li>• Enabled with PXE</li> </ul>
<b>OptionalBootSequence</b>	<p>Allows or prevents the installation of the Windows operating system on client systems with more than one operating system volume. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Allows the installation of the Windows operating system on client systems with more than one operating system volume.</li> <li>• Disabled—Prevents the installation of the Windows operating system on client systems with more than one operating system volume.</li> </ul> <p> <b>NOTE:</b> By default, this option is disabled to maintain compatibility with existing installation tools; however, this option can be changed if more than one operating system volume is present on the client system.</p>
<b>PciAllocationPriority</b>	<p>Allocates PCI resources, buses, memory-mapped I/O (MMIO) space, and I/O space. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Equal—Allocates equal amount of memory to all the resources when two CPUs are installed.</li> <li>• CPU1—Allocates larger amount of device-specific memory, which reduces the usable memory in 32-bit operating systems.</li> </ul>

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
<b>PciMmioSpaceSize</b>	Allocates a part of the memory to the PCI Memory Mapped I/O (MMIO). It allows reserving large or small device-specific memory regions to decrease or increase the usable memory on systems with a 32-bit operating system. The following are the possible values: <ul style="list-style-type: none"> <li>• Small—Allocates a small region of memory to PCI memory mapped I/O.</li> <li>• Large—Allocates a large region of memory to PCI memory mapped I/O. This reserves the large device-specific memory regions, but reduces the amount of usable memory in 32-bit operating system.</li> </ul>
<b>PcibusCount</b>	Sets the maximum number of PCI bus counts for the system. The following are the possible values: <ul style="list-style-type: none"> <li>• 64</li> <li>• 128</li> <li>• 256</li> </ul>
<b>PowerButton</b>	Enables, disables, or partially disables the power button. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> <li>• Partial disable</li> </ul>
<b>PowerButtonOverride</b>	This option allows you to configure the waiting time to forcibly shut down the system. The following are the possible values: <ul style="list-style-type: none"> <li>• 4s</li> <li>• 10s</li> </ul>
<b>ProgramBtnConfig</b>	Determines which component configures the system's programmable button: Rugged Control or BIOS. The following are the possible values: <ul style="list-style-type: none"> <li>• ConfigRcc</li> <li>• ConfigBios</li> </ul>
<b>ProgramBtn1</b>	Determines which action to take when you press the P1 button. The following are the possible values: 0-17
<b>ProgramBtn2</b>	Determines which action to take when you press the P2 button. The following are the possible values: 0-17
<b>ProgramBtn3</b>	Determines which action to take when you press the P3 button. The following are the possible values: 0-17
<b>SfpNic</b>	Enables or disables Small Formfactor Pluggable (SFP) device. The following are the possible values: <ul style="list-style-type: none"> <li>• Disabled—Disables the SFP device.</li> <li>• Enabled—Enables the SFP device.</li> <li>• EnabledPxe—Enables the SFP device with PXE support.</li> </ul>
<b>Sata0</b>	Enables or disables the first SATA drive controller. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata1</b>	Enables or disables the second SATA drive controller. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata2</b>	Enables or disables the third SATA drive controller. The following are the possible values:

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata3</b>	<p>Enables or disables the fourth SATA drive controller. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata4</b>	<p>Enables or disables the fifth SATA drive controller. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata5</b>	<p>Enables or disables the sixth SATA drive controller. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata6</b>	<p>Enables or disables the seventh SATA drive controller. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata7</b>	<p>Enables or disables the eighth SATA drive controller. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Sata8</b>	<p>Sets SATA port 8 to off or auto. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Serial1</b>	<p>Configures the first (or only) built-in serial port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• Com1</li> <li>• Com2</li> <li>• Com3</li> <li>• Com4</li> <li>• COM1_BMC</li> <li>• BMCSERIAL</li> <li>• BMCLAN</li> <li>• RAC</li> <li>• RS232</li> <li>• RS422</li> <li>• RS485</li> <li>• Auto</li> </ul>
<b>Serial2</b>	<p>Configures the second (if available) built-in serial port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• COM2</li> <li>• COM4</li> <li>• RS232</li> <li>• RS422</li> <li>• RS485</li> <li>• Auto</li> </ul>
<b>Serial3</b>	<p>Configures the third (if available) built-in serial port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• RS232</li> </ul>

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• RS422</li> <li>• RS485</li> <li>• Auto</li> </ul>
<b>Serial4</b>	<p>Configures the fourth (if available) built-in serial port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disable</li> <li>• RS232</li> <li>• RS422</li> <li>• RS485</li> <li>• Auto</li> </ul>
<b>Serial5</b>	<p>Configures the fifth (if available) built-in serial port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• Auto</li> </ul>
<b>Serial6</b>	<p>Configures the sixth (if available) built-in serial port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled</li> <li>• Auto</li> </ul>
<b>SignOfLifeByLogo</b>	<p>This option indicates that, during POST the power button has been pressed by displaying the customized logo. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>SmartErrors</b>	<p>Controls whether hard drive errors for integrated drives are reported during system startup. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>StealthMode</b>	<p>Configures the Dell Stealth Mode features. Sets the operation mode of the system elements. If enabled, the system elements operate in the pre-programmed stealth mode. If disabled, the system elements operate in the normal mode. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul> <p>Following are the system elements that have effect of stealth mode on them:</p> <ul style="list-style-type: none"> <li>• DisOnboardLEDs</li> <li>• DisOnboardLCDScreen</li> <li>• DisOnboardSpeakers</li> <li>• DisOnboardFans</li> <li>• DisBluetoothRadio</li> <li>• DisGPSReceiver</li> <li>• DisWLANRadio</li> <li>• DisWWANRadio</li> <li>• DisOnboardLEDs</li> </ul>
<b>TabletButtonIllumination</b>	<p>Sets the Tablet Button illumination level. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Off</li> <li>• 25pct</li> <li>• 50pct</li> <li>• 75pct</li> <li>• 100pct</li> </ul>
<b>TabletButtonsTimeoutAc</b>	<p>This feature defines the illumination timeout value for the tablet buttons when an AC adapter is connected to the system. The buttons are illuminated when they are pressed, and remains illuminated for that specified timeout period. The tablet button illumination timeout value works when button illumination is enabled. If you select Never, the buttons</p>

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<p>remain illuminated whenever the system is connected to the AC adapter. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Never</li> <li>• 5s</li> <li>• 10s</li> <li>• 15s</li> <li>• 30s</li> <li>• 1m</li> <li>• 5m</li> <li>• 15m</li> </ul>
<b>TabletButtonsTimeoutBatt</b>	<p>This feature defines the illumination timeout value for the tablet buttons when the system is running on battery power. The buttons are illuminated when they are pressed, and remains illuminated for that specified timeout period. The tablet button illumination timeout value works when button illumination is enabled. If you select Never, the buttons remain illuminated whenever the system is running on battery power. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Never</li> <li>• 5s</li> <li>• 10s</li> <li>• 15s</li> <li>• 30s</li> <li>• 1m</li> <li>• 5m</li> <li>• 15m</li> </ul>
<b>TbtPcieModeAutoSwitch</b>	<p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>TelemetryAccessLvl</b>	<p>This feature controls the type of telemetry for data support. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled—No telemetry</li> <li>• Basic—Flash and diagnostics only</li> <li>• Enhanced—Flash, diagnostics, and boot event</li> <li>• Full—All telemetry</li> </ul>
<b>Touchscreen</b>	<p>Enables or disables the touchscreen. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UefiNwStack</b>	<p>This option is disabled by default. If enabled, UEFI Networking protocols are installed/available, allowing pre-OS and early OS networking features to use the enabled NICs. This option may be used without turning on PXE. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Enables speed boot time, limits network security, and network access capability. Select the UefiNwStack option to run diagnostics and recovery of the system</li> <li>• Disabled—Disables speed boot time, network security, and restricts network access capability.</li> <li>• AutoEnable—This option is not displayed when the UefiNwStack is enabled by platform customization. Enables speed boot time, limits network security, and increases network access capability. Select the UefiNwStack option to enable multiple applications to work on boot (BitLocker works with limitations).</li> <li>• SelectiveEnable—The speed of the boot time reduces, limits network security, and increases network access capability. Select the UefiNwStack option for BitLocker to work on boot.</li> </ul>
<b>UnobtrusiveMode</b>	<p>Enables or disables the toggling of light emissions using hotkey Fn+B. The following are the possible values:</p>



**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled—Pressing Fn+B will toggle light emissions from the system.</li> <li>• Disabled—Pressing Fn+B keys has no effect and will not toggle light emissions from the system.</li> </ul>
<b>Usb4CmM</b>	<p>Select the USB4 CM mode. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Firmware</li> <li>• Software</li> <li>• OS</li> <li>• Pass</li> </ul>
<b>UsbPowerShare</b>	<p>Configures the USB PowerShare feature behavior. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Charges the external devices, such as phones and laptop music players, using the stored system battery when the system is turned off or in sleep mode. This feature works only if: <ul style="list-style-type: none"> <li>◦ The device is connected through the USB PowerShare port on the laptop.</li> <li>◦ The system is connected to an AC power source.</li> <li>◦ The battery charge is less than 50 percent.</li> </ul> </li> <li>• Disabled—Turns off this feature, and devices attached to the USB PowerShare port will not be charged when the system is in a sleep mode or turned off.</li> </ul>
<b>Vmdnvmepcie0</b>	<p>Enables or disables the VMD for Front NVMe Port (PCIE0). The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Vmdnvmepcie1</b>	<p>Enables or disables the VMD for Front NVMe Port (PCIE1). The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Vmdnvmepcie0cpu1</b>	<p>Enables or disables the VMD for Front NVMe Port (PCIE0-CPU1). The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Vmdnvmepcie1cpu1</b>	<p>Enables or disables the VMD for Front NVMe Port (PCIE1-CPU1). The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Vmdpcieslot</b>	<p>Enables or disables the VMD for PCIe Slot. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>WatchdogTimer</b>	<p>Enables or disables the system to reboot or reset when the watchdog time expires. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>WdtOsBootProtection</b>	<p>Enables or disables Watchdog OS Boot Protection. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—The application configures a chipset-based timer to reset or shutdown the system.</li> <li>• Disabled—The application cannot configure a chipset-based timer to reset or shutdown the system. By default the Application Watchdog Timer is disabled.</li> </ul>
<b>WlanRegionCode</b>	<p>Sets the WLAN code for specific region. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• rtw—(Rest of the World) Sets the WLAN region code for the rest of the world. This option is selected by default.</li> <li>• na—(North America (FCC)) Sets the WLAN region code for Canada and the United States.</li> </ul>

**Table 26. SystemConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• eur—(Europe) Sets the WLAN region code for Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Ireland, Italy, Luxembourg, Netherlands, Norway, Poland, Portugal, Slovakia, Spain, Sweden, Switzerland, Turkey, and United Kingdom.</li> <li>• jpn—(Japan) Sets the WLAN region code for Japan only.</li> <li>• aus—(Australia) Sets the WLAN region code for Australia, New Zealand, Saudi Arabia, South Africa, UAE, and Vietnam.</li> <li>• chn—(China, South Asia) Sets the WLAN region code for China and India.</li> <li>• twn—(Taiwan) Sets the WLAN region code for Colombia, Peru, and Taiwan.</li> <li>• idn—(Indonesia) Sets the WLAN region code for Indonesia only.</li> </ul>

## SystemInformation

**Table 27. SystemInformation**

Attribute Name	Description
<b>Asset</b>	An asset tag is a string that can be used by an IT administrator to uniquely identify a particular system. Possible values: String containing 0 to 14 characters.
<b>BIOSVersion</b>	Displays the current version of the system BIOS firmware. Possible values: Read-only
<b>ExpressServiceCode</b>	The express service code is a mathematical hash applied to the service tag. The express service code is seen in BIOS Setup and on an exterior sticker. Possible values: Read-only
<b>ManufactureDate</b>	Displays the system manufacture date (mm/dd/yyyy). Possible values: Read-only
<b>OwnershipTag</b>	The ownership tag is a string that can be used to display a system-specific message on the BIOS start-up and setup screens. Possible values: String containing 0 to 80 characters
<b>OwnershipDate</b>	Displays the date (mm/dd/yyyy) the system was first powered on after leaving the factory. Possible values: Read-only
<b>SvcTag</b>	The service tag is the system's serial number that uniquely identifies the Dell system. Possible values: Read-only

## SystemLogs

**Table 28. SystemLogs**

Attribute Name	Description
<b>BiosLogClear</b>	Prevents or allows the system event log to be cleared on the next boot. The following are the possible values: <ul style="list-style-type: none"> <li>• Keep—Does not clear the system event log on the next boot.</li> <li>• Clear—Clears the system event log on the next boot.</li> </ul>
<b>PowerLogClear</b>	Prevents or allows the power event log to be cleared on the next boot. The following are the possible values: <ul style="list-style-type: none"> <li>• Keep—Does not clear the power event log on the next boot.</li> <li>• Clear—Clears the power event log on the next boot.</li> </ul>
<b>ThermalLogClear</b>	Prevents or allows the thermal event log to be cleared on the next boot. The following are the possible values: <ul style="list-style-type: none"> <li>• Keep—Does not clear the thermal event log on the next boot.</li> <li>• Clear—Clears the thermal event log on the next boot.</li> </ul>

# System Management

Table 29. System Management

Attribute Name	Description
<b>AutoRtcRecovery</b>	Enabling and disabling the BIOS attempts additional automatic recovery mechanism. The following are the possible values: <ul style="list-style-type: none"><li>• Enabled—When enabled, the BIOS attempts additional automatic recovery mechanism to recover the system in case of unsuccessful boots.</li><li>• Disabled—When disabled, the BIOS does not attempt the additional automatic recovery mechanism.</li></ul>
<b>VerticalIntegration</b>	Enabling and disabling the Dell OS Agent(s) which is capable of scheduling an onboard diagnostic on a subsequent boot. The following are the possible values: <ul style="list-style-type: none"><li>• Enabled—When enabled, the Dell OS Agent(s) is capable of scheduling an onboard diagnostic on the subsequent boot, which can assist in prevention and resolution of the hardware related issues.</li><li>• Disabled—When disabled, Dell OS Agent(s) is not capable of scheduling an onboard diagnostic and scans can be initiated manually in the pre-boot environment.</li></ul>

# ThermalConfiguration

Table 30. ThermalConfiguration








Attribute Name	Description
<b>FanSpdAutoLvlonCpuZone</b>	Sets the speed of the fan on CPU zone. The following are the possible values: <ul style="list-style-type: none"><li>• 0 to 100</li></ul>
<b>FanSpdAutoLvlonPsuZone</b>	Sets the speed of the fan on PSU zone. The following are the possible values: <ul style="list-style-type: none"><li>• 0 to 100</li></ul>
<b>FanSpdAutoLvlonCpuMemZone</b>	Sets the speed of the fan on CPU memory zone. The following are the possible values: <ul style="list-style-type: none"><li>• 0 to 100</li></ul>
<b>FanSpdAutoLvlonPcieZone</b>	Sets the speed of the fan on PCIe zone. The following are the possible values: <ul style="list-style-type: none"><li>• 0 to 100</li></ul>
<b>FanSpdAutoLvlonFlexBayZone</b>	Sets the speed of the fan on Flex Bay zone. The following are the possible values: <ul style="list-style-type: none"><li>• 0 to 100</li></ul>
<b>FanSpdAutoLvlonUpperPcieZone</b>	Sets the speed of the fan on Upper PCIe zone. The following are the possible values: <ul style="list-style-type: none"><li>• 0 to 100</li></ul>

# TPMSecurity

Table 31. TPMSecurity

Attribute Name	Description
<b>PpibypassSedBlockSidCommand</b>	When there is no drive ownership and the PpibypassSedBlockSidCommand is enabled, the BIOS requires user input while sending the Block SID authentication command to SED drives. When PpibypassSedBlockSidCommand is disabled, BIOS does not require user input while sending the Block SID command. The following are the possible values: <ul style="list-style-type: none"><li>• Disabled</li><li>• Enabled</li></ul>

**Table 31. TPMSecurity (continued)**

Attribute Name	Description
	<p> <b>NOTE:</b> You can enable PpibypassSedBlockSidCommand in manufacturing mode or while setting up the BIOS Setup Administrator password.</p> <p> <b>NOTE:</b> The read-only mechanism can be changed when the system is in manufacturing mode, while the PpibypassSedBlockSidCommand is enabled.</p>
<b>SHA256</b>	<p>Sets the hash algorithm used for TPM 2.0 measurements. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Disabled—Sets hash algorithm to SHA-1.</li> <li>• Enabled—Sets hash algorithm to SHA-256.</li> <li>• SHA384—Sets hash algorithm to SHA-384.</li> <li>• SHA512—Sets hash algorithm to SHA-512.</li> </ul> <p> <b>NOTE:</b> This value cannot be changed if TPM is already owned.</p>
<b>TpmActivation</b>	<p>Activates and enables the TPM normal state for TPM use. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Activates the TPM.</li> <li>• Disabled—Displays the current activation state of TPM.</li> </ul> <p> <b>NOTE:</b> Deactivate is a read-only possible value. TPM can be deactivated only from the BIOS setup screen.</p> <p> <b>NOTE:</b> Make sure admin password is set before enabling TpmActivation (on specific platforms).</p>
<b>TpmClear</b>	<p>When you enable the TpmClear attribute, TPM ownership is cleared during the next boot, and the system firmware sets the value of the attribute to disabled. When you disable the TpmClear attribute, TPM ownership remains unchanged. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul> <p> <b>NOTE:</b> You cannot enable or disable this feature using Dell Command   Configure.</p>
<b>TpmPpiAcpi</b>	<p>Controls whether the system accept ACPI physical presence commands from the OS.</p> <ul style="list-style-type: none"> <li>• Enabled—System accepts ACPI physical presence commands from the OS.</li> <li>• Disabled—System does not accept ACPI physical presence commands from the OS.</li> </ul>
<b>Tpmppiclearoverride</b>	<p>When enabled tpmppiclearoverride performing the TPM clear command within operating system does not require user interaction. When disabled, performing the TPM clear command within the operating system does require user interaction.</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul> <p> <b>NOTE:</b> You can enable Tpmppiclearoverride in manufacturing mode or while setting up the BIOS Setup Administrator password.</p>
<b>TpmPpiDpo</b>	<p>Controls the physical presence requirement for the following operations: Disable, Deactivate, and SetOwnerInstall_False. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>TpmPpiPo</b>	<p>Controls the physical presence requirement for the following operations: Enable, Activate, and SetOwnerInstall_True. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Physical presence is not required to perform any of these operations.</li> <li>• Disabled—Physical presence is required to perform these operations.</li> </ul>
<b>TpmSecurity</b>	<p>Controls whether the Trusted Platform Module (TPM) in the system is enabled and visible to the operating system. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—BIOS turns on the TPM during POST, and can be used by the operating system.</li> </ul>

**Table 31. TPMSecurity (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>Disabled—BIOS does not on the TPM during POST, and the TPM is nonfunctional and invisible to the operating system.</li> </ul> <p><b>NOTE:</b> Disabling this option does not change any TPM settings that you may have configured nor does it delete or change any information or keys you may have stored there. It simply turns off the TPM so that it cannot be used. When you re-enable this option, TPM works exactly as it did before it was disabled.</p>

## USBConfiguration



**Table 32. USBConfiguration**

Attribute Name	Description
<b>AlwaysAllowDellDocks</b>	<p>Allows or restricts the Dell Type-C Thunderbolt docks to function when the Thunderbolt is disabled. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Allows the Dell Type-C Thunderbolt docks to function even when the Thunderbolt is disabled.</li> <li>Disabled—Restricts the Dell Type-C Thunderbolt docks to function when the Thunderbolt is disabled.</li> </ul>
<b>BIOSEnumMode</b>	<p>Thunderbolt PCIe Enumeration Mode controls when the operating system or BIOS performs the enumeration of Thunderbolt PCIe devices. The following are the possible values:</p> <ul style="list-style-type: none"> <li>BIOSAssistEnum</li> <li>NativeEnum</li> </ul>
<b>DisableDockDevicesexceptvideo</b>	<p>Enables or disables all devices such as serial, audio, LAN, and USB ports in the docking station. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul> <p><b>NOTE:</b> This option works only when UsbPortsExternal is enabled.</p>
<b>FrontUSB3.0Ports</b>	<p>Enables or disables the front USB 3.0 ports. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>RearUSB3.0Ports</b>	<p>Enables or disables the rear USB 3.0 ports. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ThunderboltBoot</b>	<p>Enables or disables booting from the Thunderbolt device. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ThunderboltPorts</b>	<p>Enables or disables the thunderbolt ports controller in the system. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>Thunderbolt</b>	<p>Enables or disables the thunderbolt controller in the system. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>ThunderboltPreboot</b>	<p>Enables OROMs and preboot UEFI drivers that are provided by Thunderbolt devices or PCIe devices. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> </ul>

**Table 32. USBConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>Disabled</li> </ul>
<b>ThunderboltSecLvl</b>	<p>Configures the thunderbolt security level. The following are the possible values:</p> <ul style="list-style-type: none"> <li>NoSec—Disables the thunderbolt security.</li> <li>UserAuth—Allows minimum user notification. Connection manager requests connection approval from the host software, based on the unique ID of the connecting device, auto approval might or might not be given.</li> <li>SecConn—Allows one-time saved key device. Connection manager requests connection approval from the host software; approval is given only if the host challenge to device is acceptable.</li> <li>DpUsbOnly—Allows to connect only display port.</li> </ul>
<b>UsbGpsCoexistence</b>	<p>This feature optimizes the system for maximum performance of either USB devices or the dedicated GPS radio. The following are the possible values:</p> <ul style="list-style-type: none"> <li>OptiUsb</li> <li>OptiGps</li> </ul>
<b>USbPortsRear7</b>	<p>Enables or disables USbPortsRear7. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort07</b>	<p>Enables or disables USB port 07. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort08</b>	<p>Enables or disables USB port 8. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort09</b>	<p>Enables or disables USB port 9. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort12</b>	<p>Enables or disables USB port 12. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort13</b>	<p>Enables or disables USB port 13. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort14</b>	<p>Enables or disables USB port 14. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort15</b>	<p>Enables or disables USB port 15. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort16</b>	<p>Enables or disables USB port 16. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort17</b>	<p>Enables or disables USB port 17. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort18</b>	<p>Enables or disables USB port 18. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>USBPort19</b>	<p>Enables or disables USB port 19. The following are the possible values:</p>

**Table 32. USBConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>USBPort24</b>	Enables or disables USB port 24. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>USBPort25</b>	Enables or disables USB port 25. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>USBPort26</b>	Enables or disables USB port 26. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>USBPort27</b>	Enables or disables USB port 27. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>USBPort28</b>	Enables or disables USB port 28. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>USBPort29</b>	Enables or disables USB port 29. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Usb30</b>	Enables or disables USB 3.0. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbEmu</b>	<p>If Boot Support is enabled, the system allows to boot any type of USB Mass Storage devices such as hard drive, memory key, floppy, so on</p> <p> <b>NOTE:</b> USB-aware operating system always see USB Mass Storage devices irrespective of this setting if the port is enabled.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> <li>• EnabledWithNoUSBBoot</li> </ul>
<b>UsbPortsExternal</b>	<p>Enables or disables the device that is attached to this USB port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Devices attached to this USB port are enabled and available in the operating system.</li> <li>• Disabled—Devices attached to this USB port are disabled and not visible in the operating system.</li> </ul> <p> <b>NOTE:</b> USB mouse and keyboard work even if the external USB port is disabled.</p>
<b>UsbPortsFront</b>	Enables or disables all front USB Ports in the systems. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsFront1</b>	Enables or disables USB front port 1. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsFront2</b>	Enables or disables USB front port 2. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

**Table 32. USBConfiguration (continued)**

Attribute Name	Description
<b>UsbPortsFront3</b>	Enables or disables USB front port 3. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsFront4</b>	Enables or disables USB front port 4. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsInternal</b>	Enables or disables all front USB Ports in the system. <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsRear</b>	Enables or disables all back USB Ports. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsRear1</b>	Enables or disables USB rear port 1. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsRear2</b>	Enables or disables USB rear port 2. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsRear3</b>	Enables or disables USB rear port 3. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsRear4</b>	Enables or disables USB rear port 4. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsRear5</b>	Enables or disables USB Ports Rear 5. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsRear6</b>	Enables or disables USB Ports Rear 6. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsSide</b>	Enables or disables all side USB Ports in the system. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsSide1</b>	Enables or disables USB side port 1. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbPortsSide2</b>	Enables or disables USB side port 2. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbRearDual</b>	Enables or disables the rear left dual USB ports. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbRearDual2Stack</b>	Enables or disables the rear right dual USB ports. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>UsbRearQuad</b>	Enables or disables the rear quad USB ports. The following are the possible values:



**Table 32. USBConfiguration (continued)**

Attribute Name	Description
	<ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>UsbPortsInternal2</b>	<p>Enables or disables the internal USB port. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Enables the internal USB port</li> <li>Disabled—Disables the internal USB port 2</li> </ul>

## Video

**Table 33. Video**

Attribute Name	Description
<b>AmbLightSen</b>	<p>Enables or disables the ambient light sensor. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>BootTimeVideo</b>	<p>Sets the onboard or the first video controller for boot time messages. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Onboard—The onboard video controller is used for boot-time messages.</li> <li>Addin—The first add-in video controller is used for boot-time messages.</li> </ul> <p><b>NOTE:</b> Depending on the BIOS search and system slot layout, the first add-in device changes.</p>
<b>BrightnessAc</b>	<p>Sets the panel brightness in effect when the system is using AC power. Possible values: Integers ranging from 0 to 15</p>
<b>BrightnessBattery</b>	<p>Sets the panel brightness in effect when the system is using battery power only. Possible values: Integers ranging from 0 to 15</p>
<b>DockDisplayThruIntGfx</b>	<p>The Dock Display Port Through Integrated Graphics feature enables the docking station DVI no1 or Display Port no1 interface to drive an external video display when Switchable Graphics is enabled and running from the integrated graphics controller. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—Uses the integrated video controller as video source.</li> <li>Disabled—Uses the external video controller as video source.</li> </ul>
<b>DynBacklightCtrl</b>	<p>Enables or disables the Dynamic Backlight Control (DBC) feature within the BIOS. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>HybridGraphics</b>	<p>Allows the integrated and discrete graphics controllers. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—The system allows the integrated and discrete graphics controllers to work together to optimize the graphics capability and battery life.</li> <li>Disabled—Displays are driven by the discrete graphics controller to prioritize graphics capability over battery life.</li> </ul>
<b>MultiDisplay</b>	<p>Enables or disables MultiDisplay. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>Optimus</b>	<p>Enables or disables the Optimus feature. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—This feature automatically turns off the power of the Graphics Processing Unit (GPU) when not required, and turns it on when required.</li> <li>Disabled—This feature does not automatically turn on or off the power of the GPU. In mobile PCs, when the GPU power is off the driver redirects graphics commands to the integrated graphics chip.</li> </ul>

**Table 33. Video (continued)**

Attribute Name	Description
<b>PrimaryVideoSlot</b>	<p>Selects which PCI Express slot contains the primary boot video device. A monitor connected to the primary video device displays BIOS setup and initial operating system text and graphics. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Slot0—Sets the 1st slot as the primary video device slot.</li> <li>Slot1—Sets the 2nd slot as the primary video device slot.</li> <li>Slot2—Sets the 3rd slot as the primary video device slot.</li> <li>Slot3—Sets the 4th slot as the primary video device slot.</li> <li>Slot4—Sets the 5th slot as the primary video device slot.</li> <li>Slot5—Sets the 6th slot as the primary video device slot.</li> <li>Slot6—Sets the 7th slot as the primary video device slot.</li> <li>Slot7—Sets the 8th slot as the primary video device slot.</li> <li>Slot8—Sets the 9th slot as the primary video device slot.</li> <li>Slot9—Sets the 10th slot as the primary video device slot.</li> <li>Slot10—Sets the 11th slot as the primary video device slot.</li> <li>Slot11—Sets the 12th slot as the primary video device slot.</li> <li>Slot12—Sets the 13th slot as the primary video device slot.</li> <li>Slot13—Sets the 14th slot as the primary video device slot.</li> <li>Slot14—Sets the 15th slot as the primary video device slot.</li> <li>Auto—Automatically scans the slots and selects the first video device slot found with video card as a primary video device slot.</li> <li>Onboard - Sets the onboard video device slot as primary video device slot.</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>This option has no effect if only one video device is present in the system.</li> <li>If the selected slot does not contain a video device, the system BIOS scans the slots and selects the primary video device.</li> </ul>
<b>PrivacyScreen</b>	<p>AlwaysOn, enables, or disables the privacy screen. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled—The PrivacyScreen is applied to the embedded display panel and can be toggled between public mode and privacy mode using the Fn+F9 key combination on the embedded keyboard.</li> <li>Disabled - The PrivacyScreen is not applied to the embedded display panel.</li> <li>AlwaysOn - The PrivacyScreen is always on and cannot be turned off.</li> </ul>
<b>SwitchableGraphics</b>	<p>Enables or disables switchable graphics technologies such as NVIDIA, Optimus, and AMD PowerExpress. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>

## VirtualizationSupport

**Table 34. VirtualizationSupport**


Attribute	Description
<b>AmdVtEnable</b>	<p>This field specifies whether the Virtual Machine Monitor (VMM) utilizes the additional hardware capabilities that are provided by AMD-V Technology. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>
<b>AmdViEnable</b>	<p>This field specifies whether the Virtual Machine Monitor (VMM) utilizes the additional hardware capabilities that are provided by AMD-Vi Technology. The following are the possible values:</p> <ul style="list-style-type: none"> <li>Enabled</li> <li>Disabled</li> </ul>

**Table 34. VirtualizationSupport (continued)**

Attribute	Description
<b>IntelVMDTechnology</b>	Enables or disables the Intel Volume Management Device (VMD) technology. Selecting Auto Enables VMD for any PCIe SSD connected to PCIe root ports. If the Auto option is not selected, then it disables VMD for all ports. SSD works only as native NVMe device. The following are the possible values: <ul style="list-style-type: none"> <li>• Auto</li> <li>• Disabled</li> </ul>
<b>KernelDma</b>	This setting controls the Kernel DMA protection for the internal and the external ports. It does not directly enable the DMA protection in the operating system. However, the operating system that supports the DMA protection indicates that the BIOS supports the KernelDma feature. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PreBootDma</b>	This setting controls the pre-boot DMA protection for the internal and the external ports. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>VmdPcieSlot</b>	Enables or disables the Intel Volume Management Device (VMD) technology PCIe slot. Selecting Auto Enables VMD for any PCIe SSD connected to PCIe root ports. If the Auto option is not selected, then it disables VMD for all ports. SSD works only as native NVMe device. The following are the possible values: <ul style="list-style-type: none"> <li>• Auto</li> <li>• Disabled</li> </ul>
<b>TrustExecution</b>	Determines whether a Measured Virtual Machine Monitor (MVVM) can utilize the additional hardware capabilities that are provided by the Intel Trusted Execution Technology. <i>i</i> <b>NOTE:</b> TPM has to be enabled and activated. Also, Virtualization Technology and VT for Direct I/O must be enabled to use this feature. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>Virtualization</b>	Enables or disables the VT technology in applicable CPUs. Trusted execution required for Virtualization technology to be enabled. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>VtForDirectIo</b>	Determines whether a Virtual Machine Monitor (VMM) can utilize the additional hardware capabilities provided by Intel Virtualization Technology for Direct IO. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>PcieLinkSpeed</b>	This feature allows you to select the maximum PCIe link speed within the system in the BIOS setup. Adjusting this setting improves the compatibility with older PCIe add-in adapters. The following are the possible values: <ul style="list-style-type: none"> <li>• Auto—Setting the system to Auto option, allows the devices (if capable) to obtain the maximum speed for hardware configuration.</li> <li>• Gen1—Setting the system to Gen1 changes the device capabilities to use the 1.1 version.</li> <li>• Gen2</li> <li>• Gen3</li> <li>• Gen4</li> </ul>

# Wireless

Table 35. Wireless

Attribute Name	Description
<b>AntennaSwitch</b>	<p>This setting determines the antenna usage when the system is connected to a docking station. The option designates which wireless radio is connected to which dock antenna. The System Antennas Only option indicates the system antennas that are used, and the dock antennas that are not used, even when the system is docked. When the system is undocked, the system antennas are used and this setting has no effect. Ant A indicates dock antenna A, and Ant B indicates dock antenna B.</p> <p> <b>NOTE:</b> This setting applies to rugged docking stations and does not apply to USB Type-C docking stations.</p> <p>The following are the possible values:</p> <ul style="list-style-type: none"> <li>• AllInternal</li> <li>• WlanWwanExt</li> <li>• WlanGpsExt</li> <li>• WwanGpsExt</li> <li>• WlanExt</li> <li>• WwanExt</li> <li>• GpsExt</li> </ul>
<b>BluetoothDevice</b>	<p>Enables or disables the internal Bluetooth device. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>DynamicWirelessTransmitPower</b>	<p>When enabled, the system increases the power transmission capability of the WLAN device. This improves the performance in the system configurations within the regulatory validated guidelines. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>LidMountedWirelessActivityLED</b>	<p>This additional LED is mounted in the lid in a visible position. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Always Off—The LED always stays off irrespective of network activity.</li> <li>• LED Indicates Wireless Activity Status—The LED becomes active whenever any of the wireless devices are capable of connecting to a wireless network. Wireless activity is defined as the following three inputs: <ul style="list-style-type: none"> <li>◦ WWAN activity</li> <li>◦ Bluetooth activity</li> <li>◦ Wi-Fi activity</li> </ul> </li> </ul>
<b>WirelessLan</b>	<p>Enables or disables the internal wireless LAN device. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>WirelessSwitchBluetoothCtrl</b>	<p>Determines that bluetooth is controlled by the wireless On-Off switch. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Physical wireless On-Off switch can turn the bluetooth On-Off.</li> <li>• Disabled—Physical wireless On-Off switch cannot turn the bluetooth On-Off.</li> </ul>
<b>WirelessSwitchGps</b>	<p>Determines that GPS radio of WWAN device is controlled by the wireless On-Off switch. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Physical wireless On-Off switch can turn the GPS On or Off.</li> <li>• Disabled—Physical wireless On-Off switch cannot turn the GPS On or Off.</li> </ul>
<b>WirelessSwitchCellularCtrl</b>	<p>Determines that WWAN is controlled by the wireless On-Off switch. The following are the possible values:</p> <ul style="list-style-type: none"> <li>• Enabled—Physical wireless On-Off switch can turn the WWAN On-Off.</li> <li>• Disabled—Physical wireless On-Off switch cannot turn the WWAN On-Off.</li> </ul>

**Table 35. Wireless (continued)**

Attribute Name	Description
<b>WirelessSwitchUwb</b>	Determines that UWB (Ultra Wide Band) Radio will be controlled by the wireless On-Off switch. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Physical wireless On-Off switch can turn the UWB Radio On-Off.</li> <li>• Disabled—Physical wireless On-Off switch cannot turn the UWB Radio On-Off.</li> </ul>
<b>WirelessSwitchWiGigCtrl</b>	Determines that Wireless Gigabit Alliance (WiGig) radio can be controlled by the physical wireless On/Off switch. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Physical wireless On/Off switch turns the WiGig radio On/Off.</li> <li>• Disabled—Physical wireless On/Off switch does not turn the WiGig radio On-Off.</li> </ul>
<b>WirelessSwitchWlanOnlyCtrl</b>	Determines that WLAN is controlled by the wireless On-Off switch. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Physical wireless On-Off switch can turn the WLAN On-Off.</li> <li>• Disabled—Physical wireless On-Off switch cannot turn the WLAN On-Off.</li> </ul>
<b>WirelessWwan</b>	Enables or disables the internal wireless WAN device. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>WirelessSwitchWlanCtrl</b>	Determines that WLAN and WiGig Radio is controlled by the wireless On-Off switch. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled—Physical wireless On-Off switch can turn the WLAN and WiGig Radio On-Off.</li> <li>• Disabled—Physical wireless On-Off switch cannot turn the WLAN and WiGig Radio On-Off.</li> </ul>
<b>WirelessUwb</b>	Enable or disables Ultra Wide Band (UWB) radio. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>
<b>WWanBusMode</b>	WWanBusMode sets the interface type of the Wireless Wan (WWAN) card. It is recommended that the system running Windows must set this field to PCIe, while all the other systems must set this field to USB. The following are the possible values: <ul style="list-style-type: none"> <li>• PcieMode</li> <li>• UsbMode</li> </ul>
<b>ZigBee</b>	Enables or disables the ZigBee feature. The following are the possible values: <ul style="list-style-type: none"> <li>• Enabled</li> <li>• Disabled</li> </ul>

## Error reporting in Dell Command | PowerShell Provider 2.6

Dell Command | PowerShell Provider provides an Error Reporting feature. Dell Command | PowerShell Provider uses the PowerShell ErrorVariable parameter to capture the ErrorRecord. This ErrorVariable can be used to get more information such as exception, error ID, error category, and recommended action, and so on, about an error.

**NOTE:** If the system does not have a WMI-ACPI compliant BIOS. Update the BIOS with a compatible version, if available.

Example: To set the error variable.

```
gi .\POSTBehavior\numl -ErrorVariable ev
```

Example: To see more information about the error.

```
$ev.ErrorDetails
```

The table below describes all the possible Error IDs generated by Dell Command | PowerShell Provider that are categorized by error categories.

**Table 36. Error reporting in Dell Command | PowerShell Provider**

Error Category	Error ID	Scenarios	Example
InvalidArgument	InvalidPath	Path is not complete while doing set operation.	NA
	PasswordProvidedIncorrectly	Trying to provide both plain text password and secure password.	NA
	NullDrive	Newly created drive is null or Trying to remove drive which is already null.	NA
	NoRoot	Drive root is empty or null.	NA
InvalidData	InvalidPossibleValue	Using set-item cmdlet for an attribute with Invalid possible value.	<pre>si .\POSTBehavior\Numlock "on"</pre>
	NumberNotInRange	Doing set operation by giving out of range integer value for an attribute which accepts integer value in a particular range.	<pre>si .\PowerManagement\AutoOnHr "54"</pre> <pre>si .\PowerManagement\AutoOnMn "67"</pre> <pre>si .\PeakShiftBatteryThreshold "13"</pre>

**Table 36. Error reporting in Dell Command | PowerShell Provider (continued)**

Error Category	Error ID	Scenarios	Example
	ReadOnlyValue	Trying to set read-only value for chassis intrusion status.	<pre>si .\Security\ChassisIntrusionStatus "DoorClosed"</pre>
	SetNotAllowed	Set operation is not enabled using Dell Command   PowerShell Provider but enabled using BIOS Setup Menu.	<pre>si .\Security\MasterPasswordLockout "Disabled"</pre>
	NotValidNumber	Doing set operation by giving noninteger value for an attribute accepts integer value.	<pre>si .\PowerManagement\AutoOnHr "on"</pre> <pre>si .\PowerManagement\AutoOnMn "43.67"</pre>
	StringLengthNotInRange	Doing set operation by giving string which has out of range length for an attribute which accepts a string having length within a range.	<pre>si .\SystemInformation\Asset "thisismorethan10characters"</pre>
	InvalidTimeFormat	Doing set operation by giving invalid time format.	<pre>si .\PeakShiftDayConfiguration Sunday -StartTime "34:34"</pre>
	InvalidPrimaryBatteryCustomChargeDifference	Not keeping the minimum difference between CustomChargeStart and CustomChargeStop.	<pre>si .\PowerManagement\CustomChargeStart "55"</pre> <pre>si .\PowerManagement\CustomChargeStop "58"</pre>
	NewPasswordNotInRange	Trying to set a password that is not in supported range by system.	<pre>si .\Security\AdminPassword "12"</pre> <pre>si .\Security\SystemPassword "del"</pre>

**Table 36. Error reporting in Dell Command | PowerShell Provider (continued)**

Error Category	Error ID	Scenarios	Example
	InvalidPeakShiftTimes	Not maintaining the time dependency between PeakShift StartTime, EndTime, and ChargeStartTime.	<pre>si .\PowerManagement\PeakShiftDayConfiguration Sunday -StartTime "14:30" -EndTime "12:30" -ChargeStartTime "14:45"</pre>
	InvalidDayOfWeek	Providing invalid day.	<pre>si .\PowerManagement\PeakShiftDayConfiguration Sun -StartTime "14:30" -EndTime "12:30" -ChargeStartTime "14:45"</pre>
	InCorrectBootOrder	Trying to provide duplicate boot device number.	<pre>si .\BootSequence\BootSequence "1,2,1"</pre>
	UnsupportedColorName	Trying to set unsupported color for KeyboardBacklightEnabledColors or KeyboardBacklightActiveColor.	<pre>si .\SystemConfiguration\KeyboardBacklightEnabledColors "Red,White,Purple"</pre>
	NotPrintableChar	Trying to configure non-ascii character for string based features.	<pre>si .\SystemInformation\Asset "XY 的 Z"</pre>
	InvalidCombinationOfNoColorAndSupportedColors	Trying to set colors for KeyboardBacklightEnabledColors with NoColor Value.	<pre>si .\SystemConfiguration\KeyboardBacklightEnabledColors "Red,White,Custom1,NoColor"</pre>
	DuplicateColorName	Trying to provide same color more than once for KeyboardBacklightEnabledColors.	<pre>si .\SystemConfiguration\KeyboardBacklightEnabledColors "Red,White,Custom1,Custom1"</pre>
	OnlyOneColorAllowedForActiveColor	Trying to set multiple colors for KeyboardBacklightActiveColor.	<pre>si .\SystemConfiguration\KeyboardBacklightActiveColor "Red, White"</pre>



**Table 36. Error reporting in Dell Command | PowerShell Provider (continued)**

Error Category	Error ID	Scenarios	Example
	InvalidRGBFormat	Trying to provide RGB values in an incorrect format for KeyboardBacklightCustom1Color or KeyboardBacklightCustom2Color.	<pre>si .\SystemConfiguration\KeyboardBacklightCustom1Color "234:34"</pre>
	NotValidNumberForRGB	Trying to provide invalid number for R, G or B components for KeyboardBacklightCustom1Color or KeyboardBacklightCustom2Color.	<pre>si .\SystemConfiguration\KeyboardBacklightCustom1Color "234:34:567"</pre>
InvalidOperation	SetItemForReadOnlyError	Attempt to set read-only attribute.	<pre>si .\SystemInformation\ExpressServiceCode dsdasfjskfjskfskj  si .\SystemInformation\SvcTag sdwadnakjsd</pre>
	NewDriveNotSupported	If newly created drive name is not equal to DellSmbios.	NA
ObjectNotFound	DellSmbiosPathNotFound	Path is correct but either attribute name, or category name is wrong or category does not have any supported attribute for local system and trying to get or set some attributes.	<pre>dir .\PowerManagement\  gi .\PowerManagement\Numlck  si .\PowerManagement\Numlck "enabled"  si .\POSTBehavior\Numlock "enabled"</pre>
OpenError	DefaultDriveInitFailed	DellSMBIOS Drive creation fails in system.	NA
SecurityError	PasswordSetButNotProvided	Doing set operation for any attribute without providing password if set on your system.	<pre>si .\POSTBehavior\Numlock "enabled"</pre>
	FailedToSetAdminPassword	Trying to set admin password if system and/or HDD password is already set.	<pre>si .\Security\AdminPassword</pre>

**Table 36. Error reporting in Dell Command | PowerShell Provider (continued)**

Error Category	Error ID	Scenarios	Example
			"12345"
	SecureBootEnabledOrLegacyO romDisabled	Trying to Configure BootList as Legacy	si .\BootConfiguration\Bo otList "Legacy"
WriteError	SMBIOSWriteFailed	Provided incorrect password while doing set operation if password is already set.	si . \POSTBehavior\numlock "enabled" -Password <wrong password>

# Accessing documents from the Dell support site

You can access the required documents by selecting your product.

1. Go to [www.dell.com/manuals](http://www.dell.com/manuals).
2. Click **Browse all products**, click **Software**, and then click **Client Systems Management**.
3. To view the required documents, click the required product name and version number.