

**Dell Chassis Management Controller Version 1.4 for
PowerEdge FX2/FX2s
RACADM Command Line Reference Guide**



Notes, cautions, and warnings

-  **NOTE:** A NOTE indicates important information that helps you make better use of your product.
-  **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.
-  **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.

Contents

1 Introduction.....	11
What's new in this release.....	11
Supported RACADM Interfaces.....	11
RACADM Syntax Usage.....	11
SSH or Telnet RACADM.....	11
Remote RACADM.....	12
RACADM Command Options.....	12
Displayable Characters.....	12
Supported RACADM Subcommands.....	12
Other Documents You May Need.....	15
2 RACADM Subcommand Details.....	16
Guidelines to Quote Strings Containing Special Characters When Using RACADM Commands.....	16
"?"and "?<subcommand>"	17
help and help <subcommand>.....	18
chassislog.....	18
chassislog export.....	19
chassislog clear.....	20
chassisaction.....	20
closessn.....	21
clrsel.....	21
config.....	22
connect.....	23
deploy.....	23
eventfilters.....	24
fanoffset.....	26
feature.....	26
featurecard.....	27
fwupdate.....	27
get.....	30
getactiveerrors.....	31
getassettag.....	31
getchassisname.....	31
getconfig.....	32
getdcinfo.....	33
getsleduplinkstatus.....	34
getflexaddr.....	35
getioinfo.....	37
getled.....	38
getmacaddress.....	38
getmodinfo.....	43



getniccfg.....	44
getpbinfo.....	46
getpciecfg.....	47
getpminfo.....	48
gettracelog.....	49
gettractime.....	49
getsel.....	50
getslotname.....	50
getsensorinfo.....	51
getssninfo.....	53
getstoragemoduleinfo.....	53
getsvctag.....	55
getsysinfo.....	55
gettracelog.....	57
getversion.....	57
ifconfig.....	59
jobqueue.....	59
krbkeytabupload.....	60
license.....	60
netstat.....	63
ping.....	64
ping6.....	64
racdump.....	64
racreset.....	70
racresetcfg.....	70
remoteimage.....	71
serveraction.....	72
set.....	73
setassettag.....	74
setchassisname.....	74
setflexaddr.....	74
setled.....	75
setniccfg.....	76
settractime.....	77
setslotname.....	78
setsysinfo.....	79
SSH or Telnet RACADM.....	79
sshpkauth.....	80
sslkeyupload.....	81
sslcertupload.....	81
sslcertview.....	82
sslcsrgen.....	83
sslresetcfg.....	84
testemail.....	84
testfeature.....	85



testtrap.....	86
tracert.....	87
tracert6.....	87

3 CMC Property Database Group and Object Descriptions..... 88

idRacInfo.....	88
idRacProductInfo (Read Only).....	88
idRacDescriptionInfo (Read Only).....	88
idRacVersionInfo (Read Only).....	89
idRacBuildInfo (Read Only).....	89
idRacName (Read Only).....	89
cfgLanNetworking.....	89
cfgNicPv4Enable (Read or Write).....	89
cfgNicVlanEnable (Read or Write).....	90
cfgNicVlanId (Read or Write).....	90
cfgNicVlanPriority (Read or Write).....	90
cfgDNSDomainNameFromDHCP (Read/Write).....	90
cfgDNSDomainName (Read or Write).....	91
cfgDNSRacName (Read/Write).....	91
cfgDNSRegisterRac (Read/Write).....	91
cfgDNSServersFromDHCP (Read/Write).....	92
cfgDNSServer1 (Read/Write).....	92
cfgDNSServer2 (Read/Write).....	93
cfgNicEnable (Read/Write).....	93
cfgNicIpAddress (Read/Write).....	93
cfgNicNetmask (Read/Write).....	93
cfgNicGateway (Read/Write).....	93
cfgNicUseDhcp (Read or Write).....	94
cfgNicMacAddress (Read Only).....	94
cfgUserAdmin.....	94
cfgUserAdminIndex (Read Only).....	94
cfgUserAdminPrivilege (Read/Write).....	95
cfgUserAdminUserName (Read/Write).....	96
cfgUserAdminPassword (Write Only).....	96
cfgUserAdminEnable (Read/Write).....	97
cfgEmailAlert.....	97
cfgEmailAlertIndex (Read Only).....	97
cfgEmailAlertEnable (Read/Write).....	97
cfgEmailAlertAddress (Read/Write).....	97
cfgEmailAlertEmailName.....	98
cfgSessionManagement.....	98
cfgSsnMgtRacadmTimeout (Read/Write).....	98
cfgSsnMgtWebserverTimeout (Read/Write).....	98
cfgSerial.....	99
cfgSerialBaudRate (Read/Write).....	99
cfgSerialConsoleEnable (Read/Write).....	99



cfgSerialConsoleQuitKey (Read or Write).....	99
cfgSerialConsoleIdleTimeout (Read/Write).....	100
cfgSerialConsoleNoAuth (Read/Write).....	100
cfgSerialConsoleCommand (Read/Write).....	100
cfgSerialConsoleColumns.....	100
cfgSerialHistorySize (Read/Write).....	100
cfgSerialSshEnable (Read/Write).....	101
cfgSerialTelnetEnable (Read/Write)	101
cfgOobSnmp.....	101
cfgOobSnmpAgentCommunity (Read/Write).....	101
cfgOobSnmpAgentEnable (Read/Write).....	101
cfgOobSnmpProtocol.....	102
cfgOobSnmpTrapFormat.....	102
cfgTraps.....	102
cfgTrapsIndex (Read Only).....	102
cfgTrapsEnable.....	102
cfgTrapsAlertDestIpAddr.....	103
cfgTrapsCommunityName.....	103
cfgTrapsSNMPv3UserId (Read Only).....	103
cfgTrapsSNMPv3UserName.....	103
cfgRacTuning.....	103
cfgRacTuneDefCredentialWarningEnable.....	104
cfgRacTuneRemoteRacadmEnable (Read/Write).....	104
cfgRacTuneChassisMgmtAtServer.....	104
cfgRacTuneHttpPort (Read/Write).....	104
cfgRacTuneHttpsPort (Read/Write).....	104
cfgRacTuneIpRangeEnable (Read/Write).....	105
cfgRacTuneIpRangeAddr (Read/Write).....	105
cfgRacTuneIpRangeMask (Read/Write).....	105
cfgRacTuneIpBlkEnable (Read/Write).....	105
cfgRacTuneIpBlkFailCount (Read/Write).....	105
cfgRacTuneIpBlkFailWindow (Read/Write).....	106
cfgRacTuneIpBlkPenaltyTime (Read/Write).....	106
cfgRacTuneSshPort (Read/Write).....	106
cfgRacTuneTelnetPort (Read/Write).....	106
cfgRacTuneDaylightOffset (Read Only).....	106
cfgRacTuneTimezoneOffset	107
cfgRacTuneSledNetworkUplink.....	107
cfgRacTuneUserBlkEnable.....	107
cfgRacTuneWebserverEnable (Read/Write).....	108
cfgRacTuneFipsModeEnable.....	108
cfgRacTuneTLSProtocolVersionEnable.....	109
cfgServerInfo.....	109
cfgServerInfoIndex (Read Only).....	109
cfgServerSlotNumber (Read Only).....	109



cfgServerServiceTag (Read Only).....	109
cfgServerName (Read/Write).....	109
cfgServerFW (Read Only).....	109
cfgServerBIOS (Read Only).....	110
cfgServerBmcMacAddress (Read Only).....	110
cfgServerNic1MacAddress (Read Only).....	110
cfgServerNic2MacAddress (Read Only).....	110
cfgServerNic3MacAddress (Read Only).....	110
cfgServerNic4MacAddress (Read Only).....	110
cfgServerNicEnable (Read/Write).....	110
cfgServerNodeId	110
cfgServerIPMIOverLanEnable (Read/Write).....	110
cfgServerDNSRegisterIMC (Read/Write).....	111
cfgServerDNSIMCName (Read/Write).....	111
cfgServerRootPassword (Write Only).....	111
cfgServerFirstBootDevice (Read/Write).....	111
cfgServerBootOnce (Read/Write).....	111
cfgStorageModule.....	112
cfgStorageModuleStorageMode (Read/Write).....	112
cfgStorageModuleServiceTag (Read Only).....	112
cfgStorageModuleAssetTag (Read/Write).....	112
ConnectedServer (Read Only).....	112
RAID-EnabledControllers (Read Only).....	113
cfgActiveDirectory.....	113
cfgAD RacName (Read/Write).....	113
cfgADCertValidationEnable (Read/Write).....	113
cfgAD RacDomain (Read or Write).....	113
cfgADRootDomain.....	113
cfgADEnable (Read/Write).....	114
cfgADAuthTimeout (Read/Write).....	114
cfgADSCLEnable.....	114
cfgADDomainController.....	114
cfgADDomainController1 (Read/Write).....	115
cfgADDomainController2 (Read/Write).....	115
cfgADDomainController3 (Read/Write).....	115
cfgADGlobalCatalog1 (Read/Write).....	115
cfgADGlobalCatalog2 (Read/Write).....	115
cfgADGlobalCatalog3 (Read/Write).....	115
cfgADType (Read/Write).....	115
cfgADDcSRVLookupDomainName (Read/Write).....	116
cfgADDcSRVLookupDomainName (Read/Write).....	116
cfgADDcSRVLookupEnable (Read/Write).....	116
cfgADSpecifyServerEnable.....	116
cfgLDAP.....	116
cfgLdapEnable (Read/Write).....	117



cfgLdapServer (Read/Write).....	117
cfgLdapPort (Read/Write).....	117
cfgLdapBasedn (Read/Write).....	117
cfgLdapUserAttribute (Read/Write).....	117
cfgLdapGroupAttribute (Read/Write).....	118
cfgLdapGroupAttributelsDN (Read/Write).....	118
cfgLdapBinddn (Read/Write).....	118
cfgLdapBindpassword (Write Only).....	118
cfgLdapSearchFilter (Read/Write).....	118
cfgLDAPCertValidationEnable (Read/Write).....	119
cfgLDAPNetworkTimeout.....	119
cfgLDAPSearchTimeout.....	119
cfgLDAPSRVLookupDomainName.....	119
cfgLDAPSRVLookupEnable.....	119
cfgLDAPSRVLookupServiceName (Read/Write).....	120
cfgLdapRoleGroup.....	120
cfgLdapRoleGroupDN (Read/Write).....	120
cfgLdapRoleGroupPrivilege (Read/Write).....	120
cfgLocation.....	121
cfgLocationDatacenter (Read/Write).....	121
cfgLocationAisle (Read/Write).....	121
cfgLocationRack (Read/Write).....	121
cfgLocationRackslot (Read/Write).....	121
cfgLocationDevicesize (Read Only).....	121
cfgStandardSchema.....	122
cfgSSADRoleGroupIndex (Read Only).....	122
cfgSSADRoleGroupName (Read/Write).....	122
cfgSSADRoleGroupDomain (Read/Write).....	122
cfgSSADRoleGroupPrivilege (Read/Write).....	122
cfgChassisPower.....	123
cfgChassisInPower (Read Only).....	123
cfgChassisPeakPower (Read Only).....	123
cfgChassisPeakPowerTimestamp (Read Only).....	124
cfgChassisMinPower (Read Only).....	124
cfgChassisMinPowerTimestamp (Read Only).....	124
cfgChassisPowerStatus (Read Only).....	124
cfgChassisRedundantState (Read Only).....	124
cfgChassisMaxPowerConservationMode (Read/Write).....	125
cfgChassisPowerCapUpperBound (Read Only).....	125
cfgChassisPowerCapLowerBound (Read Only).....	125
cfgChassisSledPowerButtonEnable.....	125
cfgChassisPowerCap (Read/Write).....	125
cfgChassisPowerCapF (Read/Write).....	126
cfgChassisPowerCapBTU (Read/Write).....	126
cfgChassisPowerCapFBTU (Read/Write).....	126



cfgChassisPowerCapPercent (Read/Write).....	126
cfgChassisPowerCapFPercent (Read/Write).....	126
cfgChassisRedundancyPolicy (Read/Write).....	127
cfgChassisInMaxPowerCapacity (Read Only).....	127
cfgChassisInRedundancyReserve (Read Only).....	127
cfgChassisPowerClear (Write Only).....	127
cfgChassisPowerClearTimestamp (Read Only).....	127
cfgChassisPowerButtonEnable (Read/Write).....	128
cfgChassisPowerCapBTU (Read/Write).....	128
cfgChassisACPowerRecoveryDisable.....	128
cfgKVMInfo.....	128
cfgKvmEnable	128
cfgKvmMapping	128
cfgAlerting.....	129
cfgAlertingEnable.....	129
cfgAlertingSourceEmailName.....	129
cfgIPv6LanNetworking.....	129
cfgIPv6Enable (Read or Write).....	130
cfgIPv6AutoConfig (Read/Write).....	130
cfgIPv6Address.....	130
cfgIPv6PrefixLength (Read/Write).....	130
cfgIPv6Gateway (Read/Write).....	130
cfgCurrentIPv6DNSServersFromDHCP6	131
cfgIPv6DNSServer1 (Read/Write).....	131
cfgIPv6DNSServer2 (Read/Write).....	131
cfgCurrentLanNetworking (Read Only).....	131
cfgNicCurrentIpAddress.....	132
cfgNicCurrentNetmask.....	132
cfgNicCurrentGateway.....	132
cfgNicCurrentDhcpWasUsed.....	132
cfgNicCurrentVlanEnable (Read Only).....	132
cfgNicCurrentVlanID (Read Only).....	132
cfgNicCurrentVlanPriority (Read Only).....	133
cfgDNSCurrentServer1.....	133
cfgDNSCurrentServer2.....	133
cfgDNSCurrentDomainName.....	133
cfgNicCurrentIPv4Enabled.....	133
cfgCurrentIPv6LanNetworking (Read Only).....	133
cfgCurrentIPv6Enabled (Read/Write).....	134
cfgCurrentIPv6AutoConfigWasUsed.....	134
cfgCurrentLinkLocalAddress.....	134
cfgCurrentIPv6Address.....	134
cfgCurrentIPv6Gateway	134
cfgCurrentIPv6DNSServersFromDHCP6	134
cfgCurrentIPv6DNSServer1.....	134



cfgCurrentIPv6DNSServer2.....	134
cfgNetTuning.....	135
cfgNetTuningNicSpeed.....	135
cfgNetTuningNicAutoneg (Read/Write).....	135
cfgNetTuningNicFullDuplex (Read/Write).....	135
cfgNetTuningNicMtu (Read/Write).....	135
cfgNetTuningNicRedunadant.....	136
cfgRacSecurity.....	136
cfgRacSecCsrCommonName (Read/Write).....	136
cfgRacSecCsrOrganizationName (Read/Write).....	136
cfgRacSecCsrOrganizationUnit (Read/Write).....	137
cfgRacSecCsrLocalityName (Read/Write).....	137
cfgRacSecCsrStateName (Read/Write).....	137
cfgRacSecCsrCountryCode (Read/Write).....	137
cfgRacSecCsrEmailAddr (Read/Write).....	137
cfgRacSecCsrKeySize (Read/Write).....	138
cfgPCIe.....	138
cfgPCIeReassignmentEnable (Read/Write).....	138
cfgQuickDeploy.....	138
cfgActionOnServerInsertion.....	138
cfgSetiDRACRootPasswordOnServerInsertion.....	138
cfgiDRACRootPassword.....	139
cfgEnableiDRACLAN.....	139
cfgEnableiDRACIPv4.....	139
cfgEnableiDRACIPMIOverLAN.....	139
cfgEnableiDRACIPv4DHCP.....	139
cfgStartingiDRACIPv4Address.....	140
cfgiDRACIPv4GateWay.....	140
cfgiDRACIPv4Netmask.....	140
cfgEnableiDRACIPv6.....	140
cfgEnableiDRACIPv6AutoConfig.....	141
cfgiDRACIPv6PrefixLength.....	141
cfgiDRACIPv6Gateway.....	141
cfgReservedIPAddressNumbers.....	141
cfgUseCMCDNSSettings.....	141



Introduction

This document provides information about the RACADM subcommands, supported RACADM interfaces, and property database groups and object definitions of CMC for PowerEdge FX2/FX2s.

 **NOTE:** The terms “storage sled” and “storage module” are used interchangeably in this document.

What’s new in this release

- Added the `cfgQuickDeploy` group.
- Added the `cfgTrapsSNMPv3UserId` and `cfgTrapsSNMPv3UserName` to the `cfgTraps` group.
- Added the `cfgChassisACPowerRecoveryDisable` command to the `cfgChassisPower` group.
- Added the `cfgRacTuneFipsModeEnable` and `cfgRacTuneTLSProtocolVersionEnable` property to the `cfgRacTuning` group.
- Added the `cfgOobSnmpProtocol` and `cfgOobSnmpTrapFormat` properties to the `cfgOobSnmp` group.

Supported RACADM Interfaces

The RACADM command-line utility provides a scriptable interface that allows you to remotely configure your Chassis Management Controller (CMC). The utility runs on the management station and the managed system. It is available on the *Dell OpenManage Systems Management and Documentation DVD* or at support.dell.com.

The RACADM utility supports the following interfaces:

- SSH or Telnet — Also referred as Firmware RACADM, is accessible by logging in to CMC using SSH or telnet. You do not have to specify the CMC IP, user name or password to run Firmware RACADM commands.
- Remote — Supports executing RACADM commands from a remote management station such as a laptop or desktop. You must install the DRAC Tools utility from the OpenManage software on the remote computer to run Remote RACADM commands. To execute Remote RACADM commands, you must formulate the command such as a an SSH/Telnet RACADM command except that you must also use the `-r -i` options or the `-r -u -p` options. For more information about these options, see the "RACADM Subcommand Details."

RACADM Syntax Usage

The following section describes the syntax usage for SSH/Telnet and Remote RACADM.

SSH or Telnet RACADM

- `racadm getconfig -g <groupname> [-o <objectname>] [-i <indexnumber>]`
- `racadm <subcommand>`

Example

- `racadm getconfig -g idracinfo`
- `racadm getsysinfo`



Remote RACADM

```
racadm -r <racIpAddr> -u <username> -p <password> getconfig -g <groupname> [-o <objectname>] [-i <indexnumber>]
```

```
racadm -r <racIpAddr> -u <username> -p <password> <subcommand>
```

Example

```
racadm -r <racIpAddr> -u myuser -p mypass getconfig -g idracinfo
```

```
racadm -r <racIpAddr> -u myuser -p mypass getsysinfo
```

RACADM Command Options

The following table lists the options for the RACADM command.

Option	Description
-r <racIpAddr>	Specifies the controller's remote IP address.
-u <usrName>	Specifies the user name that is used to authenticate the command transaction. If the -u option is used, the -p option must be used, and the -i option is not allowed.
-p <password>	Specifies the password used to authenticate the command transaction. If the -p option is used, the -i option is not allowed.
-S	Specifies that RACADM should check for invalid certificate errors. RACADM stops the execution of the command with an error message if it detects an invalid certificate.
-i <indexnumber>	Specifies the index number for the indexed group, if applicable.
-g <groupname>	Specifies the group name, if applicable.
-o <objectname>	Specifies the object name, if applicable.

The following table provides the supported RACADM interfaces.

Type	Local RACADM	SSH/Telnet RACADM	Remote RACADM
CMC	No	Yes	Yes

 **NOTE: Multiple instances of remote RACADM can be run on a management station.**

Displayable Characters

Displayable characters include the following set:

```
abcdefghijklmnopqrstuvwxyz
```

```
ABCDEFGHIJKLMNPOQRSTUVWXYZ
```

```
0123456789~`!@#$%^&*()_+=={ } [ ] | \ : " ; ' < > , . ? /
```

Supported RACADM Subcommands

The following table provides the list of RACADM subcommands and their corresponding interface support. For more information about the RACADM sub-commands including syntax and valid entries, see [RACADM Subcommand Details](#).

Subcommand	CMC	
	Telnet/SSH/Serial	Remote RACADM
"?" and "?<subcommand>"	Yes	Yes
chassisaction	Yes	Yes
chassislog	Yes	Yes
closeasn	Yes	Yes
clrsel	Yes	Yes
config	Yes	Yes
connect	Yes	Yes
deploy	Yes	Yes
eventfilters	Yes	Yes
fanoffset	Yes	Yes
feature	Yes	Yes
featurecard	Yes	Yes
fwupdate	Yes	Yes
get	Yes	Yes
getactiveerrors	Yes	Yes
getassettag	Yes	Yes
getchassisname	Yes	Yes
getconfig	Yes	Yes
getdcinfo	Yes	Yes
getflexaddr	Yes	Yes
getioinfo	Yes	Yes
getled	Yes	Yes
getmacaddress	Yes	Yes
getmodinfo	Yes	Yes
getniccfg	Yes	Yes
getpbinfo	Yes	Yes
getpciecfg	Yes	Yes
getpminfo	Yes	Yes
getraclog	Yes	Yes
getractime	Yes	Yes
getsel	Yes	Yes
getsleduplinkstatus	Yes	Yes
getsensorinfo	Yes	Yes
getslotname	Yes	Yes
getssninfo	Yes	Yes



Subcommand	CMC	
getsvctag	Yes	Yes
getsysinfo	Yes	Yes
getversion	Yes	Yes
help and help <subcommand>	Yes	Yes
ifconfig	Yes	Yes
jobqueue	Yes	Yes
krbkeytabupload	No	Yes
license	Yes	Yes
netstat	Yes	Yes
ping	Yes	Yes
ping6	Yes	Yes
racdump	Yes	Yes
racreset	Yes	Yes
racresetcfg	Yes	Yes
remoteimage	Yes	Yes
serveraction	Yes	Yes
set	Yes	Yes
setassettag	Yes	Yes
setflexaddr	Yes	Yes
setled	Yes	Yes
setniccfg	Yes	Yes
setractime	Yes	Yes
setslotname	Yes	Yes
setsysinfo	Yes	Yes
sshpkauth	Yes	Yes
sslkeyupload	No	Yes
sslcertview	Yes	Yes
sslcsrgen	Yes	Yes
sslresetcfg	Yes	Yes
testemail	Yes	Yes
testfeature	Yes	Yes
testtrap	Yes	Yes
tracert	Yes	Yes
tracert6	Yes	Yes

Other Documents You May Need

To access the documents from the Dell Support site. Along with this Reference Guide, you can access the following guides available at dell.com/support/manuals.

- The *CMC FX2/FX2s Online Help* provides information about using the Web interface. To access the Online Help, click **Help** on the CMC web interface.
- The *Chassis Management Controller for PowerEdge FX2/FX2s User's Guide* provides information about using the FX2/FX2s-related Web interface features.
- The *Dell Chassis Management Controller (CMC) for Dell PowerEdge FX2/FX2s Version Release Notes* provides last-minute updates to the system or documentation or advanced technical reference material intended for experienced users or technicians.
- The *Integrated Dell Remote Access Controller 7 (iDRAC7) User's Guide* provides information about installation, configuration, and maintenance of the iDRAC on managed systems.
- The *Dell OpenManage Server Administrator's User's Guide* provides information about installing and using Server Administrator.
- The *Dell Update Packages User's Guide* provides information about obtaining and using Dell Update Packages as part of your system update strategy.
- Dell systems management application documentation provides information about installing and using the systems management software.

The following system documents provide more information about the system in which FX2/FX2s CMC is installed:

- The safety instructions that came with your system provide important safety and regulatory information. For additional regulatory information, see the Regulatory Compliance home page at www.dell.com/regulatory_compliance. Warranty information may be included within this document or as a separate document.
- The setup placemat shipped with your system provides information about the initial system setup and configuration.
- The server module's *Owner's Manual* provides information about the server module's features and describes how to troubleshoot the server module and install or replace the server module's components. This document is available online at dell.com/poweredgemanuals.
- The rack documentation included with your rack solution describes how to install your system into a rack, if required.
- For the full name of an abbreviation or acronym used in this document, see the Glossary at dell.com/support/manuals.
- Systems management software documentation describes the features, requirements, installation, and basic operation of the software.
- Documentation for any components you purchased separately provides information to configure and install these options.
- Any media that ships with your system that provides documentation and tools for configuring and managing your system, including those pertaining to the operating system, system management software, system updates, and system components that you purchased with your system. For more information on the system, scan the Quick Resource Locator (QRL) available on your system and the system setup placemat that shipped with your system. Download the QRL application from your mobile platform to enable the application on your mobile device.

Updates are sometimes included with the system to describe changes to the system, software, and/or documentation. Always read the updates first, because they often supersede information in other documents.



RACADM Subcommand Details

This section provides detailed descriptions about the RACADM subcommands, including the syntax and valid entries.

Guidelines to Quote Strings Containing Special Characters When Using RACADM Commands

When using strings that contain special characters, use the following guidelines:

Strings containing the following special characters must be quoted using double quotation marks:

- \$ (dollar sign)
- " (double quotation mark)
- ` (backward quotation mark)
- \ (backward slash)
- ~ (tilde)
- | (vertical bar)
- ((left parentheses)
-) (right parentheses)
- & (ampersand)
- > (greater than)
- < (less than)
- # (pound)
- ASCII code 32 (space)

 **NOTE: The - (dash) character cannot be the first character of the string, regardless of whether the string is quoted.**

There are different escaping rules for double quotation marks.

There are different escaping rules for using single quotation mark and double quotation marks.

For using double quotation marks:

The following characters must be escaped by prepending a backward slash:

- \$ (dollar sign)
- " (double quotation mark)
- ' (single quotation marks)
- ` (back quotation mark)

For example, use the following for a string that contains the special characters, \$, "", ` and \.

For using single quotation marks:

- No character escaping is necessary.
- A single quotation mark cannot be used even with a backslash escaped.

 **NOTE:** An empty string may be specified as either "" (using double quotation marks) or " (using single quotation mark).

"?"and "?<subcommand>"

Description

Displays all the subcommands you can use with the RACADM command and a one-line description of each subcommand.

? followed by <subcommand> displays the syntax for the specified command.

To use this subcommand, you must have the **CMC Login User** privilege.

You can also use the **help** and **help <subcommand>** commands to obtain the same information.

Synopsis

```
· racadm ?  
· racadm ? <subcommand>
```

Input

NA

Output

NA

Example for RACADM ?

The following output example shows only part of the actual output for the racadm ? command. Descriptions shown in this example may vary slightly from the descriptions in your racadm session.

```
racadm ?  
  
help          -- list racadm subcommand description  
help <subcommand> -- display usage summary for a subcommand  
?            -- list racadm subcommand description  
? <subcommand> -- display usage summary for a subcommand  
arp          -- display the networking arp table  
chassisaction -- execute chassis or switch power-up/down/cycle or  
clrraclog    -- clear the CMC log  
clrsel       -- clear the System Event Log (SEL)  
config       -- modify CMC configuration properties  
...  
setniccfg    -- modify network configuration properties  
settractime  -- set the time on the CMC  
setslotname  -- sets the name of the slot in the chassis  
setsysinfo   -- set the chassis name and chassis location  
sslcertview  -- display a CA/server certificate in the CMC  
sslcsrgen    -- generate a certificate CSR from the CMC  
testemail    -- test CMC e-mail notifications  
testfeature  -- test CMC feature x  
testtrap     -- test CMC SNMP trap notifications  
traceroute   -- determine the route of a packet  
traceroute6  -- determine the route of a packet
```

Example for RACADM ? <subcommand>


```
racadm ? getsysinfo  
  
getsysinfo -- display general CMC and system information  
Usage:  
racadm getsysinfo [-d] [-c] [-A] [-4] [-6]  
-----  
Valid Options:  
-d : show CMC information  
-c : show chassis information  
-A : do not show headers or labels  
-4 : show CMC IPv4 information  
-6 : show CMC IPv6 information
```




help and help <subcommand>

Description	Lists all the subcommands available for use with RACADM and provides a short description for each. You may also type a subcommand, group, object, or FQDD alternate name after help .
Synopsis	<ul style="list-style-type: none">· <code>racadm help</code>· <code>racadm help <subcommand></code>
Input	None
Output	<ul style="list-style-type: none">· The help command displays a complete list of subcommands.· The <code>racadm help <subcommand></code> command displays information for the specified subcommand only.· The <code>racadm help -g <groupname></code> command displays information for the specified group.· The <code>racadm help -o <objectname></code> command displays information for the specified object.· The <code>racadm help <FQDD Alias>.<Group></code> command displays information for the specified group.· The <code>racadm help <FQDD Alias>.<Object></code> command displays information for the specified object.· The <code>racadm help <FQDD Alias>.<Group>.<Object></code> command displays information for the specified object.
Example	<pre>racadm help system.power racadm help system.power.supply</pre>

chassislog

Description	<p>Allows you to view, export, or clear the chassis log history.</p> <p>To clear a chassis log, you must have the Clear Logs Administrator privilege.</p> <p> NOTE: It is recommended that you use Firmware RACADM to run this subcommand.</p>
Synopsis	<pre>racadm chassislog view [-i] racadm chassislog view [-c <category>] [-s <severity>] [-b <subcategory>] [-q <sequence no.>] [-n <number of records>] [-r <start timestamp>] [-e <end timestamp>]</pre>
Input	<ul style="list-style-type: none">· <code>-i</code> — Displays the number of records present in the active log. You cannot use this option with any other option.· <code>-c</code> — The log type to filter the records. Provide multiple categories using a "," as the delimiter. The value is case-insensitive. Valid Category values:<ul style="list-style-type: none">– All– System– Updates– Audit– Config· <code>-b</code> — The subcategory used to filter the records. Provide multiple subcategories using a "," as the delimiter. The value is case-insensitive.· <code>-q</code> — The sequence number from which the records must be displayed.· <code>-n</code> — Specifies the n Number of records to be displayed.

- `-r` — Displays events that have occurred after this time. The time format is yyyy-mm-dd HH:MM:SS. The time stamp must be provided within double quotes.
- `-e` — Displays events that have occurred before this time. The time format is yyyy-mm-dd HH:MM:SS. The time stamp must be provided within double quotes.
- `-s` — The severity used to filter the records. Provide multiple severities using a "," as the delimiter. The value is case-insensitive. Valid Severity values:
 - 1. Warning
 - 2. Critical
 - 3. Info

 **NOTE: To view or export the Chassis log, only CMC Login User permission is required.**

Example

- Display the number of records present in the Chassis Log:
`racadm chassislog view -i`
- Display the records having severities set to warning or critical, starting from sequence number 4:
`racadm chassislog view -s warning,critical -q 4`
- Display 5 records starting from sequence number 20:
`racadm chassislog view -q 20 -n 5`
- Display all records of events that have occurred between 2011-01-02 23:33:40 and 2011-01-03 00:32:15:
`racadm chassislog view -r "2011-01-02 23:33:40" -e "2011-01-03 00:32:15"`
- Display all the available records from the active Chassis log:
`racadm chassislog view -n all`
- Display the last 25 records from the Chassis log:
`racadm chassislog view`

chassislog export

Description

Exports the Chassis log to a remote share.

Synopsis

```
racadm chassislog export -f<filename> -u<username> -p<password> -l<CIFS or NFS share>
racadm -r<cmcip> -u<cmc username> -p<cmc password> chassislog export -f<filename> -u<username> -p<password> -l<CIFS or NFS share>
```

- `racadm chassislog export -f <filename> -u <username> -p <password> -l <CIFS share>`
- `racadm chassislog export -f <filename> -l <NFS share>`
- `racadm -r <cmcip> -u <cmc username> -p <cmc password> chassislog export -f <filename> -u <username> -p <password> -l <CIFS share>`
- `racadm -r <cmcip> -u <cmc username> -p <cmc password> chassislog export -f <filename> -l <NFS share>`

Input

- `-f`: Filename of the exported Chassis Log.
- `-u`: Username for the remote share to where the file must be exported. Username in a domain can be given as domain/username
- `-p`: Password for the remote share to where the file must be exported.
- `-l`: Network share location (see the "Example" section for NFS or CIFS share) to where the Chassis Log must be exported.

Example

- Export the Chassis Log to a remote CIFS share
`racadm chassislog export -f Mylog.xml -u admin -p mypass -l //192.168.0.5/share`



- Export the Chassis Log to a remote NFS share


```
racadm chassislog export -f Mylog.xml -l 192.168.0.5:/home/lclog_user
```

chassislog clear

Description

Deletes the data in the chassis log.

To clear the chassis log, you must have the **Clear Logs Administrator** privilege.

Synopsis

```
racadm chassislog clear
```

```
racadm -r <cmcip> -u <cmc username> -p <cmc password> chassislog clear
```

Example

- Clear the Chassis Log


```
racadm chassislog clear
```
- Clear the Chassis Log using remote racadm


```
racadm -r 192.168.0.1 -u root -p <default root user password> chassislog clear
```



NOTE: The default local account credential is root (user name) and calvin (user password).

chassisaction

Description

Runs a power action on the chassis or a switch.

To use this subcommand, you must have the **Chassis Control Administrator** privilege.

Synopsis

```
racadm chassisaction [-m <module>] <action>
```

Input

- m <module> — Module on which you want to carry out the action. Values are:
 - chassis — this is the default value, if **-m** is not specified.
 - switch-n**, where n=1 to 2
- <action> — Action that you want to run on the specified module. Values are:
 - powerdown — (Chassis only) Turns off the chassis.
 - powerup — (Chassis only) Turns on the chassis.
 - powercycle — Power cycles the module.
 - nongraceshutdown — (Chassis only) Non-gracefully turns off the chassis.
 - reset — Performs a hard reset of the module.

When < module > = switch, < action > must be powercycle or reset.

Output

None

Example

Perform a reset of switch-1:

```
racadm chassisaction -m switch-1 reset
```

```
Module power operation successful.
```

closeesn

Description

Closes a communication session on the device. Use the `getssninfo` command to view a list of sessions that can be closed using this command.

To use this subcommand, you must have the **Administrator** privilege.

Synopsis

- `racadm closeesn -i <session id>`
- `racadm closeesn -a`
- `racadm closeesn -u <username>`

Input

- **-i** *<session id>* — The session ID of the session to be ended, which can be retrieved using RACADM **getssninfo** subcommand.
Session executing this command cannot be ended.
- **-a** — Closes all sessions.
- **-u** *<user name>* — Close all sessions for a particular user name.
 - Remote RACADM: **-u** option or **-i** option

Output

None

Example

- `racadm closeesn -i 1234`
Closes the session 1234.
- `racadm closeesn -u root`
Closes all the sessions for root user.
- `racadm closeesn -a`
Closes all the sessions.

clrsel

Description

Deletes all existing records from the System Event Log (SEL).

To use this subcommand, you must have the **Clear Logs** privilege.

Synopsis

```
racadm clrsel [-m <module>]
```

Input

-m — The *<module>* option can have the following values:

- `server-<n>` where, n = 1 to 4
- `server-<nx>` where n = 1 to 4 and x = a to d (lower case)

 **NOTE: n= 2 and 4 are valid only for multinode sleds.**

Example

- Clear cmc sel log:
`racadm clrsel`
- Clear sel log on server 1:
`racadm clrsel -m server-1`
- Clear sel log on server 2a:
`racadm clrsel -m server-2a`




config

Description


Allows you to set CMC configuration parameters individually or to batch them as part of a configuration file. If the data is different, that CMC object is written with the new value.

Synopsis

- `racadm config [-c|-p] -f <filename>`
- `racadm config -g <group name> -o <object name> [-i <index>] <value>`

 **NOTE: The configuration file retrieved using remote racadm are not interoperable. For the config -f < file name > command, use the configuration file retrieved from the same interface.**

Input

 **NOTE: The -f and -p options are not supported for the serial/Telnet/SSH console.**

- `-f` — The `-f < filename >` option causes config to read the contents of the file specified by `< filename >` and configure CMC.
- `-p` — This option must be used with the `-f` option. It directs **config** to delete the password entries contained in the config file `-f < filename >` after the configuration is complete. To apply the password, you must remove the preceding Read-Only marker '#' in the config file before running the config `-f` command.
- `-g` — The `-g < groupName >`, or **group** option, must be used with the `-o` option. The `< groupName >` specifies the group containing the object that is to be set.
- `-o` — The `-o < objectName > < Value >`, or **object** option, must be used with the `-g` option. This option specifies the object name that is written with the string `< value >`.
- `-i` — The `-i < index >`, or **index** option, is valid only for indexed groups and can be used to specify a unique group. The `< index >` is a decimal integer from 1 through n, where n can vary from 1 to maximum number of indexes a particular group supports. If `-i < index >` is not specified, a value of 1 is assumed for groups, which are tables that have multiple entries. The index is specified by the index value, not a named value.
- `-c` — The `-c` or **check** option, is used with the **config** subcommand and allows the user to parse the `.cfg` file to locate syntax errors. If issues are found, the line number and a short description about the issue is displayed. This option is a check-only.

Output


This subcommand generates error output for any of the following reasons:

- Invalid syntax, group name, object name, index, or other invalid database members.
- RACADM CLI failures.

This subcommand returns an indication of the number of configuration objects that were written out of the total objects in the `.cfg` file.

Examples

- `racadm config -g cfgLanNetworking -o cfgNicIpAddress 192.168.0.1.`
Sets the **cfgNicIpAddress** configuration parameter (object) to the value 192.168.0.1. This IP address object is contained in the **cfgLanNetworking** group.
- `racadm config -f myrac.cfg.`
Configures or reconfigures CMC. The **myrac.cfg** file may be created from the **getconfig** command. This file may also be edited manually as long as the parsing rules are followed.

 **NOTE: The myrac.cfg file does not contain passwords. To include passwords in the file, you must enter them manually. If you want to remove password information from the myrac.cfg file during configuration, use the -p option.**

connect

Description


Connects to the switch or server serial console.

Synopsis


- `racadm connect [-b] -m <module>`
- `racadm connect [-b] <server-n>`
- `racadm connect [-b] <switch-n>`

Input

`-b` — Connects to the switch or console using the binary mode. This is an optional argument; a server or a switch must be present.

 **NOTE: If you use the `-b` option, reset the CMC to terminate the connect operation.**

- `server-<n>`: where `n` = 1 to 4
- `server -<nx>`: where `n` = 1 to 4 and `x` = a to d (lower case)

 **NOTE: The values 2 and 4 for `n` are valid only for multi-node sleds.**

- `switch-n`: where `n` = 1 to 2 or `<a1 | a2>`

Examples

- Connect to I/O Module 1 serial console
`racadm connect -m switch-1`
- Connect to server 1 serial console
`racadm connect -m server-1`

deploy

Table 1. deploy

Description

Deploys blade server or IOM by specifying the required properties.

To use this subcommand, you must have the **Server Administrator** privilege.

 **NOTE: You can also use `setniccfg` to configure static IP address, subnet mask, gateway, DHCP, speed, and duplex properties.**


Synopsis

- `racadm deploy -m <module> -u root -p <password> -s <ipaddress> <subnet> <gateway> -b <device> -o <no|yes>`
- `racadm deploy -m <module> -u root -p <password> -s -6 <ipv6Address> <prefixlen> <gateway> -b <device> -o <no|yes>`
where `<prefixlen>` is a number between 0 and 128.
- `racadm deploy -m <module> -u root -p <password> -d [-6]`
- `racadm deploy -a -u root -p <password>`

Input

- `-b <device>` — Specifies the first boot device; must be used with `-o`.
- Use with `-m <module>` to specify for an individual server, or with `-a` for all servers
Legal values: `device=None, PXE, HDD, CD-DVD, vFDD, vCD-DVD, SD, FDD, RFS`
- `-o <no|yes>` — Indicates if the server should boot from the device once; must be used with `-o`.
Use with `-m <module>` to specify for an individual server, or with `-a` for all servers.
- `-a` — server/switch. Applies options to all modules present in the chassis of the given module type. Specify the value as `server` or `switch`. Default value is `server`. Switches must support Ethernet Management.
- `-u root` — Indicates that the `<password>` is supplied for the root user on the server. `root` is a constant parameter, the only value that is valid with the `-u` option. Required **Username** when you are setting IOA values.



- **-m** < *module* > — Specifies the server you want to configure.
Legal value must be one of the following values:
 - server-*n* where *n*=1–4
 - switch-*n* where *n*=1–2.
 - **-p** < *password* > — Specifies the password for the root user on the server or switch.
Legal values: For switches, valid passwords are 6 - 32 ASCII characters in length, ranging in value 32–125 (decimal). For servers, valid passwords are 1 – 20 ASCII characters in length, ranging in value 32 – 126 (decimal).
 - **-s** <*ipaddress subnet gateway*> — Sets the IP address, subnet mask, and gateway for the specified server, separated by single spaces.
 - ipaddress — A string representing a valid IP address. For example, 192.168.0.20.
 - subnet — A string representing a valid subnet mask. For example, 255.255.255.0.
 - gateway — A string representing a valid gateway address. For example, 192.168.0.1.
 - **-d** — Enables DHCP for the specified server.
The **-s** and **-d** options cannot be used together in the same command.
 - **-6** — Enables IPv6 auto configuration (when used with **-d**.) Sets static IPv6 addresses (when used with **-s**).
 - **-v** — SNMPv2 community string. Valid community strings are 1–20 characters in length, with valid ASCII characters in the range [33–125] (decimal). Protocol version set to SNMPv2. Permission on community string is read-only.
-  **NOTE: This input is available in IOA only.**
- **-q** — Displays or modifies the quick deploy parameters.
 - **-n** — Specifies the number of reserved IP addresses for quick deploy. The valid values are 2 and 4.
 - **-e** — Uses the CMC DNS settings for quick deploy. The legal values are:
 - 1 — Enable
 - 0 — Disable
 - **--qd** — Updates the quick deploy parameters to the servers. This option works only with the **-q** option.

Output

None

Example

- ```
racadm deploy -m server-1 -s 192.168.0.20 255.255.255.0 192.168.0.1
```

  
The server was deployed successfully.  
  
The deploy command generates an error when used on the extension slot of a multi-slot server.
- ```
racadm deploy -m server-2 192.168.0.11 255.255.255.0 192.168.0.1
```


ERROR: Server in slot 9 is an extension of the server in slot 1.
- ```
rracadm deploy -m server-1 -u root -p <default root user password> -s -6 ::/64 :: 10
```

# eventfilters

## Description

Gets, sets, and displays the list of event filter settings.

To use this subcommand with the **get** option, you must have the **CMC Login User** privilege.

## Synopsis

- `racadm eventfilters <eventfilters command type>`
- `racadm eventfilters get -c <alert descriptor>`
- `racadm eventfilters set -c <alert descriptor>-n <notifications>`



**NOTE: The general format of an alert descriptor:**

`cmc.alert.category.[subcategory].[severity]`

**where, category is mandatory, but subcategory and severity are optional. A severity cannot precede a subcategory.**

Valid category values are:

- System
- Config
- Updates
- Audit

Valid severity values are:

- Critical
- Warning
- Informational

Valid examples of alert descriptors are:

- `cmc.alert.all`
- `cmc.alert.audit`
- `cmc.alert.audit.lic`
- `cmc.alert.audit.warning`
- `cmc.alert.audit.lic.critical`

**Input**

- **get** — Displays the list of event filter settings.
- **set** — Configures the actions and notifications for a given event filter configuration.
- **-c** — Alert descriptor of the specific event filter.
- **-n** — The notification to be sent when the event occurs. Valid values are all, snmp, ipmi, email, or none. You can append multiple notifications separated by a comma. You cannot enter the values **all** or **none** with other notifications.



**NOTE: If both event generation interval and notifications are configured and there is an error while configuring the notifications, the event generation interval is not set. The valid values are from 0–365. 0 disables the event generation.**

**Example**

- Display all available event filter configurations:  
`racadm eventfilters get -c cmc.alert.all`
- Display eventfilter configurations for a specific category. For example, audit:  
`racadm eventfilters get -c cmc.alert.audit`
- Display eventfilter configurations for a specific subcategory. For example, licensing under the audit category:  
`racadm eventfilters get -c cmc.alert.audit.lic`
- Display eventfilter configurations for a specific severity. For example, warning under the audit category:  
`racadm eventfilters get -c cmc.alert.audit.warning`
- Display eventfilter configurations for a specific severity and subcategory. For example, a severity of warning in the subcategory licensing under audit category:  
`racadm eventfilters get -c cmc.alert.audit.lic.warning`
- Clear all available alert settings: `racra`  
`racadm eventfilters set -c cmc.alert.all -n none`
- Configure using subcategory as a parameter. For example, all configurations under the licensing subcategory in the audit category are assigned poweroff as action and all notifications are enabled:  
`racadm eventfilters set -c cmc.alert.audit.lic -n all`



- Configure using subcategory and severity as parameters. For example, all Information events under the licensing subcategory in the audit category are assigned poweroff as action and all notifications are disabled:

```
racadm eventfilters set -c cmc.alert.audit.lic.info -n none
```

## fanoffset

### Description

Configures the internal fans to run at a higher speed than the normal speed.

To use this subcommand, you must have the **Chassis Configuration Administrator** privilege.

### Synopsis

```
racadm fanoffset [-s <off|low|medium|high>
```

Valid category values are:

- off
- low
- medium
- high

### Input

**s** — Sets the fan speed.

### Example

- Disable the fanoffset feature.  

```
racadm fanoffset -s off
```
- Increases fan speed by 20% of fan's maximum speed. Minimum speed for fan is 35% of the maximum.  

```
racadm fanoffset -s low
```
- Increases fan speed by 50% of fan's maximum speed. Minimum speed for fan is 65% of the maximum.  

```
racadm fanoffset -s medium
```
- Sets fans to run at 100% of fan's maximum speed.  

```
racadm fanoffset -s high
```

## feature

### Description

Displays all active chassis features. The information displayed includes feature name, date activated, and the serial number of the SD card used to activate the feature.

Dell Feature Cards may contain more than one feature.

 **NOTE: To use this subcommand to deactivate FlexAddress or ExtendedStorage, you must have the Chassis Configuration Administrator privilege. A user with login privileges can view status only.**


 **NOTE: To deactivate FlexAddress features, the chassis must be turned off.**

### Synopsis

- ```
racadm feature -s
```
- ```
racadm feature -d -c <featurename>
```
- ```
racadm feature -r -c ExtendedStorage
```

Input

- **-s** — Displays the status of active features.
- **-d** — Deactivates the feature specified in **-c** option.

 **NOTE: When the FlexAddress and FlexAddressPlus features are active, deactivating one of them results in deactivation of the other feature also. However, ExtendedStorage is not affected by the deactivation of FlexAddress or FlexAddressPlus.**

- `-r` — Repair damaged/unformatted ExtendedStorage media.

 **NOTE: The `-r` switch requires that the ExtendedStorage feature be deactivated.**

 **CAUTION: Using the `-r` switch reformats the SD media in the CMC cardslot. Any existing ExtendedStorage data will be lost.**

- `-c` — `<featurename>` must be one of the following:
- `flexaddress` (with `-d`)
- `flexaddressplus` (with `-d`) `ExtendedStorage` (with `-d` or `-r`)

featurecard

Description

Verifies proper SD card installation and displays the SD card status.

To use this subcommand, you must have the **Chassis Configuration Administrator** privilege.

Synopsis

```
racadm featurecard -s
```

Input

-s — Lists active SD card features and SD card status.

Output

An example of output is given here.

```
racadm featurecard -s
```

```
CMC: The feature card inserted is valid, serial number =  
CN0H871T137401112222A00 The feature card contains the following  
feature(s):  
FlexAddress: bound  
FlexAddressPlus: bound  
ExtendedStorage: bound
```


fwupdate

Description

Allows you to update the CMC firmware, chassis infrastructure firmware. You can:

- Check the firmware update process status.
- Update the firmware from an FTP or a TFTP server by providing an IP address and optional path.
- Update the firmware from the local file system using remote RACADM.
- The subcommand updates one or more devices of a single type at a time.

To use this subcommand, you must have the **Chassis Configuration Administrator** privilege.

 **NOTE: Running the subcommand to update the CMC firmware resets the CMC, causing all network connections to get logged off.**

 **NOTE: The subcommand generates an error, when used on the extension slot of a multi-slot server.**

The CMC firmware performs a signature verification step to ensure the authenticity of the uploaded firmware. The firmware update process is successful only if CMC authenticates the firmware image from the service provider as valid image. The firmware update process is

stopped, if CMC cannot verify the signature of the uploaded firmware image. A warning event is then logged and an appropriate error message is displayed.

 **NOTE: Run the firmware update command through only one remote racadm session at a time.**


Synopsis


- Using Remote RACADM:


```
racadm fwupdate -p -u -d <firmware image>
```

 **NOTE: iDRAC7 targets are not supported from CMC. Use the CMC GUI to update iDRAC7 targets from CMC.**

When using FTP, if you provide the full path to the image file on the CLI, then the CMC uses that path to locate that file on the host. If you do not provide a full path, then the CMC searches the home directory of the specified user for the file if the host system is running Linux or another variant of UNIX. If the host system is running Windows, then a default folder, such as **C:\ftproot** is searched.

 **NOTE: While performing firmware update using the racadm fwupdate command, if the number of characters in the firmware image path is greater than 256 characters, Remote RACADM session logs off with the error message ERROR: Specified path is too long.**

 **NOTE: While performing firmware CMC firmware upgrade if the uploaded firmware image file does not contain a verification signature or it contains a verification signature, which is not valid or corrupted, the following message is displayed:**
Invalid firmware: The firmware image validation was unsuccessful

 **NOTE: While performing CMC firmware downgrade, if the current CMC firmware does not recognize the computed signature of the earlier version, the following message is displayed:**

Firmware downgrade is unsuccessful: a downgrade to this firmware version is not supported

- ```
racadm fwupdate -g -u -a 192.168.0.100 -d fx2_cmc.bin -m cmc-active
```


## Input

 **NOTE: Firmware update from local RACADM (using the -p, -u, or -d options) is not supported on Linux operating system.**

- p** — The **-p** option is used to update the firmware file from the client. The **-u** option must be used with the **-p** option.
- f** — The FTP is used to download the firmware.
- g** — For CMC, the firmware is downloaded using the TFTP server.
- u** — The firmware update operation is performed.
- a** — Specifies the TFTP server IP address or FQDN used for the firmware image (used with **-g**).

 **NOTE: CMC accepts IPv4, IPv6, or fully qualified domain names (FQDN) for both FTP and TFTP servers.**

- d** — Specifies the source path where the firmware image is stored.



 **NOTE: The default source path is local Default: Designated TFTP default directory on that host for the file if -g option is absent. If -g is used, it defaults to a directory configured on the TFTP server.**

- o** — Turns off the servers to perform an update.
- m <module >** —

Specifies the module or device to be updated. *<module >* is one of the following values:

 **NOTE: You can also specify multiple modules: -m <module 1> -m <module 2>, and so on.**


- m cmc**

- iominf-n, where n = 1
- main-board
- hdd-fqdd, where fqdd is FQDD of the HDD
- -s — Displays the current status of the firmware update.
  -  **NOTE: Use -m to display the status of the module update. Omit -m to display the status of the CMC update.**
  -  **NOTE: Use all to get the status of all the targets that must be updated.**
- -c — Cancels the current firmware update of a module.

**Output**

Displays a message indicating the operation that is being performed.

**Example**

-  **NOTE: The following commands apply to CMC update.**
- Upload a firmware image from the client and start firmware update:
 

```
racadm fwupdate -p -u -d fx2_cmc.bin
```
- Upload the firmware image from the TFTP server and start the firmware update:
 

```
racadm fwupdate -g -u -a 192.168.0.100 -d fx2_cmc.bin -m cmc-active
```

TFTP firmwareate has been initiated. This update process may take several minutes to complete.
- Upload the firmware image from the FTP server and start the firmware update.
 

```
racadm fwupdate -f 192.168.0.100 root <default root password> -d fx2_cmc.bin -m
```
- Start IOM infrastructure firmware update.
 

```
racadm fwupdate -u -m iominf-1
```
- View the current firmware update status of all firmware targets:
 

```
racadm fwupdate -s -m all
```
- View the current firmware update status of a particular module:
 

```
racadm fwupdate -s -m cmc-active
```
- Cancel a firmware update in progress:
 

```
racadm fwupdate -c
```
- Signed CMC Firmware Image:
 

```
racadm fwupdate -g -u -a <TFTP IP> -d <Firmware Path> -m
```

Firmware update has been initiated. This update process may take several minutes to complete.

```
racadm fwupdate -s -m cmc-active
```

Invalid firmware: The uploaded firmware image does not contain A verification signature.

The following table describes the firmware update methods supported for each interface.

| FW Update Method  | CMC |
|-------------------|-----|
| Local RACADM      | No  |
| Local RACADM—TFTP | No  |
| Local RACADM—FTP  | No  |




| FW Update Method     | CMC |
|----------------------|-----|
| Remote RACADM        | Yes |
| Remote RACADM—TFTP   | Yes |
| Remote RACADM—FTP    | Yes |
| Firmware RACADM—TFTP | Yes |
| Firmware RACADM—FTP  | Yes |

## get

### Description

Saves CMC configuration properties or CMC Event Filter configurations to a file.

 **NOTE: If CMC is not in the network, you cannot export the chassis configuration profile to a remote network share with proxy using the `get` command. But, you can export the chassis configuration profile to the local management station.**

### Synopsis

```
racadm get -f <filename>
racadm -r <CMC IP> -u <username> -p <password> get -f <filename>
racadm -r <CMC IP> -u <username> -p <password> get -f <filename> -t
xml
racadm get -f <filename> -t xml -u <username> -p <password> -l
<CIFS share>
racadm get -f <filename> -t xml -l <NFS share>
```

### Input

- `-f`: save event filter configurations to a file.
- `-u`: username of the remote share where the file must be exported.
- `-p`: password for the remote share where the file must be exported.
- `-l`: network share location where the file must be exported.
- `-t`: specify the file type that has to be exported. Valid value is "XML".
- `--clone`: export the cloned configuration file. Only the XML file format is supported. The configuration file can be exported to a local or remote share.
- `--replace`: export the replaced configuration file. Only XML file format is supported. The configuration file can be exported to a local or remote share.
- `--includeph`: include password hash attributes

### Example

- Export event filter configurations to a file by using remote `racadm`.  

```
racadm -r 192.168.0.120 -u abc -p <password> get -f file.txt
```
- Export the CMC XML configuration to a local share using remote `racadm`  

```
racadm -r 192.168.0.120 -u abc -p <password> get -f file.xml -t
xml
```
- Export the CMC XML configuration to a CIFS share  

```
racadm get -f file.xml -t xml -u myuser -p mypass -l //
192.168.0.0/share
```
- Export the CMC XML configuration to an NFS share  

```
racadm get -f file.xml -t xml -l 192.168.0.0:/myshare
```

## getactiveerrors

|                    |                                                                                                                                                                                                                                                           |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b> | Displays the active errors in a chassis.<br><br>To run this subcommand, you must have the <b>CMC Login User</b> privilege.                                                                                                                                |
| <b>Synopsis</b>    | <code>racadm getactiveerrors [-s &lt;severity&gt; ] [-m &lt;module&gt;]</code>                                                                                                                                                                            |
| <b>Input</b>       | valid values for <severity>: critical, warning, info<br><br>valid values for <module>: server-n, where n = 1 to 4<br><br>switch-n, where n = 1 to 2<br><br>cmc-n, where n = 1<br><br>fan-n, where n = 1 to 8<br><br>ps-n, where n = 1 or 2<br><br>chassis |
| <b>Output</b>      | Display entire log:<br><br><code>racadm getactiveerrors</code><br><br>- Display specific module log:<br><br><code>racadm getactiveerrors -m server-1</code><br><br>- Display entire informational log:<br><br><code>racadm getactiveerrors -s info</code> |

## getassettag

|                    |                                                                                                                                                        |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b> | Displays the asset tag for the chassis.<br><br>To use this subcommand, you must have the <b>CMC Login User</b> privilege.                              |
| <b>Synopsis</b>    | <code>racadm getassettag [-m &lt;module&gt;]</code>                                                                                                    |
| <b>Input</b>       | <b>-m &lt; module &gt;</b> — Specifies the module whose asset tag you want to view.<br><br>Legal value: chassis                                        |
| <b>Example</b>     | <ul style="list-style-type: none"><li><code>racadm getassettag -m chassis</code></li><li><code>racadm getassettag chassis 78373839-33</code></li></ul> |

## getchassisname

|                    |                                   |
|--------------------|-----------------------------------|
| <b>Description</b> | Displays the name of the chassis. |
|--------------------|-----------------------------------|



To use this subcommand, you must have the **CMC Login User** privilege.

**Synopsis**

```
racadm getchassisname
```

**Example**

```
racadm getchassisname
CMC-1
```

## getconfig

**Description**

Retrieves CMC configuration parameters individually, or all CMC configuration groups may be retrieved and saved to a file.

**Synopsis**

- `racadm getconfig -f <filename>`
- `racadm getconfig -g <groupName> [-i <index>]`
- `racadm getconfig -u <username>`
- `racadm getconfig -h`
- `racadm getconfig -g <groupName> -o <objectName> [-i index]`

**Input**

- **-f** — The **-f <filename>** option directs getconfig to write the entire CMC configuration to a configuration file. This file can be used for batch configuration operations using the **config** subcommand.
- **-g** — The **-g <groupName>**, or **group** option, can be used to display the configuration for a single group. The **groupName** is the name for the group used in the **racadm.cfg** files. If the group is an indexed group, use the **-i** option.
- **-h** — The **-h**, or **help** option, displays a list of all available configuration groups in alphabetical order. This option is useful when you do not have exact group names.
- **-i** — The **-i <index>**, or **index** option, is valid only for indexed groups and can be used to specify a unique group. The **<index>** is a decimal integer from 1 through n, where n can vary from 1 to maximum number of indexes a particular group supports. If **-i <index>** is not specified, a value of 1 is assumed for groups, which are tables that have multiple entries. The index is specified by the index value, not a *named* value.
- **-m** — Indicates the module on which you want to carry out the action. The **-m <module>** displays the following information for a particular server, group of servers, individual storage, or storage groups:
  - session
  - WEB/SSH/Telnet
  - remote system log
  - storage mode
  - service tag
  - asset tag

The **<module>** must have one of the following values:

- `server-<n>` — where n = 1 to 4
- `server-<nx>` — where n = 1 to 4 and x = a to d (lower case). The n = 2 and 4 are valid for multi-node sleds only.
- `storage-<n>` — where n = 1 to 4

 **NOTE: The -m option is available only for `cfgRemoteHosts`, `cfgRacTuning`, `cfgSerial`, `cfgSessionManagement`, `cfgLanNetworking`, and `cfgIPv6LanNetworking` commands.**

- **-o** — The **-o <objectname>** or **object** option specifies the object name that is used in the query. This option is optional and can be used with the **-g** option.
- **-u** — The **-u <username>**, or **user name** option, can be used to display the configuration for the specified user. The **<username>** option is the login name for the user.
- **-v** — The **-v** option displays additional details with the display of the properties and is used with the **-g** option.



## Output

This subcommand generates error output upon encountering either of the following:

- Invalid syntax, group name, object name, index, or other invalid database members
- RACADM CLI transport failures

If errors are not encountered, this subcommand displays the contents of the specified configuration.

## Example

- Displays all of the configuration properties (objects) that are contained in the group **cfgLanNetworking**.

```
racadm getconfig -g cfgLanNetworking
```

- Saves all group configuration objects from CMC to **myrac.cfg**.

```
racadm getconfig -f myrac.cfg
```

If you do not configure the following key attributes in their respective groups for a particular index, the groups are not saved in to the file. This is applicable for all the index groups.

| Group             | Key Attribute           |
|-------------------|-------------------------|
| cfgEmailAlert     | cfgEmailAlertAddress    |
| cfgLDAPRoleGroup  | cfgLDAPRoleGroupDN      |
| cfgServerInfo     | cfgServerBmcMacAddress  |
| cfgStandardSchema | cfgSSADRoleGroupName    |
| cfgTraps          | cfgTrapsAlertDestIPAddr |
| cfgUserAdmin      | cfgUserAdminUserName    |

- Displays a list of the available configuration groups on CMC in an alphabetical order.

```
racadm getconfig -h
```

- Displays the configuration properties for the user named **root**.

```
racadm getconfig -u root
```

- Displays the user group instance at index 2 with verbose information for the property values.

```
racadm getconfig -g cfgUserAdmin -i 2 -v
```

- Displays the storage sled information.


```
racadm getconfig -g cfgStoragemodule -m storage-3
```

## getdcinfo

### Description

Displays general I/O module and daughter card configuration information. Only the CMC controls daughtercards.

To use this subcommand, you must have the **CMC Login User** privilege.

 **NOTE: Fabric verification for server DCs is performed only when the chassis is turned on. When the chassis is on stand-by power, iDRACs on the server modules remain turned off and thus are unable to report the server's DC fabric type. The DC fabric type may not be reported in the CMC user interface until iDRAC on the server is turned on.**

### Synopsis

```
racadm getdcinfo
```

### Input

**-n** — Displays the model names for the daughter cards in servers.



## Example

The following example is for a system with multi-slot servers.

```
racadm getdcinfo
```

```
Group A I/O Type : Gigabit Ethernet
```

```
Group B I/O Type : PCIe
```

```
Group C I/O Type : PCIe
```

| <IO#>    | <Type>           | <State> | <Role> |
|----------|------------------|---------|--------|
| switch-1 | Gigabit Ethernet | OK      | Master |

| <Server#> | <Presence>  | <DC1 Type> | <DC1 State> | <DC2 Type> | <DC2 State> |
|-----------|-------------|------------|-------------|------------|-------------|
| server-1  | Present     | PCIe       | OK          | PCIe       | OK          |
| server-2  | Not Present | None       | N/A         | None       | N/A         |
| server-3  | Present     | PCIe       | OK          | None       | N/A         |
| server-4  | Not Present | None       | N/A         | None       | N/A         |

```
getdcinfo -n
```

| <Server#> | <Presence>  | <DC1 Model Name> | <DC2 Model Name> |
|-----------|-------------|------------------|------------------|
| server-1  | Present     | None             | None             |
| server-2  | Not Present | None             | None             |
| server-3  | Not Present | None             | None             |
| server-4  | Present     | None             | Broadcom M5708t  |

## getsleduplinkstatus

**Description** Displays multi-node sled network switch uplink status.

**Synopsis** racadm getsleduplinkstatus

**Examples**

```
racadm getsleduplinkstatus
```

Sled No : 2

|                |        |
|----------------|--------|
| Port No        | = 3    |
| A1 Link Status | = Up   |
| A2 Link Status | = Down |

Port No = 4

|                |      |
|----------------|------|
| A1 Link Status | = Up |
| A2 Link Status | = Up |

Sled No : 3

|                |        |
|----------------|--------|
| Port No        | = 5    |
| A1 Link Status | = Up   |
| A2 Link Status | = Down |

Port No = 4

```
A1 Link Status = Up
A2 Link Status = Up
```

## getflexaddr


### Description

Displays enabled or disabled status for the entire chassis. If used with `-i`, the command displays MACs/WWN on a per-slot-basis.

The decoder values in the **Type** column indicate the protocols of the network cards:

- **0**— Unsupported
- **1**— iSCSI
- **2**— FCoE-FIP
- **3**— iSCSI/FCoE-FIP

To use this subcommand, you must have **CMC Login User** privilege.

 **NOTE: If FlexAddress is not activated on the chassis, the command displays server-assigned MAC/WWN addresses. If the slot is empty, the command leaves the server-assigned MAC/WWN addresses blank. If an external console controls the MAC/WWN addresses, the command displays an externally managed message.**

### Synopsis

```
racadm getflexaddr [-i <slotNum>]
```

### Input

`-i <slotNum >` — Specifies the slot information to be displayed. `<slotNum >` must be from 1 to 4.

### Example

Display current FlexAddress settings for all the slots and fabrics.

```
racadm getflexaddr
```

| <code>&lt;Slot#&gt;</code> | <code>&lt;Status&gt;</code> | <code>&lt;Server Presence&gt;</code> |
|----------------------------|-----------------------------|--------------------------------------|
| 1a                         | Enabled                     | Present                              |
| 1b                         | Enabled                     | Present                              |
| 1c                         | Enabled                     | Present                              |
| 1d                         | Enabled                     | Not Present                          |
| 2                          | Enabled                     | Present                              |
| 3a                         | Disabled                    | Present                              |
| 3b                         | Disabled                    | Present                              |
| 3c                         | Disabled                    | Present                              |
| 3d                         | Disabled                    | Present                              |
| 4                          | Disabled                    | Present                              |

```
idrac System Disabled
```

Display the current FlexAddress setting for slot 1.

```
racadm getflexaddr -i 1
```



Slot-1 server presence = Present

Slot-1 flexaddress enabled = 1

| <Fabric>         | <Type>          | <Server-Assigned>        | <Chassis-Assigned>               |
|------------------|-----------------|--------------------------|----------------------------------|
| slot1a<br>-idrac | Controller      | 18:A9:9B:FD:C3:FF        | F0:1F:AF:88:21:A0 (active)       |
| slot1-<br>A1     | 10 GbE<br>KR    | 00:90:FA:51:31:E2        | F0:1F:AF:88:21:A1 (active)       |
|                  | 10 GbE KR/<br>3 | 00:90:FA:<br>51:31:E3    | F0:1F:AF:88:21:A3 (active)       |
|                  | FCoE-<br>WWN    | 10:00:00:90:FA:51:31:E3) | 20:01:F0:1F:AF:88:21:A3 (active) |
|                  | 10 GbE KR/<br>3 | 00:90:FA:<br>51:31:E5    | F0:1F:AF:88:22:75 (active)       |
|                  | FCoE-<br>WWN    | 10:00:00:90:FA:51:31:E5  | 20:01:F0:1F:AF:88:22:75 (active) |
|                  | 10 GbE<br>KR    | 00:90:FA:<br>51:31:E5    | 20:01:F0:1F:AF:88:22:73 (active) |
|                  | 10 GbE KR/<br>3 | 00:90:FA:<br>51:31:E5    | F0:1F:AF:88:22:75 (active)       |
|                  | FCoE-<br>WWN    | 10:00:00:90:FA:51:31:E5  | 20:01:F0:1F:AF:88:22:75 (active) |
|                  | 10 GbE<br>KR    | 10:00:00:90:FA:51:31:E5  | 20:01:F0:1F:AF:88:22:75 (active) |
|                  | 10 GbE<br>KR    | 00:90:FA:<br>51:31:E7    | F0:1F:AF:88:22:77 (active)       |
|                  | 10 GbE<br>KR    | 00:90:FA:<br>51:31:E7    | F0:1F:AF:88:22:7B (active)       |
|                  | 10 GbE<br>KR    | 00:90:FA:<br>51:31:E9    | F0:1F:AF:88:22:7D (active)       |
| slot1-<br>A2     | 10 GbE<br>KR    | 00:90:FA:<br>51:31:EA    | F0:1F:AF:88:21:A2 (active)       |
|                  | 10 GbE<br>KR    | 00:90:FA:51:31:EB        | F0:1F:AF:88:21:A4 (active)       |
|                  | 10 GbE KR/<br>3 | 00:90:FA:51:31:EB        | F0:1F:AF:88:21:A4 (active)       |
|                  | FCoE-<br>WWN    | 10:00:00:90:FA:51:31:EB  | 20:01:F0:1F:AF:88:21:A4 (active) |
|                  | 10 GbE KR/<br>3 | 00:90:FA:51:31:EC        | F0:1F:AF:88:22:74 (active)       |



|                 |                         |                                  |
|-----------------|-------------------------|----------------------------------|
| 10 GbE KR/<br>3 | 00:90:FA:51:31:EC       | F0:1F:AF:88:22:74 (active)       |
| FCoE-<br>WWN    | 10:00:00:90:FA:51:31:EC | 20:01:F0:1F:AF:88:22:74 (active) |
| 10 GbE KR/<br>3 | 10:00:00:90:FA:51:31:EC | 20:01:F0:1F:AF:88:22:74 (active) |
| 10 GbE KR/<br>3 | 00:90:FA:51:31:ED       | F0:1F:AF:88:22:76 (active)       |
| FCoE-<br>WWN    | 10:00:00:90:FA:51:31:ED | 20:01:F0:1F:AF:88:22:76 (active) |
| 10 GbE<br>KR    | 00:90:FA:51:31:EE       | F0:1F:AF:88:22:78 (active)       |
| 10 GbE<br>KR    | 00:90:FA:51:31:EF       | F0:1F:AF:88:22:7A (active)       |
| 10 GbE<br>KR    | 00:90:FA:<br>51:31:EF   | F0:1F:AF:88:22:7A (active)       |
| 10 GbE<br>KR    | 00:90:FA:51:31:F0)      | F0:1F:AF:88:22:7C (active)       |
| 10 GbE<br>KR    | 00:90:FA:<br>51:31:F1   | F0:1F:AF:88:22:7E (active)       |

 **NOTE: 10 GbE KR/3 — The value 3 indicates the protocol type.**

## getioinfo

### Description

Displays general information about the stack and I/O modules on the chassis.

To use this subcommand, you must have the **CMC Login User** privilege.

 **NOTE: The fabric type may be any supported I/O fabric type, such as Ethernet, Fiber Channel, and Infiniband.**

### Synopsis

```
racadm getioinfo [-m <module>] [-s]
```

### Input

- -m — Specifies the module or device. The <module> must be switch — <n>, where n = 1-2
- -s — Displays the stack information.

### Example

```
• racadm getioinfo
```

| <IO>     | <Name> | <Type>        | <Presence>  | <POST> | <Power> | <Role> | <Secure Mode> | <Mode> |
|----------|--------|---------------|-------------|--------|---------|--------|---------------|--------|
| switch-1 | N/A    | None          | Not Present | N/A    | N/A     | N/A    | No            | N/A    |
| switch-2 | PE     | 10 Gigabit KR | Present     | OK     | ON      | Master | No            | N/A    |

```
• racadm getioinfo -m switch-1
```



| <IO>     | <Name>                   | <Type>           | <Presence> | <POST> | <Power> | <Role> | <SecureMode> | <Mode> |
|----------|--------------------------|------------------|------------|--------|---------|--------|--------------|--------|
| Switch-1 | 1GBE PASS-THROUGH MODULE | Gigabit Ethernet | Present    | OK     | ON      | Master | No           | N/A    |

## getled

### Description

Displays the LED settings on a module: blinking, not blinking, or unknown (for empty slots).

To use this subcommand, you must have the **Login User** privilege.

### Synopsis

```
racadm getled -m <module>
```

### Input

CMC only options:

-m <module> — Specifies the module whose LED settings you want to view.

<module> can be one of the following:

- server-n where n=1 or 4
- switch-n where n=1 or 2
- chassis
- CMC active

### Example

For CMC:

- racadm getled -m server-4  
   <module> <LED state> server-4 Blinking
- racadm getled -m chassis  
   <module> <LED state> server-4 Not blinking
- racadm getled -m server-1  
   <module> <LED state> server-1 ON
- racadm getled -m server-1  
   <module> <LED state> server-1 Extension(1)

## getmacaddress

### Description

Displays the MAC/WWN addresses for all modules or for a specified module.

The decoder values in the **Type** column indicate the protocols of the network cards.

- **0**— Unsupported
- **1**— iSCSI
- **2**— FCoE-FIP
- **3**— iSCSI/FCoE-FIP

To use this subcommand, you must have the **CMC Login User** privilege.

### Synopsis

- racadm getmacaddress
- racadm getmacaddress -m chassis
- racadm getmacaddress -m switch-<n>
- racadm getmacaddress [-m <module>] [-t iscsi] [-x]
- racadm getmacaddress [-a]

- `racadm getmacaddress -c IO-Identity`
- `racadm getmacaddress -c Flexaddress`
- `racadm getmacaddress -c Factory`
- `racadm getmacaddress -c all`

## Input

- **-m** *< module >* — Specifies the module whose MAC address you want to view. *< module >* may be one of the following:
  - `server-n` , where  $n=1-4$
  - `switch-n` , where  $n=1-2$
- **-t** — Displays the iSCSI MAC addresses for all servers or the specified server if used with `-m` option.
- **-x** — Displays the extra MACs (Ethernet or iSCSI) for servers with additional LOM MACs and must be used with `-m` option.
- **-a** — Displays the Ethernet and iSCSI MAC/WWN addresses for all iDRAC/LOMs/mezzanine cards. When FlexAddress is enabled for a particular slot, then the chassis-assigned MAC/WWN address is displayed.
- **-c** — Displays the Ethernet, iSCSI, MAC/WWN, assignment type, and partition status of all LOMs or mezzanine cards. Valid values for `-c` option are:
  - **IO-Identity** — Displays the user-defined MAC/WWN addresses.
  - **FlexAddress** — Displays the chassis assigned WWN/MAC addresses.
  - **Factory** — Displays the MAC/WWN addresses for all LOMs or mezzanine cards.
  - **all** — Displays the console assigned MAC/WWN of all LOMs or mezzanine cards.

## Example

- Displays the NDC or LOM MAC address.  
`racadm getmacaddress`
- Display iSCSI MAC addresses for all servers.  
`racadm getmacaddress -t iscsi`
- Display iSCSI MAC for server-1.  
`racadm getmacaddress -m server-1 -t iscsi`
- Display extra iSCSI MACs for server-1 (if available).  
`racadm getmacaddress -m server-1 -t iscsi -x`
- Displays the user-defined MAC and WWN address.
  - `racadm getmacaddress -c io-identity`
  - `racadm getmacaddress -c io-identity -m server -2`
- Displays the console assigned MAC/WWN of all LOMs or mezzanine cards.  
`racadm getmacaddress -c all`
- Displays the chassis assigned WWN/MAC address.  
`racadm getmacaddress -c flexaddress`
- Displays the MAC/WWN addresses for all LOMs or mezzanine cards.  
`racadm getmacaddress -c factory`

Displays the MAC address for chassis.

`racadm getmacaddress -m chassis`



| <Name> | <Presence> | <BMC MAC Address> | <NIC1 MAC Address> | <NIC2 MAC Address> |
|--------|------------|-------------------|--------------------|--------------------|
| CMC    | Present    | N/A               | 74:86:7A:D5:33:44  | N/A                |

Displays the MAC address for switch -1

```
racadm getmacaddress -m switch-1
```

| <Name>   | <Presence> | <BMC MAC Address> | <NIC1 MAC Address> | <NIC2 MAC Address> |
|----------|------------|-------------------|--------------------|--------------------|
| Switch-1 | Present    | Not Installed     | 00:00:00:00:00:00  | Not Installed      |

Displays the MAC address for switch -1

```
racadm getmacaddress -m server-1
```

| <Name>    | <Presence>  | <BMC MAC Address> | <NIC1 MAC Address> | <NIC2 MAC Address> |
|-----------|-------------|-------------------|--------------------|--------------------|
| Server-1a | Present     | F8:DB:88:3E:01:80 | F8:DB:88:3E:01:81  | F8:DB:88:3E:01:84  |
| Server-1b | Present     | F8:DB:88:3E:02:50 | F8:DB:88:3E:02:6F  | F8:DB:88:3E:02:72  |
| Server-1c | Present     | F8:DB:88:3E:08:09 | F8:DB:88:3E:01:E9  | F8:DB:88:3E:01:EC  |
| Server-1b | Not Present | Not Installed     | Not Installed      | Not Installed      |

Display extra MACs for server-1 (if available).

```
racadm getmacaddress -m server-1 -x
```

| <Name>   | <Presence> | <BMC MAC Address> | <NIC1 MAC Address> | <NIC2 MAC Address> |
|----------|------------|-------------------|--------------------|--------------------|
| server-1 | Present    | 00:11:43:FD:B7:2A | 00:11:43:FD:B7:2A  | 00:11:43:FD:B7:2B  |
|          |            |                   | 00:11:43:FD:B7:2C  | 00:11:43:FD:B7:2D  |

Displays the MAC address.

```
racadm getmacaddress
```

| <Name>     | <Type>           | <Presence>  | <BMC MAC Address> | <NIC1 MAC Address> | <NIC2 MAC Address> |
|------------|------------------|-------------|-------------------|--------------------|--------------------|
| CMC        | N/A              | Present     | N/A               | 74:86:7A:D5:33:44  | N/A                |
| Server-1-A | Gigabit Ethernet | Present     | 74:86:7A:D6:CF:22 | Not Installed      | Not Installed      |
| Server-2   | Not Installed    | Not Present | Not Installed     | Not Installed      | Not Installed      |
| Server-3-A | 10 GbE KR iSCSI  | Present     | 74:86:7A:D6:D0:38 | E0:DB:55:25:65:9C  | E0:DB:55:25:65:9E  |
|            | FCoE-FIP         | Present     |                   | E0:DB:55:25:65:9D  | E0:DB:55:25:65:9E  |
|            | FCoE-WWN         | Present     |                   |                    |                    |
|            | 10 GbE KR        | Present     |                   |                    |                    |



|          |                  |             |               |                                                                               |                                                                               |
|----------|------------------|-------------|---------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
|          |                  |             |               | E0:DB:<br>55:25:65:9D<br>20:01:E0:DB:<br>55:25:65:9D<br>E0:DB:<br>55:25:65:A0 | E0:DB:<br>55:25:65:9F<br>20:01:E0:DB:<br>55:25:65:9F<br>E0:DB:<br>55:25:65:A2 |
| Server-4 | Not Installed    | Not Present | Not Installed | Not Installed                                                                 | Not Installed                                                                 |
| Switch-1 | Gigabit Ethernet | Present     | Not Installed | 00:00:00:00:00:00                                                             | Not Installed                                                                 |

Displays Ethernet and iSCSI MAC address of all LOMs or mezzanine cards.

racadm getmacaddress

| <Name>   | <Presence>  | <BMC MAC Address> | <NIC1 MAC Address> | <NIC2 MAC Address> |
|----------|-------------|-------------------|--------------------|--------------------|
| CMC      | Present     | N/A               | 00:1E:4F:1F:3C:58  | N/A                |
| Server-1 | Present     | 00:1E:4F:2A:AF:7B | 00:1E:4F:2A:D3:97  | 00:1E:4F:2A:D3:99  |
| Server-2 | Present     | 00:22:19:D2:1E:84 | N/A                | N/A                |
| Server-3 | Not Present | N/A               | N/A                | N/A                |
| Server-4 | Present     | 00:18:8B:FF:45:2A | 00:18:8B:FF:AA:02  | 00:18:8B:FF:AA:04  |
| Switch-1 | Present     | N/A               | 00:00:00:00:00:00  | N/A                |

Displays the user-defined MAC and WWN address.

racadm getmacaddress -c IO-Identity

| <Name>     | <Type>           | <Presence> | <Active WWN/MAC>> | <Partition Status>> | <Assignment Type>> |
|------------|------------------|------------|-------------------|---------------------|--------------------|
| server-1-A | IDRAC-Controller | Present    | 18:A9:9B:FD:C4:DF | N/A                 | Factory            |
|            | Gigabit Ethernet | Present    | 00:0A:00:0A:00:00 | Unknown             | IO-Identity        |
|            | Gigabit Ethernet | Present    | 00:0A:00:0A:00:01 | Unknown             | IO-Identity        |
|            | Gigabit Ethernet | Present    | 00:0A:00:0A:00:02 | Unknown             | IO-Identity        |
|            | Gigabit Ethernet | Present    | 00:0A:00:0A:00:03 | Unknown             | IO-Identity        |

Displays the MAC/WWN addresses for all LOMs or mezzanine cards.

racadm getmacaddress -c factory



| <Name>     | <Type>               | <Presence> | <Active WWN/<br>MAC>> | <Partition<br>Status>> | <Assignment<br>Type>> |
|------------|----------------------|------------|-----------------------|------------------------|-----------------------|
| Server-3-A | IDRAC-<br>Controller | Present    | 5C:F9:DD:D6:1C:<br>CE | N/A                    | Factory               |
|            | Gigabit<br>Ethernet  | Present    | 84:8F:<br>69:FC:E8:F0 | Unknown                | IO-Identity           |
|            | Gigabit<br>Ethernet  | Present    | 84:8F:<br>69:FC:E8:F1 | Unknown                | IO-Identity           |
| Switch-1   | 10 GbE KR            | Present    | F8:B1:56:45:DD:<br>BD | N/A                    | Factory               |

Displays the chassis assigned WWN/MAC address.

```
racadm getmacaddress -c flexaddress
```

| <Name>     | <Type>               | <Presence> | <Active WWN/<br>MAC>> | <Partition<br>Status>> | <Assignment<br>Type>> |
|------------|----------------------|------------|-----------------------|------------------------|-----------------------|
| Server-4-A | IDRAC-<br>Controller | Present    | F8:DB:88:3D:<br>9F:A7 | N/A                    | FlexAddress           |
|            | 10 GbE KR            | Present    | F8:DB:88:3D:<br>9F:A9 | Disabled               | FlexAddress           |
|            | 10 GbE KR/3          | Present    | F8:DB:<br>88:3D:A2:78 | Unknown                | FlexAddress           |
|            | 10 GbE KR/3          | Present    | F8:DB:<br>88:3D:A2:7B | N/A                    | FlexAddress           |

 **NOTE: 10 GbE KR/3— The value 3 indicates the protocol type.**

Displays the console assigned MAC/WWN of all LOMs or mezzanine cards.

```
racadm getmacaddress -c all
```

| <Name>     | <Type>               | <Presence> | <Active WWN/<br>MAC>>       | <Partition<br>Status>> | <Assignment<br>Type>> |
|------------|----------------------|------------|-----------------------------|------------------------|-----------------------|
| Server-1-A | IDRAC-<br>Controller | Present    | 18:A9:9B:FD:C4:<br>DF       | N/A                    | Factory               |
|            | Gigabit<br>Ethernet  | Present    | 00:0A:00:0A:<br>00:00       | Unknown                | IO-Identity           |
| Server-3-A | Gigabit<br>Ethernet  | Present    | 4:8F:<br>69:FC:E8:F1        | Unknown                | Factory               |
| Server-4-A | 10 GbE KR/3          | Present    | F8:DB:<br>88:3D:A2:7A       | Unknown                | FlexAddress           |
|            | FCoE-WWN             | Present    | 20:01:F8:DB:<br>88:3D:A2:7A | Unknown                | FlexAddress           |

# getmodinfo

**Description** Displays configuration and status information for all modules or a specified module (server, storage sled, switch, CMC, fan unit, blower, power supply unit, chassis, main-board, IO cable, and FPC cable) in the chassis.

To use this subcommand, you must have **CMC Login User** privilege.

 **NOTE: The Service Tag field is blank for modules that do not have Service Tags.**

**Synopsis** racadm getmodinfo [-m <module>] [-A] ra

**Input** · **-m <module >** — Specifies the module for which the configuration and status information is required. The default command (no options) displays information about all the major components in the chassis.

<module > can be one of the following values:

- server-*n* , where n = 1 to 4
- server-*nx* , where n = 1 to 4; x = a to d
- switch-*n* , where n = 1 or 2
- pcie-*n* , where n = 1 to 8
- CMC-*n* , where n = 1
- fan-*n* , where n = 1 to 8
- ps-*n* , where n = 1 to 2
- chassis
- main-board
- io-cable
- fpc cable

· **-A** — Does not display the headers and labels in the output.

**Example** · racadm getmodinfo -m switch-1

· <module> <presence> <pwrState> <health> <svcTag> Switch-1 Present ON OK CG09074

· racadm getmodinfo

| <module>   | <presence> | <pwrState> | <health> | <svcTag> | <node Id> |
|------------|------------|------------|----------|----------|-----------|
| Chassis    | Present    | ON         | OK       | ST0MP19  | N/A       |
| Main-Board | Present    | ON         | OK       | N/A      | N/A       |
| Storage-2  | Present    | OFF        | Not OK   | 6666666  | N/A       |
| Storage-3  | Present    | OFF        | Not OK   | 6666666  | N/A       |
| Storage-4  | Present    | OFF        | OK       | 6666666  | N/A       |
| Fan-1      | Present    | ON         | OK       | N/A      | N/A       |
| Fan-2      | Present    | ON         | Unknown  | N/A      | N/A       |
| Fan-3      | Present    | ON         | Unknown  | N/A      | N/A       |
| Fan-4      | Present    | ON         | Unknown  | N/A      | N/A       |



|           |         |         |         |         |          |
|-----------|---------|---------|---------|---------|----------|
| Fan-5     | Present | ON      | OK      | N/A     | N/A      |
| Fan-6     | Present | ON      | Unknown | N/A     | N/A      |
| Fan-7     | Present | ON      | Unknown | N/A     | N/A      |
| Fan-8     | Present | ON      | Unknown | N/A     | N/A      |
| PS-1      | Present | Online  | OK      | N/A     | N/A      |
| PS-2      | Present | Online  | OK      | N/A     | N/A      |
| CMC       | Present | Primary | OK      | N/A     | N/A      |
| Switch-1  | Present | ON      | OK      | 0000000 | N/A      |
| Switch-2  | Present | ON      | OK      | N/A     | N/A      |
| Server-1  | Present | OFF     | OK      | H23H23Z | H23H23Z  |
| Server-2a | Present | OFF     | OK      | JD3FRTW | JD3FRTWa |
| Server-2b | Present | OFF     | OK      | JD3FRTW | JD3FRTWb |
| Server-2c | Present | OFF     | OK      | JD3FRTW | JD3FRTWc |
| Server-2d | Present | OFF     | OK      | JD3FRTW | JD3FRTWd |
| Cable-IO  | Present | ON      | OK      | STOMP11 | N/A      |
| Cable-CP  | Present | ON      | OK      | STOMP11 | N/A      |

## getniccfg

### Description

Displays the current NIC settings.

### Synopsis

```
racadm getniccfg
```

### Input

```
racadm getniccfg
```

```
racadm getniccfg -m <module>
```

where `-m` must be one of the following values:

- `chassis`  
: default state if `-m` is not specified
- `server-n`  
: where `n` = 1 to 4
- `switch-n`  
: where `n` = 1 or 2

### Example

```
racadm getniccfg
```

```
NIC Enabled = 1
```

```
IPv4 Enabled = 1
```

DHCP Enabled = 1  
Static IP Address = 192.168.0.120  
Static Subnet Mask = 255.255.255.0  
Static Gateway = 192.168.0.1  
Current IP Address = 192.168.0.12  
Current Subnet Mask = 255.255.254.0  
Current Gateway = 192.168.0.1  
IPv6 Enabled = 0  
Autoconfiguration Enabled = 1  
Static IPv6 Address = ::/64  
Static IPv6 Gateway = ::  
Link Local Address = ::  
Current IPv6 Address 1 = ::  
Current IPv6 Gateway = ::  
Speed = Autonegotiate  
Duplex = Autonegotiate  
VLAN Enable = 0  
VLAN ID = 1  
VLAN priority = 0  
`racadm getniccfg -m server-1`  
LOM Model Name = BCM 10GbE 2P 57810s bNDC  
LOM Fabric Type = 10 GbE KR  
IPv4 Enabled = 1  
DHCP Enabled = 1  
IP Address = 192.168.0.18  
Subnet Mask = 255.255.255.0  
Gateway = 192.168.0.1  
IPv6 Enabled = 0  
Autoconfiguration Enabled = 0  
Link local Address =  
IPv6 Gateway = ::  
VLAN Enable = 0



```

VLAN ID = 1
VLAN priority = 0
racadm getniccfg -m switch-1
DHCP Enabled = 1
IP Address = 192.168.0.12
Subnet Mask = 255.255.255.0
Gateway = 0.0.0.0

```

## Output

The **getniccfg** subcommand displays an appropriate error message if the operation is not successful. Otherwise, the output is displayed in the following format:

```

NIC Enabled = 1
IPv4 Enabled = 1
DHCP Enabled = 1
Static IP Address = 192.168.0.120
Static Subnet Mask = 255.255.255.0
Static Gateway = 192.168.0.1
Current IP Address = 10.94.225.212
Current Subnet Mask = 255.255.255.128
Current Gateway = 10.94.225.129
IPv6 Enabled = 0
Autoconfiguration Enabled = 1
Static IPv6 Address = ::/64
Static IPv6 Gateway = ::
Link Local Address = ::
Current IPv6 Address 1 = ::
Current IPv6 Gateway = ::
Speed = Autonegotiate
Duplex = Autonegotiate
VLAN Enable = 0
VLAN ID = 1
VLAN priority = 0
$
$ racadm getniccfg -m server-3
LOM Model Name = BCM GbE 4P 5720 bNDC
LOM Fabric Type = Gigabit Ethernet
IPv4 Enabled = 1
DHCP Enabled = 0
IP Address = 0.0.0.0
Subnet Mask = 0.0.0.0
Gateway = 0.0.0.0
IPv6 Enabled = 0
Autoconfiguration Enabled = 1
Link local Address =
IPv6 Gateway = ::
VLAN Enable = 0
VLAN ID = 1
VLAN priority = 0

```

## getpbinfo

**Description** Displays power budget status information.

To use this subcommand, you must have the **CMC Login User** privilege.

## Synopsis

```
racadm getpbinfo
```

## Example

```
racadm getpbinfo

[Power Budget Status]
System Input Power = 90 W
Peak System Power = 93 W
Peak System Power Timestamp = 20:28:32 03/04/2014
Minimum System Power = 83 W
Minimum System Power Timestamp = 20:28:02 03/04/2014
Overall Power Health = OK
Redundancy = Yes
System Input Power Cap = 3371 W
Redundancy Policy = Redundancy Alerting Only
System Input Max Power Capacity = 2382 W
Input Redundancy Reserve = 0 W
Max Power Conservation Mode = 11:20:08 02/27/2014
Power Available for Server Power-on = 1965 W

[Chassis Power Supply Status Table]
<name> <Model> <Power State> <Input Current> <Input Volts> <Output Rated Power>
PS1 OCC6WF Online 0.3 A 208.0 V 1100 W
PS2 OGYH9V Online 0.3 A 209.0 V 1100 W
```

## getpciecfg

### Description

Displays the FQDD of the PCIe slots and their mapping information and properties.

 **NOTE: To use this subcommand, you must have CMC Login User privilege.**

 **NOTE: Lengthy PCIe card names and server slot names are truncated when the assignments for all PCIe slots are displayed.**

### Synopsis

```
racadm getpciecfg [-c <FQDD>]
```

### Input

- **-a** — Use this option to display the assignment of PCIe slots .
- **-c** — Use this option to select a specific PCIe adapter or Virtual Adapter.
- **FQDD** — FQDD of the selected PCIe slot

### Example

- Displays FQDDs of all the PCIe slots:

```
racadm getpciecfg

<PCIe Slot#> <FQDD>
PCIe slot 01 PCIE.ChassisSlot.1
PCIe slot 02 PCIE.ChassisSlot.2
PCIe slot 03 PCIE.ChassisSlot.3
PCIe slot 04 PCIE.ChassisSlot.4
PCIe slot 05 PCIE.ChassisSlot.5
PCIe slot 06 PCIE.ChassisSlot.6
PCIe slot 07 PCIE.ChassisSlot.7
PCIe slot 08 PCIE.ChassisSlot.8
```
- Displays the assignment of PCIe slots and Virtual Adapters:

```
racadm getpciecfg -a
<PCIe Slot#> <Name> <pwrState> <Server Slot Name> <Server Slot#>
PCIe slot-1 PCIe Card 1 ON
SLOT-04 4
```



|                          |                            |     |
|--------------------------|----------------------------|-----|
| PCIe slot-2<br>UNMAPPED  | Not Present<br>N/A         | N/A |
| PCIe slot-3<br>SLOT-03   | PCIe Card 3<br>3           | OFF |
| PCIe slot-4<br>SLOT-03   | Extension PCIe Card 3<br>3 | ON  |
| PCIe slot-5<br>SLOT-02   | PCIe Card 5<br>2           | OFF |
| PCIe slot-6<br>UNMAPPED  | Not Present<br>N/A         | N/A |
| PCIe slot-7<br>localhost | PCIe Card 7<br>1           | ON  |
| PCIe slot-8<br>UNMAPPED  | Not Present<br>N/A         | N/A |

- Displays the properties of a PCIe slot selected using FQDD:  

```
racadm getpciecfg -c pcie.chassisslot.1
```

## getpminfo

### Description

Displays power management status information.

To use this subcommand, you must have **CMC Login User** privilege.

### Synopsis

```
racadm getpminfo
```

### Example

```
racadm getpminfo
```

```
[Real-Time Power Statistics]
System Input Power = 89 W (303 BTU/h)
Peak System Power = 93 W (317 BTU/h)
Peak System Power Start Time = 20:26:06 03/04/2014
Peak System Power Timestamp = 20:28:32 03/04/2014
Minimum System Power = 83 W (283 BTU/h)
Minimum System Power Start Time = 20:26:06 03/04/2014
Minimum System Power Timestamp = 20:28:02 03/04/2014
System Idle Power = 89 W (303 BTU/h)
System Potential Power = 417 W (1422 BTU/h)
System Input Current Reading = 0.6 A

[Real-Time Energy Statistics]
System Energy Consumption = 62.2 kWh
System Energy Consumption Start Time = 15:56:11 02/12/2014
System Energy Consumption Timestamp = 06:07:07 03/05/2014

[System Power Status]
Chassis Power State = ON
Overall Power Health = OK
Redundancy = Yes

[System Power Policy Configuration]
System Input Power Cap = 3371 W (11502 BTU/h | 100%)
Redundancy Policy = Redundancy Alerting Only

[Power Budgeting]
System Input Max Power Capacity = 2382 W
Input Redundancy Reserve = 0 W
Power Available for Server Power-on = 1965 W
```

# gettracelog

## Description


Lists all the trace log entries in CMC.

## Synopsis

- `racadm gettracelog -i [-A]`
- `racadm gettracelog [-s <start>] [-c <count>] [--more] [-A] [-o]`

## Input

- **-i** - Displays the number of entries in CMC trace log.
- **--more** - Displays one screen at a time and prompts the user to continue (similar to the UNIX `more` command).
- **-o** - Displays each entry in a single line.
- **-c** - Specifies the number of records to display.
- **-s** - Specifies the starting record to display.
- **-A** - Does not display headers or labels.

 **NOTE: The -A and -o options are deprecated.**

## Output

The default output display shows the record number, timestamp, source, and description. The timestamp begins at midnight, January 1 and increases until the system boots. After the system boots, the system's timestamp is used.

## Example

```
Record: 1
Date/Time: Dec 8 08:21:30
Source: ssnmgrd[175]
Description: root from 192.68.157.103: session timeout
 sid 0be0aef4
```

# getractive

## Description

Displays the current CMC time.

## Synopsis

- `racadm getractive [-d]`
- `racadm getractive [-d] [-z] [-n]`

## Input

- **-d** — Displays the time in the format, `yyyymmddhhmmss.mmmmmms`.
- **-z** — Displays timezone. This option is specific to CMC only.
- **-n** — Displays NTP peer information. This option is specific to CMC only.

 **NOTE: If no options are provided, the getractive subcommand displays the time in a common readable format.**

## Output

The current CMC time is displayed.

## Example

- `racadm getractive`  
Thu Dec 8 20:15:26 2005
- `racadm getractive -d`  
20051208201542.000000



# getsel

## Description

Displays all sensor event log entries in the DRAC.

## Synopsis

- `racadm getsel -i [-A]`
- `racadm getsel [-s <start>] [-c <count>] [-A] [-o] [-E] [-R] [--more]`

If no arguments are specified, the entire log is displayed.

## Input

- **-A** — Specifies output with no display headers or labels.
- **-c** — Provides the number of records to be displayed.
- **-o** — Displays each entry in the SEL in a single line.
- **-s** — Specifies the starting record used for the display.
- **-E** — Displays RAW SEL data with the other data for each entry.
- **-R** — Displays only RAW SEL data for each entry.
- **-i** — Displays the number of entries in the SEL.
- **--more** — Displays one screen at a time and prompts the user to continue (similar to the UNIX **more** command.)

 **NOTE: The -A, -E, -o, and -R options are deprecated.**

## Output

```
Record: 12

Date/Time: 11/20/2011 14:19:34

Source: system

Severity: Ok

Description: C: boot completed.
```


## Example

```
racadm getsel
```

# getslotname

## Description

Displays the name, host name, and iDRAC DNS name of all the four slots, or of a specified slot (indicated by the slot number) in the chassis. Optionally, use this command to find if the slot name or host name, or iDRAC DNS name is displayed in the CMC web interface, or with the `getslotname [-i <slotNum> | -h]` command. If the host name is not available, the static slot name is used.

 **NOTE: Lengthy slot names, host names, or iDRAC DNS names are truncated when the slot names are displayed.**

To use this subcommand, you must have **CMC Login User** privilege.

## Synopsis

- `racadm getslotname`
- `racadm getslotname [-i <slotNum> | -h]`
- `racadm getslotname -h`

## Input

- None -  
Displays the slot name for all the four slots in the chassis.
- `-i < slotNum >` - specifies the slot number.  
Values: 1 to 4
- `-h` - Specifies whether to display the slot name, iDRAC DNS name, or the host name (if available). The values are:

- 0 — Displays the slot name
- 1 — Displays the host name instead of the slot name
- 2 — Displays the iDRAC DNS name instead of the slot name

**Example**

- Display all slots names.  

```
racadm getslotname
```

| <Slot #> | <Slot Name> | <Host name> | <iDRAC DNS Name> |
|----------|-------------|-------------|------------------|
| 1        | SLOT-01     |             |                  |
| 2        | Webserver01 |             | WXP-8GRB221      |
| 3        | Webserver3  |             | WXP-319QWEcet5   |
| 4        | SLOT-04     |             |                  |
- Display the name of the third slot.  

```
racadm getslotname -i 3
```
- Verify if the option '0' is set for displaying the slot name.
- Verify if the option '1' is set for displaying the host name.
- Verify if the option '2' is set for displaying the iDRAC DNS name.

## getsensorinfo

**Description**

Displays status of chassis sensors.

 **NOTE: To use this subcommand, you must have CMC Login User privilege.**

**Synopsis**

```
racadm getsensorinfo
```

**Examples**

```
racadm getsensorinfo
```

```
Sensor Type : Voltage
```

| <Sensor Name>        | <Status> | <Reading> | <LC> | UC  |
|----------------------|----------|-----------|------|-----|
| CPU1 VCORE PG        | OK       | 0         | 600  | N/A |
| System Board 12V PG  | OK       | 0         | 600  | N/A |
| System Board 3.3V PG | OK       | 4037      | 600  | N/A |
| System Board 5V PG   | OK       | 4045      | 600  | N/A |
| CPU1 PLL PG          | OK       | 4107      | 600  | N/A |
| System Board 1.5V PG | OK       | 0         | 600  | N/A |
| System Board 1.1V PG | OK       | 0         | 600  | N/A |
| CPU1 M01 VTT PG      | OK       | 0         | 600  | N/A |
| CPU1 M23 VDDQ PG     | OK       | 0         | 600  | N/A |
| CPU1 M23 VTT PG      | OK       | 0         | 600  | N/A |
| CPU1 VSA PG          | OK       | 0         | 600  | N/A |
| CPU1 M01 VDDQ PG     | OK       | 0         | 600  | N/A |



|             |    |   |     |     |
|-------------|----|---|-----|-----|
| NDC PG      | OK | 0 | 600 | N/A |
| CPU1 VTT PG | OK | 0 | 600 | N/A |
| MEZZB PG    | OK | 0 | 600 | N/A |
| MEZZC PG    | OK | 0 | 600 | N/A |
| PERC1 PG    | OK | 0 | 600 | N/A |

Sensor Type : Current

| <Sensor Name>        | <Status> | <Reading> | <LW> | <LC> | <UW> | <UC> |
|----------------------|----------|-----------|------|------|------|------|
| System Board Current | OK       | 22        | 3    | -7   | 42   | 47   |

Sensor Type : Processor

| <Sensor Name>        | <Status> | <AC-OK status> | <lc> | <uc>     |
|----------------------|----------|----------------|------|----------|
| CPU1 Status Detected | N/A      | OK             | N/A  | Presence |
| CPU2 Status Absent   | N/A      | N/A            | N/A  | N/A      |

Sensor Type : Memory

| <Sensor Name>         | <Status> | <State> | <lc> | <uc>     |
|-----------------------|----------|---------|------|----------|
| DIMM SLOT A1 Detected | N/A      | OK      | N/A  | Presence |
| DIMM SLOT A2 Detected | N/A      | OK      | N/A  | Presence |
| DIMM SLOT A3 Detected | N/A      | OK      | N/A  | Presence |
| DIMM SLOT A4 Detected | N/A      | OK      | N/A  | Presence |
| DIMM SLOT A5 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT A6 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT A7 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT A8 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT A9 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT A10 Absent  | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT A11 Absent  | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT A12 Absent  | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B1 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B2 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B3 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B4 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B5 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B6 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B7 Absent   | N/A      | OK      | N/A  | N/A      |
| DIMM SLOT B8 Absent   | N/A      | OK      | N/A  | N/A      |



```

Absent N/A N/A
DIMM SLOT B9 OK
Absent N/A N/A
DIMM SLOT B10 OK
Absent N/A N/A
DIMM SLOT B11 OK
Absent N/A N/A
DIMM SLOT B12 OK
Absent N/A N/A

```

```

Sensor Type : Battery
<Sensor Name> <Status> <Reading> <lc> <uc>
System Board CMOS Battery OK
Present N/A N/A

```

## getssninfo

### Description

Displays a list of users that are connected to CMC. The following information is displayed:

- Session ID
- Username
- IP address (if applicable)
- Session type (for example, serial or Telnet)
- Login date and time in MM/DD/YYYY HH:MM:SS format



**NOTE: Based on the Session ID (SSNID) or the user name (User), the CMC administrator can close the respective sessions or all the sessions using the, `closeesn` subcommand. For more information, see [closeesn](#).**

### Synopsis

```
racadm getssninfo [-A] [-u <username> | *]
```

### Input

- **-A** - eliminates the printing of data headers.
- **-u** - The `-u <username>` user name option limits the printed output to only the detail session records for the given user name.

### Examples

```
racadm getssninfo
```

| SSNID | Type | User | IP Address   | Login Date/Time     |
|-------|------|------|--------------|---------------------|
| 6     | GUI  | root | 192.168.0.10 | 04/07/2010 12:00:34 |

```
racadm getssninfo -A
```

```
"root" "192.68.174.19" "Telnet" "NONE"
```

```
racadm getssninfo -A -u *
```

```
"root" "192.68.174.19" "Telnet" "NONE"
```

```
"bob" "192.68.174.19" "GUI" "NONE"
```

## getstoragemoduleinfo

### Description

Displays the storage module configuration and status information.

### Synopsis

- `racadm getstoragemoduleinfo`



```
· racadm getstoragemoduleinfo <FQDD>
```

## Input

**-c** — The **-c** <FQDD> option can be used to view the details of a storage sled. The availability of this option is based on the <FQDD> input. This command is supported only when a storage sled is present in the CMC FX2/FX2s chassis.

## Examples

```
racadm getstoragemoduleinfo
```

```
<Storage Slot> <FQDD>
Storage-1 N/A
Storage-2 System.Modular.02
Storage-3 System.Modular.03
Storage-4 System.Modular.04
```

Display format of storage sled information when the storage mode is “joined” or has a single controller.

```
racadm getstoragemoduleinfo -c System.Modular.02
Storage-2 FQDD = System.Modular.02
Chassis Slot = 2
Name = SLOT-02
Model = PowerEdge FD332
Status = Not OK
Service Tag = 2435678
Asset Tag = ABCD12345
Intrusion State = Open
Storage Mode = Joined
Number of Controllers = 1
FQDD = RAID.Modular.2-1
 Physical Disk Slots = 0-15
 Connected Server = SLOT-01
 Controller Mode Capability = HBA and RAID
```

Display format of storage sled information when the storage mode is “split single host”.

```
racadm getstoragemoduleinfo -c System.Modular.03
Storage-2 FQDD = System.Modular.03
Chassis Slot = 3
Name = SLOT-03
Model = PowerEdge FD332
Status = Not OK
Service Tag = 8748596
Asset Tag = KLOP98656
Intrusion State = Closed
Storage Mode = Split single host
Number of Controllers = 2
FQDD = RAID.Modular.3-1
 Physical Disk Slots = 0-7
 Connected Server = SLOT-01
 Controller Mode Capability = HBA
FQDD = RAID.Modular.3-2
 Physical Disk Slots = 8-15
 Connected Server = SLOT-1
 Controller Mode Capability = HBA
```

Display format of storage sled information when the storage mode is “Split dual host”.

```
racadm getstoragemoduleinfo -c System.Modular.03
Storage-3 FQDD = System.Modular.03
Chassis Slot = 3
```

```

Name = SLOT-03 (Storage)
Model = PowerEdge FD332
Status = OK
Service Tag = 4657248
Asset Tag = ERHJ57834
Intrusion State = Closed
Storage Mode = Split dual host
Number of Controllers = 1
FQDD = RAID.Modular.3-1
 Physical Disk Slots = 0-7
 Connected Server = SLOT-01
 Controller Mode Capability = RAID
FQDD = RAID.Modular.2-1
 Physical Disk Slots = 8-15
 Connected Server = SLOT-2
 Controller Mode Capability = HBA and RAID

```

Display format when storage sleds are not installed on the CMC FX2 or CMC FX2s system.

```
racadm getstoragemoduleinfo
```

This command is not supported on this configuration.

## getsvctag

**Description** Displays the Service Tag of the host system.

**Synopsis** `racadm getsvctag`

**Input** `getsvctag`


**Output**

| <Module>  | <ServiceTag> | <NodeId> |
|-----------|--------------|----------|
| Chassis   | STPST02      | N/A      |
| Switch-1  | 0000000      | N/A      |
| Switch-2  | N/A          | N/A      |
| Server-1  | FC830        | FC830    |
| Server-2  | Extension(1) | N/A      |
| Storage-3 | 7647563      | N/A      |
| Storage-4 | 7654321      | N/A      |

**Example** `racadm getsvctag`

## getsysinfo

**Description** Displays information related to CMC and chassis.

 **NOTE: The Hostname and OS Name fields in the getsysinfo output display accurate information only if Dell OpenManage Server Administrator is installed on the managed system. Else, these fields may be blank or inaccurate. An exception to this are VMware operating system names, which are displayed even if Server Administrator is not installed on the managed system.**

**Synopsis** `racadm getsysinfo [-d] [-c] [-A] [-4] [-6]`

**Input**

- **-d** - Displays CMC information.
- **-c** - Displays chassis information.
- **-A** - Does not display headers and labels.
- **-4** - Displays IPv4 information.
- **-6** - Displays IPv6 information.



## Output

```
CMC Information:
CMC Date/Time = Tue Jan 29 2013 23:00
CMC Location = CMC-1
Primary CMC Location = 4.40
CMC Version = 1.10
Last Firmware Update = Mon Jan 28 2013 08:41
Hardware Version = A04
```

```
CMC Network Information:
NIC Enabled = 1
MAC Address = D4:AE:52:AC:CA:C6
Register DNS CMC Name = 1
DNS CMC Name = cmc-servicetag
Current DNS Domain = swtest.com
VLAN ID = 1
VLAN Priority = 0
VLAN Enabled = 0
```

```
CMC IPv4 Information:
IPv4 Enabled = 1
Current IP Address = 192.168.164.115
Current IP Gateway = 192.168.164.1
Current IP Netmask = 255.255.255.0
DHCP Enabled = 1
Current DNS Server 1 = 192.168.165.80
Current DNS Server 2 = 0.0.0.0
DNS Servers from DHCP = 1
```

```
CMC IPv6 Information:
IPv6 Enabled = 0
Autoconfiguration Enabled = 1
Link Local Address = ::
Current IPv6 Address 1 = ::
Current IPv6 Gateway = ::
Current IPv6 DNS Server 1 = ::
Current IPv6 DNS Server 2 = ::
DNS Servers from DHCPv6 = 1
```

```
Chassis Information:
System Model = PowerEdge FX2s
System AssetTag = 00000
Service Tag = STPST06
Express Service Code = 62746758870
Chassis Name = CMC-STPST06
Chassis Location = [UNDEFINED]
Chassis Midplane Version = 1.0
Power Status = ON
System ID = 1488
PCIe Switch Board Type = Gen 3
```

 **NOTE: In the Chassis Information output, the PCIe Switch Board Type information is displayed only for PowerEdge FX2s chassis model.**

## Examples

```
racadm getsysinfo -d
racadm getsysinfo -c
racadm getsysinfo -A
racadm getsysinfo -4
racadm getsysinfo -6
```

# gettracelog

## Description


Lists all the trace log entries in CMC.

## Synopsis

- `racadm gettracelog -i [-A]`
- `racadm gettracelog [-s <start>] [-c <count>] [--more] [-A] [-o]`

## Input

- **-i** - Displays the number of entries in CMC trace log.
- **--more** - Displays one screen at a time and prompts the user to continue (similar to the UNIX `more` command).
- **-o** - Displays each entry in a single line.
- **-c** - Specifies the number of records to display.
- **-s** - Specifies the starting record to display.
- **-A** - Does not display headers or labels.

 **NOTE: The -A and -o options are deprecated.**

## Output

The default output display shows the record number, timestamp, source, and description. The timestamp begins at midnight, January 1 and increases until the system boots. After the system boots, the system's timestamp is used.

## Example

```
Record: 1
Date/Time: Dec 8 08:21:30
Source: ssnmgrd[175]
Description: root from 192.68.157.103: session timeout
 sid 0be0aef4
```

# getversion

## Description

Displays the current software version, model and generation information, and whether the target device can be updated.

 **NOTE: To use this subcommand, you must have CMC Login User privilege.**

## Synopsis

- `racadm getversion`
- `racadm getversion [-b | -c] [-m <module>]`
- `racadm getversion -l [-m <module>] [-f <filter>]`

## Input

 **NOTE: The -b, -c and -l options are not available for CMC modules.**

 **NOTE: The -l option requires that the Lifecycle Controller service is enabled on the servers. For version information, see the RACADM Readme available at [dell.com/support/manuals](http://dell.com/support/manuals).**

- **(none)** — Displays the version information for all targets or devices.

| <Server>  | <iDRAC Version> | <Blade Type>    |
|-----------|-----------------|-----------------|
| <Gen>     | <Updatable>     |                 |
| server-1a | 2.15.15.15 (18) | PowerEdge FC430 |
| iDRAC8    | Y               |                 |
| server-1b | 2.40.40.40 (13) | PowerEdge FC430 |
| iDRAC8    | Y               |                 |
| server-1c | 2.10.10.10 (49) | PowerEdge FC430 |
| iDRAC8    | Y               |                 |



```

server-1d 2.40.40.40 (13) PowerEdge FC430
iDRAC8 Y
server-3a 2.10.10.10 (27) PowerEdge FC430
iDRAC8 Y
server-3b 2.10.10.10 (49) PowerEdge FC430
iDRAC8 Y
server-3c 2.30.30.30 (10) PowerEdge FC430
iDRAC8 Y
server-3d 2.10.10.10 (49) PowerEdge FC430
iDRAC8 Y

<Switch> <Model Name> <HW
Version> <FW Version>
switch-1 1GBE PASS-THROUGH MODULE A00
N/A

<CMC> <CMC
Version> <Updatable>
cmc
2.00.000.20161003sahu Y

<Chassis Infrastructure> <FW Version> <FQDD>
Main Board 1.20.A00.201502058
System.Chassis.
1#Infra
structure.1

```

- **-b** — Displays the server's current BIOS version (default is iDRAC version).
- **-c** — Displays the server's current CPLD version.
- **-l** — Displays the firmware versions Lifecycle Controller components.
- **-f < filter >** — Filters the components. Must be used with **-l** and be one of the following values:
  - bios: BIOS
  - idrac: iDRAC
  - usc: Unified Server Configurator (Lifecycle Controller)
  - diag: 32-bit Diagnostics
  - drivers: OS Driver Package
  - nic-x: Network Interface card. See -l output for possible values of x.
- **-m < module >** — Specifies the module or device for which you must retrieve the version information.
  - < module > is one of the following:
    - server-n , where n = 1 to 4.
    - switch-n , where n = 1 to 2.
    - CMC
    - mainboard

### Example

- Retrieve the version for a server 4  

```
racadm getversion -m server-4
```
- Retrieve the Lifecycle Controller component versions for servers 1 and 3:  

```
racadm getversion -l -m server-1 -m server-3
```
- Retrieve the Lifecycle Controller BIOS versions for servers 1 and 3:  

```
racadm getversion -l -m server-1 -m server-3 -f bios
```
- Retrieve the version for all modules:  

```
racadm getversion
```
- Retrieve the iDRAC version in all the servers that are attached to the chassis:  

```
racadm getversion -f idrac
```

# ifconfig

## Description

Displays the contents of the network interface table.

To use this subcommand, you must have the **Administrator** privilege.

## Synopsis

```
racadm ifconfig
```

## Example

```
$ racadm ifconfig
eth0 Link encap:Ethernet HWaddr 00:1D:09:FF:DA:23
 inet addr:192.168.0.1 Bcast:192.168.0.120
 Mask:255.255.255.0
 UP BROADCAST RUNNING MULTICAST MTU:1500
Metric:1
 RX packets:2550665 errors:0 dropped:0 overruns:0
frame:0
 TX packets:0 errors:0 dropped:0 overruns:0
carrier:0
 collisions:0 txqueuelen:1000
 RX bytes:272532097 (259.9 MiB) TX bytes:0
(0.0 B)
```

# jobqueue

## Description

Displays the jobs in that are currently being run, delete the jobs, and create a job.



**NOTE: To view the jobs, you must have CMC Login User privilege.**



**NOTE: To delete the jobs, you must have Chassis Configuration Administrator privilege.**

## Synopsis

- racadm jobqueue view
- racadm jobqueue delete
- racadm jobqueue create

## Input

- **-i** — Specifies the JobID that is displayed or deleted.
- **--all** — The JobIDs that are not applied are deleted.
- **<fqdd>** — Specifies an FQDD for which a job has to be created.
- **reboot type** — Specifies a reboot type. Valid options are **none: No Reboot Job** which is the default.
- **start time** — Specifies a start time for job to be scheduled in yyyyymmddhhmmss format. If you specify TIME\_NOW, the job is immediately run.
- **Expiration time** — Specifies the expiry time for the job to complete in yyyyymmddhhmmss format. If you specify TIME\_NA, the wait-time is not applicable for the job.

## Example

- Display all the jobs:

```
-----JOB QUEUE-----
[Job ID=RID_853106266329]
Job Name=Reboot4
Status=New
Start Time=[NOW]
Expiration Time=[NOW]

```



```
[Job ID=RID_852218430518]
Job Name=Reboot4
Status=New
Start Time=[NOW]
Expiration Time=[NOW]
```

```

[Job ID=RID_852215634901]
Job Name=Reboot4
Status=New
Start Time=[NOW]
Expiration Time=[NOW]

```

- Delete the specified job:  
racadm jobqueue delete -i RID\_860202993201
- racadm jobqueue delete -i <JobID>

## krbkeytabupload

### Description

Uploads a Kerberos keytab file.

To run this subcommand, you must have the **Configure Chassis Administrator** privilege.

### Synopsis

```
racadm krbkeytabupload [-f <filename>]
```

<filename> is the name of the file including the path.

### Input

**-f** — Specifies the file name of the keytab to be uploaded. If the file is not specified, the keytab file in the current directory is selected.

### Output

Returns 0 when successful, and a non-zero number, when unsuccessful.

### Example

```
racadm krbkeytabupload -f c:\keytab\krbkeytab.tab
```

## license

### Description

Manages the CMC and storage sled licenses.

### Synopsis

racadm license <license command type>. The command type can be:

- View the license using the following options:
  - racadm license view
  - racadm license view [-c <component>]
  - racadm license view -c <storage sled FQDD>
- Import the license:

```
racadm license import [-u <username>] [-p <password>] [-f <license file name>] [-l <NFS or CIFS share>] [-c <FQDD>]
```
- Export the license using the following options:
  - racadm license export [-u <username>] [-p <password>] [-f <license file name>] [-l <NFS/CIFS share>] [-t <transaction ID>]
  - racadm license export [-u <username>] [-p <password>] [-f <license file name>] [-l <NFS/CIFS share>] [-e <entitlement ID>]
  - racadm license export [-u <username>] [-p <password>] [-f <license file name>] [-l <NFS/CIFS share>] [-c <FQDD>]

- racadm license export [-u <username>] [-p <password>] [-f <license file name>] [-l <NFS/CIFS share>] [-c <FQDD>] [-e <entitlement ID>] [-t <transaction ID>]
- Delete the license using the following options:
  - racadm license delete [-t <transaction ID>]
  - racadm license delete [-e <entitlement ID>]
  - racadm license delete [-c <component>]
- Replace the license:
 

```
racadm license replace [-u <username>] [-p <password>] [-f <license file name>] [-l <NFS/CIFS share>] [-t <transaction ID>]
```

## Input

 **NOTE: License operations the <licensefile> name should be fewer than 56 Characters.**

 **NOTE: Only a user with administrator-level privileges can use the import, export, delete, and replace commands. An Administrator privilege is not necessary to use the view command.**

- **view** — View license information.
- **import** — Installs a new license.
- **export** — Exports a license file.
- **delete** — Deletes a license from the system.
- **replace** — Replaces an older license with a given license file.

Use the following options along with the commands:

- **-c** — Specifies the FQDD of the component or device, on which the license is present.
- **-l** — Network share location to import or export the license file.
- **-f** — File name of the license file.

 **NOTE: During export, the license file is named <servicetag>\_<entitlement ID>.xml.**

- **-u** — User name of the remote share.
- **-p** — Password for the remote share.
- **-e** — Specifies the entitlement ID of the license file.
- **-t** — Specifies the transaction ID of the license file.

## Examples

- View licenses:

```
- View all the license information in the chassis.
racadm license view

CMC.Integrated.1
 Status = OK
 Device = CMC.Integrated.1
 Device Description = Chassis Management Controller
for PowerEdge FX2/FX2s
 Unique Identifier =
 License #1
 Status = OK
 Transaction ID = 8
 License Description = CMC
Enterprise Evaluation License
 License Type = EVALUATION
 Entitlement ID =
A2Wir6lJlMoP8iBAAtqsEKDv8
 Expiration =
1982-04-07T21:00:00
```

- View the storage sled license information in the chassis.

```
racadm license view -c <FQDD>
```

```
System.Modular.03
 Status = OK
 Device = System.Modular.03
 Device Description = Dual PERC Controller for
PowerEdge FD332
 Unique Identifier = PQR123
 License #1
 Status = OK
 Transaction ID = 522
 License Description = PowerEdge
FD332 Dual RAID License
 License Type = PERPETUAL
 Entitlement ID =
Q3nJiS1xnX4rdRlat24qjdfb
 License Bound = PQR243
 Expiration = Never Expires
```

- Import a license:

- Import a license from a CIFS share to a device (for example, Integrated CMC):

```
racadm license import -u admin -p passwd -f License.xml -l //
x.x.x.x/licshare -c cmc.integrated.1
```

- Import a license from an NFS share to a device (for example, Integrated CMC):

```
racadm license import -f License.xml -l x.x.x.x:/share -c
cmc.integrated.1
```

- Import a license from the local file system using Remote RACADM:

```
racadm license import -u admin -p passwd -r x.x.x.x -f C:
\Mylicdir\License.xml -c cmc.integrated.1
```

- Export a license file:

- Export license to an NFS share using transaction ID (for example, transaction 27).

```
racadm license export -f License.xml -l x.x.x.x/licshare -t
27
```

- Export the license to a CIFS share specifying the entitlement ID (for example, abcdxyz):

```
racadm license export -u admin -p passwd -f License.xml -l //
x.x.x.x/licshare -e abcdxyz
```

- Export license to a CIFS share specifying the FQDD. While using the `-c` option and exporting licenses from a device, more than one license file may be exported. Therefore, if a file name is provided, an index is appended to the end of the file name such as LicenseFile0.xml, LicenseFile1.xml, and so on. In this case, the device is an embedded CMC:

```
racadm license export -u root -p <default root user
password> -f LicenseFile.xml -l //x.x.x.x/licshare -c
cmc.embedded.1
```

- Delete a license:

- Delete licenses on a particular device. For example, Embedded CMC:

```
racadm license delete -c cmc.embedded.1
```

- Delete license using an entitlement ID. For example, xYZabcdefg

```
racadm license delete -e xYZabcdefg
```

- Delete license using a transaction ID. For example, 2.

```
racadm license delete -t 2
```

- Delete a storage sled license. For example, System.Modular.03

```
racadm license delete -c System.Modular.03
```

- Replace a license.

- Replace the license on a device with a license file that is on an NFS share, and using a transaction ID. For example, transaction 27.  
`racadm license replace -f License.xml -l x.x.x.x:/licshare -t 27`
- Replace license on a device with a license file that is on a CIFS share and using a transaction ID. For example, transaction 27.  
`racadm license replace -u admin -p passwd -f License.xml -l //x.x.x.x/licshare -t 27`
- Replace license on a device with a license file on the local file system.  
`racadm license replace -f License.xml -t 27`
- Replace a storage sled license  
`racadm license replace -f nfs/"CfDuqtnJTobaSYGNzmdA4Buz_xyz_dual.xml" -l x.x.x.x:/nfs -t 8`

## netstat

### Description

Displays the routing table and the current connections.

To use this subcommand, you must have the **Execute Diagnostic Commands** permission.

### Synopsis

```
racadm netstat
```

### Input

```
racadm netstat
```

### Output

```
Kernel IPv6 routing table
Destination Next Hop Flags Metric Ref Use Iface
::
1/128 ::
 U 0 30 1 lo
fe80::200:ff:fe00:d01/128
 U 0 0 1 lo
fe80::/64 ::
 U 256 0 0 eth1
ff00::/8 ::
 U 256 0 0 eth1

Kernel IP routing table
Destination Gateway Genmask Flags MSS
Window irtt Iface
192.168.161.0 0.0.0.0 255.255.255.0 U 0
0 0 bond0
0.0.0.0 198.168.161.1 0.0.0.0 UG 0
0 0 bond0

Active Internet connections (w/o servers)
Proto Recv-Q Send-Q Local Address Foreign
Address State
tcp 0 0 127.0.0.1:8195
127.0.0.1:52887 ESTABLISHED
tcp 0 0 127.0.0.1:199
127.0.0.1:52174 ESTABLISHED
tcp 0 0 127.0.0.1:52175
127.0.0.1:199 ESTABLISHED
tcp 0 0 127.0.0.1:199
127.0.0.1:52175 ESTABLISHED
tcp 0 0 192.168.155.10:22
192.168.155.20:45106 ESTABLISHED
```



```
tcp 0 0 127.0.0.1:52174
127.0.0.1:199 ESTABLISHED
tcp 0 0 127.0.0.1:52887
127.0.0.1:8195 ESTABLISHED
```

## ping

### Description

Verifies that the destination IP address is reachable from CMC with the current routing-table contents. A destination IP address is required. An ICMP echo packet is sent to the destination IP address based on the current routing-table contents.

To use this subcommand for CMC, you must have the Administrator privilege for CMC.

### Synopsis

```
racadm ping <ipaddress>
```

## ping6

### Description

Verifies that the destination IPv6 address is reachable from a CMC, or with the current routing-table contents. A destination IPv6 address is required. An ICMP echo packet is sent to the destination IPv6 address based on the current routing-table contents.

To use this subcommand for CMC, you must have the Administrator privilege.

### Synopsis

```
racadm ping6 <ipv6address>
```

### Example

```
racadm iping6 192.168.0.2
IPING6 192.168.0.2 (192.168.0.2): 56 data bytes
64 bytes from 192.168.0.2: icmp_seq=0 ttl=121 time=2.9
ms

--- 192.168.0.2 ping statistics ---
1 packets transmitted, 1 packets received, 0 percent
packet loss

round-trip min/avg/max = 2.9/2.9/2.9 ms
```

## racdump

### Description

This subcommand displays the comprehensive chassis status and configuration state information, and historic event logs. Used for post-deployment configuration verification and during debugging sessions.

To use this subcommand for CMC, you must have the **CMC Login User** privilege.

### Synopsis

```
racadm racdump
```

### Input

Racdump includes the following subsystems and aggregates the following RACADM commands:

- General System/RAC information — `getsysinfo`
- Session information — `getssinfo`
- Sensor information — `getsensorinfo`
- Switches information (IO Module) — `getioinfo`
- Mezzanine card information (Daughter card) — `getdcinfo`
- All modules information — `getmodinfo`

- Power budget information — getpbinfo
- KVM information — getkvminfo
- NIC information (CMC module) — getniccfg
- Redundancy information — getredundancymode
- Trace log information — gettracelog
- RAC event log — getraclog
- System event log — getsel

## Output

The following information is displayed when the `racdump` subcommand is processed:

- General system/RAC information
- Cooredump
- Session information
- Process information
- Firmware build information

## Example

```
racadm racdump
```

```
=====
General System/RAC Information
=====
CMC Information:
CMC Date/Time = Mon Jul 04 2016 18:50
Primary CMC Location = CMC
Primary CMC Version = 2.00
Last Firmware Update = Mon Jul 03 2016 20:06
Hardware Version = A00

CMC Network Information:
NIC Enabled = 1
MAC Address = F8:BC:12:32:E6:80
Register DNS CMC Name = 0
DNS CMC Name = cmc-grapple
Current DNS Domain = SSEFW.COM
VLAN ID = 1
VLAN Priority = 0
VLAN Enabled = 0

CMC IPv4 Information:
IPv4 Enabled = 1
Current IP Address = 10.94.224.187
Current IP Gateway = 10.94.224.1
Current IP Netmask = 255.255.255.0
DHCP Enabled = 1
Current DNS Server 1 = 10.116.2.250
Current DNS Server 2 = 10.116.2.251
DNS Servers from DHCP = 1

CMC IPv6 Information:
IPv6 Enabled = 0
Autoconfiguration Enabled = 1
Link Local Address = ::
Current IPv6 Address 1 = ::
Current IPv6 Gateway = ::
Current IPv6 DNS Server 1 = ::
Current IPv6 DNS Server 2 = ::
DNS Servers from DHCPv6 = 1

Chassis Information:
System Model = PowerEdge FX2s
System AssetTag = 00000
Service Tag = grapple
```



```

Express Service Code = 108126335602
Chassis Name = CMC-grapple
Chassis Location = [UNDEFINED]
Chassis Midplane Version = 1.0
Power Status = ON
System ID = 1488
PCIe Switch Board Type = Gen 3

```

```

=====
Session Information
=====

```

```

SSNID Type User IP Address Login Date/Time
49580 SSH root 10.94.78.51 07/04/2016 18:07:40

```

```

=====
Sensor Information
=====

```

| <senType> | <Num> | <sensorName> | <status> | <reading> | <units> |
|-----------|-------|--------------|----------|-----------|---------|
| <LC>      | <UC>  | <PWM>        |          |           |         |
| FanSpeed  | 1A    | Fan-1A       | OK       | 8040      | rpm     |
| 3720      | N/A   | 67           |          |           |         |
| FanSpeed  | 1B    | Fan-1B       | OK       | 7080      | rpm     |
| 3720      | N/A   | 67           |          |           |         |
| FanSpeed  | 2     | Fan-2        | OK       | 11040     | rpm     |
| 5520      | N/A   | 67           |          |           |         |
| FanSpeed  | 3     | Fan-3        | OK       | 11040     | rpm     |
| 5520      | N/A   | 67           |          |           |         |
| FanSpeed  | 4     | Fan-4        | OK       | 11160     | rpm     |
| 5520      | N/A   | 67           |          |           |         |
| FanSpeed  | 5A    | Fan-5A       | OK       | 8040      | rpm     |
| 3720      | N/A   | 67           |          |           |         |
| FanSpeed  | 5B    | Fan-5B       | OK       | 7080      | rpm     |
| 3720      | N/A   | 67           |          |           |         |
| FanSpeed  | 6     | Fan-6        | OK       | 11040     | rpm     |
| 5520      | N/A   | 67           |          |           |         |
| FanSpeed  | 7     | Fan-7        | OK       | 11040     | rpm     |
| 5520      | N/A   | 67           |          |           |         |
| FanSpeed  | 8     | Fan-8        | OK       | 10920     | rpm     |
| 5520      | N/A   | 67           |          |           |         |

| <senType> | <Num> | <sensorName>    | <status> | <reading> | <units> |
|-----------|-------|-----------------|----------|-----------|---------|
| <LC>      | <UC>  |                 |          |           |         |
| Temp      | 1     | Chassis Ambient | OK       | 23        |         |
| Celsius   | -7    | 47              |          |           |         |
| Temp      | 2     | Server-1a       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |
| Temp      | 3     | Server-1b       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |
| Temp      | 4     | Server-1c       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |
| Temp      | 5     | Server-1d       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |
| Temp      | 6     | Server-3a       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |
| Temp      | 7     | Server-3b       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |
| Temp      | 8     | Server-3c       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |
| Temp      | 9     | Server-3d       | OK       | N/A       |         |
| Celsius   | N/A   | N/A             |          |           |         |

| <senType> | <Num> | <sensorName> | <status> | <health> |
|-----------|-------|--------------|----------|----------|
| PWR       | 1     | PS-1         | Online   | OK       |
| PWR       | 2     | PS-2         | Online   | OK       |

| <senType> | <Num> | <sensorName> | <status> |
|-----------|-------|--------------|----------|
| Cable     | 1     | Cable-IO     | OK       |
| Cable     | 2     | Cable-CP     | OK       |



```

=====
Switches Information
=====
<IO Name SecureMode Mode Type Presence POST Power
Role
Switch-1 1GBE PASS-THROUGH MODULE Gigabit Ethernet Present OK
ON Master No N/A
Switch-2 N/A N/A None Not Present N/A N/
A
=====

```

```

=====
Daughter Card Information
=====
Group A I/O Type : Gigabit Ethernet
Group B I/O Type : PCIe
Group C I/O Type : PCIe

```

```

<IO#> <Type> <State> <Role>
switch-1 Gigabit Ethernet OK Master
switch-2 None N/A N/A

```

```

<Server#> <Presence> <DC1 Type> <DC1 State> <DC2 Type> <DC2 State>
server-1a Present None N/A PCIe OK
server-1b Present PCIe OK None N/A
server-1c Present None N/A PCIe OK
server-1d Present PCIe OK None N/A
server-2 Extension(1) None N/A None N/A
server-3a Present None N/A PCIe OK
server-3b Present PCIe OK None N/A
server-3c Present None N/A PCIe OK
server-3d Present PCIe OK None N/A
server-4 Extension(3) None N/A None N/A

```

```

=====
All Modules Information
=====
<module> <presence> <pwrState> <health> <svcTag> <nodeId>
Chassis Present ON OK grapple N/A
Main-Board Present ON OK N/A N/A
Fan-1 Present ON OK N/A N/A
Fan-2 Present ON OK N/A N/A
Fan-3 Present ON OK N/A N/A
Fan-4 Present ON OK N/A N/A
Fan-5 Present ON OK N/A N/A
Fan-6 Present ON OK N/A N/A
Fan-7 Present ON OK N/A N/A
Fan-8 Present ON OK N/A N/A
PS-1 Present Online OK N/A N/A
PS-2 Present Online OK N/A N/A
CMC Present Primary OK N/A N/A
Switch-1 Present ON OK N/A N/A
Switch-2 Not Present N/A N/A N/A N/A
Server-1a Present OFF OK 1111111 1111111
Server-1b Present OFF OK 6P3RG52 6P3RG52
Server-1c Present OFF OK HP3RG52 HP3RG52
Server-1d Present OFF OK DN3RG52 DN3RG52
Server-2 Extension(1) N/A N/A N/A N/A
Server-3a Present OFF OK N/A N/A
Server-3b Present OFF OK 6Q3RG52 6Q3RG52
Server-3c Present OFF OK N/A N/A
Server-3d Present OFF OK 1FXSG52 1FXSG52
Server-4 Extension(3) N/A N/A N/A N/A
Cable-IO Present ON OK grapple N/A
Cable-CP Present ON OK grapple N/A

```

```

=====
Power Budget Information
=====

```



```

[Power Budget Status]
System Input Power = 186 W
Peak System Power = 195 W
Peak System Power Timestamp = 21:16:21 10/03/2016
Minimum System Power = 140 W
Minimum System Power Timestamp = 20:08:27 10/03/2016
Overall Power Health = OK
Redundancy = No
System Input Power Cap = 3371 W
Redundancy Policy = None
System Input Max Power Capacity = 3371 W
Input Redundancy Reserve = 0 W
Max Power Conservation Mode = No
Power Available for Server Power-on = 2712 W

```

```

[Chassis Power Supply Status Table]
<Name> <Model> <Power State> <Input Current> <Input Volts>
<Output Rated Power>
PS1 095HR5 Online 0.4 A 239.8 V
1600 W
PS2 095HR5 Online 0.4 A 240.0 V
1600 W

```

```

=====
Nic Information
=====

```

```

NIC Enabled = 1
IPv4 Enabled = 1
DHCP Enabled = 1
Static IP Address = 192.168.0.120
Static Subnet Mask = 255.255.255.0
Static Gateway = 192.168.0.1
Current IP Address = 10.94.224.187
Current Subnet Mask = 255.255.255.0
Current Gateway = 10.94.224.1
IPv6 Enabled = 0
Autoconfiguration Enabled = 1
Static IPv6 Address = ::/64
Static IPv6 Gateway = ::
Link Local Address = ::
Current IPv6 Address 1 = ::
Current IPv6 Gateway = ::
Speed = Autonegotiate
Duplex = Autonegotiate
Redundant mode = 0
VLAN Enable = 0
VLAN ID = 1
VLAN priority = 0

```

```

=====
Tracelog Information
=====

```

```

Jul 4 17:13:00 CMC-grapple systemd[1]: Stopping Rotate Logs...
Oct 4 17:14:00 CMC-grapple systemd[1]: logrotate.service holdoff time over, scheduling
restart.
Oct 4 17:14:00 CMC-grapple systemd[1]: Stopping Rotate Logs...
Oct 4 17:14:07 CMC-grapple ssnmgrd: root from 10.94.78.51: session timeout sid 25332
Oct 4 17:14:07 CMC-grapple ssnmgrd: root from 10.94.78.51: session timeout sid 25332
Oct 4 17:14:07 CMC-grapple sshd[11379]: Session close PID succeeds: sid=25332, User: root,
IP: 10.94.78.51
Oct 4 17:14:07 CMC-grapple sshd[11379]: Session close PID succeeds: pid=11379 sid=25332
Oct 4 18:47:43 CMC-grapple systemd[1]: Stopping System Logging Service...
Oct 4 18:48:08 CMC-grapple systemd[1]: logrotate.service holdoff time over, scheduling
restart.
Oct 4 18:48:08 CMC-grapple systemd[1]: Stopping Rotate Logs...
Oct 4 18:49:08 CMC-grapple systemd[1]: logrotate.service holdoff time over, scheduling
restart.

```



Oct 4 18:49:08 CMC-grapple systemd[1]: Stopping Rotate Logs...  
Oct 4 18:50:08 CMC-grapple systemd[1]: logrotate.service holdoff time over, scheduling restart.  
Oct 4 18:50:08 CMC-grapple systemd[1]: Stopping Rotate Logs...

=====  
Raclog Information  
=====

SeqNumber = 7  
Message ID = USR8513  
Category = Audit  
AgentID = CMC  
Severity = Information  
Timestamp = 2016-07-04 20:25:07  
Message Arg 1 = root  
Message Arg 2 = 10.94.18.232  
Message Arg 3 = SSH  
Message = root login successful from 10.94.18.232 (type=SSH).

-----  
SeqNumber = 6  
Message ID = PSU8517  
Category = Audit  
AgentID = CMC  
Severity = Information  
Timestamp = 2016-07-04 20:24:39  
Message = PSU redundancy policy changed.

-----  
SeqNumber = 4  
Message ID = USR8513  
Category = Audit  
AgentID = CMC  
Severity = Information  
Timestamp = 2016-07-04 20:23:46  
Message Arg 1 = root  
Message Arg 2 = 10.94.18.232  
Message Arg 3 = GUI  
Message = root login successful from 10.94.18.232 (type=GUI).

-----  
SeqNumber = 3  
Message ID = USR8501  
Category = Audit  
AgentID = CMC  
Severity = Information  
Timestamp = 2016-07-04 20:22:06  
Message Arg 1 = 7990  
Message Arg 2 = 41269  
Message = Successfully closed Session process: pid=7990 sid=41269

-----  
SeqNumber = 2  
Message ID = USR8501  
Category = Audit  
AgentID = CMC  
Severity = Information  
Timestamp = 2016-07-04 20:22:06  
Message Arg 1 = 7990  
Message Arg 2 = 48120  
Message = Successfully closed Session process: pid=7990 sid=48120

=====  
sel Information  
=====

Mon Oct 03 2016 20:21:57 Normal Log cleared.  
Mon Oct 03 2016 20:24:39 Normal The power supplies are not redundant.



# racreset

## Description

Performs a CMC or a RAC reset operation.

 **NOTE: To use this subcommand, you must have the Chassis Administrator privilege.**

 **NOTE: When you run a racreset subcommand, CMC may require up to two minutes to return to a usable state.**

## Synopsis

```
racadm racreset [-m <module>]
```

## Input

-m<module> — This option can have one of the following values:

- server <-n>, where n= 1-4
- server <-nx>, where n=1-4 and x=a-d (lower case)
- sled-n , where n=1-4

 **NOTE: The -m sled-n option is available only for multinode servers.**

 **NOTE: You can use the -f option to force the reset. This option is available only with the -m option.**

 **NOTE: You can specify multiple modules: -m <module 1> -m <module 2>.**

## Example

- Reset CMC:  

```
racadm racreset
```
- Reset server 1.  

```
racadm racreset -m server-1
```
- Reset servers 1 and 3.  

```
racadm racreset -m server-1 -m server-3
```
- Racreset on multinode server  

```
racadm racreset -m sled-1
```
- Force racreset on multinode server  

```
racadm racreset -m sled-1 -f
```

# racresetcfg

## Description

Resets CMC configuration to factory default settings.

 **NOTE: To use this, you must have the Chassis Administrator privilege.**

## Synopsis

```
racadm racresetcfg [-m <module>] [-c <feature>]
```

## Input

- -m : <module> — Must be one of the following values:
  - chassis — default state, if -m is not specified.
  - server-n, where n=1-4
  - switch-n, where n=1-2
- -c : <feature> — Must be one of the following values:
  - ad — Reset Active Directory properties to the default value. The default setting is "disabled".
  - pcap — Reset Power Cap properties to the default value.
  - flex — Reset FlexAddress properties to the default value. The default setting is "enabled".

-  **NOTE: The `-c` option is valid with only `<module=chassis>`.**

### Example

- Perform reset of configuration data to defaults for server-1 module  
`racadm racresetcfg -m server-1`
- Perform reset of power cap feature.  
`racadm racresetcfg -c pcap`
- Perform reset of configuration data to default for switch-1 module  
`racadm racresetcfg -m switch-1`

## remoteimage

### Description

Connects, disconnects, or deploys a media file on a remote server.

To use this subcommand, you must have the **Administrator** permission.

### Synopsis

- `racadm remoteimage [-m <module> | -a]`
- `racadm remoteimage -d -m <module>`
- `racadm remoteimage -d -a`
- `racadm remoteimage -s [-m <module> | -a]`
- `racadm remoteimage -c -m <module> -u <username> -p <password> -l <image_path>`
- `racadm remoteimage -c -a -u <username> -p <password> -l <image_path>`
- `racadm remoteimage -e -m module -u <username> -p <password> -l <image_path>`
- `racadm remoteimage -e -a -u <username> -p <password> -l <image_path>`

### Input

- `-c` — Connect a remote image.
- `-d` — Disconnect the remote image.
- `-e` — Deploys a remote image
- `-s` — Display the connection status; `-a` is assumed, if not specified.
- `-m <module>` — The `<module>` option can have the following values:
  - `server- $\langle n \rangle$` , where  $n=1-4$
  - `server- $\langle nx \rangle$` , where  $n=1-4$  and  $x=a-d$  (lower case)
- `-u` — Username to access the network share.
- `-p` — Password to access the network share.
- `-l` — Image location on the network share; use double quotation marks with a location.

-  **NOTE: The `-u`, `-p`, and `-l` options are applicable only to connect and deploy actions.**

### Example

- `racadm remoteimage -c -u "user" -p "pass" -l //shrloc/foo.iso`  
 Remote Image is now Configured.
- `racadm remoteimage -d`  
 Disable Remote File Started. Please check status using `-s` option to verify if the Remote File Share is ENABLED or DISABLED.
- `racadm remoteimage -s`  
 Remote File Share is Enabled.  
 UserName



Password

ShareName //192.168.0.1/xxx/dtk\_3.3\_73\_Linux.iso

## serveraction

### Description

Enables you to perform power management operations on the host system.

To use this subcommand, you must have the **Execute Server Control Commands** permission.

### Synopsis

```
racadm serveraction -m <module> <action>
```

```
racadm serveraction -a <action>
```

### Input

- `-m<module>` —  
server-*n*, where *n*=1–4
- `-a` — Performs action on all servers. Not allowed with the `powerstatus` action.
- `<action>` — Specifies the action. The options for the `<action>` string are:
  - `graceshutdown` — Performs a graceful shutdown of the server. If the operating system on the server cannot be cleanly shut down, this operation is not performed.
  - `hardreset` — Performs a reset (reboot) operation on the managed system.
  - `powercycle` — Issues a power-cycle operation on the managed system. This action is similar to pressing the power button on the system's front panel to turn off, and then turn on the system.
  - `powerdown` — Turns off the managed system.
  - `powerup` — Turns on the managed system.
  - `powerstatus` — Displays the current power status of the server (ON or OFF).
  - `reset` — Performs a virtual reset of the server. This operation simulates reseating the server by resetting the iDRAC on a server.

 **NOTE: The `reset` option is not available for individual FM120 servers.**

 **NOTE: The `-f` option is required to force the 'reset' action.**

 **NOTE: The action `powerstatus` is not allowed with an `-a` option.**

### Output

Displays an error message if the requested operation fails, or a success message if the operation is completed.

### Example

- Turn off server 3 from the CMC.  

```
racadm serveraction -m server-3 powerdown
```

Server power operation successful.
- Turn off server 3 from iDRAC.  

```
racadm serveraction powerdown
```

Server power operation successful
- Turn off server 3 from CMC when power is already turned off on that server.  

```
racadm serveraction -m server-3 powerdown
```


Server is already powered OFF.

- Turn off the server from CMC when power is already turned off on that server.  
`racadm serveraction powerdown`  
 Server is already powered OFF
- Get Power Status of server 2 on CMC  
`racadm serveraction -m server-2 powerstatus`  
 ON
- Get Power status action on multinode server:  
`racadm serveraction -m server-1a powerstatus`
- Get Power Status on iDRAC  
`racadm serveraction powerstatus`  
 Server Power Status: ON
- Reseat action on a multinode sled  
`racadm serveraction -f -m sled-1 reseat`
- Explanation of Support  
 CMC needs to support graceful shutdown  
 The support of address individual blades is expected on the CMC

## set

### Description

Import saved CMC configuration or CMC Event Filter configuration from a file.

 **NOTE: If CMC is not in the network, you cannot import the chassis configuration profile from a remote network share with proxy using the `set` command. But, you can import the chassis configuration profile from the local management station.**

### Synopsis

```
racadm -r <CMC IP> -u <CMC username> -p <CMC password> set -f <filename>
racadm -r <CMC IP> -u <CMC username> -p <CMC password> set -f <filename> -t xml
racadm set -f <filename> -t xml -u <username> -p <password> -l <CIFS share>
racadm set -f <filename> -t xml -l <NFS share>
```

### Input

- `-f`: import CMC configuration or CMC event filter from a file.
- `-u`: username of the remote share from where the file must be imported.
- `-p`: password for the remote share from where the file must be imported.
- `-l`: network share location from where the file must be imported.
- `-t`: specify the file type to be imported. The valid value is "XML".

### Example

- Configure event filter configurations from a configuration file using remote `racadm`  
`racadm -r 192.168.0.120 -u <username> -p <password> set -f file.txt`
- Configure a CMC from an XML configuration file on a local share using remote `racadm`  
`racadm -r 192.168.0.120 -u <username> -p <password> set -f myfile.xml -t xml`
- Configure a CMC from an XML configuration file on a remote CIFS share  
`racadm set -f myfile.xml -t xml -u myuser -p mypass -l //192.168.0.0/myshare`
- Configure a CMC from an XML configuration file on a remote NFS share  
`racadm set -f myfile.xml -t xml -l 192.168.0.0:/myshare`




## setassettag

### Description

Sets the N-byte ASCII asset tag for the chassis.

To use this subcommand, you must have the **Administrator** privilege.

 **NOTE: The special characters " (double quote), ` (back quote), & (ampersand), and \ (backslash) are not supported for this subcommand.**

### Synopsis

```
racadm setassettag -m chassis <asset tag>
```

### Input

**-m** <module> — Specifies the module whose asset tag you want to set.

Legal value: chassis

You can obtain the same output if you do not include this option, because there is only one legal value.

<assettag> is a maximum of 64 non-extended ASCII characters.

### Example

```
· racadm setassettag -m chassis 783839-33
· racadm setassettag 783839-33


The asset tag was changed successfully.
```

## setchassisname

### Description

Sets the name of the chassis.

To use this subcommand, you must have the **Administrator** privilege.

 **NOTE: The special characters " (double quote), ` (back quote), & (ampersand), and \ (backslash) are not supported for this subcommand.**

### Synopsis

```
racadm setchassisname <name>
```

 **NOTE: Chassis name is a maximum of 64 non-extended ASCII characters.**

### Example

```
racadm setchassisname dellchassis-1

The chassis name was set successfully.root
```


## setflexaddr

### Description

Enables or disables FlexAddress on a particular slot or fabric.

To use this subcommand, you must have the **Chassis Configuration Administrator** privilege.

If the fabric type is determined to be Infiniband, the operation is canceled and the command returns an error. If the FlexAddress feature is not activated, the command returns an error.

 **NOTE: The server must be turned off to change the slot state. All servers must be turned off to change the fabric state. The MAC/WWN addresses must be managed locally (not by an external console) to use this command.**

### Synopsis

```
racadm setflexaddr [-i <slot#> <state>][-f <fabricName> <state>]
```

< slot# > = 1 to 4

< fabricName > = A1 or A2

< state > = 0 or 1

where **0** is disable and **1** is enable.

### Input

- -i <slot#> <state> — Enables or disables FlexAddress for the specified slot.
- -f <fabricName> <state> — Enables or disables FlexAddress for the specified fabric.

### Example

- racadm setflexaddr -i 1 0  
Slot 1 FlexAddress state set successfully
- racadm setflexaddr -f A 1  
Fabric A FlexAddress state set successfully
- racadm setflexaddr -f idrac 1

## setled

### Description

Sets the state (blinking or not blinking) of the LED on the specified module.

To blink or unblink the chassis, I/O modules or the CMC, you must have the **Debug Administrator** privilege on CMC. To enable the servers to blink or unblink, you must have the **Server Administrator** or **Debug Administrator** privilege on CMC.

### Synopsis

```
racadm setled -m <module> -l <ledState>
```

### Input

- -m<module> — Specifies the module whose LED you want to configure.  
<module> can be one of the following:
  - server-n, where n=1-4
  - switch-n, where n=1-2
  - cmc-active
  - chassis
- -l<ledstate> — Specifies whether the LED should blink.  
<ledstate> can be one of the following:
  - 0 — no blinking
  - 1 — blinking

### Example

- racadm setled -m server-1 -l 1  
LED state was set successfully.

 **NOTE: The setled command generates an error when used on the extension slot of a multi-slot server.**

- racadm setled -m server-2 -l 1  
ERROR: Server in slot 9 is an extension of the server in slot 1.

# setniccfg

## Description

Sets the CMC IP address. It displays an error message if the requested operation could not be performed, or a success message, if the operation is completed successfully.

To use this subcommand, you must have the **Configure Chassis Administrator** permission.

 **NOTE: The terms NIC and Ethernet management port may be used interchangeably.**

## Synopsis

- `racadm getniccfg`
- `racadm getniccfg -m <module>`,  
where `-m` must be one of the following values:
  - `chassis`: default state if `-m` is not specified
  - `server-n`: where `n` = 1 to 4
  - `switch-n`: where `n` = 1 or 2
- `racadm setniccfg -d`
- `racadm setniccfg -d6`
- `racadm setniccfg -s <IPv4Address> <netmask> <IPv4 gateway>`
- `racadm setniccfg -s6 <IPv6 Address> <IPv6 Prefix Length> <IPv6 Gateway>`
- `racadm setniccfg -o`
- `racadm setniccfg -p [-6]`
- `racadm setniccfg [-m <module>] -k [<speed> <duplex>]`
- `racadm setniccfg [-i <slot>] -v [<vlan_id> <vlan_priority>]`

## Input

- `-d` — Enables DHCP for the NIC (default is “DHCP disabled”).
- `-d -6` — Enables AutoConfig for the NIC. It is enabled by default.
- `-s` — Enables static IP settings. The IPv4 address, netmask, and gateway can be specified. Otherwise, the existing static settings are used. `<IPv4Address >`, `<netmask >`, and `<gateway >` must be typed as dot-separated strings.  
`racadm setniccfg -s 192.168.0.120 255.255.255.0 192.168.0.1`
- `-s -6` — Enables static IPv6 settings. The IPv6 address, Prefix Length, and the IPv6 gateway can be specified.
- `-o` — Enable or disable NIC.
- `-m<module>` — Must be one of the following values:
  - `chassis`: Default state if `- m` is not specified.
  - `server-n`: where `n=1-4`
  - `server-nx`: where `n=1-4`; `x=a-d` (lower case)
  - `switch-n`: where `n=1-2`
- `-i <slot>` — Must be number `n`, where `n=1 to 4`
- `-v` — When performing on a switch, release and renew any DHCP lease on that port for the changes to be effective. The VLAN settings must be one of the following legal values:
  - no arguments imply remove vlan tag, not compatible with `server-nx`. For example (“server-4b”) notation
  - `<vlan_id>` 1 to 4000, 4021, and 4094 inclusive
  - `<vlan_priority>` 0 to 7, inclusive
- `-p` — Disables IPV4 (default)/IPV6 protocol
- `-k` — Must be one of the following legal values:
  - no arguments imply autonegotiate

- <speed> = 10, 100
- <duplex> = half, full
- -r — Enable or disable redundant mode. The legal values are:
  - 1 — Enable
  - 0 — Disable

 **NOTE: The options -o, -k, -p, and -r can be specified for chassis only.**

- -6:
  - Sets static IPv6 addresses (w/ -s option).
  - Enables autoconfig for IPv6 (w/ -d option).
  - Disables IPv6 (w/ -p option).
  - Can be specified for chassis or servers.

### Example

- `racadm setniccfg -s 192.168.0.120 255.255.255.0 192.168.0.1`
- `racadm setniccfg -d`
- `racadm setniccfg -d6`
- Configuration of speed = 100Mbps and duplex= full duplex:  
`racadm setniccfg -k 100 full`
- Configuration of speed and duplex to autonegotiate:  
`racadm setniccfg -k`
- Configuration of redundant mode:  
`racadm setniccfg -r 1`
- Configuration of VLAN id and priority of a slot or all blades in a sleeve:  
`racadm setniccfg -i 5 -v 1000 7`
- Configuration of CMC to a static IPv6 address:  
`racadm setniccfg -m chassis -s -6 2001:DB8::2 64 2001:DB8::1`
- Configuration of server to use stateless autoconfiguration address:  
`racadm setniccfg -m server-1 -d -6`
- Configuration of VLAN id and priority for a switch:  
`racadm setniccfg -m switch-1 -v 1000 7`
- Removal of VLAN configuration from a switch:  
`racadm setniccfg -m switch-1 -v`

## setractime

### Description

Sets the date and time on the CMC.

To use this subcommand, you must have the **Administrator** privilege.

### Synopsis

- `racadm setractime -d <yyyymmddhhmmss.mmmmmmmsoff>`
- `racadm setractime -l YYYYMMDDhhmmss`
- `racadm setractime -z {?|timezone|timezone-prefix*}`

### Input


- -d — Sets the time in the string yyyymmddhhmmss.mmmmmmmsoff where:
  - yyyy is the year



- mm is the month
- dd is the day
- hh is the hour
- mm is the minutes
- ss is the seconds
- mmmmmm is the number of microseconds
- s is a + (plus) sign or a - (minus) sign, which indicates the sign of the offset.
- off is the offset in minutes

 **NOTE: 'Off' is the offset in minutes from GMT and must be in 15-minute increments. The timezone is represented as an offset from GMT, and the clock does not automatically adjust to daylight savings time (for the '-d' option).**

- -z <zone> - Sets the time zone by name or index, or lists possible time zones. For example, PST8PDT (Western United States), 294 (Seoul), 344 (Sydney). <zone> may be:
  - <?> lists the major timezone names/prefixes.
  - <timezone> is the case-sensitive name of your timezone or the index listed by '-z timezone-prefix\*!.
  - <timezone-prefix\*> is a prefix of one or more timezones, followed by '!\*

 **NOTE: The timezone or daylight savings time is fully supported for '-l' and '-z' options. Omit the '-l' option to set the timezone only (eg. '-z US/Central').**

- -l — Sets the local date and time in the string yyymmddhhmmss where:
  - yyyy is the year
  - mm is the month
  - dd is the day
  - hh is the hour
  - mm is the minute
  - ss is the second

— Setting the time using the -l and -z options is recommended. This command format allows the CMC to fully support local time zones, including the ability to automatically adjust the CMC time to the local Daylight Savings Time.

### Example

The setractable subcommand supports dates ranging from 1/1/1970 00:00:00 through 12/31/2030 23:59:59. To set the local time to October 24, 2007 at 3:02:30 PM:

```
racadm setractable -l 20071024150230
```

The time was set successfully.

## setslotname

### Description

Sets the name of the slot and enables the feature to display the host name (if available) or iDRAC DNS name of all the four slots, or of a specified slot (indicated by the slot number) in the chassis. Optionally, use this command to set whether the slot name or host name is displayed in

the CMC web interface or with the **getslotname -i <slot Num>** command. If the host name is not available, the static slot name is used.

To use this subcommand, you must have the **Administrator** privilege.

 **NOTE:**

- The OMSA server agent must be present and running on the server to use the Display Hostname feature. If the agent is not running, the setting is ignored. For more information, see the *Dell OpenManage Server Administrator User's Guide* at [support.dell.com/manuals](http://support.dell.com/manuals).
- The special characters " (double quote), ` (back quote), & (ampersand), and \ (backslash) are not supported for this subcommand.

**Synopsis**

- `racadm setslotname [-i <slotNum> <slotname> | -h 0|1|2]`
- `racadm setslotname -h <value>`

**Input**

- `-i <slotNum>` — Specify the slot number in the chassis. Valid values: 1 to 4.
- `<slotname>` — The new name to be assigned to the slot.
- `-h <values>` — Displays the Hostname, Slotname, or iDRAC DNS name. The legal values are:
  - 0 — Displays the Slotname
  - 1 — Displays the Hostname
  - 2 — Displays the iDRAC DNS name

**Example**


- Set the name of slot 3 as server3:  
`racadm setslotname -i 3 server3`
- Enable system to display host names (1=Hostname):  
`racadm setslotname -h 1`

## setsysinfo

**Description**

Sets the name or location of the chassis.

To use this subcommand, you must have the **Administrator** privilege.

 **NOTE: The special characters " (double quote), ` (back quote), &(ampersand), and \ (backslash) are not supported for this subcommand.**

**Synopsis**

`racadm setsysinfo [-c chassisname|chassislocation] <string>`

**Input**

- `<string>` — Indicates a maximum of 64 non-extended ASCII chassis name or location.
- `-c` — Sets the chassis name or location.

**Example**

```
racadm setsysinfo -c chassisname "Dell Rack System"
The chassis name was set successfully.
```

## SSH or Telnet RACADM

- `racadm getconfig -g <groupname> [-o <objectname>][-i <indexnumber>]`
- `racadm <subcommand>`

**Example**

- `racadm getconfig -g idracinfo`



## sshpkauth

### Description

Enables you to upload and manage up to four different SSH public keys per user. You can upload a key file or key text, view keys, or delete keys.

RSA key size should be between 768 and 4096 and the recommended DSA key size is 1024.

This command has three mutually exclusive modes—upload, view, and delete that are determined by the options.

### Upload

The upload mode allows you to upload a keyfile or to copy the key text on the command line. You cannot upload and copy a key at the same time.

Remote RACADM:

```
racadm sshpkauth -i <2 to 16> -k <1 to 4> -f <filename>
racadm sshpkauth -i <2 to 16> -k <1 to 4> -t
<key-text>
```

Telnet/ssh/serial RACADM:

```
racadm sshpkauth -i <2 to 16> -k <1 to 4> -t
<key-text>
```

### View

The view mode allows the user to view a key specified by the user or all keys.

```
racadm sshpkauth -i <2 to 16> -v -k <1 to 4>
racadm sshpkauth -i <2 to 16> -v -k all
```

### Delete

The delete mode allows the user to delete a key specified by the user or all keys.

```
racadm sshpkauth -i <2 to 16> -d -k <1 to 4>
racadm sshpkauth -i <2 to 16> -d -k all
```

### Synopsis

```
racadm sshpkauth
```

### NOTE:

For DSA keys greater than 2048, use the following racadm command. CMC accepts RSA keys up to key strength 4096, but the recommended key strength is 1024.

```
racadm -r 192.168.8.14 -u root -p <default root user password>
sshpkauth -i svcacct -k 1 -p 0xffff -f dsa_2048.pub
```

### Input

- **-i** < user index > - Index for the user. <user index> must be between 2 and 16 on iDRAC.
- **-k** [< key index > | all] - Index to assign the PK key being uploaded. *all* only works with the *-v* or *-d* options. <key index> must be between 1 and 4 or *all* on iDRAC.
- **-t** < PK Key Text > - Key text for the SSH Public key.
- **-f** < filename > - File containing the key text to upload. The *-f* option is not supported on Telnet/ssh/serial RACADM.
- **-v** - View the key text for the index provided.
- **-d** - Delete the key for the index provided.

## Examples :

- Upload an invalid key to iDRAC User 2 in the first key space using a string:  

```
$ racadm sshpkauth -i 2 -k 1 -t "This is invalid key Text"
```

ERROR: Key text appears to be corrupt
- Upload a valid key to iDRAC User 2 in the first key space using a file:  

```
$ racadm sshpkauth -i 2 -k 1 -f pkkey.key
```

Key file successfully uploaded.
- Get all keys for User 2 on iDRAC:  

```
$ racadm sshpkauth -v -i 2 -k all
```

```
***** User ID 2 *****
```

Key ID 1:

```
ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEAzzy+k2npnKqVEXGXIZo0sbR6JgA5YNbWs3ekoxXV
fe3yJVpVc/5zrrr7XrwKbJAJTqSw8Dg3iR4n3vUaP+lPHmUv5Mn55Ea6LHUs1AXFqXmOd1Thd
wilU2VLw/iRH1ZymUFnut8gggPQgqV2L8bsUaMqb5PooIIvV6hy4isCNJU=
1024-bit RSA, converted from OpenSSH by xx_xx@xx.xx
```

Key ID 2:  
Key ID 3:  
Key ID 4:

## sslkeyupload

### Description

Uploads SSL key from the client to CMC.

To use this subcommand, you must have **Server Administrator** permission.

### Synopsis

```
racadm sslkeyupload -t <type> -f <filename>
```

### Input

- **-t** — Specifies the key to upload.  
1 = SSL key used to generate the server certificate
- **-f** — Specifies the file name of the SSL key to be uploaded.

### Output

Returns 0 when successful and a nonzero number when unsuccessful.

### Example

```
racadm sslkeyupload -t 1 -f c:\sslkey.txt
```

## sslcertupload

### Description

Uploads a custom SSL server or CA certificate for Directory Service from the client to CMC.

To use this subcommand, you must have the **Server Administrator** permission.

### Synopsis

```
racadm sslcertupload -t <type> [-f <filename>]
```

### Input

- **-t** — Specifies the type of certificate to upload, either the CA certificate for Directory Service or the server certificate.  
— 1 = server certificate.  
— 2 = CA certificate for Directory Service
- **-f** — Specifies the file name of the certificate to be uploaded.
- **-e** — Allows for upload of multiple certificate format types.



- 1 = Base64

- 2 = PKCS12

The current release does not support this option.

- -p — Pin for decrypting the PKCS12 file uploaded.  
If *<format type>* is selected as 2, it is mandatory to specify -p option.

The current release does not support this option.

### Output

The `sslcertupload` command returns 0 when successful, and returns a nonzero number when unsuccessful.

### Example

```
racadm sslcertupload -t 1 -f c:\cert\cert.txt
```

## sslcertview

### Description

Displays the SSL server or CA certificate that exists on CMC..

To use this subcommand, you must have the **CMC Login User** privilege.

### Synopsis

```
racadm sslcertview -t <type> [-A]
```

### Input

- -t — Specifies the type of certificate to view, either the CA certificate or server certificate.  
—1 = server certificate  
—2 = CA certificate for Directory Service.
- -A — Prevents printing of headers or labels.

### Output

```
racadm sslcertview -t 1
```

```
Serial Number 00
```

#### Subject Information:

```
Country Code (CC) US
State (S) Texas
Locality (L) Round Rock
Organization (O) Dell Inc.
Organizational Unit (OU) Remote Access Group
Common Name (CN) CMC Default certificate
```

#### Issuer Information:

```
Country Code (CC) US
State (S) Texas
Locality (L) Round Rock
```

```

Organization (O) Dell Inc.
Organizational Unit (OU) Remote Access Group
Common Name (CN) CMC Default certificate
Common Name (CN) CMC Default certificate
Valid From Jul 8 16:21:56 2005 GMT
Valid To Jul 7 16:21:56 2010 GMT

```

```
racadm sslcertview -t 1 -A
```

```

00
US
Texas
Round Rock
Dell Inc.
Remote Access Group
CMC default certificate
US
Texas
Round Rock
Dell Inc.
Remote Access Group
CMC default certificate
Jul 8 16:21:56 2005 GMT
Jul 7 16:21:56 2010 GMT

```

## sslcsrgen

### Description

Generates and downloads a CSR file to the client's local file system. The CSR can be used for creating a custom SSL certificate that can be used for SSL transactions on CMC.


To use this subcommand, you must have the **Chassis Configuration Administrator** permission.

### Synopsis

- `racadm sslcsrgen [-g] [-f <filename>]`
- `racadm sslcsrgen -s`

### Input

- **-g** — Generates a new CSR.
- **-s** — Returns the status of a CSR generation process (generation in progress, active, or none).
- **-f** — Specifies the filename of the location, <filename>, where the CSR is downloaded.

 **NOTE: If the -f option is not specified, the filename defaults to sslcsr in your current directory.**

### Output

If no options are specified, a CSR is generated and downloaded to the local file system as sslcsr by default. The -g option cannot be used with the -s option, and the -f option can only be used with the -g option.



The `sslcsr`gen -s subcommand returns one of the following status codes:


- CSR was generated successfully.
- CSR does not exist.

#### Example

```
racadm sslcsrigen -s

or

racadm sslcsrigen -g -f c:\csr\csrtest.txt
```

 **NOTE:** Before a CSR can be generated, the CSR fields must be configured in the RACADM `cfgRacSecurity` group. For example: `racadm config -g cfgRacSecurity -o cfgRacSecCsrCommonName MyCompany`

 **NOTE:** In telnet/ssh console, you can only generate and not download the CSR file.

 **NOTE:** The duration for generating a CSR key depends on the length specified for the key.

## sslresetcfg

#### Description

Restores the web-server certificate to factory default and restarts web-server. The certificate takes effect 30 seconds after the command is entered.

To use this subcommand, you must have the **Chassis Configuration Administrator** privilege for CMC.

#### Synopsis

```
racadm sslresetcfg
```

#### Example

```
$ racadm sslresetcfg

Certificate generated successfully and webserver restarted.
```

## testemail

#### Description

Sends a test e-mail from CMC to a specified destination. Prior to executing the test e-mail command, make sure that the SMTP server is configured and the specified index in the **RACADM `cfgEmailAlert`** group is enabled and configured properly.

#### Synopsis

```
racadm testemail -i <index>
```

#### Input

-i — Specifies the index of the e-mail alert to test.

#### Output

Success: Test e-mail sent successfully

Failure: Unable to send test e-mail

#### Example

Commands for the **cfgEmailAlert** group:

- Enable the alert —  
`racadm config -g cfgEmailAlert -o cfgEmailAlertEnable -i 1`
- Set the destination e-mail address —  
`racadm config -g cfgEmailAlert -o cfgEmailAlertAddress -i 1 user1@mycompany.com`
- Set the custom message that is sent to the destination e-mail address —  
`racadm config -g cfgEmailAlert -o cfgEmailAlertCustomMsg -i 1 "This is a test!"`
- Make sure that the SMTP IP address is configured properly —  
`racadm config -g cfgRemoteHosts -o cfgRhostsSmtpServerIpAddr 192.168.0.152`

- View the current e-mail alert settings —  
`racadm getconfig -g cfgEmailAlert -i <index>`  
 where <index> is a number from 1 to 4.

## testfeature

The following tables describe the **testfeature** subcommand options.

| Option                | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>-f</b> <feature>   | Specifies the feature name. <b>testfeature</b> supports the following features: <ul style="list-style-type: none"> <li>• <code>ad</code> — Tests Active Directory configuration using simple authentication (user name and password).</li> <li>• <code>adkrb</code> — Tests Active Directory configuration using the Kerberos authentication.</li> <li>• <code>ldap</code> — Tests LDAP configuration and operation (requires user name and password).</li> </ul> |
| <b>-u</b> <username > | The user name specified in an appropriate format for the selected authentication method. That is, Active Directory users are specified as <code>user_name@domain_name</code> .                                                                                                                                                                                                                                                                                    |
| <b>-p</b> <password > | The password for the indicated user account.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>-d</b> <bitmask >  | A bitmask (specified as a hexadecimal value) to select various diagnostic messaging levels. This option is optional.                                                                                                                                                                                                                                                                                                                                              |



**NOTE: -d option is not supported with the remote racadm interface.**

### testfeature -f ad

#### Description

Tests Active Directory configuration using simple authentication (user name and password). Use the optional `-d` switch to obtain additional diagnostic information, as needed.

This subcommand when executed performs the following:

- Checks command syntax.
- Verifies whether the required system resources are available.
- Validates Active Directory configuration.
- Verifies the SSL certificate and if the certificate signing request (key) exists.
- Acquires LDAP and Global Catalog Service records from DNS.
- Acquires user privileges from the Active Directory server.
- Checks the time to acquire user privileges with the allotted time to login.



**NOTE: In the event of an error, the command displays the test that failed, all the tests performed earlier to the test that failed, and all the error messages.**

#### Synopsis

```
testfeature -f ad -u <username> -p <password> [-d <diagnostic-
message-level>]
```

#### Example

- `testfeature -f ad -u user@domain -p secret`  
`SUCCESSFUL: User permissions are xxxxxppp.`  
  
 The last three digits are the user's permissions.
- `testfeature -f adkrb -u user_name@domain_name`  
`SUCCESSFUL: User permissions are 80000fff.`
- `testfeature -f ldap -u harold -p barrel`



```
SUCCESSFUL: User permissions are 0x00000fff.
```

## testfeature -f adkrb

### Description

Tests the Active Directory configuration using the Kerberos authentication (single sign-on or Smart Card login). Use the optional **-d** switch to obtain additional diagnostic information, as needed. This subcommand, when run, performs the following:

- Checks command syntax.
- Verifies if the required system resources are available.
- Validates Active Directory configuration.
- Verifies if the SSL certificate and certificate signing request (key) exists.
- Acquires LDAP and Global Catalog Service records from DNS.
- Verifies if the CMC can acquire CMC, LDAP and Global Catalog servers FQDN through reverse IP lookups.
- Verifies that the CMC principal name matches the principal name in the uploaded Keytab file.
- Verifies that the CMC acquires a Kerberos TGT.
- Acquires user privileges from the Active Directory server.
- Checks the time to acquire user privileges with the allotted time to login.



**NOTE: In the event of an error, the command outputs all tests performed up to and including the test that failed, and all the error messages.**

### Synopsis

```
testfeature -f adkrb -u <username> [-d <diagnostic-message-level>]
```

## testfeature -f ldap

### Description

Tests LDAP configuration and operation, and reports success as each stage of the authentication process proceeds. After successful completion, this command prints the CMC privileges assumed by the specified *<username>*.

If a failure occurs, the command stops with an error message that displays the required corrective action. Use the optional **-d** switch to obtain additional diagnostic information, as needed.

### Synopsis

```
testfeature -f ldap -u <username> -p <password> [-d <diagnostic-message-level>]
```

## testtrap

### Description

Tests the RAC's SNMP trap alerting feature by sending a test trap from CMC to a specified destination trap listener on the network.

To use this subcommand, you must have the **Test Alerts** permission.



**NOTE: Before you execute the testtrap subcommand, make sure that the specified index in the RACADM cfgAlerting group is configured properly.**

### Synopsis

```
racadm testtrap -i <index>
```

### Input

**-i** — Specifies the index of the trap configuration to be used for the test. Valid values are from 1 to 4.

### Example

Commands for the `cfgIpmiPet` group:

- Enable the alert  
`racadm config -g cfgIpmiPet -o cfgIpmiPetAlertEnable -i 1`
  - Set the destination e-mail IP address  
`racadm config -g cfgIpmiPet -o cfgIpmiPetAlertDestIpAddr -i 1 192.168.0.110`
  - View the current test trap settings  
`racadm getconfig -g cfgIpmiPet -i <index>`
- where <index> is a number from 1 to 4.

## traceroute

### Description

Traces the network path of routers that packets take as they are forwarded from your system to a destination IPv4 address.

To use this subcommand, you must have the **Administrator** permission.

### Synopsis

- `racadm traceroute <IPv4 address>`
- `racadm traceroute 192.168.0.1`

### Input

```
racadm traceroute 192.168.0.1
```

### Output

```
traceroute to 192.168.0.1 (192.168.0.1), 30 hops
max,
40 byte packets
1 192.168.0.1 (192.168.0.1) 0.801 ms 0.246 ms 0.253 ms
```

## traceroute6

### Description

Traces the network path of routers that packets take as they are forwarded from your system to a destination IPv6 address.

To use this subcommand, you must have the **Administrator** permission.

### Synopsis

- `racadm traceroute6 <IPv6 address>`
- `racadm traceroute6 fd01::1`

### Output


```
traceroute to fd01::1 (fd01::1) from fd01::3,
30 hops
max, 16 byte packets
1 fd01::1 (fd01::1) 14.324 ms 0.26 ms 0.244 ms
```



# CMC Property Database Group and Object Descriptions

The CMC property database contains the configuration information for CMC. Data is organized by associated object, and objects are organized by object group. The IDs for the groups and objects that the property database supports are listed in this section for CMC.

Use the group and object IDs with the RACADM subcommands to configure CMC.

 **NOTE: RACADM sets the value of objects without performing any functional validation on them. For example, RACADM allows you to set the Certificate Validation object to 1 with the Active Directory object set to 0, even though Certificate Validation can happen only if Active Directory is enabled. Similarly, the cfgADSSOEnable object can be set to 0 or 1 even if the cfgADEnable object is 0, but it takes effect only if Active Directory is enabled.**

All string values are limited to displayable ASCII characters, except where otherwise noted.

## idRacInfo

This group contains display parameters to provide information about the specifics of CMC being queried. One instance of the group is allowed.

Use this object with the `getConfig` subcommand.

To use this object, you must have **CMC Login User** privilege.

The following sections provide information about the objects in the **idRACInfo** group.

### idRacProductInfo (Read Only)

|                          |                                            |
|--------------------------|--------------------------------------------|
| <b>Description</b>       | A text string that identifies the product. |
| <b>Legal Values</b>      | A string of up to 63 ASCII characters.     |
| <b>Default for iDRAC</b> | Integrated Dell Remote Access Controller.  |
| <b>Default for CMC</b>   | Chassis Management Controller.             |

### idRacDescriptionInfo (Read Only)

|                     |                                                                                                          |
|---------------------|----------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | A text description of the RAC type.                                                                      |
| <b>Legal Values</b> | A string of up to 255 ASCII characters.                                                                  |
| <b>Default</b>      | This system component provides a complete set of remote management functions for Dell PowerEdge servers. |

## idRacVersionInfo (Read Only)

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| <b>Description</b>  | String containing the current product firmware version. |
| <b>Legal Values</b> | A string of up to 63 ASCII characters.                  |
| <b>Default</b>      | The current version number.                             |

## idRacBuildInfo (Read Only)

|                        |                                                           |
|------------------------|-----------------------------------------------------------|
| <b>Description</b>     | String containing the current RAC firmware build version. |
| <b>Legal Values</b>    | A string of up to 16 ASCII characters.                    |
| <b>Default for CMC</b> | The current CMC firmware build version.                   |

## idRacName (Read Only)

|                 |                                                   |
|-----------------|---------------------------------------------------|
| Description     | A user-assigned name to identify this controller. |
| Legal Values    | A string of up to 15 ASCII characters.            |
| Default for CMC | CMC                                               |

## cfgLanNetworking

This group contains parameters to configure CMC NIC for IPv4.

One instance of the group is allowed. Some objects in this group may require CMC NIC to be reset, which may cause a brief loss in connectivity. Objects that change CMC NIC IP address settings close all active user sessions and require users to reconnect using the updated IP address settings.

For CMC, use this object with the **config** or **getconfig** subcommands.

To use this object property for CMC, you must have the Chassis Configuration Administrator privilege.

 **NOTE: For CMC, you can configure a setting that does not have a hash sign (#) prefixed in the output. To modify a configurable object, use the -o option.**

The following sections provide information about the objects in the **cfgLanNetworking** group.

### cfgNicIPv4Enable (Read or Write)

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the IPv4 stack.                                                 |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>· 1 (TRUE)</li><li>· 0 (FALSE)</li></ul>      |
| <b>Default</b>      | <ul style="list-style-type: none"><li>· For iDRAC: 0</li><li>· For CMC: 1</li></ul> |



## cfgNicVlanEnable (Read or Write)

|                     |                                                                                                                                                                                                                                                         |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the VLAN capabilities.<br><br>All chassis management traffic, including the CMC and all iDRACs, resides on this external VLAN when enabled. No iDRAC configuration change is required to use this external management network VLAN. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>· 1 (TRUE)</li><li>· 0 (FALSE)</li></ul>                                                                                                                                                                          |
| <b>Default</b>      | <b>0</b>                                                                                                                                                                                                                                                |
| <b>Example</b>      | <ul style="list-style-type: none"><li>· <code>racadm config -g cfgLanNetworking -o cfgNicVlanEnable 1</code></li><li>· <code>racadm config -g cfgLanNetworking -o cfgNicVlanEnable 0</code></li></ul>                                                   |

## cfgNicVlanId (Read or Write)

|                     |                                                                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the VLAN ID for the network VLAN configuration in CMC. This property is only valid if <code>cfgNicVlanEnable</code> is set to 1 (enabled). |
| <b>Legal Values</b> | 1 – 4000 and 4021 – 4094                                                                                                                             |
| <b>Default</b>      | 1                                                                                                                                                    |
| <b>Example</b>      | <code>racadm config -g cfgLanNetworking -o cfgNicVlanID 1</code>                                                                                     |

## cfgNicVlanPriority (Read or Write)

|                     |                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the VLAN Priority for the network VLAN configuration in CMC. This property is only valid if <code>cfgNicVlanEnable</code> is set to 1 (enabled). |
| <b>Legal Values</b> | 0 – 7                                                                                                                                                      |
| <b>Default</b>      | 0                                                                                                                                                          |
| <b>Example</b>      | <code>racadm config -g cfgLanNetworking -o</code><br><code>cfgNicVlanPriority 7</code>                                                                     |

## cfgDNSDomainNameFromDHCP (Read/Write)

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies that the DNS domain name should be assigned from the network DHCP server. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>· 1 (TRUE)</li><li>· 0 (FALSE)</li></ul>      |
| <b>Default</b>      | 0                                                                                   |


This property is used only if `cfgNicUseDhcp` is set to 1 (true), or if both `cfgCurrentIPv6Enabled` and `cfgIPv6AutoConfig` are set to 1 (true).

The CMC can obtain its DNS domain name from either a DHCP or DHCPv6 server, if all of the following properties are set to 1 (true):


- `cfgNicIPv4Enable`
- `cfgNicUseDhcp`
- `cfgCurrentIPv6Enabled`
- `cfgIPv6AutoConfig`
- `cfgDNSDomainNameFromDHCP`
- `cfgDNSDomainName` (Read/Write)

The network administrator must make sure that these DHCP servers are configured to provide the same DNS domain name to the CMC, otherwise the domain name becomes unpredictable.

## cfgDNSDomainName (Read or Write)

|                     |                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | In the DNS domain name, parameter is only valid if <code>cfgDNSDomainNameFromDHCP</code> is set to 0 (FALSE).                                                                                                                                                                                                                                                |
| <b>Legal Values</b> | A string of up to 254 ASCII characters. At least one of the characters must be alphabetic. Characters are restricted to alphanumeric, '-', and '!'.<br><br> <b>NOTE: Microsoft Active Directory only supports Fully Qualified Domain Names (FQDN) of 64 bytes or fewer.</b> |
| <b>Default</b>      | <blank>                                                                                                                                                                                                                                                                                                                                                      |

## cfgDNSRacName (Read/Write)

|                     |                                                                                                                                                                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Displays the CMC name, which is <code>rac-service</code> tag by default. This parameter is only valid if <code>cfgDNSRegisterRac</code> is set to 1 (TRUE).                                                                                               |
| <b>Legal Values</b> | A string of up to 63 ASCII characters. At least one character must be alphabetic.<br><br> <b>NOTE: Some DNS servers only register names of 31 characters or fewer.</b> |
| <b>Default</b>      | <code>cmc-&lt;service tag&gt;</code>                                                                                                                                                                                                                      |

## cfgDNSRegisterRac (Read/Write)

|                     |                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Registers the CMC name on the DNS server. When you set this parameter, the CMC registers its DNS name for its IPv4 and IPv6 addresses with the DNS server. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>· 1 (TRUE)</li><li>· 0 (FALSE)</li></ul>                                                                             |
| <b>Default</b>      | 0                                                                                                                                                          |

 **NOTE: For IPv6, only the DHCPv6 address or static address is registered.**



**Example:**

```


racadm getconfig -g cfgLanNetworking
cfgNicEnable=1
cfgNicIPv4Enable=1
cfgNicIpAddress=192.168.0.120
cfgNicNetmask=255.255.255.0
cfgNicGateway=192.168.0.1
cfgNicUseDhcp=1
cfgNicMacAddress=00:00:00:00:00:01
cfgNicVlanEnable=0
cfgNicVlanID=1
cfgNicVlanPriority=0
cfgDNSServersFromDHCP=1
cfgDNSServer1=192.168.0.5
cfgDNSServer2=192.168.0.6
cfgDNSRacName=cmc-frankly
cfgDNSDomainName=fwad.lab
cfgDNSDomainNameFromDHCP=1
cfgDNSRegisterRac=1

```

**cfgDNSServersFromDHCP (Read/Write)**

|                     |                                                                                                                                                                                           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies if the DNS server IPv4 addresses should be assigned from the DHCP server on the network.<br><br>For CMC, this property is used only if <b>cfgNicUseDhcp</b> is set to 1 (true). |
| <b>Legal Values</b> | <ul style="list-style-type: none"> <li>· 1 (TRUE)</li> <li>· 0 (FALSE)</li> </ul>                                                                                                         |
| <b>Default</b>      | 0                                                                                                                                                                                         |

**cfgDNSServer1 (Read/Write)**

|                     |                                                                                                                                                                                                                                                                                                                                       |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the IPv4 address for DNS server 1. This property is only valid if <b>cfgDNSServersFromDHCP</b> is set to <b>0</b> (FALSE).<br><br> <b>NOTE: cfgDNSServer1 and cfgDNSServer2 may be set to identical values while swapping addresses.</b> |
| <b>Legal Values</b> | String representing a valid IPv4 address. For example: 192.168.0.20.                                                                                                                                                                                                                                                                  |
| <b>Default</b>      | 0.0.0.0                                                                                                                                                                                                                                                                                                                               |

## cfgDNSServer2 (Read/Write)

**Description** Retrieves the IPv4 address for DNS server 2. This parameter is only valid if **cfgDNSServersFromDHCP** is set to 0 (FALSE).

 **NOTE: cfgDNSServer1 and cfgDNSServer2 may be set to identical values while swapping addresses.**

**Legal Values** String representing a valid IPv4 address. For example: 192.168.0.20.

**Default** 0.0.0.0

## cfgNicEnable (Read/Write)

**Description** Enables or disables CMC network interface controller. If the NIC is disabled, the remote network interfaces to CMC are no longer accessible and CMC are only available through the local or serial RACADM interface.

**Legal Values**

- 1 (TRUE)
- 0 (FALSE)

**Default** 1

## cfgNicIpAddress (Read/Write)

**Description** Specifies the static IPv4 address to be assigned to the RAC or CMC.

 **NOTE: This parameter is only configurable if the cfgNicUseDhcp parameter is set to 0 (FALSE.)**

**Legal Values** String representing a valid IPv4 address. For example: 192.168.0.20.

**Default** 192.168.0.120

## cfgNicNetmask (Read/Write)

**Description** The subnet mask used for CMC IP address.

This property is only valid if **cfgNicUseDhcp** is set to 0 (FALSE).

 **NOTE: This parameter is only configurable if the cfgNicUseDhcp parameter is set to 0 (FALSE).**

**Legal Values** String representing a valid subnet mask. For example: 255.255.255.0.

**Default** 255.255.255.0

## cfgNicGateway (Read/Write)

**Description** CMC gateway IPv4 address.

The gateway IPv4 address used for static assignment of the RAC IP address. This property is only valid if **cfgNicUseDhcp** is set to 0 (FALSE).



 **NOTE: This parameter is only configurable if the `cfgNicUseDhcp` parameter is set to 0 (FALSE).**

**Legal Values** String representing a valid gateway IPv4 address. For example: 192.168.0.1.

**Default** 192.168.0.1

## cfgNicUseDhcp (Read or Write)

**Description** Specifies whether DHCP is used to assign the CMC IPv4 address. If this property is set to 1(TRUE), then CMC IPv4 address, subnet mask and gateway are assigned from the DHCP server on the network. If this property is set to 0 (FALSE), the user can configure the `cfgNicIpAddress`, `cfgNicNetmask` and `cfgNicGateway` properties.

**Legal Values**

- 1 (TRUE)
- 0 (FALSE)

**Default** 0

## cfgNicMacAddress (Read Only)

**Description** The CMC NIC MAC address in the format: dd:dd:dd:dd:dd:dd, where d is a hexadecimal digit in range 0 - 9, A - F


**Legal Values** String representing CMC NIC MAC address.

**Default** The current MAC address of CMC NIC. For example, 00:12:67:52:51:A3.

## cfgUserAdmin

This group provides configuration information about the users who are allowed to access CMC through the available remote interfaces.

Up to 16 instances of the user group are allowed. Each instance represents the configuration for an individual user.

 **NOTE: In the current CMC firmware version, the objects `cfgUserAdminEnable` and `cfgUserAdminPrivilege` are interrelated; changing the value of one property causes the value of the other property to change. For example, if a user does not have login privilege, the user is disabled by default. When you enable the user by changing the value of `UserAdminEnable` to 1, the right most digit of the `UserAdminPrivilege` also becomes 1. On the other hand, if you change the right-most digit of the `UserAdminPrivilege` to 0, the value of `UserAdminEnable` becomes 0.**

Use this object with the `config` or `getconfig` subcommands. You must supply an index group number to use these commands as follows: `-i <index group>`

To use this object property, you must have the **User Configuration Administrator** privilege.

The following sections provide information about the objects in the `cfgUserAdmin` group.

## cfgUserAdminIndex (Read Only)

**Description** The unique index of a user.

The index number is used to specify a unique group name. Only valid for indexed groups.

**Legal Values**

The parameter is specified by a decimal integer from 1–16.

**Default**

< index of the instance >

### cfgUserAdminPrivilege (Read/Write)

**Description**

This property specifies the role-based authority privileges allowed for the user. The value is represented as a bit mask that allows for any combination of privilege values. The table below describes the user privilege bit values that can be combined to create bit masks.

**Legal Values**

0x0000000-0x0000fff, and 0x0

**Default**

0x00000000

**Example**

```
racadm getconfig -g cfgUserAdmin -i 1

cfgUserAdminIndex=1
cfgUserAdminEnable=1
cfgUserAdminUserName=root
cfgUserAdminPassword=***** (Write-Only)
cfgUserAdminPrivilege=0x00000fff
```

The following table lists the bit masks for user privileges.

| <b>iDRAC Specific User Privilege</b> | <b>Privilege Bit Mask</b> |
|--------------------------------------|---------------------------|
| Login to iDRAC                       | 0x00000001                |
| Configure iDRAC                      | 0x00000002                |
| Configure Users                      | 0x00000004                |
| Clear Logs                           | 0x00000008                |
| Execute Server Control Commands      | 0x00000010                |
| Access Virtual Console               | 0x00000020                |
| Access Virtual Media                 | 0x00000040                |
| Test Alerts                          | 0x00000080                |
| Execute Debug Commands               | 0x00000100                |
| <b>CMC Specific User Privilege</b>   |                           |
| CMC Login User                       | 0x00000001                |
| Chassis Configuration Administrator  | 0x00000002                |
| User Configuration Administrator     | 0x00000004                |



|                               |           |
|-------------------------------|-----------|
| Clear Logs Administrator      | 0x0000008 |
| Chassis Control Administrator | 0x0000010 |
| Super User                    | 0x0000020 |
| Server Administrator          | 0x0000040 |
| Test Alert User               | 0x0000080 |
| Debug Command Administrator   | 0x0000100 |
| Fabric A Administrator        | 0x0000200 |
| Fabric B Administrator        | 0x0000400 |
| Fabric C Administrator        | 0x0000800 |

### Examples

The following table provides sample privilege bit masks for users with one or more privileges.

| User Privilege(s)                                                                  | Privilege Bit Mask                                |
|------------------------------------------------------------------------------------|---------------------------------------------------|
| The user is not allowed to access CMC.                                             | 0x00000000                                        |
| The user may only log in to CMC and view CMC and server configuration information. | 0x00000001                                        |
| The user may log in to CMC and change configuration.                               | 0x00000001 + 0x00000002 = 0x00000003              |
| The user may log in, access Virtual Media, and Virtual Console.                    | 0x00000001 + 0x00000040 + 0x00000080 = 0x000000C1 |

### cfgUserAdminUserName (Read/Write)

#### Description

The name of the user for this index. The user index is created by writing a string into this name field if the index is empty. Writing a string of double quotation marks ("" ) deletes the user at that index. You cannot change the name. You must delete and then recreate the name. The string cannot contain / (forward slash), \ (backward slash), . (period), @ (at symbol), " (quotation marks), ; (semicolon), or ' (backward quote)



**NOTE: This property value must be unique among user names.**

#### Legal Values

A string of up to 16 ASCII characters.

#### Default

- root (User 2)
- <blank> (All others)

### cfgUserAdminPassword (Write Only)

#### Description

The password for this user. User passwords are encrypted and cannot be seen or displayed after the property is written.

#### Legal Values

A string of up to 20 ASCII characters.

**Default** \*\*\*\*\*

## cfgUserAdminEnable (Read/Write)

**Description** Enables or disables an individual user.



**NOTE: You can enable a user for a given index, only if you set the password for the same user.**

**Legal Values**

- 1 (TRUE)
- 0 (FALSE)

**Default** 0

## cfgEmailAlert

This group contains parameters to configure e-mail alerting capabilities. Up to four instances of this group are allowed.

Use this object with the `getConfig` and `config` subcommands.

To use this object property for, you must have **Chassis Configuration Administrator** privileges.

The following sections provide information about the objects in the **cfgEmailAlert** group.

### cfgEmailAlertIndex (Read Only)

**Description** The unique index of an alert instance.

**Legal Values** 1-4

**Default** <instance>

### cfgEmailAlertEnable (Read/Write)

**Description** Enables or disables the alert instance.

**Legal Values**

- 1 (TRUE)
- 0 (FALSE)

**Default** 0

### cfgEmailAlertAddress (Read/Write)

**Description** Specifies the destination email address for email alerts, for example, user1@company.com.

**Legal Values** E-mail address format, with a maximum length of 64 ASCII characters.

**Default** <blank>



## cfgEmailAlertEmailName

|                     |                                                                                                                                                                        |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies name or other identifier associated with the destination e-mail address. The e-mail name can refer to an individual, group, location, department, and so on. |
| <b>Legal Values</b> | A string of up to 32 characters                                                                                                                                        |
| <b>Default</b>      | <blank>                                                                                                                                                                |

### Example

```
racadm getconfig -g cfgEmailAlert -i 2
cfgEmailAlertIndex=1
cfgEmailAlertEnable=1
cfgEmailAlertAddress=kfulton@dell.com
cfgEmailAlertName=Kevin Fulton
```

## cfgSessionManagement

This group contains parameters to configure the number of sessions that can connect to CMC or iDRAC. One instance of the group is allowed. Displays current settings for and configures idle timeout properties for Web server, Telnet, SSH, and RACADM sessions. Changes to idle timeout settings take effect at the next login. To disable idle timeout for a connection, set this property to 0.

The following sections provide information about the objects in the **cfgSessionManagement** group.

### cfgSsnMgtRacadmTimeout (Read/Write)

|                     |                                                                                                                                                                            |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Defines the idle timeout in seconds for the Remote RACADM interface. If a remote RACADM session remains inactive for more than the specified sessions, the session closes. |
| <b>Legal Values</b> | 0, 10 –1920                                                                                                                                                                |
| <b>Default</b>      | iDRAC - 60<br>CMC - 30                                                                                                                                                     |

### Example

```
racadm getconfig -g cfgSessionManagement cfgSsnMgtWebserverTimeout=0
cfgSsnMgtTelnetIdleTimeout=0
cfgSsnMgtSshIdleTimeout=300
cfgSsnMgtRacadmTimeout=0
```

### cfgSsnMgtWebserverTimeout (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Defines the Web server time-out. This property sets the amount of time (in seconds) that a connection is allowed to remain idle (there is no user input). The session is cancelled if the time limit set by this property is reached. Changes to this setting do not affect the current session. You must log out and log in again to make the new settings effective.<br><br>An expired Web server session logs out the current session. |
| <b>Legal Values</b> | 60 – 10800                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Default</b>      | 1800                                                                                                                                                                                                                                                                                                                                                                                                                                      |

# cfgSerial

This group contains configuration parameters for CMC services. One instance of the group is allowed.

Use this object with the `getConfig` or `config` subcommands.

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgSerial** group.

## cfgSerialBaudRate (Read/Write)

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| <b>Description</b>  | Sets the baud rate on the serial port.              |
| <b>Legal Values</b> | 2400, 4800, 9600, 19200, 28800, 38400, 57600,115200 |
| <b>Default</b>      | 115200                                              |

## cfgSerialConsoleEnable (Read/Write)

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the RAC or CMC serial console interface.                   |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>· 1 (TRUE)</li><li>· 0 (FALSE)</li></ul> |
| <b>Default</b>      | 1                                                                              |

## cfgSerialConsoleQuitKey (Read or Write)

**Description** This key or key combination terminates the Virtual Console text for CMC.

**Legal value:** String of up to 2 characters

This key specifies the character that ends the serial text console connect (or `racadm connect`) command.

 **NOTE: The CTRL key is represented by using the ^ (carat) character.**

 **NOTE: The CTRL key does not generate a character by itself, but must be struck simultaneously with another key to generate a character.**

For example, striking both the CTRL key and the \ key simultaneously (rather than sequentially) is denoted as ^ \.

Configuration options: The value must start with the ^ character, and must follow one of the characters — a-z, A-Z, [, ], \

In the input command, use \ without the quotes. For example:

```
config -g cfgSerial -o cfgSerialConsoleQuitKey "SHIFT+6"\\
```

**Default:** ^\



## cfgSerialConsoleIdleTimeout (Read/Write)

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| <b>Description</b>  | The maximum number of seconds to wait before an idle serial session is disconnected. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 = No timeout</li><li>• 60 – 1920</li></ul> |
| <b>Default</b>      | 1800                                                                                 |



## cfgSerialConsoleNoAuth (Read/Write)

|                     |                                                                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the RAC or CMC serial console login authentication.                                                                      |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 (enables serial login authentication)</li><li>• 1 (disables serial login authentication)</li></ul> |
| <b>Default</b>      | 0                                                                                                                                            |

## cfgSerialConsoleCommand (Read/Write)

|                     |                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies a serial command that is executed after a user logs into the serial console interface. |
| <b>Legal Values</b> | A string representing a valid serial command. For example, <code>connect server-1</code> .       |
| <b>Default</b>      | <i>&lt;blank&gt;</i>                                                                             |

## cfgSerialConsoleColumns

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the number of columns in the terminal window command line connected to the serial port. You must log out, then log in again for the changes to take effect.<br><br> <b>NOTE: The prompt counts as two characters.</b><br><br> <b>NOTE: The terminal emulator must be configured with the line wrap mode ON, if a terminal emulator is used.</b> |
| <b>Legal Values</b> | 0–256                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Default</b>      | 0 (equivalent to 80)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## cfgSerialHistorySize (Read/Write)

|                     |                                                          |
|---------------------|----------------------------------------------------------|
| <b>Description</b>  | Specifies the maximum size of the serial history buffer. |
| <b>Legal Values</b> | 0 – 8192                                                 |
| <b>Default</b>      | 8192                                                     |

## cfgSerialSshEnable (Read/Write)

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the secure shell (SSH) interface on CMC.                   |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul> |
| <b>Legal Values</b> | 1                                                                              |

## cfgSerialTelnetEnable (Read/Write)

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the Telnet console interface on CMC.                       |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul> |
| <b>Default</b>      | 0                                                                              |

## cfgOobSnmp

This group contains parameters to configure the SNMP agent and trap capabilities of CMC. One instance of the group is allowed.

The CMC SNMP agent supports the standard RFC1213 mib-2, and the Dell enterprise-specific MIB.

Use this object with the `config` or `getconfig` subcommands.

To use this object property, you must have **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgOobSnmp** group.

### cfgOobSnmpAgentCommunity (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the SNMP Community Name (identical to community string) used for SNMP traps. The community string acts as a password shared between different hosts over the network. This community string value must match with that of the other hosts for any kind of communication through SNMP. |
| <b>Legal Values</b> | A string of up to 31 characters.                                                                                                                                                                                                                                                                |
| <b>Default</b>      | public                                                                                                                                                                                                                                                                                          |

#### Example

```
racadm getconfig -g cfgOobSnmp
cfgOobSnmpTrapsEnable=1
cfgOobSnmpAgentCommunity=public
```

### cfgOobSnmpAgentEnable (Read/Write)

|                     |                                                            |
|---------------------|------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the SNMP agent.                        |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li></ul> |



- 0 (FALSE)

**Default** 0

## cfgOobSnmpprotocol

**Description** Specifies the SNMP protocol used for SNMP traps.

- Legal Values**
- 0 — All
  - 1 — SNMPv3

**Default** 0

## cfgOobSnmpprotocolFormat

**Description** Specifies the format for SNMP traps.

- Legal Values**
- 0 — SNMPv1
  - 1 — SNMPv2
  - 2 — SNMPv3

**Default** 0

## cfgTraps

This group displays information for and configures delivery of SNMP traps for a specific user.

This object property is applicable only to CMC. Use this object with the **config** or **getconfig** subcommands.

To use this object property, you must have **Chassis Configuration Administrator** privilege.

### cfgTrapsindex (Read Only)

**Description** Indicates the unique index of an alert instance.

**Legal Values** 1 - 4

**Default** 1

### cfgTrapsenable

**Description** Enables or disables event traps.

- Legal Values**
- 1 (TRUE)
  - 0 (FALSE)

**Default** None

## cfgTrapsAlertDestIpAddr

|                     |                                                                      |
|---------------------|----------------------------------------------------------------------|
| <b>Description</b>  | Sets the IP address that receives the alert.                         |
| <b>Legal Values</b> | A string representing a valid IP address. For example, 192.168.0.20. |
| <b>Default</b>      | None                                                                 |

## cfgTrapsCommunityName

|                     |                                                                                                                                                                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Sets the community string (identical to the community name) used for authentication. The community string acts as a password shared between different hosts over the network. This community string value must match with that of the other hosts for any kind of communication through SNMP. |
| <b>Legal Values</b> | A string representing the community name.                                                                                                                                                                                                                                                     |
| <b>Default</b>      | None                                                                                                                                                                                                                                                                                          |

### Example

```
racadm getconfig -g cfgTraps -i 2
cfgTrapsIndex=2
cfgTrapsEnable=1
cfgTrapsAlertDestIpAddr=
cfgTrapsCommunityName=public
```

## cfgTrapsSNMPv3UserId (Read Only)

**Table 2. cfgTrapsSNMPv3UserId — Details**

|                     |                                                    |
|---------------------|----------------------------------------------------|
| <b>Description</b>  | Displays the SNMP user ID of an existing CMC user. |
| <b>Legal Values</b> | 1-16                                               |
| <b>Default</b>      | Empty                                              |

## cfgTrapsSNMPv3UserName

**Table 3. cfgTrapsSNMPv3UserName — Details**

|                     |                             |
|---------------------|-----------------------------|
| <b>Description</b>  | Configure SNMPv3 user name. |
| <b>Legal Values</b> | Any existing CMC user name. |
| <b>Default</b>      | Empty                       |

## cfgRacTuning

This group is used to configure various iDRAC or CMC configuration properties, such as valid ports and security port restrictions.

Use this object with the config or getconfig subcommands.

To use this object property for CMC, you must have **Chassis Configuration Administrator** privilege.



Use the **-m** option to apply this setting to iDRAC.

The following sections provide information about the objects in the **cfgRacTuning** group.

### cfgRacTuneDefCredentialWarningEnable

|                     |                                                                          |
|---------------------|--------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the display of the default password warning message. |
| <b>Legal Values</b> | 0 and 1                                                                  |
| <b>Default</b>      | 1                                                                        |


### cfgRacTuneRemoteRacadmEnable (Read/Write)

|                     |                                                  |
|---------------------|--------------------------------------------------|
| <b>Description</b>  | Enables or disables the Remote RACADM interface. |
| <b>Legal Values</b> | 1 (TRUE) or 0 (FALSE)                            |
| <b>Default</b>      | 1                                                |


### cfgRacTuneChassisMgmtAtServer

|                     |                                                                                                                      |
|---------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Modify the Rack System Management Mode                                                                               |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — Disable</li><li>• 1 — Monitor</li><li>• 2 — Manage and Monitor</li></ul> |
| <b>Default</b>      | 2                                                                                                                    |

### cfgRacTuneHttpPort (Read/Write)

|                     |                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the port number to use for HTTP network communication with.                                                                                                                                                                  |
| <b>Legal Values</b> | 10–65535                                                                                                                                                                                                                               |
|                     |  <b>NOTE: The following port numbers are reserved and cannot be used: 21, 68, 69, 111, 123, 161, 546, 801, 4096, 5988, 5989, 6900, 9000, 60106.</b> |
| <b>Default</b>      | 80                                                                                                                                                                                                                                     |

### cfgRacTuneHttpsPort (Read/Write)

|                     |                                                                                                                                                                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the port number to use for HTTPS network communication with.                                                                                                                                                                       |
| <b>Legal Values</b> | 10–65535                                                                                                                                                                                                                                     |
|                     |  <b>NOTE: The following port numbers are reserved and cannot be used: 21, 68, 69, 111, 123, 161, 546, 801, 4003, 4096, 5988, 5989, 6900, 9000, 60106.</b> |
| <b>Default</b>      | 443                                                                                                                                                                                                                                          |

## cfgRacTunelpRangeEnable (Read/Write)

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the IPv4 Address Range validation feature.                 |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul> |
| <b>Default</b>      | 0                                                                              |

## cfgRacTunelpRangeAddr (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | <p>Specifies the acceptable IPv4 address bit pattern in positions determined by the 1s in the range mask property (<b>cfgRacTunelpRangeMask</b>).</p> <p>A login from the incoming IP address is allowed only if the following are identical:</p> <ul style="list-style-type: none"><li>• <code>cfgRacTuneIpRangeMask</code> bit-wise and with incoming IP address</li><li>• <code>cfgRacTuneIpRanbeMask</code> bit-wise and with <code>cfgRacTuneIpRangeAddr</code>.</li></ul> |
| <b>Legal Values</b> | An IPv4 address formatted string, for example, 192.168.0.44.                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Default</b>      | 192.168.1.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

## cfgRacTunelpRangeMask (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | <p>Standard IP mask values with left-justified bits. For example, 255.255.255.0.</p> <p>A login from the incoming IP address is allowed only if both of the following are identical:</p> <ul style="list-style-type: none"><li>• <code>cfgRacTuneIpRangeMask</code> bit-wise and with incoming IP address</li><li>• <code>cfgRacTuneIpRanbeMask</code> bit-wise and with <code>cfgRacTuneIpRangeAddr</code>.</li></ul> |
| <b>Legal Values</b> | An IPv4 address formatted string, for example, 255.255.255.0.                                                                                                                                                                                                                                                                                                                                                          |
| <b>Default</b>      | 255.255.255.0                                                                                                                                                                                                                                                                                                                                                                                                          |

## cfgRacTunelpBlkEnable (Read/Write)

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the IPv4 address blocking feature.                         |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul> |
| <b>Default</b>      | 0                                                                              |

## cfgRacTunelpBlkFailCount (Read/Write)

|                     |                                                                                                                                                                    |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | The maximum number of login failures to occur within the window ( <code>cfgRacTunelpBlkFailWindow</code> ) before login attempts from the IP address are rejected. |
| <b>Legal Values</b> | 2 – 16                                                                                                                                                             |



Default 5

### cfgRacTuneIpBlkFailWindow (Read/Write)

**Description** Defines the time span in seconds that the failed attempts are counted. When failure attempts age beyond this limit, they are dropped from the count.

**Legal Values** 2–65535

**Default** 60

### cfgRacTuneIpBlkPenaltyTime (Read/Write)

**Description** Defines the time span in seconds that session requests from an IP address with excessive failures are rejected.


**Legal Values** 2–65535

**Default** 300

### cfgRacTuneSshPort (Read/Write)

**Description** Specifies the port number used for the SSH interface.


**Legal Values** 10–65535

 **NOTE: The following port numbers are reserved and cannot be used: 21, 68, 69, 111, 123, 161, 546, 801, 4096, 5988, 5989, 6900, 9000, 60106.**

**Default** 22

### cfgRacTuneTelnetPort (Read/Write)

**Description** Specifies the port number used for iDRAC or CMC Telnet interface.

 **NOTE: For CMC, the following port numbers are reserved and cannot be used: 21, 68, 69, 111, 123, 161, 546, 801, 4096, 5988, 5989, 6900, 9000, 60106.**

**Legal Values**

- For CMC: 10 – 65535
- For iDRAC: 1 – 65535

**Default** 23

### cfgRacTuneDaylightOffset (Read Only)

**Description** Specifies the daylight savings offset (in minutes) to use for the RAC Time. This value is 0 if the time zone is not a Daylight Saving time zone.

**Legal Values** 0 – 60

**Default** 0

## Example

```
racadm getconfig -g cfgRacTuning [-m server-<n>] -o
<
object name
> <
object value
>

cfgRacTuneRemoteRacadmEnable=1
cfgRacTuneWebserverEnable=1
cfgRacTuneHttpPort=80
cfgRacTuneHttpsPort=443
cfgRacTuneTelnetPort=23
cfgRacTuneSshPort=22
cfgRacTuneIpRangeEnable=0
cfgRacTuneIpRangeAddr=192.168.1.1
cfgRacTuneIpRangeMask=255.255.255.0
cfgRacTuneIpBlkEnable=0
cfgRacTuneIpBlkFailCount=5
cfgRacTuneIpBlkFailWindow=60
cfgRacTuneIpBlkPenaltyTime=300
cfgRacTuneTimezoneOffset=-18000
cfgRacTuneDaylightOffset=3600
```

## cfgRacTuneTimezoneOffset

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the time zone offset (in minutes) from Greenwich Mean Time (GMT) / Coordinated Universal Time (UTC) to use for the RAC Time. Some common time zone offsets for time zones in the United States are: <ul style="list-style-type: none"><li>• - 480 (PST — Pacific Standard Time)</li><li>• - 420 (MST — Mountain Standard Time)</li><li>• - 360 (CST — Central Standard Time)</li><li>• - 480 (PST — Eastern Standard Time)</li></ul> For CMC: This object property is read only. Specifies the difference in number of seconds, from the UTC/GMT. This value is negative if the current time zone is west of Greenwich. |
| <b>Legal Values</b> | - 720–7800                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Default</b>      | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## cfgRacTuneSledNetworkUplink

|                     |                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Configuration of all the sleds that contain an internal network switch (for example, the FM120).                                                                        |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 - Standard (aggregated)</li><li>• 2 - Network Adaptor Isolation (Enhanced Security)</li><li>• 3 - Isolated Networks</li></ul> |
| <b>Default</b>      | 1                                                                                                                                                                       |

## cfgRacTuneUserBlkEnable

|                    |                                                                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b> | Blocks the login for maximum of 5 minutes after 5 unsuccessful login attempts. The login using any interface such as <b>WSMAN</b> or <b>GUI</b> is blocked after 5 unsuccessful attempts. |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|





**NOTE: This is applicable only to configure the user privilege.**

**Legal Values**

- 1 – Enabled
- 0 – Disabled

**Default** 0 — Disabled

### Example

```
racadm getconfig -g cfgRacTuning [-m server-<n>] -o
<
object name
> <
object value
>

cfgRacTuneRemoteRacadmEnable=1
cfgRacTuneWebserverEnable=1
cfgRacTuneHttpPort=80
cfgRacTuneHttpsPort=443
cfgRacTuneTelnetPort=23
cfgRacTuneSshPort=22
cfgRacTuneIpRangeEnable=0
cfgRacTuneIpRangeAddr=192.168.1.1
cfgRacTuneIpRangeMask=255.255.255.0
cfgRacTuneIpBlkEnable=0
cfgRacTuneIpBlkFailCount=5
cfgRacTuneIpBlkFailWindow=60
cfgRacTuneIpBlkPenaltyTime=300
cfgRacTuneTimezoneOffset=-18000
cfgRacTuneDaylightOffset=3600
```

### cfgRacTuneWebserverEnable (Read/Write)

**Description** Enables or disables the Web server. If this property is disabled, CMC is not accessible using client Web browsers. This property has no effect on the Telnet/SSH or RACADM interfaces.

**Legal Values**

- 1 (TRUE)
- 0 (FALSE)

**Default** 1

### cfgRacTuneFipsModeEnable

**Description** Enables or disables the FIPS mode.

**Legal Values** 0 and 1

**Default** 0

**Usage**

```
racadm getconfig -g cfgRacTuning -o
cfgRacTuneFipsModeEnableracadm config -g
cfgRacTuning -o cfgRacTuneFipsModeEnable 1
```



**NOTE: The firmware racadm prompts you to confirm whether the FIPS mode has to be enabled, but remote racadm does not prompt you to do so.**



## cfgRacTuneTLSProtocolVersionEnable

|                     |                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Sets the minimum TLS protocol version.                                                                                                                                                 |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 - TLSv1.0, TLSv1.1, and TLSv1.2 are enabled.</li><li>• 1 - TLSv1.1 and TLSv1.2 are enabled.</li><li>• 2 - only TLSv1.2 is enabled.</li></ul> |
| <b>Default</b>      | 1                                                                                                                                                                                      |

## cfgServerInfo

For CMC, this group allows you to displays information for and configure a server in the chassis.

For iDRAC this group allows you to select the BIOS first boot device and provides the option to boot the selected device only once.

Use this object with the config or getconfig subcommands.

To use this object property for CMC, you must have **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgServerInfo** group.

### cfgServerInfoIndex (Read Only)

|                    |                                        |
|--------------------|----------------------------------------|
| <b>Description</b> | Displays the index name of the server. |
|--------------------|----------------------------------------|

### cfgServerSlotNumber (Read Only)

|                    |                                                                      |
|--------------------|----------------------------------------------------------------------|
| <b>Description</b> | Specifies the location of the specified server (1–4) in the chassis. |
|--------------------|----------------------------------------------------------------------|

### cfgServerServiceTag (Read Only)

|                    |                                                   |
|--------------------|---------------------------------------------------|
| <b>Description</b> | Displays the service tag of the specified server. |
|--------------------|---------------------------------------------------|

### cfgServerName (Read/Write)

|                     |                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Displays the name of the specified server.                                                                                                                               |
| <b>Legal Values</b> | Maximum of 15 non-extended ASCII characters, (ASCII codes 32–126). For more information, see <a href="#">Guidelines to Quote Strings Containing Special Characters</a> . |
| <b>Default</b>      | SLOT - <i>&lt;slot number&gt;</i>                                                                                                                                        |

### cfgServerFW (Read Only)

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| <b>Description</b> | Displays the server's CMC management firmware revision. |
|--------------------|---------------------------------------------------------|



## **cfgServerBIOS (Read Only)**

**Description** Displays the server's BIOS revision.

## **cfgServerBmcMacAddress (Read Only)**

**Description** Displays the BMC MAC address of the specified server.

## **cfgServerNic1MacAddress (Read Only)**

**Description** Displays the MAC address of the server NIC 1.

## **cfgServerNic2MacAddress (Read Only)**

**Description** Displays the MAC address of the server NIC 2.

## **cfgServerNic3MacAddress (Read Only)**

**Description** Displays the MAC address of the server NIC 3.

## **cfgServerNic4MacAddress (Read Only)**

**Description** Displays the MAC address of the server NIC 4.

## **cfgServerNicEnable (Read/Write)**

**Description** Enables or disables LAN channel.

**Legal Values**

- 1 (Enable)
- 0 (Disable)

## **cfgServerNodeld**

**Description** Unique identification for a server provided by Dell for support and maintenance.

## **cfgServerIPMIOverLanEnable (Read/Write)**

**Description** Enables or disables IPMI LAN channel.

**Legal Values**

- 1 (enable)
- 0 (disable)

## cfgServerDNSRegisterIMC (Read/Write)

**Description** Enables or disables DNS name registration for the CMC.

**Legal Values**

- 1 (enable)
- 0 (disable)

## cfgServerDNSIMCName (Read/Write)

**Description** Displays the DNS domain name for the CMC.

## cfgServerRootPassword (Write Only)

**Description** Displays the password for CMC as a series of asterisks (\*). It cannot be seen or displayed after this property is written.

## cfgServerFirstBootDevice (Read/Write)

**Description** Sets or displays the first boot device.

This object is read-write.

 **NOTE: For a vFlash Partition to be configured as First Boot Device, it has to be attached first. When a detached or non-existent VFlash partition or a non-standard boot device is configured as first boot device, the following error message is displayed:**

Invalid object value

**Legal Values**

- 0 = None
- 0 = Default
- 4 = PXE
- 8 = HDD
- 20 = CD-DVD
- 24 = BIOS
- 28 = vFDD
- 32 = vCD-DVD
- 40 = SD
- 44 = RFS
- 48 = F11
- 52 = F10
- 60 = FDD

**Default** 0 = None

## cfgServerBootOnce (Read/Write)

**Description** Enables or disables the server boot once feature.



This object is read-write.

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>· 1 = TRUE</li><li>· 0 = FALSE</li></ul> |
| <b>Default</b>      | 0                                                                              |

## cfgStorageModule

This group contains the parameters to configure storage sleds.  
Use this command with the `config` and `getConfig` commands.

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgStorageModule** group.

### cfgStorageModuleStorageMode (Read/Write)

|                     |                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Displays the configuration mode of the storage sled.                                                             |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>· 2 — Split-single</li><li>· 1 — Split-dual</li><li>· 0 — Joined</li></ul> |

### cfgStorageModuleServiceTag (Read Only)

|                     |                                                                                    |
|---------------------|------------------------------------------------------------------------------------|
| <b>Description</b>  | Displays the Service Tag of the storage sled.                                      |
| <b>Legal Values</b> | Any printable string of up to seven alpha-numeric characters, without white space. |

### cfgStorageModuleAssetTag (Read/Write)

|                     |                                                                                  |
|---------------------|----------------------------------------------------------------------------------|
| <b>Description</b>  | Displays the Asset Tag of the storage sled.                                      |
| <b>Legal Values</b> | Any printable alpha-numeric string of up to 254 characters, without white space. |

### ConnectedServer (Read Only)

|                      |                                                                           |
|----------------------|---------------------------------------------------------------------------|
| <b>Description</b>   | Displays the name of the compute sled to which storage sled is connected. |
| <b>Legal Values</b>  | None                                                                      |
| <b>Default Value</b> | None                                                                      |

## RAID-EnabledControllers (Read Only)

|                       |                                                                                                                                  |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>    | Displays the name of the RAID-enabled controller. This property is updated when the single RAID or dual RAID license is applied. |
| <b>Legal Values</b>   | None                                                                                                                             |
| <b>Default Values</b> | None                                                                                                                             |

## cfgActiveDirectory

This group contains parameters to configure the Active Directory feature.

Use this object with the `getconfig` or `config` subcommands.

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgActiveDirectory** group.

### cfgADRacName (Read/Write)

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
| <b>Description</b>  | Name of CMC as recorded in the Active Directory forest.                 |
| <b>Legal Values</b> | Any printable text string of up to 254 characters, with no white space. |
| <b>Default</b>      | <blank>                                                                 |

### cfgADCertValidationEnable (Read/Write)

|                     |                                                                                                                      |
|---------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables Active Directory certificate validation as a part of the Active Directory configuration process. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul>                                       |
| <b>Default</b>      | 1                                                                                                                    |

### cfgADRacDomain (Read or Write)

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
| <b>Description</b>  | Active Directory Domain in which CMC resides.                           |
| <b>Legal Values</b> | Any printable text string of up to 254 characters, with no white space. |
| <b>Default</b>      | <blank>                                                                 |

### cfgADRootDomain

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the root domain of the domain forest.                         |
| <b>Legal Values</b> | Any printable text string of up to 254 characters, with no white space. |



**Default** <blank>

## cfgADEnable (Read/Write)

**Description** Enables or disables Active Directory user authentication on CMC.  
If this property is disabled, LDAP authentication may be used for user login.

**Legal Values**

- 1 (TRUE)
- 0 (FALSE)

**Default** 0

## cfgADAuthTimeout (Read/Write)

**Description** Specifies the number of seconds to wait for Active Directory authentication requests to complete before timing out.

 **NOTE: To modify this property, you must have the Configure CMC permission.**

**Legal Values** 15–300 seconds

**Default** 120

## cfgADSCLEnable

**Description** Enables you to log on to the CMC without enabling the Smart Card login.

**Legal Values**

- 1 (Enable)
- 0 (Disable)

**Default** 0

## cfgADSSOEnable (Read/Write)

**Description** Enables or disables Active Directory single sign-on authentication on CMC.

**Legal Values**

- 1 (TRUE)
- 0 (FALSE)

**Default** 0

## cfgADDomainController

**Description** Specifies the AD server from which you want the CMC to obtain user names. Must be used with **cfgADSpecifyServerEnable**.

**Legal Values** Valid IP address or fully qualified domain name (FQDN).

## cfgADDomainController1 (Read/Write)

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the LDAP server from which you want the CMC to obtain user names .                                    |
| <b>Legal Values</b> | A string of up to 254 ASCII characters representing a valid IP address or a fully qualified domain name (FQDN). |

## cfgADDomainController2 (Read/Write)

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the LDAP server from which you want the CMC to obtain user names .                                    |
| <b>Legal Values</b> | A string of up to 254 ASCII characters representing a valid IP address or a fully qualified domain name (FQDN). |

## cfgADDomainController3 (Read/Write)

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the LDAP server from which you want the CMC to obtain user names .                                    |
| <b>Legal Values</b> | A string of up to 254 ASCII characters representing a valid IP address or a fully qualified domain name (FQDN). |

## cfgADGlobalCatalog1 (Read/Write)

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the Global Catalog server from which you want the CMC to obtain user names.                           |
| <b>Legal Values</b> | A string of up to 254 ASCII characters representing a valid IP address or a fully qualified domain name (FQDN). |

## cfgADGlobalCatalog2 (Read/Write)

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the Global Catalog server from which you want the CMC to obtain user names.                           |
| <b>Legal Values</b> | A string of up to 254 ASCII characters representing a valid IP address or a fully qualified domain name (FQDN). |

## cfgADGlobalCatalog3 (Read/Write)

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the Global Catalog server from which you want the CMC to obtain user names.                           |
| <b>Legal Values</b> | A string of up to 254 ASCII characters representing a valid IP address or a fully qualified domain name (FQDN). |

## cfgADType (Read/Write)

|                     |                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Determines the schema type to use with Active Directory.                                                                                                                |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (Enables Active Directory with the extended schema)</li><li>• 2 (Enables Active Directory with the standard schema)</li></ul> |
| <b>Default</b>      | 1                                                                                                                                                                       |



## cfgADDcSRVLookupDomainName (Read/Write)

|                     |                                                                                                          |
|---------------------|----------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | This is the Active Directory Domain to use when <b>cfgAddcSrvLookupbyUserDomain</b> is set to <b>0</b> . |
| <b>Legal Values</b> | String. Maximum length = 254                                                                             |
| <b>Default</b>      | Null                                                                                                     |

## cfgADDcSRVLookupDomainName (Read/Write)

|                     |                                                                                                          |
|---------------------|----------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | This is the Active Directory Domain to use when <b>cfgAddcSrvLookupbyUserDomain</b> is set to <b>0</b> . |
| <b>Legal Values</b> | String. Maximum length = 254                                                                             |
| <b>Default</b>      | Null                                                                                                     |

## cfgADDcSRVLookupEnable (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Configures CMC to use pre-configured domain controllers or to use DNS to find the domain controller. If using pre-configured domain controllers, then the domain controllers to use are specified under <b>cfgAdDomainController1</b> , <b>cfgAdDomainController2</b> , and <b>cfgAdDomainController3</b> . CMC does not fail over to the specified domain controllers when DNS lookup fails or none of the servers returned by the DNS lookup works. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)—use DNS to look up domain controllers</li><li>• 0 (FALSE)—use pre-configured domain controllers</li></ul>                                                                                                                                                                                                                                                                                            |
| <b>Default</b>      | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

## cfgADSpecifyServerEnable

|                     |                                                                                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Allows you to enable or disable and specify an LDAP server or a global catalog server. Use <b>cfgADDomainController</b> or <b>cfgADGlobalCatalog</b> to specify the IP address. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (enabled)</li><li>• 0 (disabled)</li></ul>                                                                                            |
| <b>Default</b>      | 0                                                                                                                                                                               |

## cfgLDAP

This group allows you to configure settings related to the Lightweight Directory Access Protocol (LDAP).

Use this object with the **config** or **getconfig** subcommands.

To use this object property for CMC, you must have the **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgLDAP** group.

## cfgLdapEnable (Read/Write)

**Description** Turns LDAP service on or off.  
If this property is disabled, local CMC authentication is used for user logins.

 **NOTE: For CMC, enabling this option turns off cfgADEnable.**

**Legal Values**

- 1 (TRUE)— Enable
- 0 (FALSE)— Disable

**Default** 0

## cfgLdapServer (Read/Write)

**Description** Configures the address of the LDAP Server. IPv4 and IPv6 are supported.

 **NOTE: You can specify multiple servers by separating each server with a comma. For example, example.com, sub1.example.com**

**Legal Values** String.  
Maximum length = 254

**Default** Null

## cfgLdapPort (Read/Write)

**Description** Port of LDAP over SSL. Non-SSL port is not supported.

**Legal Values** 1– 65535

 **NOTE: The following port numbers are reserved and cannot be used: 21, 68, 69, 123, 161, 546, 801, 4096, 5988, 5989, 6900, 9000, 60106.**

**Default** 636

## cfgLdapBasedn (Read/Write)

**Description** The Domain Name of the branch of the directory where all searches should start from.

**Legal Values** String. Maximum length = 254

**Default** Null

## cfgLdapUserAttribute (Read/Write)

**Description** Specifies the user attribute to search for. It is recommended to be unique within the chosen baseDN, otherwise a search filter must be configured to make sure the uniqueness of the login user. If the userDN cannot be uniquely identified, login fails with error.

**Legal Values** String. Maximum length = 254



**Default** Null  
*uid* if not configured.

### cfgLdapGroupAttribute (Read/Write)

**Description** Specifies which LDAP attribute is used to check for group membership. This should be an attribute of the group class. If not specified, then CMC uses the member and unique member attributes.

**Legal Values** String. Maximum length = 254

**Default** Null

### cfgLdapGroupAttributesDN (Read/Write)

**Description** If enabled, the CMC performs DN matching; otherwise, the CMC uses the username provided at login for matching.

**Legal Values**

- 1 (TRUE)—Use the *userDN* from the LDAP Server
- 0 (FALSE)—Use the *userDN* provided by the login user

**Default** 1

### cfgLdapBinddn (Read/Write)

**Description** The distinguished name of a user used to bind to the server when searching for the login user's DN. If not provided, an anonymous bind is used. This is optional but is required if anonymous bind is not supported.

 **NOTE: If *cfgLDAPBindDN* is [null] and *cfgLDAPBindPassword* is [null], then the CMC attempts an anonymous bind.**

**Legal Values** String. Maximum length = 254

**Default** Null

### cfgLdapBindpassword (Write Only)

**Description** A bind password to use in conjunction with the bindDN. The bind password is sensitive data, and should be protected. This is optional but is required if anonymous bind is not supported.

**Legal Values** String. Maximum length = 254

**Default** Null

### cfgLdapSearchFilter (Read/Write)

**Description** A valid LDAP search filter. This is used if the user attribute cannot uniquely identify the login user within the chosen baseDN. The search filter only applies to userDN search and not the group membership search.

**Legal Values** String of maximum length = 1024 characters

**Default** (objectclass=\*)  
Searches for all objects in tree.

### cfgLDAPCertValidationEnable (Read/Write)

**Description** Controls certificate validation during SSL handshake.

**Legal Values**

- 1 (TRUE)—CMC uses the CA certificate to validate the LDAP server certificate during SSL handshake.
- 0 (FALSE)—CMC does not perform the certificate validation task of SSL handshake.

**Default** 1

### cfgLDAPNetworkTimeout

**Description** Configures the network timeout in seconds.

**Legal Values** Positive integer

**Default** 30 seconds

### cfgLDAPSearchTimeout

**Description** Configures the search timeout in seconds.

**Legal Values** Positive integer

**Default** 120 seconds

### cfgLDAPSRVLookupDomainName

**Description** Configures the domain name to be used in the SRV lookup.

**Legal Values** String of maximum length of 254 alphanumeric characters and hyphens. The string must begin with a letter.

**Default** [null]

### cfgLDAPSRVLookupEnable

**Description** Configures the CMC to query a DNS server for SRV records.

**Legal Values**

- 1 (true)
- 0 (false)

**Default** 0



## cfgLDAPSRVLookupServiceName (Read/Write)

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| <b>Description</b>  | Configures the service name to be used in the SRV lookup. |
| <b>Legal Values</b> | String of maximum length of 254 characters.               |
| <b>Default</b>      | ldap                                                      |

## cfgLdapRoleGroup

Use this object with the `getconfig` or `config` subcommands.

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

This group configures Generic LDAP Role group descriptions and defines the CMC privileges that LDAP–authenticated users are granted.

**cfgLDAPRoleGroup** is indexed, containing instances numbered from 1 to 5. Each object instance consists of a pair of properties:

- **cfgLDAPRoleGroupDN**: an LDAP distinguished name (DN)
- **cfgLDAPRoleGroupPrivilege**: a CMC privilege map

Each LDAP–authenticated user assumes the total set of CMC privileges assigned to the matching LDAP distinguished names that the user belongs to.

That is, if the user belongs to multiple role group DNs, the user receives all associated privileges for those DNs.

The following sections provide information about the objects in the **cfgLdapRoleGroup** group.

### cfgLdapRoleGroupDN (Read/Write)

|                     |                                                                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | This is the Domain Name of the group in this index.<br><br>For CMC, configure the LDAP distinguished name (DN) for the role group instance. |
| <b>Legal Values</b> | String. Maximum length = 1024                                                                                                               |
| <b>Default</b>      | None                                                                                                                                        |

#### Example

```
racadm getconfig -g cfgLDAPRoleGroup -o cfgLDAPRoleGroupDN
-i 1 cn=everyone,ou=groups,dc=openldap,dc=com
```

### cfgLdapRoleGroupPrivilege (Read/Write)

|                     |                                                                           |
|---------------------|---------------------------------------------------------------------------|
| <b>Description</b>  | A bit–mask defining the privileges associated with this particular group. |
| <b>Legal Values</b> | 0x00000000 to 0x000001ff                                                  |
| <b>Default</b>      | 0x000                                                                     |

## Example

```
racadm getconfig -g cfgLDAPRoleGroup -o cfgLDAPRoleGroupPrivilege
-i 1 0x0
```

## cfgLocation

This group defines objects that support physical location properties. Use this object with the `getconfig` or `config` subcommands.

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

### cfgLocationDatacenter (Read/Write)

|                     |                                      |
|---------------------|--------------------------------------|
| <b>Description</b>  | Indicates DataCenter name.           |
| <b>Legal Values</b> | String of up to 128 ASCII characters |
| <b>Default</b>      | 0                                    |

### cfgLocationAisle (Read/Write)

|                     |                                          |
|---------------------|------------------------------------------|
| <b>Description</b>  | Indicates aisle where server is located. |
| <b>Legal Values</b> | String of up to 128 ASCII characters     |
| <b>Default</b>      | 0                                        |

### cfgLocationRack (Read/Write)

|                     |                                         |
|---------------------|-----------------------------------------|
| <b>Description</b>  | Indicates rack where server is located. |
| <b>Legal Values</b> | String of up to 128 ASCII characters    |
| <b>Default</b>      | 0                                       |

### cfgLocationRackslot (Read/Write)

|                     |                                               |
|---------------------|-----------------------------------------------|
| <b>Description</b>  | Indicates the slot where a server is located. |
| <b>Legal Values</b> | Values from 1 - 255 (1 Byte)                  |
| <b>Default</b>      | 0                                             |

### cfgLocationDevicesize (Read Only)

|                     |                                |
|---------------------|--------------------------------|
| <b>Description</b>  | Indicates server chassis size. |
| <b>Legal Values</b> | Values from 1 - 255            |
| <b>Default</b>      | 2U                             |



# cfgStandardSchema

This group contains parameters to configure the Active Directory standard schema settings.

Use this object with the `getconfig` or `config` subcommands.

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgStandardSchema** group.

## cfgSSADRoleGroupIndex (Read Only)

|                     |                                                              |
|---------------------|--------------------------------------------------------------|
| <b>Description</b>  | Index of the Role Group as recorded in the Active Directory. |
| <b>Legal Values</b> | An integer between 1 and 5                                   |
| <b>Default</b>      | <i>&lt;instance&gt;</i>                                      |

## cfgSSADRoleGroupName (Read/Write)

|                     |                                                                        |
|---------------------|------------------------------------------------------------------------|
| <b>Description</b>  | Name of the Role Group as recorded in the Active Directory forest.     |
| <b>Legal Values</b> | Any printable text string of up to 254 characters with no white space. |
| <b>Default</b>      | <i>&lt;blank&gt;</i>                                                   |

## cfgSSADRoleGroupDomain (Read/Write)

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
| <b>Description</b>  | Active Directory Domain in which the Role Group resides.                |
| <b>Legal Values</b> | Any printable text string of up to 254 characters, with no white space. |
| <b>Default</b>      | <i>&lt;blank&gt;</i>                                                    |

## cfgSSADRoleGroupPrivilege (Read/Write)

|                     |                                                                                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Use the bit mask numbers listed in the table below to set role-based authority privileges for a Role Group. |
| <b>Legal Values</b> | 0x00000000 0x00000fff                                                                                       |
| <b>Default</b>      | <i>&lt;blank&gt;</i>                                                                                        |

### Example

```
racadm getconfig -g cfgStandardSchema -i 1
cfgSSADRoleGroupIndex=1
cfgSSADRoleGroupName=blsys-1
cfgSSADRoleGroupDomain=
cfgSSADRoleGroupPrivilege=3081
```

The following table displays the bit masks for Role Group privileges:



| Role Group Privilege            | Bit Mask   |
|---------------------------------|------------|
| Login to iDRAC                  | 0x00000001 |
| Configure iDRAC                 | 0x00000002 |
| Configure Users                 | 0x00000004 |
| Clear Logs                      | 0x00000008 |
| Execute Server Control Commands | 0x00000010 |
| Access Virtual Console          | 0x00000020 |
| Access Virtual Media            | 0x00000040 |
| Test Alerts                     | 0x00000080 |
| Execute Debug Commands          | 0x00000100 |


## cfgChassisPower

This group is applicable only to CMC and contains parameters to display or configure power for the chassis.

Use this object with the config or getconfig subcommands.

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

The following sections provide information about the objects in the **cfgChassisPower** group.

 **NOTE:** While configuring chassis power from a file, update the value for one chassis power cap property and remove the values for the other chassis power cap properties or, update the last percentage value as it is applicable to all chassis power cap properties. The chassis power cap properties are: `cfgChassisPowerCap`, `cfgChassisPowerCapF`, `cfgChassisPowerCapBTU`, `cfgChassisPowerCapFBTU`, `cfgChassisPowerCapPercent`, and `cfgChassisPowerCapFPercent`.

### cfgChassisInPower (Read Only)

|                     |                                                                                                                                           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the cumulative input power consumption data (in Watts and BTU/hr) captured from all healthy and functional PSUs in the chassis. |
| <b>Legal Values</b> | None                                                                                                                                      |
| <b>Default</b>      | None                                                                                                                                      |

### cfgChassisPeakPower (Read Only)

|                     |                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | The maximum system input power consumption (in Watts), because the value was last cleared by a user. |
| <b>Legal Values</b> | None                                                                                                 |
| <b>Default</b>      | None                                                                                                 |



## cfgChassisPeakPowerTimestamp (Read Only)

**Description** The timestamp recorded when the peak input power consumption value occurred.

**Legal Values**

**Default**

## cfgChassisMinPower (Read Only)

**Description** The minimum system input power consumption value (in Watts) over the time since the value was last cleared.

**Legal Values** None

**Default** None

## cfgChassisMinPowerTimestamp (Read Only)

**Description** The timestamp recorded when the minimum system power occurred.

**Legal Values** None

**Default** None

## cfgChassisPowerStatus (Read Only)

**Description** Indicates the power status of the chassis.

**Legal Values**

- 1 (other)
- 2 (unknown)
- 3 (OK)
- 4 (non-critical)
- 5 (critical)
- 6 (non-recoverable)

**Default** None

## cfgChassisRedundantState (Read Only)

**Description** Indicates the power supply redundancy status.

**Legal Values**

- 0 (none)
- 1 (full)

**Default** None

## cfgChassisMaxPowerConservationMode (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables maximum power conservation mode. When enabled, all servers are immediately reduced to their minimum power levels, and all subsequent server power allocation requests are denied. In this mode, performance of the servers that are turned on may be degraded, and additional servers cannot be turned on, regardless of the server priority. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 (disabled)</li><li>• 1 (enabled)</li></ul>                                                                                                                                                                                                                                                                              |
| <b>Default</b>      | 0 (disabled)                                                                                                                                                                                                                                                                                                                                                      |

## cfgChassisPowerCapUpperBound (Read Only)

|                     |                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the minimum chassis thermal capacity, power supply capacity, and server maximum input. |
| <b>Legal Values</b> |                                                                                                  |
| <b>Default</b>      |                                                                                                  |

## cfgChassisPowerCapLowerBound (Read Only)

|                     |                                                                                       |
|---------------------|---------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the minimum power required to operate the chassis with the servers running. |
| <b>Legal Values</b> |                                                                                       |
| <b>Default</b>      |                                                                                       |

## cfgChassisSledPowerButtonEnable

|                     |                                                                                    |
|---------------------|------------------------------------------------------------------------------------|
| <b>Description</b>  | Permits to use the power button on all multi-node Sleds (such as the FM120).       |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 — Enable</li><li>• 0 — Disable</li></ul> |
| <b>Default</b>      | 1                                                                                  |

## cfgChassisPowerCap (Read/Write)

|                     |                                                                                                                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the maximum power consumption limit (in Watts) for the entire chassis. The command generates an error if server throttling is necessary to achieve the power goal based on the value for this setting. |
| <b>Legal Values</b> | 539 – 3371 Watts                                                                                                                                                                                                 |
| <b>Default</b>      | 3371 Watts                                                                                                                                                                                                       |



## cfgChassisPowerCapF (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the maximum power consumption limit (in Watts) for the entire chassis. Use <b>cfgChassisPowerCapF</b> when power consumption is to be changed regardless of whether server throttling is required. This command generates an error if the value for this setting is lower than the minimum power required for the chassis configuration. |
| <b>Legal Values</b> | 539 – 3371 Watts                                                                                                                                                                                                                                                                                                                                   |
| <b>Default</b>      | 3371 Watts                                                                                                                                                                                                                                                                                                                                         |


## cfgChassisPowerCapBTU (Read/Write)

|                     |                                                                                                                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the maximum power consumption limit (in BTU/hr) for the entire chassis. The command generates an error if server throttling is necessary to achieve the power goal based on the value for this setting. |
| <b>Legal Values</b> | 1839-11501 BTU/hr                                                                                                                                                                                                 |
| <b>Default</b>      | 11501 BTU/hr                                                                                                                                                                                                      |

## cfgChassisPowerCapFBTU (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the maximum power consumption limit (in BTU/hr) for the entire chassis. Use <b>cfgChassisCapFBTU</b> when power consumption is to be changed regardless of whether server throttling is required. The command generates an error if the value for this setting is lower than the minimum power required for the chassis configuration. |
| <b>Legal Values</b> | 9264 - 56931 BTU/hr                                                                                                                                                                                                                                                                                                                              |
| <b>Default</b>      | 56931 BTU/hr                                                                                                                                                                                                                                                                                                                                     |

## cfgChassisPowerCapPercent (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates the power consumption limit as a percentage. The percentage is computed mathematically as the minimum power + (percent * (maximum power - minimum power)). The command generates an error if server throttling is necessary to achieve the power goal based on the value for this setting. |
| <b>Legal Values</b> | 16 - 100                                                                                                                                                                                                                                                                                             |
|                     |  <b>NOTE: If the specified percent is lower than the minimum value, the CMC will set the value to the minimum value.</b>                                                                                          |
| <b>Default</b>      | 100                                                                                                                                                                                                                                                                                                  |

## cfgChassisPowerCapFPercent (Read/Write)

|                    |                                                                                                                                                                          |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b> | Indicates the power consumption limit as a percentage. The percentage is computed mathematically as the minimum power + (percent * (maximum power - minimum power)). Use |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**cfgChassisPowerCapFPercent** when power consumption is to be changed regardless of whether server throttling is required.

**Legal Values** 16 - 100

 **NOTE: If the specified percent is lower than the minimum value, the CMC will set the value to the minimum value.**

**Default** 100

### cfgChassisRedundancyPolicy (Read/Write)

**Description** Sets the redundancy policy of the chassis.

**Legal Values**

- 0 (no redundancy)
- 1 (Grid redundancy)
- 3 ( Redundancy Alerting Only)

**Default** 3 ( Redundancy Alerting Only)

### cfgChassisInMaxPowerCapacity (Read Only)

**Description** Indicates the total chassis power budget (in watts) available for chassis operation.

**Legal Values** None

**Default** None

### cfgChassisInRedundancyReserve (Read Only)

**Description** Indicates the amount of redundant power (in Watts) in reserve that can be utilized in the event of an AC grid or PSU failure. This value is 0 if the Redundancy Policy is set to 0 (no redundancy).

**Legal Values**

- 0 (disabled)
- 1 (enabled)

**Default** None

### cfgChassisPowerClear (Write Only)

**Description** Resets **cfgChassisMinPower** and **cfgChassisMaxPowerCapacity**, when set to **1**.

**Legal Values** None

**Default** None

### cfgChassisPowerClearTimestamp (Read Only)

**Description** Time stamp when **cfgChassisMinPower** and **cfgChassisMaxPowerCapacity** were reset.

**Legal Values** None



**Default** None

## cfgChassisPowerButtonEnable (Read/Write)

**Description** Indicates if the chassis power button is enabled or disabled.

**Legal Values**

- 0 (disabled)
- 1 (enabled)

**Default** None

## cfgChassisPowerCapBTU (Read/Write)

**Description** Indicates the maximum power consumption limit (in BTU/hr) for the entire chassis. The command generates an error if server throttling is necessary to achieve the power goal based on the value for this setting.

**Legal Values** 9264 - 56931 BTU/hr

**Default** 43221 BTU/hr

## cfgChassisACPowerRecoveryDisable

**Description** If AC power recovery is disabled, the chassis is powered off after power outage is restored.

**Legal Values**

- 0 — Enable
- 1 — Disable

**Default** 0

## cfgKVMInfo

This group is used to view the mapping information for the KVM.

Use this object with the config or getconfig subcommands.

To use this object property, you must have **Chassis Configuration Administrator** privilege.

## cfgKvmEnable

**Description** Enable KVM operation for all slots

**Legal Values**

- 0 — Disable
- 1 — Enable

**Default** 1

## cfgKvmMapping

**Description** Selects the server to which the KVM connects

**Legal Values** 1[a-d]-4[a-d]

**Default** 0 (Unmapped)

## cfgAlerting

This group enables or disables SNMP event trap alerting and sets the event filter.

Use this object with the `config` or `getconfig` subcommands.

### cfgAlertingEnable

**Description** Enables or disables event traps on the CMC.

**Legal Values**

- 1 (true)
- 0 (false)

**Default** None

To use this object property, you must have the **Chassis Configuration Administrator** privilege.

### cfgAlertingSourceEmailName

**Description** Specifies the e-mail address used to send e-mail notifications when an event occurs.

**Legal Values** None

**Default** None

### Examples

```
racadm getconfig -g cfgAlerting -o cfgAlertingSourceEmailName
```

```
racadm config -g cfgAlerting -o cfgAlertingSourceEmailName user@home.com
```

Object value modified successfully.

To use this object property, you must have Chassis Configuration Administrator and Test Alert User privileges.

## cfgIPv6LanNetworking

This group is used to configure the IPv6 over LAN networking capabilities.

Use this object with the `config` or `getconfig` subcommands.

To use this object property for CMC, you must have Chassis Configuration Administrator privilege.

 **NOTE: To apply this setting to iDRAC, use the `-m` option.**



The following sections provide information about the objects in the **cfgIPv6LanNetworking** group.



## cfgIPv6Enable (Read or Write)

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables CMC IPv6 stack.                                            |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul> |
| <b>Default</b>      | 0                                                                              |


## cfgIPv6AutoConfig (Read/Write)

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the <b>IPv6 Auto Configuration</b> option.<br><br> <b>NOTE: If this value is set to 0, the CMC disables auto configuration and statically assigns IPv6 addresses. If this value is set to 1, the CMC obtains address and route information using stateless auto configuration and DHCPv6.</b><br><br> <b>NOTE: The CMC uses its MAC address for its DUID (DUID-LL) when communicating with a DHCPv6 server.</b> |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Default</b>      | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |


## cfgIPv6Address

|                     |                                                                                                                       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Assigns a static IPv6 address to the CMC. This property is used only if <b>cfgIPv6AutoConfig</b> is set to 0 (false). |
| <b>Legal Values</b> | A string representing a valid IPv6 address. For example, 2001:DB8:1234:5678:9ABC:DE11:C00C:BEEF                       |
| <b>Default</b>      | ::                                                                                                                    |

## cfgIPv6PrefixLength (Read/Write)

|                     |                                                                                                                                                                                                                           |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the prefix length for IPv6 address.<br><br> <b>NOTE: This property is used only if cfgIPv6AutoConfig is set to 0 (false)</b> |
| <b>Legal Values</b> | 0–128                                                                                                                                                                                                                     |
| <b>Default</b>      | 64                                                                                                                                                                                                                        |

## cfgIPv6Gateway (Read/Write)

|                     |                                                                                                                                                                                                        |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | CMC gateway IPv6 address.<br><br> <b>NOTE: This property is used only if cfgIPv6AutoConfig is set to 0 (false.)</b> |
| <b>Legal Values</b> | Specifies string representing a valid IPv6 entry.                                                                                                                                                      |

**Default** ::

## cfgCurrentIPv6DNSServersFromDHCP6

**Description** Indicates whether the DNS server addresses are assigned from the DHCPv6 server.

## cfgIPv6DNSServer1 (Read/Write)

**Description** Specifies the IPv6 DNS server address.

 **NOTE: This property is used only if cfgIPv6DNSServersFromDHCP6 is set to 0 (false).**

**Legal Values** A string representing a valid IPv6 entry. For example, 2001:DB8:1234:5678:9ABC:DE11:C00C:BEEF

**Default** ::

## cfgIPv6DNSServer2 (Read/Write)

**Description** Specifies the IPv6 DNS server address.

 **NOTE: This property is only valid if cfgIPv6DNSServersFromDHCP6 is set to 0 (false).**

**Legal Values** A string representing a valid IPv6 entry. For example, 2001:DB8:1234:5678:9ABC:DE11:C00C:BEEF

**Default** ::

### Example

```
$ racadm getconfig -g cfgIPv6LanNetworking
cfgCurrentIPv6Enabled=1
cfgIPv6AutoConfig=1
cfgIPv6Address=::
cfgIPv6PrefixLength=64
cfgIPv6Gateway=::
cfgIPv6DNSServersFromDHCP6=1
cfgIPv6DNSServer1=::
cfgIPv6DNSServer2=::
```

If both IPv4 and IPv6 are enabled on the CMC, IPv6 DNS servers take priority. The order of preference for DNS servers is:

- cfgIPv6DNSServer1
- cfgIPv6DNSServer2
- cfgDNSServer1
- cfgDNSServer2

## cfgCurrentLanNetworking (Read Only)

This group displays the current CMC NIC properties.



Use this object with the **getconfig** subcommand.

To use this object property, you must have the **CMC Login User** privilege.

### Synopsis

```
racadm getconfig -g cfgCurrentLanNetworking
```

## cfgNicCurrentIpAddress

**Description** Displays the IP address the CMC is currently using.

**Legal Values** Valid IPv4 addresses. For example: 192.168.0.20.

## cfgNicCurrentNetmask

**Description** Displays the subnet mask the CMC is currently using.

**Legal Values** Valid IPv4 addresses. For example: 192.168.0.20.

## cfgNicCurrentGateway

**Description** Displays the Gateway address the CMC is currently using.

**Legal Values** Valid IPv4 addresses. For example: 192.168.0.20.

## cfgNicCurrentDhcpWasUsed

**Description** Indicates whether DHCP is used to configure the NIC.

**Legal Values** 0 – address is static.  
1– address was obtained from the DHCP server.

**Default** None

## cfgNicCurrentVlanEnable (Read Only)

**Description** Indicates whether the VLAN is enabled.

**Legal Values** 0- VLAN is disabled  
1- VLAN is enabled

## cfgNicCurrentVlanID (Read Only)

**Description** Indicates the Current Virtual Lan ID

**Legal Values** Integer

## cfgNicCurrentVlanPriority (Read Only)

**Description** Indicates the Current Virtual Lan Priority.

**Legal Values** Integer

## cfgDNSCurrentServer1

**Description** Displays the IP address for DNS server 1.

**Legal Values** A Valid IPv4 DNS IP

## cfgDNSCurrentServer2

**Description** Displays the IP address for DNS server 2.

## cfgDNSCurrentDomainName

**Description** Displays the DNS domain name.

## cfgNicCurrentIPv4Enabled

**Description** Indicates whether IPv4 is enabled on the CMC. If the current property value is set to 0 (false), the remote network interfaces to the CMC are not accessible over IPv4.

### Example

```
racadm getconfig -g cfgCurrentLanNetworking
cfgNicCurrentIPv4Enabled=1
cfgNicCurrentIpAddress=192.68.152.116
cfgNicCurrentNetmask=255.255.255.0
cfgNicCurrentGateway=192.68.152.1
cfgNicCurrentDhcpWasUsed=0
cfgNicCurrentVlanEnable=0
cfgNicCurrentVlanID=1
cfgNicCurrentVlanPriority=0
cfgDNSCurrentServer1=192.168.0.5
cfgCurrentIPv6DNSServer2=192.168.0.6
cfgDNSCurrentDomainName=MYDOMAIN
```

## cfgCurrentIPv6LanNetworking (Read Only)

This group displays the current CMC IPv6 properties.

This group is applicable only for CMC. Use this object with the **getconfig** subcommand.

To use this object property, you must have the **CMC Login User** privilege.



## cfgCurrentIPv6Enabled (Read/Write)

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | Enables or disables the IPv6 stack.                                            |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 1 (TRUE)</li><li>• 0 (FALSE)</li></ul> |
| <b>Default</b>      | 0                                                                              |

## cfgCurrentIPv6AutoConfigWasUsed

|                     |                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates whether auto configuration is used to obtain IPv6 settings, including stateless IPv6 address(es) and gateway. |
| <b>Legal Values</b> | 0 (static addressing is used)<br>1 (address is obtained from the DHCPv6 server and/or stateless auto configuration)     |
| <b>Default</b>      | None                                                                                                                    |

## cfgCurrentLinkLocalAddress

|                    |                                                          |
|--------------------|----------------------------------------------------------|
| <b>Description</b> | Displays the current IPv6 link-local address of the CMC. |
|--------------------|----------------------------------------------------------|

## cfgCurrentIPv6Address

|                    |                                                                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b> | Displays the current IPv6 addresses. This property displays up to 15 global IPv6 addresses, including stateful and stateless addresses. |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------|

## cfgCurrentIPv6Gateway

|                    |                                    |
|--------------------|------------------------------------|
| <b>Description</b> | Displays the current IPv6 gateway. |
|--------------------|------------------------------------|

## cfgCurrentIPv6DNSServersFromDHCP6

|                    |                                                                                 |
|--------------------|---------------------------------------------------------------------------------|
| <b>Description</b> | Indicates whether the DNS server addresses are assigned from the DHCPv6 server. |
|--------------------|---------------------------------------------------------------------------------|

## cfgCurrentIPv6DNSServer1

|                    |                                             |
|--------------------|---------------------------------------------|
| <b>Description</b> | Displays the IPv6 address for DNS server 1. |
|--------------------|---------------------------------------------|

## cfgCurrentIPv6DNSServer2

|                    |                                             |
|--------------------|---------------------------------------------|
| <b>Description</b> | Displays the IPv6 address for DNS server 2. |
|--------------------|---------------------------------------------|

# cfgNetTuning

This group enables users to configure the advanced network interface parameters for the RAC NIC or CMC. When configured, the updated settings may take up to a minute to become active.

The following sections provide information about the objects in the **cfgNetTuning** group.

 **CAUTION: Use extra precaution when modifying properties in this group. Inappropriate modification of the properties in this group can result in your RAC NIC become inoperable.**

## cfgNetTuningNicSpeed

|                     |                                                                                                               |
|---------------------|---------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the speed for the CMC NIC. This property is used only if <b>cfgNetTuningNicAutoNeg</b> is set to 0. |
| <b>Legal Values</b> | 10, 100, or 1000                                                                                              |
| <b>Default</b>      | 100                                                                                                           |

## cfgNetTuningNicAutoneg (Read/Write)

|                     |                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables autonegotiation of physical link speed and duplex. If enabled, autonegotiation takes priority over other values set in this group. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 = Auto Negotiation is Disabled</li><li>• 1 = Auto Negotiation is Enabled</li></ul>               |
| <b>Default</b>      | 1                                                                                                                                          |

### Example

```
racadm getconfig -g cfgNetTuning

cfgNetTuningNicSpeed=100
cfgNetTuningNicFullDuplex=1
cfgNetTuningNicMtu=1500
cfgNetTuningNicAutoneg=1
```

## cfgNetTuningNicFullDuplex (Read/Write)

|                     |                                                                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Specifies the duplex setting for the RAC or CMC NIC. This property is used only if the <b>cfgNetTuningNicAutoNeg</b> is set to 0 (disabled). |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 (Half Duplex)</li><li>• 1 (Full Duplex)</li></ul>                                                  |
| <b>Default</b>      | 1                                                                                                                                            |

## cfgNetTuningNicMtu (Read/Write)

|                     |                                                                     |
|---------------------|---------------------------------------------------------------------|
| <b>Description</b>  | The size in bytes of the maximum transmission unit used by CMC NIC. |
| <b>Legal Values</b> | 576 – 1500                                                          |



**Default** 1500

 **NOTE:** IPv6 requires a minimum MTU of 1280. If IPv6 is enabled, and `cfgNetTuningMtu` is set to a lower value, the CMC uses an MTU of 1280.

## cfgNetTuningNicRedundant

**Description** Specifies either Stacking or Redundant mode for CMC Management Port 2.

**Legal Values**

- 0 – Stacking
- 1 – Redundant

**Default** 0 – Stacking

 **NOTE:** When Management Port 2 is set for Redundant but is cabled for Stacking, the downstream CMCs (further from the top-of-rack switch) will not have a network link.

 **NOTE:** When Management Port 2 is set for Stacking but is cabled for Redundant (two connections to the TOR switch), routing loops could cause a network storm.

## cfgRacSecurity

This group is used to configure settings related to CMC SSL certificate signing request (CSR) feature. The properties in this group must be configured before generating a CSR from CMC.

Use this object with the `config` or `getconfig` subcommands.

To use this object property, you must have **Chassis Configuration Administrator** privilege.

For more information on generating certificate signing requests, see the subcommand "`sslcsrgen`."

The following sections provide information about the objects in the **cfgRacSecurity** group.

### cfgRacSecCsrCommonName (Read/Write)

**Description** Specifies the CSR Common Name (CN) that must be an IP or CMC name as given in the certificate.

**Legal Values** A string of up to 254 characters.

**Default** <blank>

### cfgRacSecCsrOrganizationName (Read/Write)

**Description** Specifies the CSR Organization Name (O).

**Legal Values** A string of up to 254 characters.

**Default** <blank>

## cfgRacSecCsrOrganizationUnit (Read/Write)

|                     |                                           |
|---------------------|-------------------------------------------|
| <b>Description</b>  | Specifies the CSR Organization Unit (OU). |
| <b>Legal Values</b> | A string of up to 254 characters.         |
| <b>Default</b>      | <blank>                                   |

## cfgRacSecCsrLocalityName (Read/Write)

|                     |                                   |
|---------------------|-----------------------------------|
| <b>Description</b>  | Specifies the CSR Locality (L).   |
| <b>Legal Values</b> | A string of up to 254 characters. |
| <b>Default</b>      | <blank>                           |

## cfgRacSecCsrStateName (Read/Write)

|                     |                                   |
|---------------------|-----------------------------------|
| <b>Description</b>  | Specifies the CSR State Name (S). |
| <b>Legal Values</b> | A string of up to 254 characters. |
| <b>Default</b>      | <blank>                           |

## cfgRacSecCsrCountryCode (Read/Write)

|                     |                                      |
|---------------------|--------------------------------------|
| <b>Description</b>  | Specifies the CSR Country Code (CC). |
| <b>Legal Values</b> | A string of 2 alphabet country code. |
| <b>Default</b>      | US                                   |

## cfgRacSecCsrEmailAddr (Read/Write)

|                     |                                   |
|---------------------|-----------------------------------|
| <b>Description</b>  | Specifies the CSR email address.  |
| <b>Legal Values</b> | A string of up to 254 characters. |
| <b>Default</b>      | <blank>                           |

### Example

```
racadm config -g cfgRacSecurity

cfgRacSecCsrKeySize=1024
cfgRacSecCommonName=
cfgRacSecOrganizationName=
cfgRacSecOrganizationUnit=
cfgRacSecLocalityName=
cfgRacSecStateName=
cfgRacSecCountryCode=
cfgRacSecEmailAddr=
```



## cfgRacSecCsrKeySize (Read/Write)

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| <b>Description</b>  | Specifies the SSL asymmetric key size for the CSRs. |
| <b>Legal Values</b> | 1024, 2048, 4096                                    |
| <b>Default</b>      | 2048                                                |

## cfgPCle

Displays the PCIe reassignment information.

Use this sub command with the `getConfig` and `config` commands.

The following section provides information about the objects in the **cfgPCle** group.

### cfgPCleReassignmentEnable (Read/Write)

|                     |                                                                                    |
|---------------------|------------------------------------------------------------------------------------|
| <b>Description</b>  | Indicates whether the PCIe reassignment is enabled or disabled.                    |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — Disable</li><li>• 1 — Enable</li></ul> |

 **NOTE: Power off all the servers in the FX2s chassis before changing the PCIe reassignment.**

## cfgQuickDeploy

This group is used to configure iDRAC deployment settings. You must have blade administrator privileges for configuring the settings.

### cfgActionOnServerInsertion

**Table 4. cfgActionOnServerInsertion — Details**

|                     |                                                                                                                                                                                |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Configures settings when a new server is inserted into the slot.                                                                                                               |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — No Action</li><li>• 1 — QuickDeploy Only</li><li>• 2 — Server Profile Only</li><li>• 3 — Quick Deploy and Server Profile</li></ul> |
| <b>Default</b>      | 0                                                                                                                                                                              |

### cfgSetiDRACRootPasswordOnServerInsertion

**Table 5. cfgSetiDRACRootPasswordOnServerInsertion — Details**

|                     |                                                                                                                                                                                                                                                          |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Sets the iDRAC root password when a server is inserted into the chassis.                                                                                                                                                                                 |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 (False) — If the value is '1' when the server is inserted, the iDRAC root password is not set.</li><li>• 1 (True) — If the value is '1' when the server is inserted, the iDRAC root password is set.</li></ul> |

**Default** 0

## cfgiDRACRootPassword

Table 6. cfgiDRACRootPassword — Details

|                     |                                                                          |
|---------------------|--------------------------------------------------------------------------|
| <b>Description</b>  | The root password is applied when servers are inserted into the chassis. |
| <b>Legal Values</b> | Up to 64 characters.                                                     |
| <b>Default</b>      | calvin                                                                   |

## cfgEnableiDRACLAN

Table 7. cfgEnableiDRACLAN — Details

|                     |                                                                                    |
|---------------------|------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables the LAN channel for iDRAC when servers are inserted into the chassis.      |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — Disable</li><li>• 1 — Enable</li></ul> |
| <b>Default</b>      | 1                                                                                  |

## cfgEnableiDRACIPv4

Table 8. cfgEnableiDRACIPv4 — Details

|                     |                                                                                                |
|---------------------|------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables IPv4 for each iDRAC in the chassis. Any iDRAC that is not IPv6 is always IPv4 enabled. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — Disable</li><li>• 1 — Enable</li></ul>             |
| <b>Default</b>      | 1                                                                                              |

## cfgEnableiDRACIPMIOverLAN

Table 9. cfgEnableiDRACIPMIOverLAN

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables IPMI over LAN channel for iDRAC when servers are inserted into the chassis. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — Disable</li><li>• 1 — Enable</li></ul>  |
| <b>Default</b>      | 0                                                                                   |

## cfgEnableiDRACIPv4DHCP

Table 10. cfgEnableiDRACIPv4DHCP — Details

|                     |                                                                    |
|---------------------|--------------------------------------------------------------------|
| <b>Description</b>  | Enables DHCP for iDRAC when servers are inserted into the chassis. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — Disable</li></ul>      |



- 1 — Enable

**Default** 1

## cfgStartingiDRACIPv4Address

**Table 11. cfgStartingiDRACIPv4Address — Details**

|                     |                                                                  |
|---------------------|------------------------------------------------------------------|
| <b>Description</b>  | The static IPv4 address for the iDRAC located in the first slot. |
| <b>Legal Values</b> | IP format                                                        |
| <b>Default</b>      | 192.168.0.121                                                    |

## cfgiDRACIPv4GateWay

**Table 12. cfgiDRACIPv4GateWay — Details**

|                     |                                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------|
| <b>Description</b>  | IPv4-specific default gateway that is common to all the IPv4-enabled iDRACs present in the chassis. |
| <b>Legal Values</b> | IP format                                                                                           |
| <b>Default</b>      | 0.0.0.0                                                                                             |

## cfgiDRACIPv4Netmask

**Table 13. cfgiDRACIPv4Netmask — Details**

|                     |                                                                                |
|---------------------|--------------------------------------------------------------------------------|
| <b>Description</b>  | IPv4-specific subnet mask that is common to all iDRACs present in the chassis. |
| <b>Legal Values</b> | IP format                                                                      |
| <b>Default</b>      | 255.255.255.0                                                                  |

## cfgEnableiDRACIPv6

**Table 14. cfgEnableiDRACIPv6 — Details**

|                     |                                                                                       |
|---------------------|---------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables IPv6 for each IPv6-capable iDRAC present in the chassis.                      |
| <b>Legal Values</b> | <ul style="list-style-type: none"> <li>• 0 — Disable</li> <li>• 1 — Enable</li> </ul> |
| <b>Default</b>      | 0                                                                                     |

## cfgEnableiDRACIPv6AutoConfig

Table 15. cfgEnableiDRACIPv6AutoConfig — Details

|                     |                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Enables the IPv6 feature that allows each iDRAC present in the chassis to set its IPv6 address automatically, without manual configuration of the host or DHCP servers. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — Disable</li><li>• 1 — Enable</li></ul>                                                                                      |
| <b>Default</b>      | 0                                                                                                                                                                       |

## cfgiDRACIPv6PrefixLength

Table 16. cfgiDRACIPv6PrefixLength — Details

|                     |                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------|
| <b>Description</b>  | The length of the subnet in bits that is common to all IPv6-enabled iDRACs present in the chassis. |
| <b>Legal Values</b> | 0–128                                                                                              |
| <b>Default</b>      | 64                                                                                                 |

## cfgiDRACIPv6Gateway

Table 17. cfgiDRACIPv6Gateway — Details

|                     |                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------|
| <b>Description</b>  | IPv6-specific default gateway that is common to all IPv6-enabled iDRACs present in the chassis. |
| <b>Legal Values</b> | IPv6 format                                                                                     |
| <b>Default</b>      | ::                                                                                              |

## cfgReservedIPAddressNumbers

Table 18. cfgReservedIPAddressNumbers — Details

|                     |                                                                         |
|---------------------|-------------------------------------------------------------------------|
| <b>Description</b>  | The number of static IPv4 addresses reserved for iDRACs in the chassis. |
| <b>Legal Values</b> | 32                                                                      |
| <b>Default</b>      | 32                                                                      |

## cfgUseCMCDNSSettings

Table 19. cfgUseCMCDNSSettings — Details

|                     |                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <b>Description</b>  | Propagates the CMC DNS Server settings (IPv4 and IPv6) to iDRAC when a blade server is inserted in the chassis. |
| <b>Legal Values</b> | <ul style="list-style-type: none"><li>• 0 — False</li><li>• 1 — True</li></ul>                                  |



Default

0

