

Dell SupportAssist Version 1.2 for Servers Reportable Items for Linux



Notes, cautions, and warnings

 **NOTE:** A NOTE indicates important information that helps you make better use of your computer.

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.

Copyright © 2016 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell™ and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2016 - 02

Rev. A00

Contents


1 Introduction.....	5
Data categories.....	5
Accessing the Summary items.....	6
Summary items.....	6
Summary.....	6
Accessing the System items.....	8
System items.....	8
Main Chassis.....	8
Hardware Log.....	9
BIOS.....	9
Battery.....	14
Processor.....	14
Fan.....	16
Fan Redundancy.....	16
Firmware.....	16
Component Detail.....	16
Front Panel.....	17
FRU.....	17
Intrusion.....	17
Memory Array.....	17
Network.....	18
Port.....	23
Power Supply.....	23
Power Supply Redundancy.....	23
Remote Access Device.....	23
Removable Flash Media.....	25
Slot.....	25
Temperature.....	26
Voltage.....	26
Auto Recovery.....	27
Hardware Performance.....	27
Power Management.....	27
Accessing the Storage items.....	28
Storage items.....	28
Controller.....	28
SATA/IDE Controller.....	36
Fibre Channel Controller.....	37

Accessing the Software items.....	38
Software items.....	38
Operating System.....	38
OpenManage.....	47
Accessing the Logs.....	49
Logs.....	49
Logs.....	49


Introduction


Dell SupportAssist for Servers is an application that enables automated support from Dell by proactively identifying hardware issues in Dell devices. By default, SupportAssist collects system information periodically from each monitored device and sends the data securely to Dell. Typically, system information is collected as follows:

- Periodically — At regular intervals, depending on the configured collection frequency. By default, SupportAssist is configured to collect system information from Dell PowerEdge servers once a month.
- On case creation — When a support case is created for an issue that has been identified by SupportAssist.

 **NOTE:** When an issue is detected on devices with a Basic Support entitlement, SupportAssist does not create a support case. However, system information is collected and sent to Dell.

- On demand — If requested by the Dell Technical Support agent to manually initiate the collection of system information from a device.

 **NOTE:** If required, you can disable the periodic collection of system information for a specific device type or for all device types. For more information, see “Configuring data collection settings” in the *Dell SupportAssist Version 1.2 for Servers User’s Guide*.

 **NOTE:** If the security policy of your company restricts sending certain identity information outside of the company network, you can disable the collection of such data from monitored devices. For more information, see “Configuring data collection settings” in the *Dell SupportAssist Version 1.2 for Servers User’s Guide*.


The collected system information is saved in a secured database on the system on which SupportAssist is installed. You can view the collected system information through the configuration viewer available in SupportAssist.


This document provides the list of attributes that may be available in the data collected by SupportAssist from devices that are running a Linux operating system.

Data categories

The following are the top-level categories of data that you can view:

- Summary
- System
- Storage
- Software
- Logs

 **NOTE:** If a device that you have added in SupportAssist by using the operating system IP address or the host name does not have Dell OpenManage Server Administrator (OMSA) installed, System and Storage items will not be available in periodic collections from that device.

 **NOTE:** If you have disabled the collection of identity information from devices, the identity information is replaced by tokenized values in the collected data. The tokenized values are represented as TOKEN n —for example, TOKEN0, TOKEN1, or TOKEN2.

Accessing the Summary items

To access the Summary items:

On the configuration viewer, click **PowerEdge xxx** → **Summary**.

Summary items

Summary

Category	Sub category	Attribute name
Collection Settings		Options
		Identification Shared With Dell
		Mode
		Source
Error Summary		Name
		Location
		Status
Main Chassis		Server Model
		Server Service Tag
		Express Service Code
		Chassis Lock
		Server Asset Tag
System		Host Name
		System Location
Processor		Manufacturer
		Family
		Version
		Current Speed
		Maximum Speed
		External Clock Speed
		Voltage
Memory		Total Installed Capacity
		Total Maximum Capacity

Category	Sub category	Attribute name
		Total Installed Capacity Available To The OS
		Memory Array Count
Memory Array		Location
		Use
		Installed Capacity (MB)
		Maximum Capacity (MB)
		Slots Available
		Slots Used
		ECC Type
Operating System		OS Name
		Version
		Install Date
BIOS		Manufacturer
		Version
		Release Date
Network		Network Interface
		IPv4 Address
		IPv6 Address
		Subnet Mask
		MAC Address
		Default Gateway
Controller		ID
		Name
		State
		Firmware Version
		Driver Version
		Number of Connectors
		Rebuild Rate
		BGI Rate
		Check Consistency Rate


Category	Sub category	Attribute name
		Reconstruct Rate
		Abort Check Consistency On Error
		Allow Revertible Hot Spare And Replace Member
		Load Balance
		Auto Replace Member On Predictive Failure
		Cache Memory Size (MB)
		Patrol Read Mode
		Patrol Read State
		Patrol Read Iterations
		Number of Extenders

Accessing the System items

To access the System items:

On the configuration viewer, click **PowerEdge xxx** → **Server** → **System**.

System items

 **NOTE:** If a device that you have added in SupportAssist by using the operating system IP address or the host name does not have Dell OpenManage Server Administrator (OMSA) installed, System data will not be available in periodic collections from that device.

Main Chassis

Category	Sub category	Attribute name
Main Chassis		Chassis Lock
		Chassis Name
		Device System Id
		Express Service Code
		Flash Chassis Identify LED State
		Flash Chassis Identify LED Timeout value
		Fault LED Flash On Severity Level
		Host Name

Category	Sub category	Attribute name
		System Location
		Index
		Server Asset Tag
		Server Model
		Server Module Location
		Server Service Tag
		System Revision
		System Revision Name
	Additional Information	DRAC or iDRAC Version
		Lifecycle Controller Version
	Modular Enclosure Information	Product
		Description
		Version
		IP Address
		Chassis Service Tag
		Model
		IP Address Type
		IP Address Source
		Express Service Code

Hardware Log

Category	Sub category	Attribute name
Hardware Log		Description
		Date And Time
		Severity
		Raw SEL Data

BIOS

Category	Sub category	Attribute name
BIOS		Manufacturer
		Version
		Release Date

Category	Sub category	Attribute name
	System Security	Intel(R) AES-NI
		System Password
		Setup Password
		Password Status
		TPM Security
		TPM Information
		TPM Status
		TPM Command
		Intel(R) TXT
		AC Power Recovery
		AC Power Recovery Delay
		User Defined Delay (60s to 240s)
		UEFI Variable Access
		Secure Boot
		Secure Boot Policy
	Serial Communication	External Serial Connector
		Serial Port Address
		Remote Terminal Type
		Redirection After Boot
		Failsafe Baud Rate
		Serial Communication
	SATA Setting	Embedded SATA
		Security Freeze Lock
		Write Cache
		Port <number>
		Model
		Drive Type
		Capacity
	Processor Setting	Logical Processor
		QPI Speed

Category	Sub category	Attribute name
		Alternate RTID (Requestor Transaction ID) Setting
		Virtualization Technology
		Address Translation Service (ATS)
		Adjacent Cache Line Prefetch
		Hardware Prefetcher
		DCU Streamer Prefetcher
		DCU IP Prefetcher
		Execute Disable
		Logical Processor Idling
		Configurable TDP
		X2Apic Mode
		Dell Controlled Turbo
		Number of Cores per Processor
		Processor 64-bit Support
		Processor Core Speed
		Processor Bus Speed
		Brand
		Level <level_number> Cache
		Number of Cores
		Family-Model-Stepping
	Memory Setting	System Memory Size
		System Memory Type
		System Memory Speed
		System Memory Voltage
		Video Memory
		System Memory Testing
		Memory Operating Mode
		Node Interleaving
	Snoop Mode	
	Correctable Memory ECC SMI	

Category	Sub category	Attribute name
	System Profile Setting	Energy Efficient Turbo
		Memory Frequency
		System Profile
		CPU Power Management
		Memory Patrol Scrub
		Uncore Frequency
		Memory Refresh Rate
		Energy Efficient Policy
		Number of Turbo Boost Enabled Cores for Processor <number>
		Turbo Boost
		C States
		C1E
		Collaboration CPU Performance Control
		Monitor/Mwait
	Miscellaneous Setting	Asset Tag
		Keyboard NumLock
		F1/F2 Prompt on Error
		Load Legacy Video Option ROM
		In-System Characterization
	System Information	System Model Name
		System BIOS Version
		System Management Engine Version
		System Service Tag
		System Manufacturer
		System Manufacturer Contact Information
		System CPLD Version
		UEFI Compliance Version
	Integrated Device	USB 3.0 Settings

Category	Sub category	Attribute name
		User Accessible USB Ports
		Internal USB Port
		Embedded NIC1 and NIC2
		I/OAT DMA Engine
		OS Watchdog Timer
		Embedded Video Controller
		Current State of Embedded Video Controller
		SR-IOV Global Enable
		Memory Mapped I/O above 4GB
		Slot Disablement
	Slot Number	
	Slot Number	
	Slot Number	
	Slot Number	
	Slot Number	
	Slot Number	
	Slot Number	
	Boot Option Setting	Hard-Disk Drive Sequence
		Boot Sequence
	Boot Setting	Hard-Disk Failover
		Boot Mode
		Boot Sequence Retry
	UEFI Boot Setting	UEFI Boot Sequence
		UEFI PXE boot protocol
	One Time Boot	One-Time Boot Device List
		BIOS Boot Sequence Device
		BIOS Hard-Disk Drive Sequence Device
		UEFI Boot Sequence Device

Battery

Category	Sub category	Attribute name
Battery		Probe Name
		Reading (Amp)
		Status

Processor

Category	Sub category	Attribute name
Processor		Connector Name
		Manufacturer
		Family
		Processor Brand
		Version
		Core Count
		Current Speed
		Maximum Speed
		External Clock Speed
		Voltage
		State
		Status
		Occupied
	CPU Detail	Cache1 Maximum Size
		Cache2 Maximum Size
		Cache3 Maximum Size
		Cache1 Size
		Cache1 Write Policy
		Cache1 Associativity
		Cache1 Error Correction Type
		Cache1 Location
		Cache1 Type
		Cache1 Level

Category	Sub category	Attribute name
		Cache1 Status
		Cache2 Size
		Cache2 Write Policy
		Cache2 Associativity
		Cache2 Error Correction Type
		Cache2 Location
		Cache2 Type
		Cache2 Level
		Cache2 Status
		Cache3 Size
		Cache3 Write Policy
		Cache3 Associativity
		Cache3 Error Correction Type
		Cache3 Location
		Cache3 Type
		Cache3 Level
		Cache3 Status
		Processor > CPU Detail > Support 64bit
	Capable	
	Enabled	
	Processor > CPU Detail > HyperThreading	Technology
		Capable
		Enabled
	Processor > CPU Detail > Virtualization	Technology
		Capable
		Enabled
	Processor > CPU Detail > Demand Based Switching	Technology
		Capable
		Enabled
	Processor > CPU Detail > No Execute	Technology
		Capable

Category	Sub category	Attribute name
		Enabled
	Processor > CPU Detail > Turbo Mode	Technology
		Capable
		Enabled

Fan

Category	Sub category	Attribute name
Fan		Probe Name
		Reading (Amp)
		Minimum Warning Threshold
		Maximum Warning Threshold
		Minimum Failure Threshold
		Maximum Failure Threshold
		Status

Fan Redundancy

Category	Sub category	Attribute name
Fan Redundancy		Redundancy Status

Firmware

Category	Sub category	Attribute name
Firmware		Name
		Version

Component Detail

Category	Sub category	Attribute name
Component Detail		Component ID
		Description
		Component Type
		Software Version
		Hardware Device ID
		Hardware Vendor ID

Category	Sub category	Attribute name
		Hardware Sub-Device ID
		Hardware Sub-Vendor ID

Front Panel

Category	Sub category	Attribute name
Front Panel		Power Button
		NMI Button
	LCD Information	Front Panel LCD Security Access
		Enable Remote Indication
	LCD Line Information	LCD Line 1
		Service Tag

FRU

Category	Sub category	Attribute name
FRU		Device
		Serial Number
		Part Number
		Revision
		Manufacturer
		Manufactured Date

Intrusion

Category	Sub category	Attribute name
Intrusion		Probe Name
		State
		Status

Memory Array

Category	Sub category	Attribute name
Memory Array		Location
		Use
		Installed Capacity (MB)

Category	Sub category	Attribute name
		Maximum Capacity (MB)
		Slots Available
		Slots Used
		ECC Type
		Total Installed Capacity
		Total Installed Capacity Available To The OS
		Total Maximum Capacity
	Memory	Device Name
		Size
		Speed
		Rank
		Failures
		Status
		Type
		Type Detail

Network

Category	Sub category	Attribute name
Network		Interface Name
		Link Status
		Duplex
		IRQ
		DMA
		Base IO Address
		Base Memory Address
		Description
		Vendor
		Slot Name
		Driver Name
		Driver Version
		Driver Image Path

Category	Sub category	Attribute name
		Current MAC Address
		Team Name
		Firmware Version
		Maximum Transmission Unit
		Speed
		Default Gateway
		Received Good Frames
		Received Bad Frames
		Received Alignment Errors
		Received FCS Errors
		Received Frames Too Long
		Received Bytes
		Received Total Packets
		Received Unicast Packets
		Received Multicast Packets
		Received Broadcast Packets
		Received Discarded Packets
		Received Error Packets
		Transmitted Bytes
		Transmitted Total Packets
		Transmitted Unicast Packets
		Transmitted Multicast Packets
		Transmitted Broadcast Packets
		Transmitted Discarded Packets
		Transmitted Error Packets
		Transmitted Collisions
		Transmitted Single Collision Frames
		Transmitted Multiple Collision Frames
		Transmitted Deferred Transmits
		Transmitted Late Collisions

Category	Sub category	Attribute name
		Transmitted Excessive Collisions
		Transmitted Carrier Sense Errors
		Transmitted Internal MAC Transmission Errors
		Received Internal MAC Receiving Errors
		Administrative Status
		Operational Status
		Type
		Connection Status
		DHCP Server
		Default IPv6 Gateway
		DHCPv6 Server
		Interface Description
		Transmitted Good Frames
		Transmitted Bad Frames
		Received Unknown Protocols
		Transmitted Queue Length
		TOE Enabled
		NparEP Enabled
		TOE Capable
		IPv4 Addresses
	IPv4 Address	
	Subnet Mask	
	IPv6 Addresses	Description
		Prefix Length
		IPv6 Address
		IPv6 Address Name
		Name
	Network Team Interface	Link Status
		Interface Name
		Description

Category	Sub category	Attribute name
		Vendor
		Slot Name
		Driver Name
		Driver Version
		Driver Image Path
		Current MAC Address
		Team Name
		Maximum Transmission Unit
		Speed
		Default Gateway
		Received Good Frames
		Received Bad Frames
		Received Alignment Errors
		Received FCS Errors
		Received Frames Too Long
		Received Bytes
		Received Total Packets
		Received Unicast Packets
		Received Multicast Packets
		Received Broadcast Packets
		Received Discarded Packets
		Received Error Packets
		Transmitted Bytes
		Transmitted Total Packets
		Transmitted Unicast Packets
		Transmitted Multicast Packets
		Transmitted Broadcast Packets
		Transmitted Discarded Packets
		Transmitted Error Packets
		Team Interface Transmitted Collisions

Category	Sub category	Attribute name
		Transmitted Single Collision Frames
		Transmitted Multiple Collision Frames
		Transmitted Deferred Transmits
		Transmitted Late Collisions
		Transmitted Excessive Collisions
		Team Interface Transmitted Carrier Sense Errors
		Transmitted Internal MAC Transmission Errors
		Received Internal MAC Receiving Errors
		IPv4 Address
		Subnet Mask
		IPv6 Address
		Prefix Length
		IPv6 Address Name
		Administrative Status
		Operational Status
		Type
		Connection Status
		Team Type
		DHCP Server
		Default IPv6 Gateway
		DHCPv6 Server
		Interface Description
		Transmitted Good Frames
		Transmitted Bad Frames
		Received Unknown Protocols
		Transmitted Queue Length
		Redundancy Status

Port

Category	Sub category	Attribute name
Port		External Name
		Base I/O Addr
		IRQ Level
		Maximum Speed
		Connector Type
		Port Type

Power Supply

Category	Sub category	Attribute name
Power Supply		Location
		Power Monitoring Capable
		Rated Input Wattage
		Maximum Output Wattage
		Firmware Version
		Online Status
		Status
		Type

Power Supply Redundancy

Category	Sub category	Attribute name
Power Supply Redundancy		Redundancy Status

Remote Access Device

Category	Sub category	Attribute name
Remote Access Device		IPMI Version
		System GUID
		MAC Address
		IPv4 Address
		IPv4 Subnet
		IPv4 Gateway

Category	Sub category	Attribute name
		VLAN ID
		Priority
		SOL Enabled
		Device Type
		Number Of Current Active Sessions
		Enable IPMI Over LAN
		Number Of Possible Active Sessions
		Enable VLAN ID
		IPv4 Address Source
		Remote Access Device > NIC Configuration
	Primary Network	
	Failover Network	
	Remote Access Device > Serial Port Configuration	Channel Number
		Connection Mode Setting
		Baud Rate
		Flow Control
		Channel Privilege Level Limit
		Serial Port Configuration
		Line Editing
		Delete Control
		Echo Control
		Handshaking Control
		New Line Sequence
	Input New Line Sequence	
	Remote Access Device > Serial Over LAN Configuration	Channel Number
		Baud Rate
		Minimum privileges required
		Serial Over LAN Configuration
		Retry Count
		Retry Interval

Category	Sub category	Attribute name
		Character Accumulate Interval
		Character Send Threshold
	Remote Access Device > User Setting > User	Product
		Description
		Version
		IP Address
		IP Subnet
		IP Gateway
	Remote Access Device > User	User ID
		State
		User Name
		LAN User Privilege
		Serial Over LAN Payload
		Serial Port User Privilege
		DRAC User Privilege

Removable Flash Media

Category	Sub category	Attribute name
Removable Flash Media		Type
		Connector Name
		Available Size (MB)
		State
		Storage Size (MB)

Slot

Category	Sub category	Attribute name
Slot		ID
		Slot ID
		Type
		Slot Length Adapter
		Speed Data Bus Width
		Category

Category	Sub category	Attribute name
		Hot Plug Capable
		Voltage Supply
		Shared Slot
		Card Bus
		Modem Ring Resume
		Zoom Video
		PC Card-16
		Power Management Enable (PME#) Signal
		Adapter Data Bus Width
		Adapter Manufacturer
		Adapter Description

Temperature

Category	Sub category	Attribute name
Temperature		Probe Name
		Reading (Amp)
		Minimum Failure Threshold
		Minimum Warning Threshold
		Maximum Failure Threshold
		Maximum Warning Threshold
		Status

Voltage

Category	Sub category	Attribute name
Voltage		Status
		Probe Name
		Reading
		Minimum Warning Threshold
		Maximum Warning Threshold
		Minimum Failure Threshold
		Maximum Failure Threshold

Auto Recovery

Category	Sub category	Attribute name
Auto Recovery		Action on hung Operating System
		System Reset Timer

Hardware Performance

Category	Sub category	Attribute name
Hardware Performance		Probe Name
		Status
		Cause

Power Management

Category	Sub category	Attribute name
Power Management		Status
		Probe Name
		Reading (Amp)
		Warning Threshold
		Failure Threshold
	Amperage	Location
		Reading (Amp)
	Power Headroom	System Instantaneous Head Room
		System Peak Head Room
	Power Tracking Statistics	Statistic(* Energy Consumption)
		Statistic(* System Peak Power)
		Statistic(* System Peak Amperage)
		Measurement Start Time
		Measurement Finish Time
		Reading (Amp)
		Peak Time
	Power Inventory	System Idle Power


Category	Sub category	Attribute name
		System Maximum Potential Power
	Power Budget	Enable Power Capping
		Power Capping

Accessing the Storage items

To access the Storage items:

On the configuration viewer, click **PowerEdge xxx** → **Server** → **Storage**.

Storage items

 **NOTE:** If a device that you have added in SupportAssist by using the operating system IP address or the host name does not have Dell OpenManage Server Administrator (OMSA) installed, Storage items will not be available in periodic collections from that device.

Controller

Category	Sub category	Attribute name
Controller		ID
		Name
		Firmware Version
		Driver Version
		Storport Driver Version
		Number Of Connectors
		Rebuild Rate
		BGI Rate
		Reconstruct Rate
		Check Consistency Rate
		Cache Memory Size (MB)
		Patrol Read Rate
		Patrol Read Iterations
		State
		Slot ID
Abort Check Consistency On Error		

Category	Sub category	Attribute name	
		Allow Revertible Hot Spare And Replace Member	
		Load Balance	
		Auto Replace Member On Predictive Failure	
		Persistent Hot Spare	
		CacheCade Capable	
		Encryption Capable	
		Encryption Key Present	
		Spin Down Unconfigured Drives	
		Spin Down Hot Spares	
		Spin Down Configured Drives	
		Automatic Disk Power Saving (IdleC)	
		Patrol Read Mode	
		Time Interval For Spin Down (Minutes)	
		Alarm State	
		T10 Protection Information Capable	
		Patrol Read State	
		Encryption Mode	
		Status	
		Controller Battery	Slot Number
			Status
		State	
		Next Learn Time	
		Recharge Count	
		Maximum Recharge Count	
		Maximum Learn Delay	
		Name	
		Learn State	
		Learn Mode	

Category	Sub category	Attribute name
		Predicted Capacity Status
	Connector	Name
		State
		Connector Type
		Status
	Connector > Enclosure	ID
		Name
		State
		Connector
		Firmware Version
		Service Tag
		Asset Tag
		Asset Name
		Target ID
		Split Bus Part Number
		Express Service Code
		SAS Address
		Enclosure Alarm
		Configuration
	Status	
	Connector > Enclosure > Array Disk	Status
		Connector
		Serial Number
		Name
		State
		Power Status
		Bus Protocol
Failure Predicted		
Media Type		
Revision		
T10 PI (Protection Info) Capable		

Category	Sub category	Attribute name
		Certified
		Encrypted
		Encryption Capable
		Capacity
		Used RAID Disk Space (Bytes)
		Available RAID Disk Space
		Hot Spare
		Mirror Set ID
		Progress
		Model Number
		Vendor
		Part Number
		Maximum Capable Speed
		SAS Address
		Negotiated Speed
		Product ID
		Manufactured Year
		Manufactured Week
		Manufactured Day
		Sector Size
	Device Name	
	Connector > Enclosure > Enclosure Temperature Sensor	Minimum Failure Threshold
		Minimum Warning Threshold
		Maximum Failure Threshold
		Maximum Warning Threshold
		ID
		Status
		Reading (Amp)
		Name
State		

Category	Sub category	Attribute name
	Connector > Enclosure > Enclosure EMM	Status
		Firmware Version
		Part Number
		Name
		State
	Connector > Enclosure > Enclosure Power Supply	Status
		Firmware Version
		Part Number
		Name
		State
	Connector > Enclosure > Enclosure Fan	Status
		Name
		State
		Speed
		Part Number
	Extender	ID
		Name
		State
		PCIe SSD Extender
		Firmware Version
		Asset Name
Extender > Enclosure	ID	
	Name	
	State	
	PCIe SSD Extender	
	Firmware Version	
	Asset Name	
Controller > Virtual Disk	Name	
	Encrypted	
	Progress	

Category	Sub category	Attribute name
		T10 Protection Information Capable
		Size
		Layout
		State
		Status
		Device Name
		Bus Protocol
		Media Type
		Cache Policy
		Disk Cache Policy
		Read Policy
		Stripe Element Size
		Write Policy
		Hot Spare Policy violated
	Controller > Virtual Disk > Array Disk	Connector
		Status
		Serial Number
		Name
		State
		Power Status
		Bus Protocol
		Failure Predicted
		Media Type
		Revision
		T10 PI (Protection Info) Capable
		Certified
		Encrypted
Encryption Capable		
Capacity		
Used RAID Disk Space (Bytes)		

Category	Sub category	Attribute name	
		Available RAID Disk Space	
		Hot Spare	
		Progress	
		Mirror Set ID	
		Model Number	
		Vendor	
		Part Number	
		Maximum Capable Speed	
		SAS Address	
		Negotiated Speed	
		Product ID	
		Manufactured Year	
		Manufactured Week	
		Manufactured Day	
		Sector Size	
		Device Name	
		Connector > Tape device > Tape Drive Characteristics	Name
			Status
		Firmware	
		Device Descriptor	
		Device Location	
		Parent Location	
		Manufacturer	
		Serial Number	
		Model Number	
		Asset Tag	
		POWER_ON	
		NUMBER_OF_DRIVE_CLEAN	
		DRIVE_LOADS	
	PICO		
	TLSC		

Category	Sub category	Attribute name
		LMTP
		IMLLMMH
		POHFREE
		TTLSC
		OTCO
		MMH
		TSLSC
	PCIe-SSD	ID
		Name
		State
		Number of Extenders
	PCIe-SSD Extenders	Status
		Name
		State
	PCIe-SSD Extenders > Enclosure	Name
		Firmware Version
		Asset Name
		State
		PCIe SSD Extender
		ID
	PCIe-SSD Extenders > Enclosure > Array Disk	Status
		Serial Number
		Name
		State
		Bus Protocol
		Media Type
		Revision
		Capacity
		Model Number
		Remaining Rated Write Endurance

Category	Sub category	Attribute name
		Vendor
		Maximum Capable Speed
		Negotiated Speed
		Product ID
		PCIe Maximum Link Width
		PCIe Negotiated Link Width
		Device Name
		Device Protocol
		Driver Version

SATA/IDE Controller

Category	Sub category	Attribute name
SATA/IDE Controller		Name
		Firmware Version
		Description
		Device Location
		Parent Location
		Manufacturer
		Serial Number
		Model Number
		Device Descriptor
		Asset Tag
		Status
	Channel	Name
		Device Location
		Manufacturer
		Connector Type
		Status
	Optical Device	Name
		Status
		Firmware Version

Category	Sub category	Attribute name
		Device Descriptor
		Description
		Device Location
		Parent Location
		Manufacturer
		Serial Number
		Model Number
		Asset Tag

Fibre Channel Controller

Category	Sub category	Attribute name
Fibre Channel Controller		Name
		Host WWN
		Vendor Name
		Model
		Firmware Version
		Driver version
		Serial Number
		Vendor Code
		Type
	Fibre Channel HBA port	Port Number
		Port WWN
		Port OS Name
		Port Type
		Port Speed
		Port Supported Speed
		Port State
Port FCID		

Accessing the Software items

To access the Software items:

On the configuration viewer, click **PowerEdge xxx** → **Server** → **Software**.

Software items

Operating System

Category	Sub category	Attribute name
Operating System		OS Name
		Version
		System Name
		Install Date
	Component > Software Storage > iSCSI DATA > iSCSI Session Data	Session ID
		Initiator Node Name
		Target Node Name
		Target Name
		ISID
		TSID
		Number of Connection
	Component > Software Storage > iSCSI DATA > iSCSI Session Data > Session Connection Data	Connection ID
		Initiator Portal
		Target Portal
		CID
	Component > Software Storage > iSCSI DATA > iSCSI Session Data > Session Device Data	Device Type
		Device Number
		Storage Device Type
		Partition Number
		Friendly Name
		Device Description
		Reported Mappings
		Location

Category	Sub category	Attribute name
		Initiator Name
		Target Name
		Device Interface Name
		Device Instance
		Legacy Device Name
	Component > Software Storage > iSCSI DATA	Total Portals
		Total Sessions
		Initiator Version
		Address and Socket
		Symbolic Name
		Initiator Name
		Port Number
		Operating System Name
		Version
		Install Date
		System Name
	Component > Software Storage > iSCSI DATA > Portal Data	Initiator Version
		Portal Address
		Portal Port Number
	Resource > IRQ	IRQ Number
		Device
		Interrupts Per CPU
		Type
	Resource > IO Range	Address Range
		Device
		Status
	Component > Display	Files
ServerFlags		
Module		
InputDevice		
Monitor		

Category	Sub category	Attribute name
		Modes
		Screen
		Device
		ServerLayout
		DRI
	Component > Network Adapter > Network Adapter	Adapter Name
		MAC Address
		IPv4 Address
		Broadcast
		Subnet Mask
		Default Gateway
		IPv6 Address
		Scope
		Status Characteristics
		MTU
		Metric
		Memory
		Interrupt
		RX Packets
		RX Errors
		RX Dropped
		RX Overruns
		RX Frame
		TX Packets
		TX Errors
		TX Dropped
		TX Overruns
		TX Carrier
		Collisions
		Tx Queue Length
RX bytes		

Category	Sub category	Attribute name
		TX bytes
		int6 IP Address
		int IP Address
	Component > Network Host	IP Address
		Host Name
		Value
	Component > Network > Network DNS Config	Name Server
		Search
		Value
	Component > Software Storage > Memory Usage	Memory Total
		Memory Free
		Memory Available
		Buffers
		Cached
		Memory Shared
		Swap Total
		Swap Cached
		Swap Free
	Component > Software Storage > Disk Usage	File System
		Size
		Used
		Available
		Use
		Mounted On
	Component > Software Storage > Procscsi	Channel
		Host
		ID
LUN		
Vendor		
Model		
Rev		

Category	Sub category	Attribute name
		Type
		ANSI SCSI Revision
	Component > Startup > Boot Menu List	title
		root
		kernel
		module
		hiddenmenu
		default
		timeout
		splashimage
		rootnoverify
		chainloader
	Component > Startup Boot List	Rights
		Number
		Owner
		User
		FileDate
		Process
	Component > Startup > Boot GRUB List	Inode
		Permissions
		Number of Links
		Owner Name
		Owner Group
		Size
		Process
		Date Of Modification
		Rights
		Number
		Owner
		User
FileDate		

Category	Sub category	Attribute name
		Process
		default=0
		Value
	Component > Startup > Boot List	Inode
		Rights
		Number
		Owner
		User
		Size
		File Date
		Process
	Component > Startup > Device Map List	Name
		Value
	Component > Display > Server Layout	Name
		Value
		Identifier
		Screen
	Component > Display > Files	Name
		Module Path
		Value
		Font Path
	Component > Display > Module	Name
		Value
	Component > Display > Input Device	Name
		Value
		Identifier
	Component > Display > Monitor	Name
		Identifier
		Value
		Vendor Name
Chassis Model		

Category	Sub category	Attribute name
	Component > Display > Device	Name
		Identifier
		Value
		Driver
		BusID
	Component > USB Controller Info	Controller Information
		Serial Number
	Component > USB Controller Info > USB Root Hub > USB	Bus
		Device
		ID
		Device Class
		Device Sub Class
		Device Protocol
		Manufacturer
		Product
		Serial
		Version
	Component > USB Controller Info > USB Root Hub > USB Detailed info	Bus
		Device
		bLength
		bDescriptorType
		bcdUSB
		bDeviceClass
		bDeviceSubClass
		bDeviceProtocol
		bMaxPacketSize0
		idVendor
idProduct		
bcdDevice		
iManufacturer		
iProduct		

Category	Sub category	Attribute name
		iSerial
		bNumConfigurations
		Configuration
		bLength
		bDescriptorType
		wTotalLength
		bNumInterfaces
		bConfigurationValue
		iConfiguration
		bmAttributes
		Self
		Remote
		MaxPower
		Interface
		bLength
		bDescriptorType
		bInterfaceNumber
		bAlternateSetting
		bNumEndpoints
		bInterfaceClass
		bInterfaceSubClass
		bInterfaceProtocol
		iInterface
		Endpoint
		bLength
		bDescriptorType
		bEndpointAddress
		bmAttributes
		Transfer
		Synch
		Usage

Category	Sub category	Attribute name
		wMaxPacketSize
		bInterval
		Hub
		bLength
		bDescriptorType
		nNbrPorts
		wHubCharacteristic
		No
		Per-port
		bPwrOn2PwrGood
		bHubContrCurrent
		DeviceRemovable
		PortPwrCtrlMask
		Hub
		Port
		Port
		Device
		Self
		Remote
		Environment
		Variable Value
	Environment > Environment Variable	Variable
		Variable Value
	Environment > Drivers > Drivers Loaded Module	Internal Name
		Module Size
		Use Count
		Dependant Modules
		Status
	Environment > Drivers > Drivers	Name
		Module Path
	Environment > Process	Command

Category	Sub category	Attribute name	
		PID	
		CPU	
		Memory	
		RSS	
		VSZ	
		Time	
		Start	
		STAT	
		User	
		TTY	
	Environment > Installed Application	Name	
		Publisher	
		Summary	
		Size	
		Install date	
		URL Information	
	Environment > Service	Description	
		Service	
			State

OpenManage

Category	Sub category	Attribute name
OpenManage		Version
		Item
		Server Administrator CLI
		Storage Management package for GUI component
		Server Administrator Core
		Storage Management CLI component
		Hardware Abstraction Programming Interface

Category	Sub category	Attribute name
		Storage Management accessors package
		Server Administrator Common Services
		RealSSD package for storage management
		Storage Management System Utilities Package / Libsysfs
		A library for parsing GNU style command line arguments
		Oracle Java Runtime Environment
		Meta rpm for iDRAC components
		Disney SNMP
		Server Administrator Common Framework
		iDRAC7 Command Interface
		NVMe Library
		iDRAC SNMP components
		Data Engine
		Remote Access Card Data Populator
		StoreLib package for storage management
		Storage Management SNMP component
		OSLogging control
		Instrumentation Services
		Data Engine SNMP
		Monolithic Server Virtual Media CLI Utils
		iDRAC6 Command Interface
		Server Administrator XML Support SDK
		RAC Command Interface

Category	Sub category	Attribute name
		Server Administrator XML Support SDK
		RAC Command Interface
		Integrated Tunnel Provider
		Server Administrator Install Core
		System Utilities Package/ Libsysfs for LSI storage libraries
		Modular Server Virtual Media CLI Utils
		RAC Integration Layer
		OpenManage Inventory Collector
		Storage Management common files for GUI and CLI
		Apache Tomcat Webserver

Accessing the Logs

To access the logs:

On the configuration viewer, click **PowerEdge xxx** → **Server** → **Logs**.

Logs

Logs

Category	Sub category	Attribute name
Logs	Unstructured Logs > messages	Status
		Type
		Source
		Date and Time
		Entry ID
		Message
	Unstructured Logs > dmseg	Entry
		Variable Value

Category	Sub category	Attribute name
	Unstructured Logs	PE_Destinations.txt
		Platform_Events.txt
		SNMP_Events.txt
		Alert Actions.txt
		Alert Log.txt
		Cmd Log.txt
		netstatinfo.txt
		Controller_XX/ ControllerTTYLog_Dell_PERC_X X
		seslog.txt
		dracinfo.txt
		RAC_log.txt
		RAC_tracelog.txt
		Structured Logs
	Date and Time	
	Description	
	Raw SEL data	