

Dell EMC License Manager Version 1.4

User's Guide

Notes, cautions, and warnings

 **NOTE:** A NOTE indicates important information that helps you make better use of your product.

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.

Contents

Chapter 1: About Dell EMC License Manager	5
What is New in This Release.....	5
Chapter 2: Installing License Manager	6
Minimum System Requirements.....	6
Limitations.....	6
Installing License Manager.....	6
Chapter 3: Getting Started With License Manager	8
License Manager User Interface.....	8
Menu Bar.....	9
Task Status Bar.....	10
Help Icon.....	10
License Manager Views.....	10
Understanding Licenses.....	11
License Descriptions.....	11
Filtering Data.....	12
Filter Options.....	12
Chapter 4: Working With Licensable Systems	14
Inventorying Licensable Systems.....	14
Editing an Inventory Range.....	15
Viewing inventoried systems.....	15
Removing System Information.....	15
Saving Reports.....	15
Chapter 5: Managing Licenses	16
Obtaining Licenses by Connecting to Dell Online Account.....	16
Login to Another Dell Online Account.....	17
Disconnecting from Dell Online.....	18
Importing Archived Licenses from the Dell Online Licensing Portal.....	18
Binding Licenses.....	18
Deploying Licenses.....	19
Selecting Licenses For Deployment.....	19
Selecting Systems For License Deployment.....	20
Exporting License Archives.....	20
Saving Reports.....	20
Removing Licenses From The Inventory.....	20
Removing Licenses From A System.....	20
Downloading Bound Licenses.....	21
Chapter 6: Managing Tasks and Logs	22
Cancelling Tasks.....	22
Log Entries.....	22

Clearing Completed Tasks.....	22
Viewing License Manager Logs.....	22
Generating Support Log Archives.....	23
Chapter 7: Changing the Unique iDRAC Password.....	24
Chapter 8: Troubleshooting.....	25
License Importing.....	25
License Inventory/Discovery And License Deployment.....	25
License Status Warnings.....	26
Chapter 9: Systems — Reference.....	27
System Inventory Table.....	27
Systems Detail Pane.....	28
Discovery/Inventory Wizard.....	29
Edit Inventory Range.....	29
Communication Settings.....	30
Chapter 10: Licenses — Reference.....	32
Connect to Dell Online.....	33
Bind Licenses.....	33
Manage Licenses.....	34
Chapter 11: Entitlements — Reference.....	36
Change Server Password.....	36
Chapter 12: Tasks — Reference.....	38
Chapter 13: Logs — Reference.....	39

About Dell EMC License Manager

Dell EMC License Manager is a one-to-many license deployment and reporting tool for integrated Dell Remote Access Controller (iDRAC) and Chassis Management Controller (CMC) licenses.

License Manager can download, bind, deploy, and back up:

- iDRAC licenses on all PowerEdge servers (denoted as yx2x and yx3x) that are equipped with an iDRAC9, iDRAC8, or iDRAC7 Dell Remote Access controller.
 - **NOTE:** For the server name format yxxx; y denotes alphabets, for example, M (modular), R (rack), or T (tower) and x denotes numbers. For example, a PowerEdge R720 is a 12th Generation rack mount 700 series server.
- CMC licenses on PowerEdge VRTX and PowerEdge FX or FX2s chassis.
- OpenManage Essentials perpetual licenses.
- PowerEdge storage sled licenses.

License Manager can also inventory licensable systems to report the licensing status and currently enabled management controller feature level.

Use the iDRAC licenses to enable server management capabilities such as the virtual media and remote console support currently available in the Enterprise iDRAC feature set.

Use CMC licenses to enable chassis management capabilities such as console integration, remote access, mutli-chassis management, server cloning, and so on.

You can download licenses from the Dell Online Licensing Portal at dell.com/support/retail/lkm. You can purchase licenses when you purchase a server or a chassis.

Topics:

- [What is New in This Release](#)

What is New in This Release

Managing licenses for volume binding and distribution by connecting to Dell Online.

Support for 14th generation PowerEdge servers.

Normalizing password of the root user for 14th generation PowerEdge servers.

Installing License Manager

Topics:

- [Minimum System Requirements](#)
- [Limitations](#)
- [Installing License Manager](#)

Minimum System Requirements

Table 1. Minimum System Requirements

Particulars	Requirement
Hard Disk	200 MB (minimum)
RAM	2 GB (minimum)
Operating Systems	Microsoft Windows 10 Microsoft Windows 8.1 Microsoft Windows Server 2016 Microsoft Windows Server 2012 R2 Microsoft Windows Server 2012 Microsoft Windows Server 2008 R2 Both 64-bit and 32-bit versions are supported.
Network	100 Mbps or higher
Screen Resolution	1024 X 768
Microsoft .NET	4.5
Remote Management	Windows Remote Management (WinRM) 2.0 This functionality is included in Windows 7, Windows Server 2008 R2, and later versions. The WinRM prerequisite is available through Microsoft Windows Update.

Limitations

License Manager supports up to 3500 licensable systems and an inventory of up to a class B IP address range (65,536 addresses).

Installing License Manager

1. Download License Manager from dell.com/support.
2. Double-click the **License Manager** Windows installer package.
3. Select a language for the installation, and click **OK**.
4. In the **Welcome** screen, click **Next**.

5. In **License Agreement**, select **I accept the terms in the license agreement** and click **Next**.
6. In **Setup Type**, do any of the following:
 - To accept the default installation path, choose the **Typical** installation, and click **Next**.
 - To enable specific program features and change the installation path, select the **Custom** installation option and click **Next**. In **Custom Setup**, select the License Manager features that you require; check for disk space and assign a new location for installing License Manager.
7. In the **Ready to Install the Program** screen, click **Install**.
The **InstallShield Wizard Completed** page is displayed.
8. If you want to launch License Manager, select **Launch Dell EMC License Manager**, and then click **Finish**.

Getting Started With License Manager

You can access License Manager from the Windows desktop in one of the following ways:

- Windows 8, Windows Server 2012, or later operating systems — Move the mouse pointer to the bottom-left corner, and then click the **Start** icon. On the **Start** screen, click the **License Manager** tile.
- Windows 7, Windows Server 2008, or earlier operating systems — Click **Start** → **All Programs** → **Dell OpenManage Applications** → **License Manager** → **License Manager**.
- Double-click the License Manager icon.

NOTE: Local administrator privileges are required to run License Manager.

The **Getting Started with Dell EMC License Manager** screen is displayed with information on getting started with license deployment.

Topics:

- [License Manager User Interface](#)
- [License Manager Views](#)
- [Understanding Licenses](#)
- [Filtering Data](#)

License Manager User Interface

The License Manager contains a menu bar, task status bar, navigation pane, and an active view pane.




Figure 1. License Manager Interface


1. Menu bar
2. Task status bar
3. Navigation pane
4. Active view pane

Menu Bar

The menu bar consists of the Actions, View, and Help menus.

Actions Menu

The Actions menu consists of:

- **Discover and Inventory Systems** — Launches the Discovery/Inventory Wizard. See [Inventorying Licensable Systems](#).
- **Change Server Password** — Select this option to normalize the unique password of the servers. See [Changing the Unique iDRAC Password](#) on page 24
- **Launch Dell Online License Portal** — Select this option to access the Dell Online Licensing Portal at dell.com/support/retail/lkm. Before you access the portal, make sure that your system has Internet connectivity. From the online portal you can download the licenses.
- **Import Licenses** — Launches the **Import Wizard**. See [Importing Archived Licenses from the Dell Online Licensing Portal](#) on page 18.
- **Automatically Deploy Licenses** — Selects all undeployed licenses bound to systems in inventory for deployment and launches the License Management Wizard. See [Deploying Licenses](#).
- **Connect to Dell Online** — Select this option to connect to the Dell Online Portal and gather information of all the available licenses for the purchased devices. See [Obtaining Licenses by Connecting to Dell Online Account](#) on page 16
- **Disconnect from Dell Online** — Select this option to disconnect from the Dell Online Portal. See [Disconnecting from Dell Online](#) on page 18
- **Login to another Dell account** — Select this option to log in to a different Dell Online account. See [Login to Another Dell Online Account](#) on page 17
- **Bind Licenses** — Select this option to bind all the unbound licenses to the related devices, which can then be deployed. See [Binding Licenses](#) on page 18
- **Export License Archive** — Saves an archive containing all licenses in inventory in the compressed file format. See [Managing Licenses](#).
- **Save Report** — Saves a CSV, HTML, or XML informational report from system, license, or log view. See the section on the respective view for more information.
- **Clear Log** — Removes all entries from the activity log.
 **NOTE:** This option does not remove information on tasks from task view. See [Managing Tasks and Logs](#).
- **Exit** — Closes the License Manager application. This option ends all current tasks.

View Menu

The View menu consists of:

- **Systems** — Navigates to the Systems view.
- **Licenses** — Navigates to the Licenses view.
- **Entitlements** — Navigates to the Entitlements view.
- **Tasks** — Navigates to the Tasks view.
- **Logs** — Navigates to the Logs view.
- **Getting Started** — Displays the Getting Started with Dell EMC License Manager screen.

Help Menu

The Help menu consists of:


- **License Manager Help** — To access the License Manager help. You can also access the License Manager help by clicking the help icon within each view.

- **Online Support** — To access the Dell Technical Support at dell.com/support.
- **Generate Support Log Archive** — To generate an archive of activity logs which Dell Technical Support can use to troubleshoot problems.
- **About** — To view the License Manager version and copyright information.

Task Status Bar

The Task Status bar shows the status when License Manager is connected to a Dell Online account, number of running and completed tasks. Clicking the Task Status bar activates the Task view.

Help Icon

Click the help icon  to access context-sensitive online help.

License Manager Views

License Manager supports the following primary views:

- Systems view
- Licenses view
- Entitlements view
- Tasks view
- Logs view

Systems View

The Systems view is accessible through the **Systems** link in the navigation pane. From the Systems View, you can:

- Discover and inventory licensable systems
- Deploy licenses
- View system licensing status
- Remove licenses from systems

For more information on systems view, see [Working With Licensable Systems](#).

Licenses View

The Licenses view is accessible through the **Licenses** link in the navigation pane. From the Licenses View, you can:

- Import downloaded licenses into License Manager
- View information on available licenses
- Deploy licenses
- Export a license archive

For more information on licenses view, see [Managing Licenses](#).

Entitlements View

The Entitlements view is accessible through the **Entitlements** link in the navigation pane. From the Entitlements View, you can:

- View information on available entitlements
- Download bound licenses
- Save entitlement reports

Tasks View

The Tasks view is accessible through the **Tasks** link in the navigation pane. From the Tasks View, you can:

- View archived task results
- Save reports
- Generate support log archives

For more information on tasks view, see [Managing Tasks and Logs](#).

Logs View

The Logs view is accessible through the **Logs** link in the navigation pane. From the Logs View, you can:

- View archived task results
- Save reports
- Generate support log archives

For more information on logs view, see [Managing Tasks and Logs](#).

Working With Views

The systems, licenses, tasks, and logs data view grids allow sorting, grouping, and filtering. You may also choose which columns to display in the data grid.

- **Sorting** — To sort on a particular column, click the column header. Clicking the header again sorts the column in reverse order.
- **Grouping** — To group items together, select the column on which to group from the Group By menu in the grid header.
- **Filtering** — To filter data rows, select the column on which to filter and click the filter icon. Select the filter operation and then enter the filter string. To clear the filter, select the filter icon and click **Clear Filter**.
- **Selecting Columns** — To select which columns are displayed, click the **Show/Hide Columns** icon. Selected columns are displayed.

Understanding Licenses

Dell Licenses contain the following properties:

- **Entitlement Identifiers** — Each license has an Entitlement ID, which uniquely identifies that license.
- **License Descriptions** — The description specifies the level of features enabled in the license. For more information, see [License Descriptions](#).

License Descriptions

The license description specifies the level of features enabled in the license. For more information on the iDRAC functionality supported by each feature level, access the online licensing portal at dell.com/support/retail/ikm. The following licenses are available:

- Perpetual licenses
- Evaluation licenses
- Bound licenses
- Upgrade licenses

Perpetual Licenses

Perpetual licenses are standard licenses that enable iDRAC features and do not expire.

Evaluation Licenses

Evaluation licenses allow a 30-day trial of specific iDRAC features, with an available 30-day extension.

 **NOTE:** You cannot deploy or archive evaluation licenses in License Manager.

Bound Licenses

Dell Perpetual licenses are bound to a particular system Service Tag and you can deploy the licenses only on those systems.

Upgrade Licenses


Some Dell Licenses are upgradeable. An upgrade license includes an Upgrade ID referencing the Entitlement ID of the upgraded license.

License Features

Each license includes a specific set of iDRAC features, that are enabled by the license. The license description summarizes the level of features included in the license.

Filtering Data

The License Manager allows you to filter data in the **Systems, Licenses, Entitlements, Tasks, and Logs** views. To filter data:

1. Place the mouse pointer over the column heading and click the funnel icon .
2. After selecting a filter option from the drop-down list, enter the alphanumeric characters in the field and click the **aA** button to make the filter search case-independent.
3. After you set the filter logic, click **Filter** to run the filter logic.

 **NOTE:** Click **Clear Filter** to clear a search.

Filter Options

Table 2. Filter Options

Filter Option	Description
Is equal to	To create the <i>same as</i> logic.
Is not equal to	To create the <i>different from</i> logic.
Starts with	To filter search based on the initial alphanumeric character in a text chunk. Provide the starting alphanumeric character in the field.
Ends with	To filter search based on the final alphanumeric character in a text chunk. Provide the ending alphanumeric character in the field.
Contains	To filter search based on alphanumeric characters present in a text chunk. Provide the alphanumeric character in the field.
Does not contain	To include the <i>not present</i> logic in search based on alphanumeric characters present in a text chunk.
Is contained in	To include the <i>is present</i> logic in an alphanumeric character string.
Is not contained in	To include the <i>not present</i> logic in an alphanumeric character string.
Is empty	To include the <i>is blank</i> logic.
Is not empty	To include the <i>is filled</i> logic.

Table 2. Filter Options (continued)

Filter Option	Description
Is less than	To create the <i>lesser than</i> logic.
Is less than or equal to	To create the <i>lesser than or same as</i> logic.
Is greater than	To create the <i>greater than</i> logic.
Is greater than or equal to	To create the <i>greater than or same as</i> logic.
Is null	To include the <i>is void</i> logic.
Is not null	To include the <i>is not void</i> logic.

Working With Licensable Systems

Topics:

- [Inventorying Licensable Systems](#)
- [Editing an Inventory Range](#)
- [Viewing inventoried systems](#)
- [Removing System Information](#)
- [Saving Reports](#)

Inventorying Licensable Systems

Performing discovery and inventory of licensable systems enables you to view the licensing status for those systems. Perform a system's inventory before deploying licenses for the system. The inventory process automatically retrieves the installed non-evaluation licenses for archival purposes.

To inventory systems:

1. In License Manager, click **Systems**.
2. In **Systems**, click **Run Discovery and Inventory**.
3. In the **Select IP Address** page of **Discovery / Inventory Wizard**, click **Add Range or IP**.
4. In **Edit Inventory Range** window, provide a name for the IP range or address, and perform one of the following:
 - To use an IPv4 range for inventorying systems, provide the start address, end address, and subnet mask.
 - To use an individual IP address for inventorying systems, select **Individual Address (IPv4, IPv6, or hostname)**, and provide the IP address or host name.
 - To use a text file for inventorying systems, select **Text file with IP addresses**, click **Load**, navigate and select the text file.
 - NOTE:** You must select a text file that includes an IP address or host name on each line.
 - NOTE:** To inventory the PowerEdge storage sleds, provide the IP address of only the chassis. License Manager automatically inventories the PowerEdge storage sleds while inventorying the chassis.
 - NOTE:** For PowerEdge storage sleds, License Manager displays the license level of the host CMC as the current license.
5. Click **OK**.
The IP address or range that you provided is added to the **IP Addresses and Ranges** table.

If you selected a text file, the IP addresses and host names in the text file are verified, and the invalid IP addresses or host names are displayed in the **Validation Report**.

NOTE:

- After the IP addresses are added from a text file, they are displayed as individual IP addresses.
- If there are duplicate IP addresses in the text file or if the IP addresses already exist in the **IP Addresses and Range** table, they are ignored.
- The text file cannot be edited using License Manager.

6. In the **Select IP Address** page of **Discovery / Inventory Wizard**, click **Next**.
7. In the **IP Scan Settings** page of **Discovery / Inventory Wizard**, provide the user credentials and configure the Internet Control Message Protocol (ICMP) and WS-Man options, and then click **Next**.

NOTE: For information on certificate settings, see [Communication Settings](#).

8. In the **Confirm Settings** page of the **Discovery / Inventory Wizard**:
 - Review the discovery settings you provided. Click **Back** to edit settings.

- If you do not want to view the inventory task progress in the task pane, deselect the **Show task pane after launch** option.

9. Click **Run Discovery / Inventory**.


The **Tasks** view is displayed. You can go to the **Systems** view to see the inventoried systems.

 **NOTE:** If you deselected the **Show task pane after launch** option in step 8, the **Systems** view is displayed.

Editing an Inventory Range

Specify the management controller IP addresses in the appropriate discovery/inventory tables. License Manager cannot inventory license information from installed server operating systems or hypervisors.

To edit a range:

 **NOTE:** To remove a range from License Manager, select the entry in the table and click **Remove Selected**.

1. Click **Run Discovery and Inventory**.
2. Select the entry in the table and click **Edit**.
The **Edit Inventory Range** window is displayed.
3. Edit the **IP Range or Address Name**, **IPv4 Range**, or **Individual Address (IPv4, IPv6, or hostname)** based on your preference.
4. Click **OK** to save the changes.

Viewing inventoried systems

To view inventoried systems, select **Systems**. Inventoried systems are listed in the **Systems** view. The System Inventory table provides a summary of the inventoried systems and the System Details pane provides more information about a selected system.

 **NOTE:** For PowerEdge storage sleds, License Manager displays the license level of the host CMC as the current license.

Removing System Information

1. In **Systems**, select the systems you want to remove and click **Delete**.
2. When prompted, click **Yes** to confirm.

Saving Reports

You can save system information into reports in the CSV, XML, or HTML formats.

To save reports:

1. From **Systems**, click **Save Report**.
2. Specify the folder location and file name, and in **Save as type**, select the report format, and then click **Save**.
3. In **Report Saved Successfully**, click **OK**.

Managing Licenses

Using License Manager you can deploy licenses to licensable systems. License Manager also supports the export of license archives for backup. The status of available licenses can be viewed from the Licenses view, and the entitlement details of the licenses is available in the Entitlements view. The entitlement details of the licenses are obtained by connecting to the Dell Online account.

NOTE: The factory-installed licenses are not retrieved during the discovery and inventory of iDRAC 9 systems. Therefore, the iDRAC 9 licenses are not listed in the **Licenses** view.

Before you deploy licenses:

1. Inventory the licensable systems. See [Inventorying Licensable Systems](#).
2. Obtain and import licenses by performing one of the following:
 - Connecting to Dell Online to automatically import the unbound licenses from the Dell Online account.
 - Downloading the license archives from Dell Online Licensing Portal and importing the licenses into License Manager.
3. Bind the licenses.
4. Deploy the licenses.

NOTE: To work with licenses, from the License Manager, click **Licenses** in the navigation pane.

Topics:

- [Obtaining Licenses by Connecting to Dell Online Account](#)
- [Login to Another Dell Online Account](#)
- [Disconnecting from Dell Online](#)
- [Importing Archived Licenses from the Dell Online Licensing Portal](#)
- [Binding Licenses](#)
- [Deploying Licenses](#)
- [Selecting Licenses For Deployment](#)
- [Selecting Systems For License Deployment](#)
- [Exporting License Archives](#)
- [Saving Reports](#)
- [Removing Licenses From The Inventory](#)
- [Removing Licenses From A System](#)
- [Downloading Bound Licenses](#)

Obtaining Licenses by Connecting to Dell Online Account

The License Manager can be connected to Dell Online to gather information of all the available bound and unbound licenses. To connect to Dell Online, the License Manager requires a One Time Passcode (OTP). You can disconnect from Dell Online anytime.

NOTE: Ensure that you have a Dell account before connecting to Dell Online.

To connect to Dell Online from the License Manager:

1. In the License Manager, click **Actions** > **Connect to Dell Online**.

NOTE: To connect to Dell Online from the License Manager, you will need a One Time Passcode (OTP).
2. In the **Connect to Dell Online** window, click the **Dell Online** link to request the OTP.
3. In the **Dell Online** portal, enter the credentials, and click **Sign In**.
4. The OTP is generated and displayed. Copy the generated OTP from the Dell Online Portal.

NOTE: The OTP is valid for 30 minutes. If the OTP is not used within 30 minutes, then it has to be requested again by connecting to Dell Online.

5. In the **Connect to Dell Online** window of License Manager, enter the OTP that was copied from the Dell Online Portal.
 - a. Select **Save Connection credentials** option to save the connection credentials to reconnect to Dell Online. If the Save connection credentials option is not selected or login account is changed, then the saved credentials become invalid. You must request a new OTP by connecting to Dell Online.
 - b. Select **Automatically connect on start up** option to automatically reconnect the License Manager to the Dell Online account when the License Manager starts.
 - c. Select the **Enable Proxy Settings** option to enter the proxy settings, if your network requires proxy settings to connect.

NOTE: The proxy settings are not saved with the user credentials and should be entered when prompted.

6. Click **Next**.
7. In the **Connection Results** window, you can see if the connection to Dell Online is successful. If the connection is successful, click **Next**.
8. If the License Manager is not able to connect to Dell Online because of an invalid OTP or incorrect proxy settings, then click **Close**.
To reconnect to Dell Online obtain a new OTP or ensure the correct proxy settings are entered.
9. After the download of the license information is complete, a summary of the purchased licenses that are unbound is displayed. Click **Close**.
The **Task Status** window is displayed.

The summary of the downloaded entitlements can be viewed in the **Entitlements** navigation pane. To bind the licenses to the discovered and inventoried devices, see [Binding Licenses](#) on page 18.

NOTE: To disconnect from Dell Online, see [Disconnecting from Dell Online](#) on page 18

Login to Another Dell Online Account

The License Manager supports the feature to connect to Dell Online using a different account. The systems may be discovered using more than one account and not a single account. By logging to different account, the account-specific licenses can be downloaded and bound to the discovered systems. The entitlements of the current account will not be displayed when you login to a different account.

To login to another Dell Online account:

1. In License Manager, click **Actions > Login to another Dell account**.

NOTE: Logging in using another Dell Online account will disconnect you from the current Dell Online account.

2. In **Disconnect from Dell Online** window, click **Yes**.
3. In the **Connect to Dell Online** window, click the **Dell Online** link to request the OTP.
4. In the **Dell Online** portal, enter the credentials, and click **Sign In**.
5. The OTP is generated and displayed. Copy the generated OTP from the Dell Online Portal.

NOTE: The OTP is valid for 30 minutes. If the OTP is not used within 30 minutes, then it has to be requested again by connecting to Dell EMC Online.


6. In the **Connect to Dell Online** window of License Manager, enter the OTP that was copied from the Dell Online Portal.
 - a. Select **Save Connection credentials** option to save the connection credentials to reconnect to Dell Online. If the Save connection credentials option is not selected or login account is changed, then the saved credentials become invalid. You must request a new OTP by connecting to Dell Online.
 - b. Select **Automatically connect on start up** option to automatically reconnect the License Manager to the Dell Online account when the License Manager starts.
 - c. Select the **Enable Proxy Settings** option to enter the proxy settings, if your network requires proxy settings to connect.

NOTE: The proxy settings are not saved with the user credentials and should be entered when prompted.

7. Click **Next**.
8. In the **Connection Results** window, you can see if the connection to Dell Online is successful. If the connection is successful, click **Next**.

9. If the License Manager is not able to connect to Dell Online because of an invalid OTP or incorrect proxy settings, then click **Close**.
To reconnect to Dell Online obtain a new OTP or ensure the correct proxy settings are entered.
10. After the download of the license information is complete, a summary of the purchased licenses that are unbound is displayed. Click **Close**.
The **Task Status** window is displayed.




The summary of the downloaded entitlements can be viewed in the **Entitlements** navigation pane. To bind the licenses to the discovered and inventoried devices, see [Binding Licenses](#) on page 18

 **NOTE:** To disconnect from Dell Online, see [Disconnecting from Dell Online](#) on page 18

Disconnecting from Dell Online


After disconnecting from Dell Online, the archived license files have to be imported from the Dell Online Licensing Portal. See [Importing Archived Licenses from the Dell Online Licensing Portal](#) on page 18.

To disconnect from Dell Online:

1. In the License Manager, click **Actions**, and then click **Disconnect from Dell Online**
 **NOTE:** Disconnecting from Dell Online and the logging in using another Dell Online account options are disabled if any license binding tasks are active in the tool.
2. In the **Disconnect from Dell Online** window, click **Yes**.
 **NOTE:** A new OTP must be requested to reconnect to Dell EMC Online.
 **NOTE:** Logging in using another Dell Online account will disconnect you from the current Dell Online account, and the Entitlements of the current account will not be displayed in the **Entitlements** navigation pane.

Importing Archived Licenses from the Dell Online Licensing Portal

You can download licenses from the Dell Online Licensing Portal at dell.com/support/retail/lkm. You can purchase licenses when you purchase a server or chassis. The licenses are installed from the factory. The downloaded license package contains a license archive in a compressed file format (.zip format). The license archive contains license files in .xml format. You can import archived licenses. However, you cannot import expired or evaluation licenses.

1. In License Manager, click **Actions > Launch Dell Online Licensing Portal**.
2. From the Dell licensing portal, download the required licenses to a file system.
3. From **Licenses**, select **Import Licenses**.
4. In **Select Licenses**, browse to the location where the license files are downloaded, select the license package, and then click **Open**.
 **NOTE:** If a system has a license with the same Entitlement ID, then the duplicate license is flagged for potential licensing problems.
5. In **Import Licenses**:
 - a. If you want to filter the list of validated licenses based on the matching inventoried systems, select **Import only those licenses which match inventoried systems**.
 - b. Select valid licenses.
 - c. Click **Import**.

Binding Licenses

Using the License Manager you can bind all the unbound licenses to the inventoried systems. Before you bind the licenses:

- Discover and inventory the licensable systems.
 - Obtain and import licenses by performing one of the following:
 - Connecting to Dell Online to automatically import the unbound licenses from the Dell Online account.
 - Downloading the license archives from Dell Online Licensing Portal and importing the licenses into License Manager.
1. In the License Manager, click **Actions > Bind Licenses**.
Bind Licenses window is displayed.
 2. Select the **License Type**. Click **Next**.
The License Manager binds the unbound licenses of the selected type to the respective systems. A single system can be selected to bind the license.
 3. Select the **System Name** to be bound for the license type. The **Service Tag** and **System Model** details for the system is displayed.
 4. Select **Deploy licenses after binding** option, to deploy the licenses after they are bound to a system, and click **Next**.
i **NOTE:** If **Deploy licenses after binding** option is not selected, the licenses will be bound to the system but not deployed. These licenses can be deployed later as required.
 5. If **Deploy licenses after binding** option is selected, then the Management Controller credentials window is displayed. Enter the Management Controller credentials, confirm the WS-Man protocol communication settings. Click **Next**.
 6. Summary of the binding assignments for the selected license type is displayed. Click **Save Report** to save the binding report as a .csv, .html or .xml file, and then click **Finish** to complete the binding and deployment of the selected license types.

Deploying Licenses

License Manager can automatically deploy all available licenses to discovered systems. Alternatively, you can select specific licenses or systems for deployment. Before you deploy licenses:

- Inventory systems on which you want to deploy licenses.
- Confirm that the inventoried systems are licensable.
- Confirm that the licenses are downloaded from Dell Online Licensing Portal.
- Confirm that the required licenses are imported into License Manager.

i **NOTE:** If numerous systems have licenses with the same Entitlement ID, then the duplicate licenses are flagged for potential licensing problems.

To automatically deploy licenses:


1. Select **Licenses > Deploy Licenses > Automatically Deploy Licenses**.
2. In operation selection page, click **Next**.
3. In communication settings, provide the management controller credentials, verify communication settings, and then click **Next**.
i **NOTE:** If no matching system is found for a license, the following message is displayed: **No matching licenses/systems are available**.
- i** **NOTE:** You can monitor the deployment in task view. As systems are updated, corresponding information in systems view and license view are updated.

Selecting Licenses For Deployment

1. Click **Licenses > Deploy Licenses > Deploy Selected Licenses**.
2. In the operation selection page, verify licenses you want to deploy and click **Next**.
3. In communication settings, provide the management controller credentials, verify communication settings, and then click **Next**.
i **NOTE:** You can monitor the deployment in task view. As systems are updated, corresponding information in system view and license view are updated.


Selecting Systems For License Deployment

1. In **Systems**, select the systems on which you want to deploy licenses.
2. Click **Deploy Associated Licenses**.
3. Select the licenses to deploy on the systems and click **Next**.
4. In communication settings, provide the management controller credentials, verify communication settings, and then click **Next**.

 **NOTE:** You can monitor the deployment in task view. As systems are updated, corresponding information in system view and license view are updated.

Exporting License Archives

You can export an archive of all licenses available in the system. You can use this archive as a backup when a system is repaired and the Licensing Portal is not accessible (due to a security restricted network.) You can also use the archived licenses for transfer among the License Manager installations. License Manager retrieves factory-installed licenses during discover and inventory of systems. When you archive licenses, a package containing a compressed file of .xml license files, similar to the license package downloaded from the Dell Online Licensing Portal is created.

 **NOTE:** The factory-installed licenses are not retrieved during the discovery and inventory of iDRAC 9 systems.

To export licenses:

1. From **Licenses**, select the licenses and click **Export Archive**.
2. Specify the folder location to save the archived file. Click **Save**.
The licenses are archived in the compressed file format (.zip format.)

Saving Reports

You can save system information into reports in the CSV, XML, or HTML formats.

To save reports:

1. From **Systems**, click **Save Report**.
2. Specify the folder location and file name, and in **Save as type**, select the report format, and then click **Save**.
3. In **Report Saved Successfully**, click **OK**.

Removing Licenses From The Inventory

To remove licenses from the License Manager inventory:

1. From **Licenses**, select the license you want to delete and click **Delete**.
2. In **Confirm License Removal**, click **Yes**.

Removing Licenses From A System

The **Remove License** option allows you to either remove a specific license or all licenses from a system. To remove licenses:

1. Click **Systems**.
The **System Details** pane displays the licenses installed on the system.
2. Under **Installed Licenses**, select the licenses you want to remove.
3. Click **Remove License**.
The **Remove License** window is displayed.
4. Provide the management controller credentials, confirm the communication settings, and then click **Finish**.

Downloading Bound Licenses

To download the bound licenses:

1. Click **Entitlements**.
The **Entitlements Inventory** window displays the entitlement details of the licenses imported by connecting to the Dell Online account.

2. Select the bound licenses you want to download, and click **Download Bound Licenses**.

 **NOTE:** The **Is Bound** column in the **Entitlement Inventory** table specifies whether the entitlements are bound to the licensable systems.

3. In the **Entitlements** window, click **OK** to proceed with the downloading of the bound licenses.
The **Task Status** window is displayed.

The downloaded licenses are displayed under the **Licenses** view. To deploy the downloaded licenses, see [Deploying Licenses](#) on page 19.

Managing Tasks and Logs

From the Tasks view, you can monitor the progress of long-running tasks. The Task Status table includes a summary of executing and recently completed tasks. The **Results** tab includes a summary of operation results and the Execution Logs tab includes the detailed log of the currently selected task or operation.

Topics:

- [Cancelling Tasks](#)
- [Log Entries](#)
- [Clearing Completed Tasks](#)
- [Viewing License Manager Logs](#)
- [Generating Support Log Archives](#)

Cancelling Tasks

Cancelled tasks do not terminate until the operations that are already in-progress are concluded. As such, it may take several minutes for a cancelled task to terminate. In some circumstances, tasks may complete before cancellation can take effect.

To cancel tasks:

1. From **Tasks**, select the task that you want to cancel and click **Cancel Selected Task**.
2. In **Cancel Task**, click **Yes**.

Log Entries

If a task result is selected, the **Execution Log** tab includes detailed information about the selected task log. If a task result is selected, the log is filtered to entries related to that specific result. Log entries consist of the date and time of the entry, a log code, and a detailed log message.

Clearing Completed Tasks

If the License Manager application is closed while tasks are running, then those tasks are terminated. You cannot clear tasks that are in progress.

To clear completed tasks:

1. From **Tasks**, click **Clear Completed Tasks**.
2. In **Clear Completed Tasks**, click **Yes**.

Viewing License Manager Logs

The saved result is available in the Log view. The Result Logs table includes a summary of License Manager activity including discovery and inventory, license import, and license deployment or removal operations. The Log Entries pane shows detailed results of the currently selected activity. License Manager logs summary based information. The logged information includes status, date and time, unique identifier, and a list of logged events.

To view logs, click **Logs**.

Generating Support Log Archives

When directed by technical support, click **Generate Support Log Archive**. Select the folder where you want to save the archive, and then click **Save**. This option generates a zip archive containing the text of each result log. You can provide the log to technical support as directed.

Changing the Unique iDRAC Password

License Manager supports the feature to securely change the unique user iDRAC password to the user specified password.

NOTE: This feature is supported only for the servers with iDRAC9.

NOTE: The user has to enter the service tag, and unique password information in the .csv file.

NOTE: The .csv file that is uploaded to the License Manager must be unencrypted.

To change the unique root account password:

1. In the License Manager, click **Actions > Change Server Password**.
The **Change Server Password** window is displayed.
2. To **Add Devices**, perform one of the following:
 - Enter the **Service Tag** and **Unique Password**, and click **Add**. The **Service Tag** and **Unique Password** are displayed under **System Details**.
 - Click **Generate CSV Template** under **System Details** and click **Save** to save the .csv file in the desired location.
 - In the **Report Saved Successfully** window, click **OK**. Enter the service tag and unique password information in the exported .csv file.
 - Click **Import** to import the .csv file. The **Service Tag** and **Unique Password** contained in the .csv file are displayed under **System Details**.

NOTE: The service tag and unique password information contained in the .csv file is not stored in the License Manager.

NOTE: The imported unique passwords are hidden to the user.

NOTE: The user must delete the .csv file after uploading it to the License Manager.
3. To delete a device, select the **Service Tag** and click **Delete**.
4. In the **Password Change Warning** window, click **Yes**.
The selected device is deleted from the imported list and the unique password of that device remains unchanged.
5. In the **Provide IP Address/Range** step, perform one of the following:
 - To use an IPv4 range, provide the start address, end address, and subnet mask.
 - To use an individual IP address, select **Individual Address (IPv4)**, and provide the IP address.
 - To use a text file, select **Text file with IP addresses**, click **Load**, browse, and select the text file.

NOTE: You must select a text file that includes the IP address or host name.
6. Click **Next**.
7. In the **Enter New Passwords** step, enter the new password and confirm the new password for the root user.
NOTE: The new password is not stored in the License Manager.
8. If the new passwords do not match, then a password mismatch warning is displayed in the **Passwords Mismatch** pop-up window. Click **OK**.
Retry by entering the new password and confirming the new password.
9. Click **Next**.
The **Summary** step displays the **Service Tag List** and the **IP range/address**.
10. Click **Run** to change the unique iDRAC password of the selected devices in the IP range/address to the new password.

The password change progress is displayed in the **Tasks** view. The **Results** table provides the **Status** of the **Operation**, and the **Result**. The detailed information is provided in the **Execution Log** table. If the password change feature is failing for the devices, then the entries in **Results** and **Execution Logs** can be referred to identify the issues.

Once the unique password is changed, you can log on to the devices using the new password.

Troubleshooting

Topics:

- [License Importing](#)
- [License Inventory/Discovery And License Deployment](#)
- [License Status Warnings](#)

License Importing

Cannot Import Trial Licenses

Message: Trial licenses are not supported by the license manager.

Resolution: Apply a trial license through the iDRAC or CMC GUI or RACADM CLI. For more information, see the iDRAC or CMC documentation.

License Or Archive Is Corrupt Or Unreadable

Messages:

- Unable to read archive file.
- The archive does not contain any license files.
- Unable to parse license.
- The digital signature is invalid.

Resolution: Download license archive again from the Dell Online Licensing Portal at dell.com/support/retail/lkm.

License Inventory/Discovery And License Deployment

When resolving discovery/inventory errors, verify that the remote address corresponds to an iDRAC7 or greater, by accessing the iDRAC or CMC GUI. To access the iDRAC or CMC GUI, connect to the system IP/hostname using a web browser. If the system does not contain iDRAC7, then ignore the error message.

Invalid Credentials

Message: Unable to establish communications - Access is denied.

Resolution: Enter correct credentials. If iDRACs do not share common credentials, you must run multiple discovery/inventory tasks using different credentials.

Certificate Error

Messages:

- Unable to establish communications - The SSL certificate contains a common name (CN) that does not match the hostname.
- Unable to establish communications - The SSL certificate is signed by an unknown certificate authority.

- Unable to establish communications - The SSL certificate could not be checked for revocation. The server used to check for revocation might be unreachable.
- Unable to establish communications - The SSL certificate is expired.

Resolution: If the certificate name does not match the hostname, install a certificate matching the address on which the management controller is inventoried. Alternatively, disable certificate name validation in your discovery/inventory settings. For more information, see [Communication Settings](#).

If the certificate authority is not recognized, add the certificate authority to the list of Windows Trusted Root Certification Authorities on the management console. Alternatively, disable certificate authority validation in the discovery/inventory settings. For more information, see [Communication Settings](#).

If you cannot check the certificate for revocation, make sure that the certificate revocation list server is available to the management console. Alternatively, disable certificate revocation list checking in the discovery/inventory settings. For more information, see [Communication Settings](#).

If the certificate has expired, generate and install a new certificate. Dell License Manager cannot connect to iDRACs using an expired certificate.

Unable To Connect

Messages:

- Unable to ping system - Timed Out
- Unable to establish communications - Connection to host timed out

Resolution: Verify that the management controller is connected to the network and assigned the specified address. Verify that the firewall settings allow you to access the system from the management console.

From the iDRAC or CMC GUI, verify that the address corresponds to a system that contains iDRAC7 or a later version. To access the GUI, connect to the system IP/hostname from a web browser. If the system does not contain iDRAC7, then ignore the error message.

License Status Warnings

Individual Bound License Deployed To Multiple Systems

Message: One or more licenses with the same Entitlement ID are bound to other service tags and are currently deployed.

Resolution: Install each individual bound license, distinguished by a unique Entitlement ID, on a single system specified by its service tag. By using the Dell Online Licensing Portal at dell.com/support/retail/lkm, determine that a license is properly associated with the system. Remove license instances deployed to systems other than those specified in the portal.

You may determine to which systems an Entitlement is deployed by sorting or filtering the Entitlement ID column within the System Inventory table. Improperly deployed licenses can be removed using the management controller GUI. If multiple perpetual licenses are installed on the same system their Entitlement IDs are not displayed in the table. You must inspect such systems individually and review the installed licenses listed in the System Details pane.

Original License Missing During Upgrade

Message: The license is designated as an upgrade, however the original license is not currently installed.

Resolution: Make sure that the original license is not reassigned to another system. If the original license is not present due to service performed on the system, then, ignore this message.

Systems — Reference

From Systems, you can discovery and inventory systems, deploy licenses, and save reports.

Table 3. Systems — Reference

Field	Description
Run Discovery and Inventory	Select to discover and inventory the supported management controllers.
Deploy Associated Licenses	Select to deploy licenses.
Save Report	Select to save license reports.
Delete	Select to remove systems from the License Manager inventory.

Topics:

- [System Inventory Table](#)
- [Systems Detail Pane](#)
- [Discovery/Inventory Wizard](#)
- [Edit Inventory Range](#)
- [Communication Settings](#)


System Inventory Table

The system inventory table contains a summary of licensable systems. You can sort or resize each column. Select a system to view additional information or perform tasks on that system. You can also select multiple systems deployment tasks or removal.

Table 4. System Inventory Table

Field	Description
Checkbox	Click check box to select the system.
System Name	The host name of the installed operating system, if available.
Management Controller	The host name of the management controller. Clicking the link opens the management controller GUI using Microsoft Internet Explorer. The discovery address is shown in parenthesis.
System Model	The system model name.
Upgrade Available	If a license upgrade is available for deployment, a message is displayed.
Service Tag	The factory-assigned system Service Tag that uniquely identifies each system. Each license is bound to a particular service tag indicating the system on which it is deployed.
Evaluation Installed	If applicable, the status of installed evaluation licenses are shown.
Current License	The level of functionality currently supported by the management controller. Supported levels include: <ul style="list-style-type: none"> • Enterprise • Express • Express for Blades • Basic Management

Table 4. System Inventory Table (continued)

Field	Description
	For more information on the management controller functionality supported by each feature level, access the online licensing portal at dell.com/support/retail/lkm .  NOTE: Not all hardware supports all management features. For more information, see the hardware documentation.
Purchased License	The highest license class of any perpetual license bound to the system is shown. Both installed licenses and licenses in inventory awaiting deployment are included when calculating the purchased license class.
Entitlement ID	The unique license identifier.
Additional Information	If a potential EULA violation is detected, it is indicated in this column.
Last Inventory	The date and time the system was last inventoried. The systems will automatically re-inventory when a license operation is conducted on the system.
Modular System	Name of the modular system (chassis) in which the server or sled is installed.
Node ID	The unique identifier of the server or sled installed in a modular system (chassis). Typically, the Service Tag of a server or the server node identifier of a sled.
Slot	The slot occupied by the server or sled in the modular system (chassis).

Systems Detail Pane

The system details pane shows information on a licensable system, including the installed licenses and licensable components of that system. The system details contains component details and license details.

Table 5. Systems Detail Pane

Field	Description
System Name	The host name of the installed operating system, if available.
Management Controller	The host name of the management controller.
Model	The system model.
Service Tag	The service tag of the system.
Discovery Address	The IP address or hostname at which the management controller was discovered.
Purchased License	The highest license class of any perpetual license bound to the system is shown. Both installed licenses and licenses in inventory awaiting deployment are included when calculating the purchased license class.
Current License	The current license on the system.
Installed Licenses	The list of licenses that are installed on the system.
Remove License	Select a license in the Installed License grid, and click Remove license to remove a license installed on the system.
Selected	Click check box to select the license.
Status	The license status: <ul style="list-style-type: none"> ● Green — The license is ok. ● Yellow — The license has a potential problem. ● Red — The license is not functional.
Description	The license description.
Entitlement ID	The unique license identifier.

Table 5. Systems Detail Pane (continued)

Field	Description
Expiration	Date on which the license expires (if applicable).
Term	The license term. For more information, see Understanding Licenses .
Date Purchased	The date the license was purchased.
Date Imported	The date the license was imported.

Discovery/Inventory Wizard

Provide these values to set IP range and host information.

Table 6. Discovery/Inventory Wizard

Field	Description
Add Range or IP	Click to open the Edit Inventory Range window for adding a new discovery range.
Edit	Select an existing range and click to open the Edit Inventory Range window.
Remove Selected	Click to remove the selected range.
Inventory	Click the check box to select the IP address.
Range / Address Name	Enter a unique name describing the range.
Start / Individual Address	Enter the beginning range of the IPv4 address or the individual IP address.
End Address	Enter the ending range of the IPv4 address.
Subnet Mask (Optional)	Use subnet mask to exclude network and broadcast addresses from inventory attempts. If omitted, each address is treated as a host.
Description (Optional)	Enter a description. Each inventory range can include at most a Class B network (65,536 addresses).

Edit Inventory Range

Table 7. Edit Inventory Range

Field	Description
IP Range or Address Name	Enter a unique name describing the range.
Enter an IP Range, an Individual Address, or a List of Addresses	
IPV4 Range	Select to provide an IPv4 address range.
Start Address	Enter the beginning range of the IPv4 address or the individual IP address.
End Address	Enter the ending range of the IPv4 address or the individual IP address.
Subnet Mask	Enter the subnet mask for the provided IPv4 address.
Individual IP Address (IPv4, IPv6, or hostname)	Select to provide an individual IP address.
Text file with IP addresses	Select to create an inventory range using a text file that includes an IP address or host name in each line.
Load	Click to browse and select the text file.

Table 7. Edit Inventory Range (continued)

Field	Description
Description (Optional)	Enter a description.

Communication Settings

Optimal parameter values depend on the characteristics of a network. In communication settings, you can provide credentials, Ping (ICMP) Settings, and WS-Man Settings.

Table 8. Communication Settings


Field	Description
Credentials	You must specify the credentials to conduct discovery inventory. Credential information is not persistent across task executions.
Management Controller Username	Provide the management controller user name. If using Active Directory authentication, enter username in the format Domain\User name.  NOTE: The management controller login privilege is required to perform system inventory.
Management Controller Password	Provide management controller password.
Ping Settings (ICMP)	
Require successful ping before attempting inventory	When enabled, a ping response is received from an address before attempting WS-Man inventory communications. This can improve the performance of the inventory process. However, disable this option if the network blocks ping requests. This option is enabled by default.
Retries	The number of times to re-attempt a ping before excluding the system from inventory. The default is 3 retries (4 total attempts).
Timeout	The time within which a ping response is received before the ping attempt fails. The default is 5 seconds.
WS-Man Settings	Dell License Manager uses the management controller WS-Man interface to obtain inventory information.
Validate Certificate Name	If enabled, this ensures that inventory communications are conducted only with systems identifying themselves based on a certificate that matches the address used to communicate with that system. If the iDRAC certificate does not match the discovery address, then disable certificate name validation for Dell License Manager to communicate with the iDRAC. However, if the certificate name is not validated, Dell License Manager cannot authenticate the identity of the remote system.
Validate Certificate Authority	If enabled, this ensures that the inventory communications are conducted only with systems identifying themselves based on a certificate issued by a trusted source. If the iDRAC certificate is not issued by a trusted authority, then disable validation for Dell License Manager to communicate with the iDRAC. However, if the certificate authority is not validated, Dell License Manager cannot authenticate the identity of the remote system. For validation, include a trusted certificate authority as part of the Trusted Root Certification Authorities list in Microsoft Windows. For more information, see the Microsoft Windows documentation.
Validate Certificate Revocation List	If enabled, this ensures that communications are not conducted with a system identifying itself using a certificate that is revoked. If the management console cannot communicate with a certificate revocation list server, then disable this option for communicating with iDRAC. However, if the certificate revocation list is not validated, Dell License Manager cannot authenticate the identity of the remote system.
Retries	The number of communication retry attempts made, if temporary WS-Man communication errors occur before the inventory attempt fails. The default is 1 retry (2 total attempts).

Table 8. Communication Settings (continued)

Field	Description
Timeout	The time within which the WS-Man host must begin to return data before the communication attempt fails. The default is 30 seconds.
Port	The HTTPS communication port configured on the iDRACs. The default port is 443. On this port, ensure that firewall settings allow HTTPS communication between the management station and the iDRACs.

Licenses — Reference

From Licenses, you can import and deploy matching licenses, archive exported license, and save reports.

Table 9. Licenses — Reference

Field	Description
Import Licenses	Click to import licenses from a file system.
Export Archive	Select to archive licenses.
Deploy Licenses	Select to deploy licenses matched to a licensable system. The options include: <ul style="list-style-type: none"> • Deploy Selected Licenses • Automatically Deploy Licenses
Save Report	Select to save the license report.
Delete	Select to remove licenses from License Manager local database.
Selected	Click to select a license.
Description	Details of the type of license; Enterprise License, bound, unbound, or upgraded.
Term	The license term. For more information, see Understanding Licenses .
Bound Service Tag	The Service Tag to which the license is bound. You can only deploy this license on the system with the specified tag.
Deployed	The deployment status: <ul style="list-style-type: none"> • Yes — The license is deployed. • No — The license is not deployed. • Unknown — The corresponding system is not in inventory.
Matching System	The system to which you can assign this license. <ul style="list-style-type: none"> • Yes — Indicates the associated system is in inventory. • No — Indicates the system is not in inventory.
Origin	The method in which the license was added: <ul style="list-style-type: none"> • Imported — The license was imported into Dell License Manager. • Retrieved — The license was obtained during inventory.
Date Purchased	The date the license was purchased.
Date Imported	The date the license was imported.
License	The license identification number and the details of the license.
Entitlement ID	The unique license identifier.
Upgrade ID	In the case of an upgrade license, the ID of the license to which the upgrade applies.
Expiration	Date on which the license expires (if applicable).
License Features	The features supported by the selected license.

Topics:

- [Connect to Dell Online](#)
- [Bind Licenses](#)
- [Manage Licenses](#)

Connect to Dell Online

Table 10. Connect to Dell Online

Field	Description
Enter Connection Credentials	
Dell Online	Click the link to open the Dell Online Account web page. A new OTP is generated after providing the Dell Online Account credentials.
Credentials	
OTP (One Time Password)	Enter the OTP generated by connecting to Dell Online Account.
Options	
Save Connection Credentials	Click the check box to enable the License Manager to reconnect to Dell Online Account by saving the connection credentials. NOTE: A new OTP has to be requested by connecting to Dell Online Account when the credentials expire.
Automatically connect on start up	Click the check box to enable the License Manager to automatically connect to the Dell Online Account when it is launched.
Enable Proxy Settings	Click the check box to enable proxy settings if the network requires proxy settings for the connection.
Proxy IP	Enter the proxy IP address.
User Name	Enter the username of the proxy user.
Password	Enter the password of the proxy user.
Port	Enter the port number to access the proxy server.
Connecting Results	Displays the connection status to Dell Online.
Loading Complete	Displays the summary of unbound licenses fetched from the Dell Online Account
Entitlement ID	Displays the unique license identifier.
License Type	Displays the type of license matched to a licensable system.
Description	Displays the description of the purchased licenses.
Is Bound	Specifies whether the entitlements are bound to the licensable systems.

Bind Licenses

Table 11. Bind Licenses

Field	Description
Checkbox	Click to select license type.
License Description	The description of the license.
License Count	The count of unbound licenses.
Selected	Click to select system to bind the licenses.
System Name	The name of the system to which the license will be bound.
Service Tag	The service tag of the system.
System Model	The system model name.

Table 11. Bind Licenses (continued)



Field	Description
Deploy licenses after binding	Select to deploy the licenses after the license is bound to the system.
Bind Licenses	
Management Controller Username	Provide the management controller user name.
Management Controller Password	Provide the management controller password.
WS-Man Settings	
Validate Certificate Name	If enabled, this ensures that inventory communications are conducted only with systems identifying themselves based on a certificate that matches the address used to communicate with that system. If the iDRAC certificate does not match the discovery address, then disable certificate name validation for License Manager to communicate with iDRAC. However, if the certificate name is not validated, License Manager cannot authenticate the identity of the remote system.
Validate Certificate Authority	If enabled, this ensures that communications are conducted only with systems identifying themselves based on a certificate issued by a trusted source. If the iDRAC certificate is not issued by a trusted authority, then disable validation for License Manager to communicate with the management controller. However, if the certificate authority is not validated, License Manager cannot authenticate the identity of the remote system. For validation, include a trusted certificate authority as part of the Trusted Root Certification Authorities list in Microsoft Windows. For more information, see the Microsoft Windows documentation.
Validate Certificate Revocation List	If enabled, this ensures that communications are not conducted with a system identifying itself using a certificate that is revoked. If the management console cannot communicate with a certificate revocation list server, then disable this option to communicate with iDRAC. However, if the certificate revocation list is not validated, License Manager cannot authenticate the identity of the remote system.
Retries	The number of communication retry attempts made if temporary WS-Man communication errors occur before the deployment attempt fails. The default is 1 retry (2 total attempts).
Timeout	The time within which the WS-Man host must begin to return data before the communication attempt fails. The default is 30 seconds.
Port	The HTTPS communication port configured on the iDRACs. The default port is 443. On this port, ensure that the firewall settings allow HTTPS communication between the management station and iDRACs.

Manage Licenses

Table 12. Manage Licenses

Field	Description
Checkbox	Click to select license.
Operation Status	Details on whether the license is available for deployment.
Entitlement ID	The ID of the license.
License Description	The description of the license.
System	The name of the system on which to deploy the license. If available, the host name is used, otherwise the iDRAC name is used.
Service Tag	The factory-assigned system Service Tag, which uniquely identifies each system. Each license is bound to a particular Service Tag indicating the system on which the license is deployed.

Table 12. Manage Licenses (continued)

Field	Description
	 NOTE: Licenses already deployed on a system do not appear in the Operation Selection page.
Active License	The class and term of the highest class license installed on the system.
Credentials	
Management Controller Username	Provide the management controller user name. If you are using Active Directory authentication, enter the user name in the format Domain\User name.  NOTE: The management controller login privilege is required to perform system inventory.
Management Controller Password	Provide the management controller password.
WS-Man Settings	Dell License Manager uses the management controller WS-Man interface to obtain inventory information.
Validate Certificate Name	If enabled, this ensures that inventory communications are conducted only with systems identifying themselves based on a certificate that matches the address used to communicate with that system. If the iDRAC certificate does not match the discovery address, then disable certificate name validation for Dell License Manager to communicate with iDRAC. However, if the certificate name is not validated, Dell License Manager cannot authenticate the identity of the remote system.
Validate Certificate Authority	If enabled, this ensures that inventory communications are conducted only with systems identifying themselves based on a certificate issued by a trusted source. If the iDRAC certificate is not issued by a trusted authority, then disable validation for Dell License Manager to communicate with the management controller. However, if the certificate authority is not validated, Dell License Manager cannot authenticate the identity of the remote system. For validation, include a trusted certificate authority as part of the Trusted Root Certification Authorities list in Microsoft Windows. For more information, see the Microsoft Windows documentation.
Validate Certificate Revocation List	If enabled, this ensures that communications are not conducted with a system identifying itself using a certificate that is revoked. If the management console cannot communicate with a certificate revocation list server, then disable this option to communicate with iDRAC. However, if the certificate revocation list is not validated, Dell License Manager cannot authenticate the identity of the remote system.
Retries	The number of communication retry attempts made if temporary WS-Man communication errors occur before the inventory attempt fails. The default is 1 retry (2 total attempts).
Timeout	The time within which the WS-Man host must begin to return data before the communication attempt fails. The default is 30 seconds.
Port	The HTTPS communication port configured on the iDRACs. The default port is 443. On this port, ensure that the firewall settings allow HTTPS communication between the management station and iDRACs. To save changes and proceed with discovery/inventory, click Next .
Task Settings	
Show task pane after launch	Select to view the task progress in Tasks .

Entitlements — Reference

The Entitlement Inventory table contains summary of the Entitlement IDs, type of the licenses, and the binding status of the licenses which are obtained by connecting to Dell Online.

Table 13. Entitlements — Reference

Field	Description
Save Report	Select to save the entitlements report.
Download Bound Licenses	Select to download the bound licenses which are obtained by connecting to the Dell Online account.
Entitlement ID	The unique license identifier.
License Type	The type of license matched to a licensable system.
Product Name	The name of the license associated with the licensable system.
Is Bound	Specifies whether the entitlements are bound to the licensable systems.

Topics:

- [Change Server Password](#)

Change Server Password

Table 14. Change Server Password

Field	Description
Add Devices	
Service Tag	Enter the service tag which uniquely identifies each system.
Unique Password	Enter the unique root user password of the system.
Add	Click to add the service tag and unique password of a system.
System Details	
Generate CSV Template	Click to generate a CSV template to fill the Service Tag and Unique Password information.
Import	Click the import the CSV template with the Service Tag and Unique Password information of the systems.
Delete	Click to delete the system.
Selected	Click to select all the systems.
Service Tag	Displays the list of service tags which uniquely identifies the systems.
Unique Password	Displays the unique passwords of all the systems but are hidden to the users.
Provide IP Address/Range	
IPv4 Range	
Start Address	Enter the beginning range of the IPv4 address.
End Address	Enter the ending range of the IPv4 address.
Subnet Mask	Enter the subnet mask for the provided IPv4 address.


Table 14. Change Server Password (continued)

Field	Description
Individual Address (IPv4)	Select to provide an individual IP address
Text file with IP addresses	Select to enter the IP addresses using a text file that includes an IP address or host name in each line.
Load	Click to browse and select the text file.
Enter New Password	
Enter New Password	Enter the new password for the selected systems.
Confirm Password	Enter the new password again to confirm the password change for the selected systems.

Tasks — Reference

From Tasks, you can view discovery and inventory, and license deployment task information.

Table 15. Tasks — Reference

Field	Description
Cancel Selected Task	Select to cancel a listed task.
Clear Completed Task	Select to purge completed task information.
Status	Status type of the task is listed. <ul style="list-style-type: none"> • Normal—The task is successfully completed. • Failure—The task is not completed.
ID	Unique ID assigned to the task.
Task	Description of the task.
Summary	Description of the task's status.
Progress	Indicator of the task's progress.
Start Time	Starting time of the task.
End Time	Ending time of the task.
Task Results	Provides status, operation, and result information. It includes the following tabs: <ul style="list-style-type: none"> • Results • Execution Log
Status	<ul style="list-style-type: none"> • Green—The task is successfully completed. • Yellow—The task is completed with warnings. • Red—The task is completed with errors.
Operation	The description of the operation
Result	The summary of the operation result.  NOTE: When generating results for a discovery/inventory IP range, result entries are not created for addresses where communication is not established or where a non-licensable system is detected. For result information on such systems, consult the execution log tab.
Execution Log	The Execution Log tab provides detailed information from the selected task log.

Logs — Reference

From Logs, you can view License Manager activities, clear log results, and save reports.

Table 16. Logs — Reference

Field	Description
Clear Logs	Select to purge logged information.
Generate Support Log Archive	Select to archive logged information.
Save Report	Select to save log report.
Result	Status type of the listed task: <ul style="list-style-type: none"> • Normal—The task is successfully completed. • Failure—The task is not completed.
ID	Unique ID assigned to the task.
Summary	Summary description of the logged event.
Date	Date and time at which the task completed.
Log Entries	Details of the logged information.